

© Copyright SEK. Reproduction in any form without permission is prohibited.

Kabelnät för television, ljudradio och interaktiva tjänster – Del 2: EMC-fordringar på utrustning

*Cable networks for television signals, sound signals and interactive services –
Part 2: Electromagnetic compatibility for equipment*

Som svensk standard gäller europastandarden EN 50083-2:2012. Den svenska standarden innehåller den officiella engelska språkversionen av EN 50083-2:2012.

Nationellt förord

Tidigare fastställd svensk standard SS-EN 50083-2, utgåva 3, 2006, gäller ej fr o m 2013-06-21.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Cable networks for television signals, sound signals and interactive services -
Part 2: Electromagnetic compatibility for equipment**

Réseaux de distribution par câbles pour signaux de télévision, signaux de radiodiffusion sonore et services interactifs -
Partie 2: Compatibilité électromagnétique pour les matériels

Kabelnetze für Fernsehsignale, Tonsignale und interaktive Dienste -
Teil 2: Elektromagnetische Verträglichkeit von Geräten

This European Standard was approved by CENELEC on 2011-12-21. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents

Contents	2
Foreword	5
1 Scope	7
1.1 General	7
1.2 Specific scope of EN 50083-2	7
2 Normative references	9
3 Terms, definitions, symbols and abbreviations	10
3.1 Terms and definitions	10
3.2 Symbols	15
3.3 Abbreviations	16
4 Methods of measurements	16
4.1 General operating conditions	16
4.2 Disturbance voltages from equipment	17
4.3 Radiation from active equipment	18
4.4 Immunity of active equipment	28
4.5 Screening effectiveness of passive equipment	40
4.6 Electrostatic discharge immunity test for active equipment	42
4.7 Electrical fast transient/burst immunity test for AC power ports	42
4.8 Methods of measurement for telecom signal ports of multimedia network equipment	42
4.9 Measurement of indoor receiving antennas for broadcast signals	42
5 Performance requirements	43
5.1 General	43
5.2 Disturbance voltages from equipment	43
5.3 Radiation	44
5.4 Immunity of active equipment	45
5.5 Screening effectiveness of passive equipment	51
5.6 Electrostatic discharge immunity test for active equipment	52
5.7 Electrical fast transient/burst immunity test for AC power ports	52
5.8 Performance requirements for telecom signal ports of multimedia network equipment	52
5.9 Applicability of EMC performance requirements and methods of measurement to different types of equipment	52
Annex ZZ (informative) Coverage of Essential Requirements of EU Directives	55
Bibliography	56

Figures

Figure 1 - Measurement set-up for radiation measurements in the frequency range 5 MHz to 30 MHz using the "coupling unit" method.....21

Figure 2 - Absorbing clamp method (30 MHz to 1 000 MHz)23

Figure 3 - Example of general measurement set-up24

Figure 4 - Example of measurement set-up for measurements on the input port of an active equipment24

Figure 5 - Measurement set-up for the "substitution" radiation method – First measurement step26

Figure 6 - Measurement set-up for the "substitution" radiation method – Second measurement step27

Figure 7 - Frequency allocation for out-of-band immunity measurement of active equipment with nominal upper frequency limit $\leq 1\ 000$ MHz.....30

Figure 8 - Frequency allocation for out-of-band immunity measurement of active equipment with nominal lower frequency limit ≥ 950 MHz30

Figure 9 - Frequency allocation for in-band immunity measurement of active equipment with nominal upper frequency limit $\leq 1\ 000$ MHz33

Figure 10 - Frequency allocation for in-band immunity measurement of active equipment with nominal lower frequency limit ≥ 950 MHz33

Figure 11 - Measurement set-up for internal immunity test.....35

Figure 12 - Levels of wanted and unwanted signals for the internal immunity of FSS receiving outdoor units38

Figure 13 - Levels of wanted and unwanted signals for the internal immunity of BSS receiving outdoor units39

Figure 14 - Levels of unwanted signals for the internal immunity of active equipment in Band I (47 MHz to 68 MHz).....47

Figure 15 - Levels of unwanted signals for the internal immunity of active equipment in Band II (87,5 MHz to 108 MHz)48

Figure 16 - Levels of unwanted signals for the internal immunity of active equipment in Band III (174 MHz to 230 MHz)49

Figure 17 - Levels of unwanted signals for the internal immunity of active equipment in Band IV/V (470 MHz to 862 MHz)50

Tables

Table 1 - Port structure of different network equipment	8
Table 2 - Limits of mains terminal disturbance voltage	43
Table 3 - Limits of input terminal disturbance voltages for equipment directly connected to receiving antennas	44
Table 4 - Limits of input terminal disturbance voltages for equipment directly connected to satellite outdoor units	44
Table 5 - Limits of radiated disturbance power	44
Table 6 - Limit of local oscillator terminal power	45
Table 7 - Limits of out-of-band immunity	45
Table 8 - Limits of in-band immunity	46
Table 9 - Test specification for internal immunity	46
Table 10 - Limits of immunity to image frequency signals in terms of image suppression ratio	51
Table 11 - Limits of screening effectiveness of passive equipment within the nominal frequency ranges	51
Table 12 - Test specifications for electrostatic discharge immunity test for active equipment	52
Table 13 - Test specifications for electrical fast transient/burst immunity test	52
Table 14 - Port types and environmental conditions for EMC performance requirements and methods of measurement	52
Table 15 - Emission parameters	53
Table 16 - Immunity and screening effectiveness parameters	54

Foreword

This document (EN 50083-2:2012) has been prepared by CLC/TC 209 "Cable networks for television signals, sound signals and interactive services".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2012-12-21
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2013-06-21

This document supersedes EN 50083-2:2006.

EN 50083-2:2012 includes the following significant technical changes with respect to EN 50083-2:2006:

1. Frequency extensions

- 1.1. The upper frequency limit of conventional cable network equipment was extended from 862 MHz to 1 000 MHz due to market demands.
- 1.2. The first intermediate frequency range (1st IF range) for satellite signal transmission was extended to cover now frequencies from 950 MHz up to 3 500 MHz.
- 1.3. The methods of measurement and the EMC requirements in the overlapping frequency range from 950 MHz to 1 000 MHz were allocated in relation to the upper frequency limit, 1 000 MHz, respectively the lower frequency limit, 950 MHz, of the relevant equipment under test.

2. New EMC environment in the 800 MHz band

- 2.1. The European Commission has requested CENELEC and ETSI to draft immunity requirements for equipment, to protect against disturbance from the new wireless service in the 790-862 MHz band.
- 2.2. A CENELEC/ETSI Joint Working Group "Digital Dividend" was formed to describe the new EMC environment and to advise on appropriate test methods and limits.
- 2.3. EN 50083-2 is the standard specifying immunity requirements for active and passive cable network equipment.
- 2.4. The method of measurement and the requirements for in-band immunity were extended taking into account this new EMC environment due to the allocation of broadband wireless services in the frequency band 790 MHz to 862 MHz. As a consequence, the limits of in-band immunity were specified for analogue and additionally for digital signals in this frequency range.
- 2.5. Consequently it is recommended, that, where cable networks and wireless networks coexist, only the transmission of digitally modulated signals should be used in the frequency range 790 MHz to 862 MHz.
- 2.6. For passive equipment, Class A and Class B specifications were kept in the standard but a note was added recommending that only Class A equipment should be used in the planning and implementation of new networks.

3. Indoor antennas

The methods of measurement for all kinds of indoor antennas were combined in the new 4.9.

4. Bibliography

A Bibliography was added at the end of the document referencing i.a. to CEPT Report 30 on *“The identification of common and minimal (least restrictive) technical conditions for 790-862 MHz for the digital dividend in the European Union”*.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document

1 Scope

1.1 General

Standards of the EN 50083 and EN 60728 series deal with cable networks including equipment and associated methods of measurement for headend reception, processing and distribution of television signals, sound signals and their associated data signals and for processing, interfacing and transmitting all kinds of signals for interactive services using all applicable transmission media.

This includes

- CATV-networks ¹⁾,
- MATV-networks and SMATV-networks,
- individual receiving networks

and all kinds of equipment, systems and installations installed in such networks.

The extent of this standardisation work is from the antennas and/or special signal source inputs to the headend or other interface points to the network up to the terminal input.

The standardisation of any user terminals (i.e., tuners, receivers, decoders, multimedia terminals, etc.) as well as of any coaxial, balanced and optical cables and accessories thereof is excluded.

1.2 Specific scope of EN 50083-2

This European Standard

- applies to the radiation characteristics and immunity to electromagnetic disturbance of EM-active equipment (active and passive equipment) for the reception, processing and distribution of television, sound and interactive multimedia signals as dealt with in the following parts of EN 50083 or EN 60728 series:
 - EN 60728-3 "Active wideband equipment for cable networks";
 - EN 60728-4 "Passive wideband equipment for coaxial cable networks";
 - EN 60728-5 "Headend equipment";
 - EN 60728-6 "Optical equipment";
- covers the following frequency ranges:

disturbance voltage injected into the mains	150 kHz to 30 MHz;
radiation from active equipment	5 MHz to 25 GHz;
immunity of active equipment	150 kHz to 25 GHz ²⁾ ;
screening effectiveness of passive equipment	5 MHz to 3,5 GHz (25 GHz) ³⁾ ;

¹⁾ 'CATV-networks' encompasses the HFC networks used nowadays to provide telecommunications services, voice, data, audio and video both broadcast and narrowcast.

²⁾ For „Inband immunity of active equipment“ and „Out-of-band immunity of active equipment, no requirements apply at present for the frequency range 3,5 GHz to 25 GHz. Methods of measurement and limits are investigated for inclusion in a future amendment or revised edition.

³⁾ For "Screening effectiveness of passive equipment", no requirements apply at present for the frequency range 3,5 GHz to 25 GHz. Methods of measurement and limits are investigated for inclusion in a future amendment or revised edition.

- specifies requirements for maximum allowed radiation, minimum immunity and minimum screening effectiveness;
- describes test methods for conformance testing.

No measurement needs to be performed at frequencies where no requirement is specified.

Due to the fact that cable networks, the former cabled distribution systems for television and sound signals are more and more used for interactive services, these networks may incorporate also equipment that carry besides the cable network equipment ports also one or more telecom signal port(s). This equipment shall be named as "multimedia network equipment".

The EMC behaviour of cable network equipment, telecommunication network equipment and multimedia network equipment may be described by the following port structure (Table 1):

Table 1 - Port structure of different network equipment

Port name	Cable network equipment	Telecommunication network equipment	Multimedia network equipment
Enclosure	X	X	X
Earth	X	X	X
AC/DC power supply	X	X	X
Control (e.g. alarm)	X	X	X
Antenna input port	X		X
RF network port	X		X
Telecom signal port		X	X

Table 1 shows that cable network equipment and telecommunication network equipment have four common ports and, respectively, two and one individual ports. Multimedia network equipment carry besides the common ports an antenna input port and/or a RF network port as well as a telecom signal port.

The electromagnetic compatibility requirements for "telecommunication network equipment only" are standardised in ETSI EN 300 386 (mainly) and in ETSI EN 301 489-4, those for "cable network equipment only" are given in this EN 50083-2.

Equipment for multimedia networks of the above-mentioned type has to work under the same EMC conditions as equipment that is falling under the cable network and the telecommunication network EMC-standards. Due to the fact, that this equipment has to work in close proximity, e.g. in the same operating room, the EMC environmental conditions for all three types of equipment are the same.

This means that multimedia network equipment has to fulfil the EMC requirements of one of the above mentioned standards and in addition the EMC requirements, laid down in the other EMC standard, for the additional port, by which it is connected to the other network.

By this procedure it is ensured that multimedia network equipment fulfils the EMC conditions of one of the above mentioned networks and will neither disturb the respective other system nor will be disturbed by the respective other system via the connecting port.

Coaxial cables for cable networks do not fall under the scope of this standard; reference is made to EN 50117 series. Coaxial cable assemblies for radio and TV receivers (receiver leads) do not fall under the scope of this standard; reference is made to EN 60966 series. Requirements for the electromagnetic compatibility of receiver leads are laid down in EN 60966-2-4, EN 60966-2-5 and EN 60966-2-6.

This European Standard also covers indoor receiving antennas for broadcast signals for which the requirements and the applicable methods of measurement are limited to the emission and the electrostatic discharge phenomena.

Standardisation in the field of "Electromagnetic compatibility" for any broadcast terminals (e.g. tuners, receivers, decoders, etc.) is covered by EN 55013 and EN 55020 and for multimedia terminals by EN 55022 and EN 55024.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 55013	2001	Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement (CISPR 13:2001+A1:2003+A2:2006)
+A1	2003	
+A2	2006	
+IS1	2009	
EN 55016-1-1	2010	Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus (CISPR 16-1-1:2010 + corrigendum 2011 + A1:2010)
+A1	2010	
EN 55020	2007	Sound and television broadcast receivers and associated equipment – Immunity characteristics – Limits and methods of measurement (CISPR 20:2006)
+IS1	2009	
+IS2	2010	
+A11	2011	
EN 60728-3	2011	Cable networks for television signals, sound signals and interactive services – Part 3: Active wideband equipment for cable networks (IEC 60728-3: 2010)
EN 61000-3-2	2006	Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤ 16 A per phase) (IEC 61000-3-2:2005 + A1:2008 + A2:2009)
+A1	2009	
+A2	2009	
EN 61000-4-2	2009	Electromagnetic compatibility (EMC) – Part 4-2: Testing and measurement techniques – Electrostatic discharge immunity test (IEC 61000-4-2:2008)
EN 61000-4-3	2006	Electromagnetic compatibility (EMC) – Part 4-3: Testing and measurement techniques – Radiated, radio-frequency, electromagnetic field immunity test (IEC 61000-4-3:2006 +A1:2007 + A2:2010)
+A1	2008	
+A2	2010	
+IS1	2009	
EN 61000-4-4	2004	Electromagnetic compatibility (EMC) – Part 4-4: Testing and measurement techniques – Electrical fast transient/burst immunity test (IEC 61000-4-4:2004 + A1:2010)
+A1	2010	
EN 61000-4-6	2009	Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields (IEC 61000-4-6:2008)
EN 61000-6-1	2007	Electromagnetic compatibility (EMC) – Part 6-1: Generic standards – Immunity for residential, commercial and light-industrial environments (IEC 61000-6-1:2005)
EN 61079-1	1993	Methods of measurement on receivers for satellite broadcast transmissions in the 12 GHz band – Part 1: Radiofrequency measurements on outdoor units (IEC 61079-1:1992)

ETSI EN 300 386 V1.5.1	2010	Electromagnetic compatibility and Radio spectrum Matters (ERM); Telecommunication network equipment; ElectroMagnetic Compatibility (EMC) requirements
IEC 60050-161	1990	International Electrotechnical Vocabulary (IEV)
+A1	1997	Chapter 161: Electromagnetic compatibility
+A2	1998	