



PUBLICLY AVAILABLE SPECIFICATION

PRE-STANDARD

Fibre optic interconnecting devices and passive components performance standard –

Part 088-2: Non-connectorised single-mode fibre optic LAN WDM devices with channel spacing of 800 GHz for category C – Controlled environments

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

T

ICS 33.180.20

ISBN 978-2-88910-806-0

CONTENTS

| | |
|---|----|
| FOREWORD..... | 4 |
| 1 Scope..... | 6 |
| 2 Normative references | 6 |
| 3 LAN WDM device types | 7 |
| 3.1 LAN WDM device | 7 |
| 3.2 Integrated 1 × 4 LAN WDM device..... | 8 |
| 3.3 Individual 1 × 2 LAN WDM device..... | 8 |
| 4 Test conditions | 8 |
| 5 Test report..... | 9 |
| 6 Reference components..... | 9 |
| 7 Performance requirements..... | 9 |
| 7.1 Dimensions | 9 |
| 7.2 Test details and requirements | 9 |
| Annex A (normative) Sample size | 14 |
| Annex B (informative) Logarithmic transfer matrix for an integrated 1 × 4 LAN WDM device | 15 |
| Annex C (Informative) Logarithmic transfer matrix for an individual 1 × 2 LAN WDM device | 17 |
| Annex D (informative) General information for applications of integrated 1 × 4 LAN WDM devices | 20 |
| Annex E (informative) General information for internal configurations of integrated 1 × 4 LAN WDM devices | 21 |
| Bibliography..... | 23 |
| Figure 1 – Configuration of integrated 1 × 4 LAN WDM device | 8 |
| Figure 2 – Configuration of individual 1 × 2 LAN WDM device | 8 |
| Figure D.1 – Block diagram for 100GBASE-LR4 and 100GBASE-ER4 transmit/receive paths | 20 |
| Figure E.1 – Configuration example of serial-type integrated 1 × 4 LAN WDM device (DEMUX) | 21 |
| Figure E.2 – Configuration example of serial-type integrated 1 × 4 LAN WDM device (MUX) | 21 |
| Figure E.3 – Configuration example of tree-type integrated 1 × 4 LAN WDM device (MUX/DEMUX) | 22 |
| Table 1 – Test details and requirements | 10 |
| Table A.1 – Number of samples for each test..... | 14 |
| Table B.1 – Frequency range of channel 1: 231,584 THz – 231,216 THz (1 294,53 nm – 1 296,59 nm) | 15 |
| Table B.2 – Frequency range of channel 2: 230,784 THz – 230,416 THz (1 299,02 nm – 1 301,09 nm) | 15 |

| | |
|--|----|
| Table B.3 – Frequency range of channel 3: 229,984 THz – 229,616 THz (1 303,54 nm – 1 305,63 nm) | 15 |
| Table B.4 – Frequency range of channel 4: 229,184 THz – 228,816 THz (1 308,09 nm – 1 310,19 nm) | 16 |
| Table C.1.1 – Frequency range of channel 1: 231,584 THz – 231,216 THz (1 294,53 nm – 1 296,59 nm) | 17 |
| Table C.1.2 – Frequency range of channel 2: 230,784 THz – 230,416 THz (1 299,02 nm – 1 301,09 nm) | 17 |
| Table C.1.3 – Frequency range of channel 3: 229,984 THz – 229,616 THz (1 303,54 nm – 1 305,63 nm) | 17 |
| Table C.1.4 – Frequency range of channel 4: 229,184 THz – 228,816 THz (1 308,09 nm – 1 310,19 nm) | 17 |
| Table C.2.1 – Frequency range of channel 1: 231,584 THz – 231,216 THz (1 294,53 nm – 1 296,59 nm) | 18 |
| Table C.2.2 – Frequency range of channel 2: 230,784 THz – 230,416 THz (1 299,02 nm – 1 301,09 nm) | 18 |
| Table C.2.3 – Frequency range of channel 3: 229,984 THz – 229,616 THz (1 303,54 nm – 1 305,63 nm) | 18 |
| Table C.2.4 – Frequency range of channel 4: 229,184 THz – 228,816 THz (1 308,09 nm – 1 310,19 nm) | 18 |
| Table C.3.1 – Frequency range of channel 1: 231,584 THz – 231,216 THz (1 294,53 nm – 1 296,59 nm) | 18 |
| Table C.3.2 – Frequency range of channel 2: 230,784 THz – 230,416 THz (1 299,02 nm – 1 301,09 nm) | 18 |
| Table C.3.3 – Frequency range of channel 3: 229,984 THz – 229,616 THz (1 303,54 nm – 1 305,63 nm) | 19 |
| Table C.3.4 – Frequency range of channel 4: 229,184 THz – 228,816 THz (1 308,09 nm – 1 310,19 nm) | 19 |
| Table C.4.1 – Frequency range of channel 1: 231,584 THz – 231,216 THz (1 294,53 nm – 1 296,59 nm) | 19 |
| Table C.4.2 – Frequency range of channel 2: 230,784 THz – 230,416 THz (1 299,02 nm – 1 301,09 nm) | 19 |
| Table C.4.3 – Frequency range of channel 3: 229,984 THz – 229,616 THz (1 303,54 nm – 1 305,63 nm) | 19 |
| Table C.4.4 – Frequency range of channel 4: 229,184 THz – 228,816 THz (1 308,09 nm – 1 310,19 nm) | 19 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS PERFORMANCE STANDARD –

Part 088-2: Non-connectorised single-mode fibre optic LAN WDM devices with channel spacing of 800 GHz for category C – Controlled environments

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

A PAS is a technical specification not fulfilling the requirements for a standard, but made available to the public.

IEC-PAS 61753-088-2 has been processed by subcommittee 86B: Fibre optic interconnecting devices and passive components, of IEC technical committee 86: Fibre optics.

The text of this PAS is based on the following document:

This PAS was approved for publication by the P-members of the committee concerned as indicated in the following document

| Draft PAS | Report on voting |
|-------------|------------------|
| 86B/2968PAS | 86B/2997/RVD |

Following publication of this PAS, which is a pre-standard publication, the technical committee or subcommittee concerned may transform it into an International Standard.

A list of all parts of the IEC 61753 series, under the general title *Fibre optic interconnecting devices and passive components – Performance standard* can be found on the IEC website.

This PAS shall remain valid for an initial maximum period of 3 years starting from the publication date. The stability date may be extended for a single 3-year period, following which it shall be revised to become another type of normative document, or shall be withdrawn.

FIBRE OPTIC INTERCONNECTING DEVICES AND PASSIVE COMPONENTS PERFORMANCE STANDARD –

Part 088-2: Non-connectorised single-mode fibre optic LAN WDM devices with channel spacing of 800 GHz for category C – Controlled environments

1 Scope

This Publicly Available Specification (PAS) contains the minimum initial test and measurement requirements and severities which a non-connectorised single-mode fibre optic Local Area Network Wavelength Division Multiplexing (LAN WDM) device with channel spacing of 800 GHz needs to satisfy in order to be categorised as meeting the requirements of category C – Controlled environments, as defined in Annex A of IEC 61753-1. The applications of LAN WDM devices are optical MUX and DEMUX for 100GBASE-LR4 (required operating range of 2 m to 10 km) and 100GBASE-ER4 (required operating range of 2 m to 30 km) defined in IEEE Draft P802.3ba, as shown in Annex D. The requirements cover both an integrated 1 × 4 LAN WDM device and an individual 1 × 2 LAN WDM device for cascaded module construction.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61300 (all parts), *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures*

IEC 61300-2-1, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-1: Tests – Vibration (sinusoidal)*

IEC 61300-2-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-4: Tests – Fibre/cable retention*

IEC 61300-2-9, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-9: Tests – Shock*

IEC 61300-2-14, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-14: Tests – Optical power handling and damage threshold characterization*

IEC 61300-2-17, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-17: Tests – Cold*

IEC 61300-2-18, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-18: Tests – Dry heat - High temperature endurance*

IEC 61300-2-19, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-19: Tests – Damp heat (steady state)*

IEC 61300-2-22, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-22: Tests – Change of temperature*

IEC 61300-2-42, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 2-42: Tests – Static side load for connectors*

IEC 61300-3-2, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-2: Examination and measurements – Polarization dependent loss in a single-mode fibre optic device*

IEC 61300-3-4, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-4: Examinations and measurements – Attenuation*

IEC 61300-3-6, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-6: Examinations and measurements – Return loss*

IEC 61300-3-20, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-20: Examinations and measurements – Directivity of fibre optic branching devices*

IEC 61300-3-29, *Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 3-29: Examinations and measurements – Measurement techniques for characterizing the amplitude of the spectral transfer function of DWDM components*

IEC 61753-1:2007, *Fibre optic interconnecting devices and passive components performance standard – Part 1: General and guidance for performance standard*

IEC 61753-021-2, *Fibre optic interconnecting devices and passive components performance standard – Part 021-2: Grade C/3 single-mode fibre optic connectors for category C – Controlled environment*

IEC 62074-1, *Fibre optic interconnecting devices and passive components – Fibre optic WDM devices – Part 1: Generic specification*

ITU-T Recommendation G.692:1998, *Optical interfaces for multichannel systems with optical amplifiers*

ITU-T Recommendation G.694.1:2002, *Spectral grids for WDM applications: DWDM frequency grid*

ITU-T Recommendation G.959.1 version 10.4: June 2009, *Optical transport network physical layer interfaces*

IEEE P802.3ba D2.1: May 2009, Part 3: *Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications*