



Edition 2.0 2008-11

INTERNATIONAL STANDARD

Measurement and test methods for tuning fork quartz crystal units in the range from 10 kHz to 200 kHz and standard values

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PRICE CODE

ICS 31.140

ISBN 2-8318-1018-6

R

CONTENTS

FO	REWO	ORD		4		
1	Scope					
2	Norm	lormative references				
3	3 Overview					
	3.1	Gener	al	6		
	3.2	3.2 Applied frequency range				
	3.2 Applied frequency range					
	3.4 Load care			0		
	35	Recommended drive level				
	3.6	Measurement conditions				
	3.0	Measurement of frequency-temperature characteristics				
	3.0		sapacitance frequency characteristics	7		
Л	0.0 Moad		apacitance nequency characteristics	7		
-						
	4.1	Metho	0 A	····· / 		
		4.1.1	Vector network analyzer/vector impedance analyzer	····· / 		
		4.1.2				
		4.1.3	Specifications for vector network analyzer/vector impedance analyzer	8		
		4.1.4	l est fixture	8		
		4.1.5	Measurement of equivalent circuit constants	9		
		4.1.6	Frequency pulling	10		
	4.2	Metho		10		
		4.2.1	General	10		
		4.2.2	Block diagram	10		
		4.2.3	Calibration	11		
_		4.2.4	Procedure	12		
5	Measurement conditions					
	5.1	General				
	5.2	Measurement conditions				
	5.3	Measurement of the frequency-temperature dependence				
		5.3.1	General	13		
		5.3.2	Block diagram	13		
		5.3.3	Determination of the turnover point and parabolic coefficient β (standard reference method)	14		
		5.3.4	Measurement of the frequency versus temperature characteristics (mass production method)	14		
		5.3.5	Frequency C _L curve	15		
6	Test	and env	vironmental examination	15		
	6.1	1 Application of the definition of IEC 60122-1				
	6.2	2 Magnetism – Influence of a magnetic field on the frequency				
	6.3	3 Enclosure				
	6.4	Measuring conditions and electric performance				
		6.4.1	General	16		
		6.4.2	Measurement conditions	16		
		6.4.3	Standard values	16		
Bib	liogra	phy		18		

Figure 1 – Block diagram of the measurement method using the vector network analyzer or vector impedance analyzer	8
Figure 2 – Block diagram of test fixture	9
Figure 3 – Block diagram of test fixture (including a load capacitance)	9
Figure 4 – Block diagram of test fixture for bridge method	11
Figure 5 – Block diagram of test fixture for bridge method (including a load capacitance)	11
Figure 6 – Block diagram of measurement of the frequency-temperature dependence	13
Figure 7 – Frequency–temperature template (Turnover point: 25 ± 5 °C, β = -45 × 10 ₋₉ /°C ₂)	14
Figure 8a) – $\Delta f f f$ versus C_{L} curve	15
Figure 8b) – $\Delta f f$ versus C_{L} curve	15
Figure 8 – $\Delta f / f$ versus C_{L} curve with different C_{Ls}	15
Table 1 – Specifications for vector network analyzer/vector impedance analyzer	8
Table 2 – Standard values	17

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MEASUREMENT AND TEST METHODS FOR TUNING FORK QUARTZ CRYSTAL UNITS IN THE RANGE FROM 10 kHz TO 200 kHz AND STANDARD VALUES

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committee; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60689 has been prepared by IEC technical committee 49: Piezoelectric and dielectric devices for frequency control and selection.

This second edition cancels and replaces the first edition published in 1980. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) The title of the first edition is *Measurements and test methods for 32 kHz quartz crystal units for wrist watches and standard values*. The title is modified and the frequency range of this second edition is extended to the range from 10 kHz to 200 kHz.
- b) The Lissajous method is defined in the first edition as the standard measurement method. The PI network and bridge method are used in this second edition.
- c) The PI network has a transformer for impedance matching. This composition differs from that of IEC 60444-1.

The text of this standard is based on the following documents:

FDIS	Report on voting
49/809/FDIS	49/815/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition; or
- amended.

A bilingual version of this publication may be issued at a later date.

MEASUREMENT AND TEST METHODS FOR TUNING FORK QUARTZ CRYSTAL UNITS IN THE RANGE FROM 10 kHz TO 200 kHz AND STANDARD VALUES

1 Scope

This International Standard applies to measurements and test methods for tuning fork quartz crystal units in the range from 10 kHz to 200 kHz and standard values for frequency control and selection.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60027 (all parts), Letter symbols to be used in electrical technology

IEC 60050-561, International Electrotechnical Vocabulary – Chapter 561: Piezoelectric devices for frequency control and selection

IEC 60122-1, Quartz crystal units of assessed quality – Part 1: Generic specification

IEC 60122-3, Quartz crystal units of assessed quality – Part 3: Standard outlines and lead connections

IEC 60444 (series), Measurement of quartz crystal unit parameters by zero phase technique in a π -network

IEC 60617, Graphical symbols for diagrams

ISO 1000:1992, SI units and recommendations for the use of their multiples and certain other Units