

© Copyright SEK. Reproduction in any form without permission is prohibited.

Marin nавигаcиoнs- och kommunikationsutrustning – System för automatisk identifiering (AIS) – Del 2: Utrustning i klass A för fartyg – Tekniska och operationella fordringar, provningsmetoder och erforderliga provningsresultat

*Maritime navigation and radiocommunication equipment and systems –
Automatic identification systems (AIS) –
Part 2: Class A shipborne equipment of the automatic identification system (AIS) –
Operational and performance requirements, methods of test and required test results*

Som svensk standard gäller europastandarden EN 61993-2:2013. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61993-2:2013.

Nationellt förord

Europastandarden EN 61993-2:2013

består av:

- **europastandardens ikraftsättndingsdokument**, utarbetat inom CENELEC
- **IEC 61993-2, Second edition, 2012 - Maritime navigation and radiocommunication equipment and systems - Automatic identification systems (AIS) - Part 2: Class A shipborne equipment of the automatic identification system (AIS) - Operational and performance requirements, methods of test and required test results**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 61993-2, utgåva 1, 2003, gäller ej fr o m 2015-11-23.

ICS 47.020.70

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringssarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utdriften av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringssarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringssverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtidens standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Maritime navigation and radiocommunication equipment and systems -
Automatic Identification Systems (AIS) -
Part 2: Class A shipborne equipment of the automatic identification
system (AIS) -
Operational and performance requirements, methods of test and required
test results
(IEC 61993-2:2012)**

Matériels et systèmes de navigation et de
radiocommunications maritimes -
Systèmes d'identification automatique
(AIS) -
Partie 2: Equipements AIS de type Classe
A embarqués -
Exigences d'exploitation et de
fonctionnement, méthodes d'essai et
résultats d'essai exigés
(CEI 61993-2:2012)

Navigations- und
Funkkommunikationsgeräte und -systeme
für die Seeschifffahrt -
Automatische
Identifikationssysteme (AIS) -
Teil 2: Geräte der Klasse A des
universellen automatischen
Identifikationssystems (AIS) für Schiffe -
Betriebs- und Leistungsanforderungen,
Prüfverfahren und geforderte
Prüfergebnisse
(IEC 61993-2:2012)

This European Standard was approved by CENELEC on 2012-11-23. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 80/656/CDV, future edition 2 of IEC 61993-2, prepared by IEC TC 80 "Maritime navigation and radiocommunication equipment and systems" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61993-2:2013.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2013-08-23
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2015-11-23

This document supersedes EN 61993-2:2002.

EN 61993-2:2013 includes the following significant technical changes with respect to EN 61993-2:2002:

It incorporates the technical characteristics included in Recommendation ITU-R M.1371-4, which was published in 2010. New technical characteristics result in sundry clarifications to the requirements and the ability to handle five new messages – Messages 23, 24, 25, 26 and 27.

The significant changes in this edition include:

- a new requirement in 6.9 for vessels of type “tanker” to use a low power setting;
- expanded requirements for the functionality of the minimum keyboard and display in 6.11 including new requirements for display of AIS-SART together with an AIS-SART alarm and new requirements for the protection of the static data of the ship;
- expanded requirements for the transmitters and receivers in 7.2 but with the removal of the previous requirement for 12,5 kHz channel operation which has not been used in practice;
- expanded requirements for long-range applications in Clause 8 to add a broadcast method;
- a definition of the pilot plug pin out in 7.6 together with some new requirements for interfaces;
- extensively revised test methods in Clauses 14 to 19 based on the experience of testing AIS equipment;
- expanded test methods in Annex D for DSC functionality but the removal of the previous requirement for DSC polling which is no longer used.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61993-2:2012 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

| | |
|-----------------|--|
| IEC 61097-14 | NOTE Harmonized as EN 61097-14. |
| IEC 61108-1 | NOTE Harmonized as EN 61108-1. |
| IEC 61108-2 | NOTE Harmonized as EN 61108-2. |
| IEC 61162-3 | NOTE Harmonized as EN 61162-3. |
| IEC 61162-450 | NOTE Harmonized as EN 61162-450. |
| IEC 62287-1 | NOTE Harmonized as EN 62287-1. |
| IEC 62320-1 | NOTE Harmonized as EN 62320-1. |
| IEC 62320-2 | NOTE Harmonized as EN 62320-2. |
| ISO 9000 series | NOTE Harmonized in EN ISO 9000 series. |

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|-------------------------------|--------------|---|--------------|-------------|
| IEC 60945 + corr. April | 2002 2008 | Maritime navigation and radiocommunication equipment and systems - General requirements - Methods of testing and required test results | EN 60945 | 2002 |
| IEC 61108 | Series | Maritime navigation and radiocommunication equipment and systems - Global navigation satellite systems (GNSS) | EN 61108 | Series |
| IEC 61162-1 | - | Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 1: Single talker and multiple listeners | EN 61162-1 | - |
| IEC 61162-2 | - | Maritime navigation and radiocommunication equipment and systems - Digital interfaces - Part 2: Single talker and multiple listeners, high-speed transmission | EN 61162-2 | - |
| IEC 62288 | - | Maritime navigation and radiocommunication equipment and systems - Presentation of navigation-related information on shipborne navigational displays - General requirements, methods of testing and required test results | EN 62288 | - |
| IEC 62388 | - | Maritime navigation and radio-communication equipment and systems - Shipborne radar - Performance requirements, methods of testing and required test results | EN 62388 | - |
| IMO Resolution A.694(17) | - | General requirements for shipborne radio equipment forming part of the global maritime distress and safety system (GMDSS) and for electronic navigational aids | - | - |
| IMO Resolution MSC.74(69) | - | Recommendations on performance standards - for Track control systems | - | - |
| IMO Resolution MSC.43(64) | - | Guidelines and Criteria for Ship Reporting Systems (as amended by MSC.111(73)) | - | - |
| ITU-R Recommendation M.1371-4 | - | Technical characteristics for an automatic identification system using time-division multiple access in the VHF maritime mobile band | - | - |
| ITU-R Recommendation M.825-3 | - | Characteristics of a transponder system using - digital selective calling techniques for use with vessel traffic services and ship-to-ship identification | - | - |

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|-------------------------------------|-------------|---|--------------|-------------|
| ITU-R Recommendation M.493-13 | - | Digital selective-calling system for use in the maritime mobile service | - | - |
| ITU-T Recommendation O.153 | - | Basic parameters for the measurement of error performance at bit rates below the primary rate | - | - |
| ITU-R Recommendation M.1084-5 | - | Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service | - | - |
| ITU-R Recommendation M.541-9 | - | Operational procedures for the use of digital selective-calling equipment in the maritime mobile service | - | - |

CONTENTS

| | |
|--|----|
| INTRODUCTION..... | 11 |
| 1 Scope..... | 12 |
| 2 Normative references | 12 |
| 3 Abbreviations | 13 |
| 4 General requirements | 14 |
| 4.1 General | 14 |
| 4.1.1 Overview | 14 |
| 4.1.2 General requirements | 14 |
| 4.1.3 Capabilities of the AIS | 15 |
| 4.1.4 Additional requirements | 15 |
| 4.1.5 Transmitter shutdown procedure..... | 15 |
| 4.1.6 Quality assurance..... | 15 |
| 4.2 Modes of operation..... | 15 |
| 4.3 Manuals | 15 |
| 4.4 Marking and identification..... | 16 |
| 5 Other requirements..... | 16 |
| 5.1 Environmental, power supply, special purpose and safety requirements | 16 |
| 5.2 Display of information..... | 16 |
| 6 Performance requirements | 16 |
| 6.1 Composition | 16 |
| 6.2 Time and position..... | 17 |
| 6.2.1 Source for UTC | 17 |
| 6.2.2 Source for AIS position reporting | 17 |
| 6.3 User interface..... | 17 |
| 6.4 Identification..... | 18 |
| 6.5 Information..... | 18 |
| 6.5.1 Information provided by the AIS..... | 18 |
| 6.5.2 Information reporting intervals | 19 |
| 6.5.3 Ship reporting capacity | 19 |
| 6.6 Event log | 20 |
| 6.7 Permissible initialization period | 20 |
| 6.8 Power supply..... | 20 |
| 6.9 Technical characteristics | 20 |
| 6.10 Alarms and indications, fall-back arrangements..... | 20 |
| 6.10.1 Built-in test equipment | 20 |
| 6.10.2 Alarm messages | 21 |
| 6.10.3 Status messages | 23 |
| 6.11 Display, input and output..... | 26 |
| 6.11.1 Minimum keyboard and display (MKD)..... | 26 |
| 6.11.2 Communication test | 28 |
| 6.11.3 Alarms and status information | 29 |
| 6.11.4 Data protection..... | 29 |
| 6.11.5 Distance calculation | 29 |
| 6.12 Protection from invalid controls | 30 |
| 7 Technical requirements | 30 |

| | | |
|-------|---|----|
| 7.1 | General | 30 |
| 7.2 | Physical layer | 30 |
| 7.2.1 | General | 31 |
| 7.2.2 | Transmitter parameters | 31 |
| 7.2.3 | Receiver parameters | 32 |
| 7.3 | Link layer | 32 |
| 7.3.1 | General | 32 |
| 7.3.2 | Link sublayer 1: Medium Access Control (MAC) | 33 |
| 7.3.3 | Link sublayer 2: Data Link Service (DLS) | 33 |
| 7.3.4 | Link sublayer 3 – Link Management Entity (LME) | 33 |
| 7.4 | Network layer | 35 |
| 7.4.1 | General | 35 |
| 7.4.2 | Management of regional operating settings | 35 |
| 7.5 | Transport layer | 37 |
| 7.6 | Presentation interface | 37 |
| 7.6.1 | General | 37 |
| 7.6.2 | Automatic input of sensor data | 38 |
| 7.6.3 | High speed input/output ports | 38 |
| 7.6.4 | Long-range communication ports | 41 |
| 7.6.5 | BIIT alarm output | 43 |
| 8 | Long-range applications | 43 |
| 8.1 | General | 43 |
| 8.2 | Long-range application by two-way interface | 43 |
| 8.2.1 | General | 43 |
| 8.2.2 | Interrogations and responses | 44 |
| 8.2.3 | Manual and automatic response | 44 |
| 8.2.4 | Data formats and contents | 44 |
| 8.2.5 | Addressing AIS-units | 44 |
| 8.3 | Long-range application by broadcast | 45 |
| 9 | Test conditions | 45 |
| 9.1 | Normal and extreme test conditions | 45 |
| 9.1.1 | Normal test conditions | 45 |
| 9.1.2 | Extreme test conditions | 45 |
| 9.2 | Standard test environment | 46 |
| 9.3 | Additional test arrangements | 46 |
| 9.3.1 | Arrangements for test signals applied to the receiver input | 46 |
| 9.3.2 | Encoder for receiver measurements | 46 |
| 9.3.3 | Waiver for receivers | 46 |
| 9.3.4 | Impedance | 47 |
| 9.3.5 | Artificial antenna (dummy load) | 47 |
| 9.3.6 | Facilities for access | 47 |
| 9.3.7 | Modes of operation of the transmitter | 47 |
| 9.4 | Common test conditions for protection from invalid controls | 47 |
| 9.5 | Measurement uncertainties | 47 |
| 10 | Test signals | 48 |
| 10.1 | Standard test signal number 1 (DSC) | 48 |
| 10.2 | Standard test signal number 2 (TDMA) | 48 |
| 10.3 | Standard test signal number 3 (TDMA) | 48 |
| 10.4 | Standard test signal number 4 (PRBS) | 48 |

| | |
|---|----|
| 10.5 Standard test signal number 5 (PRBS) | 48 |
| 11 Power supply, special purpose and safety tests..... | 49 |
| 12 Environmental tests | 49 |
| 13 EMC tests..... | 50 |
| 14 Operational tests | 50 |
| 14.1 Identification and operating modes | 50 |
| 14.1.1 Autonomous mode..... | 50 |
| 14.1.2 Assigned mode..... | 51 |
| 14.1.3 Polled mode | 51 |
| 14.1.4 Addressed operation..... | 52 |
| 14.1.5 Broadcast operation | 52 |
| 14.1.6 Multiple slot messages | 53 |
| 14.2 Information | 53 |
| 14.2.1 Information provided by the AIS..... | 54 |
| 14.2.2 Reporting intervals | 54 |
| 14.3 Event log | 55 |
| 14.3.1 Method of measurement | 56 |
| 14.3.2 Required results | 56 |
| 14.4 Initialization period | 56 |
| 14.4.1 Method of measurement | 56 |
| 14.4.2 Required results | 56 |
| 14.5 Technical characteristics | 56 |
| 14.5.1 Channel selection | 56 |
| 14.5.2 Transceiver protection | 57 |
| 14.5.3 Automatic power setting | 57 |
| 14.6 Alarms and indicators, fall-back arrangements | 57 |
| 14.6.1 Loss of power supply | 57 |
| 14.6.2 Monitoring of functions and integrity | 57 |
| 14.6.3 Monitoring of sensor data | 59 |
| 14.7 Display, input and output..... | 62 |
| 14.7.1 Data input/output facilities | 62 |
| 14.7.2 Initiate message transmission..... | 62 |
| 14.7.3 Communication test..... | 63 |
| 14.7.4 System control..... | 63 |
| 14.7.5 Display of received targets | 64 |
| 14.7.6 Display of position quality | 65 |
| 14.7.7 Display of targets if optional filter is implemented | 65 |
| 14.7.8 Display of received safety related messages | 66 |
| 14.7.9 Presentation of navigation information..... | 66 |
| 15 Physical tests | 66 |
| 15.1 TDMA transmitter | 67 |
| 15.1.1 Frequency error..... | 67 |
| 15.1.2 Carrier power | 67 |
| 15.1.3 Slotted transmission spectrum | 68 |
| 15.1.4 Modulation accuracy..... | 69 |
| 15.1.5 Transmitter output power characteristics | 69 |
| 15.2 TDMA receivers..... | 70 |
| 15.2.1 Sensitivity..... | 70 |

| | |
|--|----|
| 15.2.2 Error behaviour at high input levels | 71 |
| 15.2.3 Co-channel rejection..... | 71 |
| 15.2.4 Adjacent channel selectivity..... | 72 |
| 15.2.5 Spurious response rejection | 72 |
| 15.2.6 Intermodulation response rejection and blocking | 75 |
| 15.2.7 Transmit to receive switching time | 76 |
| 15.2.8 Immunity to out-of-band energy | 77 |
| 15.3 Conducted spurious emissions | 77 |
| 15.3.1 Spurious emissions from the transmitter | 77 |
| 15.3.2 Spurious emissions from the receiver | 78 |
| 16 Specific tests of link layer..... | 78 |
| 16.1 TDMA synchronisation..... | 78 |
| 16.1.1 Synchronisation test using UTC..... | 78 |
| 16.1.2 Synchronisation test using UTC with repeated messages | 79 |
| 16.1.3 Synchronisation test without UTC, semaphore..... | 79 |
| 16.1.4 Synchronisation test without UTC | 80 |
| 16.1.5 Reception of un-synchronised messages | 80 |
| 16.2 Time division (frame format)..... | 80 |
| 16.2.1 Method of measurement | 80 |
| 16.2.2 Required results | 80 |
| 16.3 Synchronisation and jitter accuracy | 81 |
| 16.3.1 Definition..... | 81 |
| 16.3.2 Method of measurement | 81 |
| 16.3.3 Required results | 81 |
| 16.4 Data encoding (bit stuffing) | 81 |
| 16.4.1 Method of measurement | 81 |
| 16.4.2 Required results | 81 |
| 16.5 Frame check sequence | 81 |
| 16.5.1 Method of measurement | 81 |
| 16.5.2 Required results | 81 |
| 16.6 Slot allocation (channel access protocols) | 82 |
| 16.6.1 Network entry | 82 |
| 16.6.2 Autonomous scheduled transmissions (SOTDMA) | 82 |
| 16.6.3 Autonomous scheduled transmissions (ITDMA) | 82 |
| 16.6.4 Safety related/binary message transmission | 83 |
| 16.6.5 Transmission of Message 5 (ITDMA) | 83 |
| 16.6.6 Assigned operation..... | 83 |
| 16.6.7 Group assignment | 84 |
| 16.6.8 Fixed allocated transmissions (FATDMA) | 88 |
| 16.6.9 Randomisation of message transmissions | 88 |
| 16.7 Message formats | 88 |
| 16.7.1 Received messages | 88 |
| 16.7.2 Transmitted messages..... | 89 |
| 17 Specific tests of network layer | 89 |
| 17.1 Dual channel operation – Alternate transmissions | 89 |
| 17.1.1 Method of measurement | 89 |
| 17.1.2 Required results | 89 |
| 17.2 Regional area designation by VDL message..... | 89 |
| 17.2.1 Method of measurement | 89 |

| | |
|--|-----|
| 17.2.2 Required results | 90 |
| 17.3 Regional area designation by serial message | 90 |
| 17.4 Regional area designation with lost position | 91 |
| 17.4.1 Method of measurement | 91 |
| 17.4.2 Required results | 91 |
| 17.5 Power setting | 91 |
| 17.5.1 Method of measurement | 91 |
| 17.5.2 Required results | 91 |
| 17.6 Message priority handling | 91 |
| 17.6.1 Method of measurement | 91 |
| 17.6.2 Required results | 91 |
| 17.7 Slot reuse and FADMA reservations | 91 |
| 17.7.1 Method of measurement | 91 |
| 17.7.2 Required results | 92 |
| 17.8 Management of received regional operating settings | 92 |
| 17.8.1 Test for replacement or erasure of dated or remote regional operating settings | 92 |
| 17.8.2 Test of correct input via presentation interface or MKD | 93 |
| 17.8.3 Test of addressed telecommand | 94 |
| 17.8.4 Test for invalid regional operating areas | 94 |
| 17.9 Continuation of autonomous mode reporting interval | 95 |
| 17.9.1 Method of test | 95 |
| 17.9.2 Required results | 95 |
| 18 Specific tests of transport layer | 95 |
| 18.1 Addressed messages | 95 |
| 18.1.1 Transmission | 95 |
| 18.1.2 Acknowledgement | 95 |
| 18.1.3 Transmission retry | 95 |
| 18.1.4 Acknowledgement of addressed safety related messages | 96 |
| 18.1.5 Behaviour of NavStatus 14 reception | 96 |
| 18.2 Interrogation responses | 96 |
| 18.2.1 Method of measurement | 96 |
| 18.2.2 Required results | 96 |
| 19 Specific presentation interface tests | 97 |
| 19.1 General | 97 |
| 19.2 Checking manufacturer's documentation | 97 |
| 19.3 Electrical test | 97 |
| 19.3.1 Method of test | 97 |
| 19.3.2 Required results | 97 |
| 19.4 Test of input sensor interface performance | 97 |
| 19.4.1 Method of measurement | 97 |
| 19.4.2 Required results | 98 |
| 19.5 Test of sensor input | 98 |
| 19.5.1 Test of GNS input | 98 |
| 19.5.2 Test of RMC input | 98 |
| 19.5.3 Test of DTM input | 99 |
| 19.5.4 Test of GBS input | 99 |
| 19.5.5 Test of VBW input | 100 |
| 19.5.6 Test of VTG input | 100 |

| | |
|--|-----|
| 19.5.7 Test of HDT/THS input | 101 |
| 19.5.8 Test of ROT input | 101 |
| 19.5.9 Test of different inputs | 102 |
| 19.5.10 Test of multiple inputs | 102 |
| 19.6 Test of high speed output | 103 |
| 19.6.1 Method of measurement | 103 |
| 19.6.2 Required results | 103 |
| 19.7 High speed output interface performance | 103 |
| 19.7.1 Method of measurement | 103 |
| 19.7.2 Required results | 103 |
| 19.8 Output of undefined VDL messages | 103 |
| 19.8.1 Method of measurement | 103 |
| 19.8.2 Required results | 103 |
| 19.9 Test of high speed input | 103 |
| 19.9.1 Method of measurement | 103 |
| 19.9.2 Required results | 104 |
| 20 Long-range functionality tests | 104 |
| 20.1 Long-range application by two-way interface | 104 |
| 20.1.1 LR interrogation | 104 |
| 20.1.2 LR "all ships" interrogation | 104 |
| 20.1.3 Consecutive LR "all ships" interrogations | 105 |
| 20.2 Long-range application by broadcast | 105 |
| 20.2.1 Long-range broadcast | 105 |
| 20.2.2 Multiple assignment operation | 106 |
| Annex A (informative) Block diagram of AIS | 108 |
| Annex B (normative) AIS interface overview (see Table 13) | 109 |
| Annex C (informative) Block diagram of standard test environment | 110 |
| Annex D (normative) DSC functionality | 111 |
| Annex E (informative) Optional PI port sentences | 117 |
| Annex F (informative) Alarm handling | 121 |
| Annex G (normative) Calculation of area size and distance | 122 |
| Annex H (normative) Transmission of binary Messages 25 and 26 | 125 |
| Bibliography | 129 |
| Figure 1 – OSI layer model | 30 |
| Figure 2 – Power versus time characteristics | 31 |
| Figure 3 – Format for repeating four-packet cluster | 48 |
| Figure 4 – Measurement arrangement for frequency error | 67 |
| Figure 5 – Measurement arrangement for carrier power | 67 |
| Figure 6 – Emission mask for slotted transmission | 68 |
| Figure 7 – Measurement arrangement for modulation accuracy | 69 |
| Figure 8 – Measurement arrangement | 70 |
| Figure 9 – Measurement arrangement with two generators | 71 |
| Figure 10 – SINAD or PER/BER measuring equipment | 74 |
| Figure 11 – Test set-up | 75 |
| Figure 12 – Transmit to receive switching time measurement setup | 76 |

| | |
|---|-----|
| Figure 13 – Regional area scenario | 90 |
| Figure D.1 – Measurement arrangement for inter-modulation..... | 114 |
| | |
| Table 1 – Information reporting intervals for autonomous mode | 19 |
| Table 2 – Integrity alarm conditions signalled using ALR sentence formatter | 22 |
| Table 3 – Sensor status indications signalled using TXT sentence formatter..... | 23 |
| Table 4 – Position sensor fallback conditions..... | 24 |
| Table 5 – Use of accuracy (PA) flag..... | 25 |
| Table 6 – ROT sensor fallback conditions | 26 |
| Table 7 – Message display on MKD | 27 |
| Table 8 – Position quality..... | 28 |
| Table 9 – Transmitter parameters | 31 |
| Table 10 – Power versus time characteristics | 32 |
| Table 11 – Receiver parameters | 32 |
| Table 12 – Use of VDL messages | 33 |
| Table 13 – Presentation interface access..... | 37 |
| Table 14 – IEC 61162-1 sensor sentences..... | 38 |
| Table 15 – AIS High-speed input data and formats | 39 |
| Table 16 – AIS high-speed output data and formats | 40 |
| Table 17 – AIS Long-range communications input data and formats | 42 |
| Table 18 – LR output data formats | 43 |
| Table 19 – LR data types | 44 |
| Table 20 – Content of first two packets | 49 |
| Table 21 – Fixed PRS data derived from Recommendation ITU-T O.153..... | 49 |
| Table 22 – Peak frequency deviation versus time | 69 |
| Table 23 – Tests to be performed | 76 |
| Table 24 – Primary channels for each region | 90 |
| Table E.1 – Property identifier | 118 |
| Table G.1 – Coordinate points | 122 |

INTRODUCTION

In comparison with the previous edition of this Standard, the structural changes to the document are that the original Clause 8 on DSC compatibility together with the corresponding tests in Clause 20 have been moved into a new Annex D. A new Clause on test signals has been added as Clause 10. The original Annex B detailing IEC 61162 sentences has been deleted and replaced with a new Annex H, noting that much of this information is now included in IEC 61162-1. The original Annex C describing long-range applications has also been deleted as IMO has decided to adopt a different system for long-range identification and tracking. A new Annex E has been added to describe optional presentation interface port sentences, a new Annex F has been added on alarm handling and a new Annex G has been added on calculation of area size and distance.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – AUTOMATIC IDENTIFICATION SYSTEMS (AIS)

Part 2: Class A shipborne equipment of the automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results

1 Scope

This part of IEC 61993 specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards adopted by the IMO in Resolution MSC.74(69), Annex 3, Shipborne Automatic Identification System. This standard incorporates the applicable technical characteristics of Class A shipborne equipment included in Recommendation ITU-R M.1371-4 and takes into account the ITU Radio Regulations, where applicable. In addition, it takes account of IMO Resolution A.694(17) to which IEC 60945 is associated. When a requirement in this standard is different from IEC 60945, the requirement of this standard takes precedence.

This part of IEC 61993 also specifies the minimum requirements both for the means to input and display data and for the interfaces to other equipment suitable to be used as means of input and display data.

NOTE All text of this standard, that is identical to that in IMO resolution MSC.74(69), Annex 3 or to that in ITU-R Recommendation M.1371-4 is printed in *italics* and references to the resolution (abbreviated to "A3") or the recommendation (abbreviated to "M.1371") and paragraph numbers are indicated in parentheses, for instance (A3/3.3) or (M.1371/A2-3.3) respectively.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945:2002, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108 (all parts), *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS)*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 62288, *Maritime navigation and radiocommunication equipment and systems – Presentation of navigation-related information on shipborne navigational displays – General requirements, methods of testing and required test results*

IEC 62388, *Maritime navigation and radiocommunication equipment and systems – Shipborne radar – Performance requirements, methods of testing and required test results*

IMO Resolution A.694(17), *General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids*

IMO Resolution MSC.43(64), as amended by MSC.111(73), *Guidelines and Criteria for Ship Reporting Systems*

IMO Resolution MSC.74(69) Annex 3, *Recommendation on performance standards for AIS*

ITU-R Recommendation M.493-13, *Digital selective-calling system for the use in the maritime mobile service*

ITU-R Recommendation M.541-9, *Operational procedures for the use of digital selective-calling (DSC) equipment in the maritime mobile service*

ITU-R Recommendation M.825-3, *Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification*

ITU-R Recommendation M.1084-5, *Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service*

ITU-R Recommendation M.1371-4, *Technical characteristics for an automatic identification system using time division multiple access in the VHF maritime mobile band*

ITU-T Recommendation O.153, *Basic parameters for the measurement of error performance at bit rates below the primary rate*