SVENSK STANDARD SS-EN 50050-2



Fastställd 2014-02-19

Utgåva 1 Sida 1 (1+29) Ansvarig kommitté

SEK TK 31

© Copyright SEK. Reproduction in any form without permission is prohibited.

Handhållen elektrostatisk sprututrustning – Säkerhetsfordringar –

Del 2: Handhållen sprututrustning för ytbeläggning med brännbart pulver

Electrostatic hand-held spraying equipment –

Safety requirements -

Part 2: Hand-held spraying equipment for ignitable coating powder

Som svensk standard gäller europastandarden EN 50050-2:2013. Den svenska standarden innehåller den officiella engelska språkversionen av EN 50050-2:2013.

Nationellt förord

Tidigare fastställd svensk standard SS-EN 50050, utgåva 3, 2006, gäller ej fr o m 2016-10-14.

SS-EN 50050-2, utgåva 1, 2014, SS-EN 50050-1, utgåva 1, 2014 och SS-EN 50050-3, utgåva 1, 2014 ersätter tillsammans SS-EN 50050, utgåva 3, 2006.

ICS 87.100.00

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284 164 29 Kista Tel 08-444 14 00 www.elstandard.se

EUROPEAN STANDARD

EN 50050-2

NORME EUROPÉENNE EUROPÄISCHE NORM

November 2013

ICS 87.100

Supersedes EN 50050:2006 (partially)

English version

Electrostatic hand-held spraying equipment Safety requirements Part 2: Hand-held spraying equipment for ignitable coating powder

Equipement manuel de projection électrostatique Exigences de sécurité Partie 2: Equipement manuel de projection de poudre de revêtement inflammable

Elektrostatische Handsprüheinrichtungen -Sicherheitsanforderungen -Teil 2: Handsprüheinrichtungen für entzündbares Beschichtungspulver

This European Standard was approved by CENELEC on 2013-10-14. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

© 2013 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

Ref. No. EN 50050-2:2013 E

Contents

Page

Forew	ord	3
0 0.1 0.2 0.3	IntroductionProcessExplosion hazardsElectric hazards	4 4
1	Scope	6
2	Normative references	7
3	Terms and definitions	8
4 4.1 4.2 4.3	Requirements for hand-held spraying equipment for ignitable coating powders General requirements Special requirements for hand-held spraying equipment with corona charging Requirements for the accessories	11 11
5 5.1 5.2 5.3 5.4 5.5 5.6	Tests	12 13 13 14
6 6.1 6.2 6.3	Information for use	15 15
Annex	A (normative) Test for ignition protection using a shunt and an oscilloscope	20
Annex B.1 B.2 B.3 B.4 B.5	B (normative) Ignition test within the gas mixture	21 21 21
Annex C.1 C.2 C.3 C.4	C (informative) Quality assurance systems for electrostatic spraying equipment General Electrical assembly Mechanical assembly Tests	23 23 24
Annex	D (normative) Requirements for explosion protection and prevention for ionisators	25
Annex	ZY (informative) Significant changes between this European Standard and EN 50050:2006	26
Annex	ZZ (informative) Coverage of Essential Requirements of EU Directives	28
Biblio	graphy	29
Tables		
Table ²	I — Test intervals	17
Table [1 — Requirements for ionisators	25

Foreword

This document (EN 50050-2:2013) has been prepared by SC 31-8, "Electrostatic painting and finishing equipment", of CLC/TC 31, "Electrical apparatus for potentially explosive atmospheres".

The following dates are fixed:

be withdrawn

•	latest date by which this document has to be implemented at national level by publication of an identical national standard or by	(dop)	2014-10-14
•	endorsement latest date by which the national standards conflicting with this document have to	(dow)	2016-10-14

In combination with EN 50050-1:2013 and EN 50050-3:2013, this document supersedes EN 50050:2006.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

0 Introduction

0.1 Process

During the electrostatic coating process the coating powder is transported in an air stream, or by air, from a powder hopper or other container, up to an applicator. As the powder particles are passing the applicator they are electrostatically charged by means of a high voltage in the range of some tens of kilovolts or triboelectrically and ejected in the form of a cloud which is directed towards the workpiece. The charged powder particles of the cloud are attracted by and applied to the earthed workpiece.

Powder, that is not applied to the workpiece (overspray) is removed by a exhaust ventilation system or other means and transported into the powder recovery unit.

After the coating process the workpieces are introduced into an oven where the powder is melted and cured into a coherent coating.

0.2 Explosion hazards

- **0.2.1** An explosion can occur, if
- the concentration of coating powder in air is above the lower explosion limit,
- an ignition source of appropriate energy for this coating powder cloud is present.

Ignition sources could be, for instance, a hot surface, a naked flame, an electric arc or a spark.

An explosion could be prevented, if at least one condition is avoided. Because it is very difficult to exclude the possibility of ignitable discharges completely, the main focus should be the prevention of ignitable concentrations of coating powder in air.

- **0.2.2** Deflagration of explosive atmospheres is only possible within a given range of concentration above the lower explosion limit.
- NOTE 1 If an explosive cloud of coating powder and air is trapped into a closed room, an explosion can lead to a fatal increase of pressure.
- NOTE 2 The particle size distribution of coating powder is usually in the range of 5 μ m to 120 μ m.
- NOTE 3 Coating powder in air is not evenly distributed inside a given volume, therefore it is possible that a part of the mixture is within the ignitable concentration range. An upper limit is safety-related not applicable.
- **0.2.3** It is important that deposits of powder are not allowed to accumulate within the spraying areas for they may be whirled up and give rise to an explosive atmosphere. This does not apply to deposits on filter devices and accumulations of coating powder in hoppers where filters and hoppers are integrated in the spraying area and are designed to collect the coating powder. See 4.6 of EN 12981:2005.
- **0.2.4** Particular attention should be paid to the prevention of electrostatic charges on different surfaces located in the vicinity of the powder cloud. This could apply to e.g. workpieces during the coating process. Grounding is very critical to the prevention of electrostatic charge to any conductive objects in the spray area.

0.3 Electric hazards

- **0.3.1** Electric shock (by direct or indirect contact) can be generated, for instance, by contact with
- live parts, which are not insulated for operational reasons,
- conductive parts, which are not connected to dangerous voltage during normal operation, but only in case of failure,
- insulated live parts with insufficient or damaged insulation due to external impact.
- **0.3.2** Inadequate earthing may occur, for instance, due to
- faulty connections to the protective earthing system,
- a too high resistance to earth (e. g. contamination by coating powder).

- **0.3.3** Hazards could occur, for instance, if hazardous malfunctions (e.g. shortcut of electronic safety circuits) occur due to interferences of the high voltage equipment and the components of the control and safety systems.
- **0.3.4** Hazardous electrostatic discharges could be generated, for instance, by non-earthed conductive components or by large insulating surfaces, especially if they are backed with conductive material.

1 Scope

1.1 This European Standard specifies the requirements for hand-held or hand-operated electrostatic spraying equipment for ignitable coating powders within a temperature range from 5 °C to 40 °C to be used in explosive atmospheres generated by their own spray cloud.

This European Standard deals with all electrical hazards significant for the electrostatic spraying of coating powders, which could also contain small quantities of added metal particles, if the work is carried out under conditions recommended by the manufacturer. In particular, this includes ignition hazards resulting from the generated explosive atmosphere. This European Standard specifies the design-related and test requirements for electrostatic spraying equipment of type A-P according to Table 1 of EN 50177:2009.

- **1.2** With regard to explosion protection and prevention measures, this standard also applies to ionisators with corona charging. Ionisators used together with or under similar conditions as electrostatic spraying equipment for ignitable coating powders are considered to be equipment of group II, category 2D for use in potentially explosive areas of zone 21 or 22. All other parts of ionisators are considered to be equipment of category 3D if they are installed or used in potentially explosive areas of zone 22, see Annex D.
- **1.3** Electrostatic applicators are considered to be equipment of group II, category 2D for use in potentially explosive areas of zone 21 or 22, which have been generated by the equipment itself. All other parts of hand-held electrostatic spraying equipment are considered to be equipment of category 3D if they are installed or used in potentially explosive areas of zone 22.
- **1.4** All other significant hazards relevant for applicators (e.g. ejection of powder, mechanical strength, electrical hazards (apart from the electrostatic hazards)), noise, explosion, contract with or inhalation of dangerous substances, ergonomics) are covered by EN 1953.
- **1.5** This European Standard also gives details regarding quality assurance systems for electrostatic spraying equipment, see Annex C.
- **1.6** Additional requirements may be applicable to equipment designed for use in food and pharmaceutical industry.
- 1.7 This European Standard does not apply to
- zone classification of the areas in and around spray booths [see EN 12981],
- zone classification of other areas with potentially explosive atmosphere [see EN 60079-10-2],
- selection, erection and application of other electrical and non-electrical equipment in areas with explosion hazard [see EN 60079-14 and EN 12981],
- cleaning of spraying areas, see instruction manual of the spray booth,
- fire prevention and protection, for instance fire hazards due to other sources [see EN 12981],
- dust hazards [see EN 12981].

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1149-5	Protective clothing – Electrostatic properties – Part 5: Performance requirements
EN 1953	Atomising and spraying equipment for coating materials – Safety requirements
EN 12981:2005	Coating plants – Spray booths for application of organic powder coating material – Safety requirements
EN 50177:2009	Stationary electrostatic application equipment for ignitable coating powders – Safety requirements
EN 60079-0	Explosive atmospheres - Electrical apparatus for explosive gas atmospheres – Part 0: General requirements (IEC 60079-0)
EN 60079-7:2007	Explosive atmospheres – Part 7: Equipment protection by increased safety "e" (IEC 60079-7:2006)
EN 60204-1	Safety of machinery – Electrical equipment of machines – Part 1: General requirements (IEC 60204-1)
EN 60529	Degrees of protection provided by enclosures (IP code) (IEC 60529)
EN 61340-4-1	Electrostatics – Part 4-1: Standard test methods for specific applications – Electrical resistance of floor coverings and installed floors (IEC 61340-4-1)
EN 62061	Safety of machinery – Functional safety of safety-related electrical, electronic and programmable electronic control systems (IEC 62061)
EN ISO 12100	Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100)
EN ISO 13849-1	Safety of machinery - Safety-related parts of control systems - Part 1: General principles for design (ISO 13849-1)
EN ISO 20344	Personal protective equipment – Test methods for footwear (ISO 20344)