



IEC 61196-1-111

Edition 2.0 2014-06

INTERNATIONAL STANDARD



**Coaxial communication cables –
Part 1-111: Electrical test methods – Stability of phase test methods**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

S

ICS 33.120.10

ISBN 978-2-8322-1660-6

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
1 Scope.....	6
2 Normative references	6
3 Terms and definitions	6
4 Phase variation with temperature.....	8
4.1 Purpose	8
4.2 Equipment	8
4.3 Test sample	8
4.4 Test environment	9
4.5 Preconditioning.....	9
4.6 Test procedure.....	9
4.7 Test result.....	11
4.7.1 Calculation of temperature coefficient of phase.....	11
4.7.2 Graph of phase temperature change.....	12
4.7.3 Maximum variation value of phase variation with temperature.....	12
4.7.4 Ratio of the relative phase temperature coefficient	12
4.8 Test report	12
4.9 Requirement	12
5 Phase constant variation with temperature	12
5.1 Purpose	12
5.2 Equipment	13
5.3 Test sample	13
5.4 Test environment	13
5.5 Preconditioning.....	13
5.6 Test procedure.....	13
5.7 Test result.....	13
5.8 Test report	14
5.9 Requirement	14
6 Phase stability with bending	14
6.1 Purpose	14
6.2 Test environment	14
6.3 Test sample	14
6.4 Equipment	15
6.5 Test procedure.....	15
6.6 Test report	16
6.7 Requirement	17
7 Phase stability with twisting	17
7.1 Purpose	17
7.2 Test environment	17
7.3 Test sample	17
7.4 Equipment	17
7.5 Test procedure.....	18
7.6 Test report	18
7.7 Requirement	19

Annex A (informative) Example for recording and calculating the phase variation with temperature	20
Figure 1 – Test sample (TS)	9
Figure 2 – Preconditioning	9
Figure 3 – TS placement diagram	10
Figure 4 – Phase–frequency graph schematic diagram	11
Figure 5 – Test sample (TS)	15
Figure 6 – Bending test.....	16
Figure 7 – Test graph schematic diagram	17
Figure 8 – Twist test	18
Figure 9 – Test graph schematic diagram	19
Figure A.1 – $\eta_{t,f} - T$ (°C) graph	21
Table A.1 – Test record and calculation	20

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COAXIAL COMMUNICATION CABLES –**Part 1-111: Electrical test methods –
Stability of phase test methods**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61196-1-111 has been prepared by subcommittee 46A: Coaxial cables, of IEC technical committee 46: Cables, wires, waveguides, R.F. connectors, R.F. and microwave passive components and accessories.

The text of this standard is based on the following documents:

FDIS	Report on voting
46A/1188A/FDIS	46A/1212/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This second edition cancels and replaces the first edition published in 2005. This edition constitutes a technical revision. This edition includes the following significant technical changes with respect to the previous edition:

- a new Clause 4 Phase variation with temperature;
- a new Clause 6 Phase stability with bending;
- a new Clause 7 Phase stability with twisting.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61196 series, published under the general title *Coaxial communication cables*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

COAXIAL COMMUNICATION CABLES –

Part 1-111: Electrical test methods – Stability of phase test methods

1 Scope

This part of IEC 61196 applies to coaxial communication cables. It specifies methods for determining the stability of phase of coaxial communication cables.

- phase variation with temperature (Clause 4);
- phase constant variation with temperature (Clause 5);
- phase stability with bending (Clause 6);
- phase stability with twisting (Clause 7).

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61196-1, *Coaxial communication cables – Part 1: Generic specification – General, definitions and requirements*

IEC 61196-1-108:2011, *Coaxial communication cables – Part 1-108: Electrical test methods – Test for characteristic impedance, phase and group delay, electrical length and propagation velocity*