

© Copyright SEK. Reproduction in any form without permission is prohibited.

Elektronisk utrustning för järnvägar – Kommunikationsnätverk för tåg (TCN) – Del 3-4: Ethernet Consist Network (ECN)

*Electronic railway equipment –
Train communication network (TCN) –
Part 3-4: Ethernet Consist Network (ECN)*

Som svensk standard gäller europastandarden EN 61375-3-4:2014. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61375-3-4:2014.

Nationellt förord

Europastandarden EN 61375-3-4:2014

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61375-3-4, First edition, 2014 - Electronic railway equipment - Train communication network (TCN) - Part 3-4: Ethernet Consist Network (ECN)**

utarbetad inom International Electrotechnical Commission, IEC.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English Version

**Electronic railway equipment - Train communication network
(TCN) - Part 3-4: Ethernet Consist Network (ECN)
(IEC 61375-3-4:2014)**

Matériel électronique ferroviaire - Réseau embarqué de
train (TCN) - Partie 3-4: Réseau Ethernet de Rame (ECN)
(CEI 61375-3-4:2014)

Elektronische Betriebsmittel für Bahnen - Zugbus - Teil 3-4:
ECN - Ethernet-Zugverband-Netzwerk
(IEC 61375-3-4:2014)

This European Standard was approved by CENELEC on 2014-04-23. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 9/1873/FDIS, future edition 1 of IEC 61375-3-4, prepared by IEC/TC 9 "Electrical equipment and systems for railways" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61375-3-4:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-01-23
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-04-23

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61375-3-4:2014 was approved by CENELEC as a European Standard without any modification.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61076-2-101	-	Connectors for electronic equipment - Product EN 61076-2-101 requirements - Part 2-101: Circular connectors - Detail specification for M12 connectors with screw-locking		-
IEC 61076-3-104	-	Connectors for electronic equipment - Product EN 61076-3-104 requirements - Part 3-104: Detail specification for 8-way, shielded free and fixed connectors for data transmissions with frequencies up to 1000 MHz		-
IEC 61156-6	-	Multicore and symmetrical pair/quad cables for digital communications - Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz - Work area wiring - Sectional specification	-	-
IEC 61375-1	-	Electronic railway equipment - Train communication network (TCN) - Part 1: General architecture	EN 61375-1	-
IEC 61375-2-1	-	Electronic railway equipment - Train communication network (TCN) - Part 2-1: Wire Train Bus (WTB)	EN 61375-2-1	-
IEC 61375-2-5	-	Electronic railway equipment - Train backbone - Part 2-5: Ethernet Train Backbone	EN 61375-2-5	-
IEC 62439 series	-	High availability automation networks	EN 62439 ¹⁾	-
ISO/IEC 7498 series	-	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	-	-
ISO/IEC 8824 series	-	Information technology - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1)	-	-
ISO/IEC 11801	-	Information technology - Generic cabling for customer premises	-	-

¹⁾ EN 62439 is superseded by EN 62439-6:2010, which is based on IEC 62439-6:2010.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEEE 802.3	-	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) - Access Method and Physical Layer Specifications	-	-
IEEE 802.1Q	-	IEEE Standard for Local and Metropolitan Area Networks: Virtual Bridged Local Area Networks	-	-
IEEE 802.1D	-	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
ANSI/TIA/EIA 568-B.1	2001	Commercial Building Telecommunications Cabling Standard - Part 1: General requirements	-	-
ANSI X3.263	1995	EN-Information Technology - Fibre Distributed - Data Interface (FDDI) - Token Ring Twisted Pair Physical Layer Medium Dependent (TP-PMD)	-	-

CONTENTS

FOREWORD.....	9
INTRODUCTION.....	11
1 Scope.....	12
2 Normative references	12
3 Terms, definitions, symbols, abbreviations and conventions	13
3.1 Terms and definitions.....	13
3.2 Symbols and abbreviated terms	14
3.3 Conventions.....	17
3.3.1 Bit numbering conventions.....	17
3.3.2 Byte order conventions	17
3.3.3 Data types	17
4 Common part.....	18
4.1 General.....	18
4.2 Architecture	18
4.2.1 Network structure	18
4.2.2 Network topology.....	19
4.2.3 End Device classes	20
4.2.4 Network Device types and Consist Switch classes	21
4.3 Data class.....	22
4.4 Functions and services	23
4.5 Redundancy.....	24
4.5.1 General	24
4.5.2 Definitions	25
4.5.3 Redundancy managed at network level.....	25
4.5.4 Redundancy managed at End Device level	26
4.6 Quality of service	27
4.6.1 General	27
4.6.2 Priority level	27
4.6.3 Assignment of priority level.....	28
4.6.4 Consist Switch behavior	28
4.6.5 Ingress rate limiting	28
4.6.6 Egress rate shaping.....	29
4.7 IP address and related definitions	29
4.7.1 Consist Network address	29
4.7.2 Train Network Address	29
4.7.3 Group Address	30
4.7.4 Name resolution and naming definitions	30
4.8 IP address and network configuration management	31
4.8.1 Consist Network address management.....	31
4.8.2 Train network address management	31
4.8.3 Static network configuration parameters	32
4.8.4 DHCP configuration parameters	32
4.8.5 IP address management for TBN redundancy	33
4.9 Network Device interface	34
4.9.1 General	34

4.9.2	Function requirements	34
4.9.3	Performance requirements.....	36
4.9.4	Physical Layer	36
4.9.5	Link Layer.....	39
4.9.6	Network Layer	39
4.9.7	Transport Layer	39
4.9.8	Application layers	40
4.10	End Device interface.....	40
4.10.1	General	40
4.10.2	Physical Layer	42
4.10.3	Link Layer.....	43
4.10.4	Network layer	43
4.10.5	Transport Layer	43
4.10.6	Application layer	43
4.11	Gateway functions	44
4.11.1	WTB gateway functions	44
4.11.2	ETB gateway functions	44
4.12	Network management	45
4.12.1	ECN network management	45
4.12.2	WTB network management	45
4.12.3	ETB network management.....	45
5	Conformance test	45
Annex A	(informative) Reliability and availability comparison between ECN architectures.....	46
A.1	General.....	46
A.2	Failure cases	46
A.2.1	Definitions	46
A.2.2	Example of failure cases – Linear topology	47
A.2.3	Example of failure cases – Parallel networks	48
A.2.4	Example of failure cases – Ring topology	49
A.2.5	Example of failure cases – Ladder topology.....	50
A.3	Redundancy level of ECN architecture	52
A.4	Reliability analysis of redundancy level.....	53
A.5	Redundancy of End Devices	55
Annex B	(informative) Railway-Network Address Translation (R-NAT)	57
B.1	General.....	57
B.2	Local Consist subnet IP address	57
B.3	TBN R-NAT	58
B.4	Interoperability issue between TBNs	58
Annex C	(normative) Transceiver with amplified signals protocol definition	60
C.1	General.....	60
C.2	Type A: Transceiver with amplified signals for Physical Layer based on IEEE 802.3 (10BASE-T).....	60
C.2.1	General	60
C.2.2	Transceiver unit.....	60
C.2.3	Transmission signal characteristics	61
C.2.4	Reception signal characteristics	64
C.3	Type B: Transceiver with amplified signals for Physical Layer based on IEEE 802.3 (100BASE-TX).....	65

C.3.1	General	65
C.3.2	Transceiver unit.....	65
C.3.3	Transmission signal characteristics	66
C.3.4	Reception signal characteristics	66
Annex D (informative)	Ladder topology protocol definition.....	68
D.1	General.....	68
D.2	Architecture of Consist Network Node	68
D.2.1	General	68
D.2.2	Concept of ladder topology	68
D.2.3	Configuration of ladder topology	69
D.2.4	Functional structure of Consist Network Node.....	70
D.2.5	Traffic Store for Process Data.....	72
D.2.6	Redundancy in ladder topology.....	73
D.2.7	Configuration parameters for ladder topology	75
D.2.8	Signal connection for trunk link	76
D.2.9	Local link connection	77
D.3	Link Layer.....	77
D.3.1	General	77
D.3.2	MAC – Media Access Control	78
D.3.3	IP address and IP address management.....	101
D.4	Consist Network Node management protocol	101
D.4.1	General	101
D.4.2	Architecture of CNN management.....	102
D.4.3	Individual CNN management information	102
D.4.4	CNN management database	105
D.4.5	Primitives for CNN management protocol	107
D.4.6	Parameters for CNN management protocol.....	107
D.4.7	Timers for CNN management protocol	108
D.4.8	Procedures for CNN management protocol	109
D.4.9	Operation of CNN management machine	112
D.4.10	Port number assignment for CNN management protocol	114
D.5	Failure cases in ladder topology.....	115
D.5.1	General	115
D.5.2	Failure cases	115
D.5.3	Restore of the network.....	119
Bibliography		120
Figure 1	– Logical view of the ECN	19
Figure 2	– Examples of ECN physical topologies	20
Figure 3	– Example of network components.....	25
Figure 4	– Examples of dual homing	27
Figure 5	– D-coded M12 connector	38
Figure 6	– Logical structure of the gateway between ECN and WTB	44
Figure A.1	– Example of single network component failure	46
Figure A.2	– Example of double network component failures	47
Figure A.3	– Example of a single component failure at a link on linear topology	47
Figure A.4	– Example of a single component failure at an active component on linear topology.....	48

Figure A.5 – Example of a single component failure at a link on parallel networks	48
Figure A.6 – Example of a single component failure at an active component on parallel networks	49
Figure A.7 – Example of a single component failure at a link on ring topology	49
Figure A.8 – Example of a single component failure at an active component on ring topology	50
Figure A.9 – Example of a single component failure at an active component on ring topology (with dual homing ED)	50
Figure A.10 – Example of a single component failure at a link on a ladder topology	51
Figure A.11 – Example of a single component failure at an active component on ladder topology	51
Figure A.12 – Example of double component failures at links on ladder topology	51
Figure A.13 – Example of double component failures at active components on ladder topology (with bypass)	52
Figure A.14 – Example of ECN architecture classified by redundancy level	53
Figure B.1 – Example of ECN local IP range, “shadow” of train IP range for R-NAT	57
Figure B.2 – Example of Railway Network Translation (R-NAT)	58
Figure B.3 – From R-NAT TBN to TBN	59
Figure B.4 – From TBN to R-NAT TBN	59
Figure C.1 – Block diagram of transceiver unit for 10BASE-T MAU	61
Figure C.2 – Differential output voltage test	61
Figure C.3 – Twisted-pair model	62
Figure C.4 – Amplified voltage template	62
Figure C.5 – Amplified transmitter waveform for start of TP_IDL	63
Figure C.6 – Start-of-TP_IDL test load	64
Figure C.7 – Amplified transmitter waveform for link test pulse	64
Figure C.8 – Amplified receiver differential input voltage – narrow pulse	65
Figure C.9 – Amplified receiver differential input voltage – wide pulse	65
Figure C.10 – Block diagram of transceiver unit	66
Figure C.11 – Signal_detect assertion threshold	67
Figure D.1 – Concept of ladder topology	69
Figure D.2 – Configuration of ladder topology	69
Figure D.3 – Basic flows of data frames on trunk links and local links in ladder topology	70
Figure D.4 – Functional structure of Consist Network Node	72
Figure D.5 – Concept of Traffic Store in ladder topology	73
Figure D.6 – Example of configuration of ladder topology	74
Figure D.7 – Block diagram of the transceiver unit for a single twisted pair connection	77
Figure D.8 – Cable connection for a single twisted pair	77
Figure D.9 – Example of CNN number assignment in ladder topology	79
Figure D.10 – Frame format for the commands	80
Figure D.11 – Link establishment between two CNNs	82
Figure D.12 – Link establishment in ladder topology	83
Figure D.13 – Local links between redundant CNNs	83
Figure D.14 – Example of CNN modes	83
Figure D.15 – Structure and primitives of Real Time MAC sub-layer	85

Figure D.16 – TPCM state machine	90
Figure D.17 – ACM state machine.....	93
Figure D.18 – State diagram of USE_TOKEN.....	95
Figure D.19 – Example of sequence of transmission	99
Figure D.20 – Architecture of CNN management.....	102
Figure D.21 – State diagram for CNNMM	113
Figure D.22 – Normal configuration of transmission paths in ladder topology	115
Figure D.23 – Re-configuration of transmission paths with a single link failure in a sub-network.....	116
Figure D.24 – Re-configuration of transmission paths with a single CNN failure in a sub-network	116
Figure D.25 – Re-configuration of transmission paths with double failures of links in a sub-network	117
Figure D.26 – Re-configuration of transmission paths with double failures of links over both sub-networks	117
Figure D.27 – Re-configuration of transmission paths with double failures of CNNs over both sub-networks	118
Figure D.28 – Re-configuration of transmission paths with double failures of a link and a CNN over both sub-networks	118
Figure D.29 – Re-configuration of transmission paths with double failures of a link and a CNN over both sub-networks	119
Table 1 – End Device classes (1).....	21
Table 2 – End Device classes (2).....	21
Table 3 – Network Device types.....	22
Table 4 – Consist Switch classes	22
Table 5 – Data class service parameters	23
Table 6 – Typical values for data class service parameters.....	23
Table 7 – Mapping of priorities to data classes	28
Table 8 – End Device static network configuration parameters.....	32
Table 9 – DHCP options	33
Table 10 – Summary of Network Device interfaces	34
Table 11 – Pinning for D-coded M12 connector.....	38
Table 12 – Summary of End Device interfaces	41
Table A.1 – Redundancy level of ECN architecture	52
Table A.2 – Reliability of redundancy level.....	54
Table A.3 – Reliability when common cause failures are considered	54
Table A.4 – Parameters for reliability and availability calculation	55
Table A.5 – Reliability and availability example values.....	55
Table A.6 – Reliability with ED redundancy comparison	56
Table A.7 – Comparison of MTBFs ratios with ED redundancy	56
Table C.1 – Output voltage template table	63
Table C.2 – Twisted pair active output interface.....	66
Table D.1 – Configuration parameters for CNN in sub-network 1	75
Table D.2 – Configuration parameters for CNN in sub-network 2	75

Table D.3 – Configuration_Process_Data_Transmission_Substitute.....	76
Table D.4 – Type_Configuration_Substitute	76
Table D.5 – Signal connection between transceivers (single twisted pair)	77
Table D.6 – CNN number	78
Table D.7 – Contents of the Destination Address field	80
Table D.8 – Contents of the Source Address field	80
Table D.9 – Contents of the Length/Type field	80
Table D.10 – Contents of command and check code fields.....	81
Table D.11 – Contents of the Padding field	81
Table D.12 – CNN mode for CNN in ladder topology	84
Table D.13 – Physical layer primitives	85
Table D.14 – Variables and parameters for real time MAC protocol.....	86
Table D.15 – Frame name	87
Table D.16 – Timers for real time MAC protocol.....	87
Table D.17 – Procedures for real time MAC protocol.....	88
Table D.18 – Events for real time MAC protocol.....	88
Table D.19 – TRRC primitives.....	88
Table D.20 – TRRC operation on acceptance of request primitives	89
Table D.21 – TRRC operation on acceptance of physical indication primitives	89
Table D.22 – State transition table for TPCM	91
Table D.23 – Procedures in TPCM state machine	92
Table D.24 – TPCM primitives	92
Table D.25 – State transition table for ACM	94
Table D.26 – State transition table for USE_TOKEN	96
Table D.27 – Variable for ACM	97
Table D.28 – Configuration parameters for real time MAC.....	97
Table D.29 – Time elements for sequence of transmission.....	99
Table D.30 – Data class service parameters	100
Table D.31 – Notation for IP address fields	101
Table D.32 – Format of individual CNN management information.....	103
Table D.33 – Description of parameters for individual CNN management information.....	104
Table D.34 – Type_Connection_Status	105
Table D.35 – Type_CNN_Flags.....	105
Table D.36 – Type_Ip_Addr_3_4.....	105
Table D.37 – Parameters of CNN management database	106
Table D.38 – Type_Connection_Status_All	106
Table D.39 – Type_Ip_Addr_3_4_All.....	107
Table D.40 – Type_Healthy_Count_All.....	107
Table D.41 – Primitives to the lower protocol layer for CNN management	107
Table D.42 – Parameters for CNN management.....	108
Table D.43 – Timers for CNN management.....	109
Table D.44 – Procedures for CNN management.....	109
Table D.45 – Functions for substitution transmission by detecting bypassed CNN	110

Table D.46 – Functions for substitution transmission by detecting link failure.....	112
Table D.47 – Events for CNN management.....	112
Table D.48 – State transition table for CNNMM.....	114
Table D.49 – Default port number for CNN management protocol	115

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ELECTRONIC RAILWAY EQUIPMENT –
TRAIN COMMUNICATION NETWORK (TCN) –****Part 3-4: Ethernet Consist Network (ECN)**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61375-3-4 has been prepared by IEC technical committee 9: Electrical equipment and systems for railways.

The text of this standard is based on the following documents:

FDIS	Report on voting
9/1873/FDIS	9/1904/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 61375 series, under the general title *Electronic railway equipment – Train communication network (TCN)*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 61375 series of international standards specifies the Consist Network based on Ethernet technology, i.e. the Ethernet Consist Network (ECN) within the TCN architecture as defined in IEC 61375-1, and End Devices which can attach to the ECN. In addition gateway services between Train Backbone and ECN are specified.

The general architecture of the TCN (see IEC 61375-1) defines a hierarchical structure with two levels of networks, Train Backbone(s) and Consist Network(s). This hierarchical structure specifies Consist Networks based on different technologies such as MVB, CANopen and ECN interfacing one Train Backbone. ECNs based on different design and implementation may be interfaced to the same Train Backbone reaching the result that the Train Backbone ensures interoperability between Consist Networks with different implementations.

The common part, consisting of Clauses 1 to 4, defines requirements and specifications which are common to all ECN implementations and End Devices and gateways.

The common part defines

- the data communication interface of End Devices connected to the ECN,
- functions and services provided by the ECN to End Devices,
- the gateway functions for data transfer between Train Backbone and the ECN, and
- performances of the ECN.

ELECTRONIC RAILWAY EQUIPMENT – TRAIN COMMUNICATION NETWORK (TCN) –

Part 3-4: Ethernet Consist Network (ECN)

1 Scope

This part of IEC 61375 specifies the data communication network inside a Consist based on Ethernet technology, the Ethernet Consist Network (ECN).

The applicability of this part of IEC 61375 to the Consist Network allows for interoperability of individual vehicles within Open Trains in international traffic.

This part of IEC 61375 may be additionally applicable to closed trains and Multiple Unit Trains when so agreed between purchaser and supplier.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61076-2-101, *Connectors for electronic equipment – Product requirements – Part 2-101: Circular connectors – Detail specification for M12 connectors with screw-locking*

IEC 61076-3-104, *Connectors for electronic equipment – Product requirements – Part 3-104: Detail specification for 8-way, shielded free and fixed connectors for data transmissions with frequencies up to 1 000 MHz*

IEC 61156-6, *Multicore and symmetrical pair/quad cables for digital communications – Part 6: Symmetrical pair/quad cables with transmission characteristics up to 1 000 MHz – Work area wiring – Sectional specification*

IEC 61375-1, *Electronic railway equipment – Train Communication Network (TCN) – Part 1: General architecture*

IEC 61375-2-1, *Electronic railway equipment – Train Communication Network (TCN) – Part 2-1: Wire Train Bus (WTB)*

IEC 61375-2-5, *Electronic railway equipment – Train Communication Network (TCN) – Part 2-5: Ethernet Train Backbone (ETB)*

IEC 62439 (all parts), *Industrial communication networks – High availability automation networks*

ISO/IEC 7498, *Information technology – Open Systems Interconnection (OSI) – The Basic reference model*

ISO/IEC 8824 (all parts), *Information technology – Abstract Syntax Notation One (ASN.1)*

ISO/IEC 11801, *Information technology – Generic cabling for customer premises*

TIA/EIA-568-B, *Commercial Building Telecommunications Cabling Standard – Part 1: General Requirements (ANSI/TIA/EIA-568-B.1-2001)*

ANSI X3.263:1995, *EN-Information Technology - Fibre Distributed Data Interface (FDDI) - Token Ring Twisted Pair Physical Layer Medium Dependent (TP-PMD) (order number ANSI INCITS 263)*

IEEE 802.1D, *IEEE Standard for Local and metropolitan area networks – Media Access Control (MAC) Bridges*

IEEE 802.1Q, *IEEE Standard for Local and metropolitan area networks – Virtual Bridged Local Area Networks*

IEEE 802.3, *IEEE Standard for Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*