

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Fältbuss – Del 4-1: Specifikation av protokoll i datalänkskiktet – Delar i fältbuss, Typ 1

*Industrial communication networks –
Fieldbus specifications –
Part 4-1: Data-link layer protocol specification –
Type 1 elements*

Som svensk standard gäller europastandarden EN 61158-4-1:2014. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61158-4-1:2014.

Nationellt förord

Europastandarden EN 61158-4-1:2014

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61158-4-1, Second edition, 2014 - Industrial communication networks - Fieldbus specifications - Part 4-1: Data-link layer protocol specification - Type 1 elements**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 61158-4-1, utgåva 1, 2008, gäller ej fr o m 2017-09-19.

ICS 25.040.40; 35.100.20; 35.110.00

Denna standard är fastställd av SEK Svensk Elstandard,
som också kan lämna upplysningar om **sakinnehållet** i standarden.
Postadress: Box 1284, 164 29 KISTA
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: www.elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English Version

**Industrial communication networks - Fieldbus specifications -
Part 4-1: Data-link layer protocol specification - Type 1 elements
(IEC 61158-4-1:2014)**

Réseaux de communication industriels - Spécifications des
bus de terrain - Partie 4-1: Spécification du protocole de la
couche liaison de données - Éléments de type 1
(CEI 61158-4-1:2014)

Industrielle Kommunikationsnetze - Feldbusse - Teil 4:
Protokollspezifikation des Data Link Layer
(Sicherheitsschicht) - Typ 1-Elemente
(IEC 61158-4-1:2014)

This European Standard was approved by CENELEC on 2014-09-19. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 65C/762/FDIS, future edition 2 of IEC 61158-4-1, prepared by IEC/TC 65C "Industrial networks" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61158-4-1:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-06-19
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-09-19

This document supersedes EN 61158-4-1:2008.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61158-4-1:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61158-5-5:2014	NOTE	Harmonised as EN 61158-5-5:2014
IEC 61158-6-5:2014	NOTE	Harmonised as EN 61158-6-5:2014
IEC 61784-1	NOTE	Harmonised as EN 61784-1
IEC 61784-2	NOTE	Harmonised as EN 61784-2

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61158-1	2014	Industrial communication networks - Fieldbus specifications - Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series	EN 61158-1	2014
IEC 61158-2	2014	Industrial communication networks - Fieldbus specifications - Part 2: Physical layer specification and service definition	EN 61158-2	2014
IEC 61158-3-1	2014	Industrial communication networks - Fieldbus specifications - Part 3-1: Data-link layer service definition - Type 1 elements	EN 61158-3-1	2014
ISO/IEC 7498-1	-	Information technology - Open Systems Interconnection - Basic reference model: The basic model	-	-
ISO/IEC 7498-3	-	Information technology - Open Systems Interconnection - Basic reference model: Naming and addressing	-	-
ISO/IEC 8886	-	Information technology - Open Systems Interconnection - Data link service definition	-	-
ISO/IEC 10038	1993	Information technology - Telecommunications and information exchange between systems - Local area networks - Media Access Control (MAC) bridges	-	-
ISO/IEC 10731	-	Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services	-	-

CONTENTS

FOREWORD.....	9
0 INTRODUCTION	11
0.1 General.....	11
0.2 Nomenclature for references within this standard	11
1 Scope.....	12
1.1 General.....	12
1.2 Specifications.....	12
1.3 Procedures.....	12
1.4 Applicability.....	13
1.5 Conformance.....	13
2 Normative references	13
3 Terms, definitions, symbols and abbreviations.....	14
3.1 Reference model terms and definitions.....	14
3.2 Service convention terms and definitions.....	16
3.3 Terms and definitions	16
3.4 Symbols and abbreviations.....	25
4 Overview of the DL-protocol	29
4.1 Three-level model of the DLL	29
4.2 Service provided by the DLL.....	31
4.3 Structure and definition of DL-addresses	38
4.4 Service assumed from the PhL	50
4.5 Functions of the DLL	52
4.6 Functional classes.....	55
4.7 Local parameters, variables, counters, timers and queues.....	56
5 General structure and encoding of PhIDUs and DLPDUs, and related elements of procedure.....	70
5.1 PhIDU structure and encoding.....	70
5.2 Common DLPDU structure, encoding and elements of procedure	70
6 DLPDU-specific structure, encoding and elements of procedure	81
6.1 Establish connection (EC) DLPDU.....	83
6.2 Disconnect connection (DC) DLPDU.....	85
6.3 Reset connection (RC) DLPDU.....	88
6.4 Compel acknowledgement (CA) DLPDU	89
6.5 Compel data (CD) DLPDU	96
6.6 Exchange data (ED) DLPDU.....	103
6.7 Data (DT) DLPDU.....	111
6.8 Status response (SR) DLPDU.....	118
6.9 Compel time (CT) DLPDU	121
6.10 Time distribution (TD) DLPDU	123
6.11 Round-trip-delay query (RQ) DLPDU	125
6.12 Round-trip-delay reply (RR) DLPDU	127
6.13 Probe node DL-address (PN) DLPDU	129
6.14 Probe response (PR) DLPDU	131
6.15 Pass token (PT) DLPDU	133
6.16 Execute sequence (ES) DLPDU	141
6.17 Return token (RT) DLPDU	148

6.18	Request interval (RI) DLPDU	149
6.19	Claim LAS (CL) DLPDU	150
6.20	Transfer LAS (TL) DLPDU	152
6.21	Wakeup (WK) DLPDU	155
6.22	Idle (IDLE) DLPDU	157
6.23	Spare DLPDUs	158
6.24	Reserved (not to be used) DLPDUs	159
7	DLPDU-parameter structure and encoding	160
7.1	Structure and encoding of EC-PARAMETERS	160
7.2	Structure and encoding of DC-PARAMETERS	165
7.3	Structure and encoding of RC-PARAMETERS	166
7.4	Structure and encoding of SD-Parameters	168
7.5	Structure and encoding of SR-parameters	176
7.6	Structure and encoding of TD-parameters	176
7.7	Structure and encoding of RQ-parameters	179
7.8	Structure and encoding of RR-parameters	179
7.9	Structure and encoding of PN-parameters	180
7.10	Structure and encoding of DD-parameters	182
8	DL-service elements of procedure	182
8.1	Operation of the DL(SAP)-address, buffer and queue management services	183
8.2	Operation of the connection-mode services	186
8.3	Operation of the connectionless-mode services	226
8.4	Operation of the scheduling guidance services	237
9	DL-support subprotocol	246
9.1	General	246
9.2	Overview of LAS operation	247
9.3	DL-support subprotocol definition	247
9.4	Elements of Procedures for receiving SPDUs	280
10	Other DLE elements of procedure	282
10.1	DLE initialization	282
10.2	LAS behavior and operation	286
10.3	DL-support operation	293
10.4	DL-bridge elements of procedure and bridge sub-protocol	298
10.5	DL-management-information	328
10.6	Implementation profiles	332
11	PICS proforma	337
11.1	Introduction	338
11.2	General	338
11.3	Normative references	338
11.4	Definitions	338
11.5	Abbreviations	338
11.6	Conformance	339
11.7	Instructions	339
11.8	Identification	339
11.9	Implementation profile	340
11.10	Major low-level capabilities	344
11.11	Major high-level capabilities	357
Annex A	(informative) Exemplary FCS implementation	366

Annex B (informative) Type 1: Formal protocol finite state machines.....	368
B.1 Basic reception and transmission FSMs	368
B.2 FSMs for DLCs	379
B.3 FSMs for scheduling.....	385
B.4 FSMs for bridges	385
Annex C (informative) Type 1: DLPDU and DL-addressing short-form summaries	387
C.1 Fields used in short-form summaries	387
C.2 DLPDU short-form summary grouped by function	388
C.3 DLPDU short-form summary in alphabetic order of DLPDU names	390
C.4 DLPDU short-form summary in alphabetic order of DLPDU acronyms.....	391
C.5 DLPDU FC code-point assignment matrix – overview and detail	392
C.6 SD-parameters (status and data-description parameters) of CA, CD, ED and DT DLPDUs.....	395
C.7 EC parameters of EC DLPDUs	398
C.8 Parameters of DC and RC DLPDUs.....	400
C.9 Parameters of TD, RQ and RR DLPDUs	401
C.10 Parameters of PN, PT, ES and RI DLPDUs	404
C.11 Addressing summary extracted from figures and tables of 4.3	404
Bibliography.....	409
Figure 1 – Relationships of DLSAPs, DLSAP-addresses, DLCEPs, DLCEP-addresses, DLSEP-addresses and group DL-addresses	19
Figure 2 – Basic structure of a DL-address	38
Figure 3 – Basic structure of a sublink selector	39
Figure 4 – DL-address alternative structures.....	39
Figure 5 – Basic structure of MAC-addresses	49
Figure 6 – Representation of a DL-address as a MAC-address	49
Figure 7 – Linear relationships of sending and receiving DLCEP sequence-number variables.....	62
Figure 8 – DL-address alternative structures.....	73
Figure 9 – SHORT DL-address field – alternative implicit structures.....	74
Figure 10 – NODE DL-address field – implicit structure	74
Figure 11 – State transition diagram for a DLCEP.....	187
Figure 12 – Projection of the sending and receiving DLCEP sequence-number variables of Figure 7 onto the cyclic sequence-number parameters of CA, CD, DT, ED and RC DLPDUs, with consequent determination of required actions	203
Figure 13 – State transitions of a DLE	283
Figure 14 – Bridged network topology	299
Figure 15 – Spanning tree representation	300
Figure 16 – DLSDU transit delay, DLPDU lifetime and bridge forwarding delay	304
Figure 17 – Forwarding and delivering a received DLPDU	308
Figure 18 – Forwarding a locally-originated DLPDU	309
Figure 19 – Republishing a DLSDU received from another link	310
Figure 20 – Bridge architecture.....	311
Figure 21 – Replacement for [IL] Fig 3-2 Bridge ports	320
Figure 22 – Replacement for [IL] Fig 3-3 Bridge architecture	321
Figure A.1 – Example of FCS generation	366

Figure A.2 – Example of FCS syndrome checking on reception.....	366
Figure C.1 – Gross structure of FC code points	392
Figure C.2 [Figure 2] – Basic structure of a DL-address	405
Figure C.3 [Figure 3] – Basic structure of a sublink selector.....	405
Figure C.4 [Figure 4] – DL-address alternative structures	405
Figure C.5 [Figure 5] – Basic structure of MAC-addresses	405
Figure C.6 [Figure 6] – Representation of a DL-address as a MAC-address	405
Table 1 – Link node selector addressing	41
Table 2 – Link-local node selector addressing.....	43
Table 3 – Link-local node designators	45
Table 4 – Node-local selector addressing	46
Table 5 – Predefined flat non-local DL-addresses	47
Table 6 – Predefined flat link-local DL-addresses	48
Table 7 – Predefined node-local DL-addresses	48
Table 8 – Correlation of DLPDUs with functional classes	54
Table 9 – FCS length, polynomial and expected residual	76
Table 10 – Summary structure of DLPDUs	82
Table 11 – DLPDU restrictions based on dominant token	83
Table 12 – Structure of EC DLPDUs	83
Table 13 – Structure of DC DLPDUs	86
Table 14 – Structure of RC DLPDUs	88
Table 15 – Structure of CA DLPDUs	90
Table 16 – Structure of CD DLPDUs	96
Table 17 – Structure of ED DLPDUs	103
Table 18 – Structure of DT DLPDUs	111
Table 19 – Structure of SR DLPDUs	119
Table 20 – Structure of CT DLPDUs	121
Table 21 – Structure of TD DLPDUs	123
Table 22 – Structure of RQ DLPDUs	125
Table 23 – Structure of RR DLPDUs	127
Table 24 – Structure of PN DLPDUs	129
Table 25 – Structure of PR DLPDUs	132
Table 26 – Structure of PT DLPDUs.....	133
Table 27 – Structure of ES DLPDUs	142
Table 28 – Structure of RT DLPDUs	148
Table 29 – Structure of RI DLPDUs.....	149
Table 30 – Structure of CL DLPDUs.....	150
Table 31 – Structure of TL DLPDUs	152
Table 32 – Structure of WK DLPDUs.....	155
Table 33 – Structure of IDLE DLPDUs	157
Table 34 – Assumed structure of undefined (spare) DLPDUs	158
Table 35 – Assumed structure of RESERVED (NOT TO BE USED) DLPDUs	160

Table 36 – Structure of an EC DLPDU's parameters	161
Table 37 – EC-parameters: 1st octet.....	161
Table 38 – EC-parameters: 2nd octet.....	161
Table 39 – EC-parameters: 3rd and 4th octets	162
Table 40 – EC-parameters: 5th and 6th octets	162
Table 41 – EC-parameters: 7th octet	163
Table 42 – EC-parameters: 8th octet	163
Table 43 – EC-parameters: 9th and 10th octets	164
Table 44 – EC-parameters: 11th octet.....	164
Table 45 – EC-parameters: 12th octet.....	165
Table 46 – EC-parameters: 13th and 14th octets	165
Table 47 – DC-parameters and RC-parameters: 1st octet	165
Table 48 – DC-parameters and RC-parameters: 2nd octet	166
Table 49 – Disconnect reasons	167
Table 50 – Reset reasons	168
Table 51 – RC-parameters: 3rd octet	168
Table 52 – RC-parameters: 4th octet	168
Table 53 – Structure of connectionless-mode CA, CD, DT and ED DLPDUs.....	169
Table 54 – Short format SD-parameters for connectionless transaction initiators	170
Table 55 – Short format SD-parameters for connectionless responders	170
Table 56 – Reply status for unitdata-acknowledgment and exchange-unitdata-reply DT DLPDUs.....	171
Table 57 – Structure of connection-oriented CA, CD, DT and ED DLPDUs.....	173
Table 58 – Short format SD-parameters for DLCEP state.....	174
Table 59 – Long format SD-parameters for DLCEP state: 1st octet	174
Table 60 – Long format SD-parameters for DLCEP state: 2nd octet	174
Table 61 – Long format SD-parameters for DLCEP state: 3rd octet.....	175
Table 62 – Reply status for SR DLPDUs	176
Table 63 – Short format SR-parameters.....	176
Table 64 – Structure of TD-parameters	177
Table 65 – Structure and encoding of the DL-time-quality measures	177
Table 66 – Approximate numeric significance of the bits of seven-octet DL-time	178
Table 67 – Approximate numeric significance of the bits of three-octet short time	179
Table 68 – Structure of RQ-parameters	179
Table 69 – Structure of RR-parameters.....	179
Table 70 – Structure and encoding of the RR-time-quality measures	180
Table 71 – Structure of PN-parameters.....	181
Table 72 – PN-parameters: 1st octet.....	181
Table 73 – PN-parameters: 2nd octet.....	181
Table 74 – PN-parameters: 3rd and 4th octets	181
Table 75 – PN-parameters: 5th octet	182
Table 76 – PN-parameters: 6th octet	182
Table 77 – Structure of DD-parameters.....	182

Table 78 – Components of returned DL-time.....	238
Table 79 – Time synchronization computation.....	240
Table 80 – SPDU 1st octet: SPDU class, and protocol version or subclass	248
Table 81 – Probe-response SPDU	249
Table 82 – DL-protocol versions supported	249
Table 83 – PR-SPDU: 3rd and 4th octets	249
Table 84 – Node-activation SPDU	251
Table 85 – Node-activation SPDU: 4th octet	251
Table 86 – LAS-data-base-status SPDU	252
Table 87 – LAS-data-base-status SPDU: 2nd octet	252
Table 88 – Live-list- change SPDU	252
Table 89 – DLE-status structure.....	253
Table 90 – Live-list-detail SPDU	254
Table 91 – DL-conformance-reply SPDU.....	255
Table 92 – DL-protocol versions supported	255
Table 93 – DL-conformance encoding (portion 1).....	255
Table 94 – DL-conformance encoding (portion 2).....	256
Table 95 – DL-conformance encoding (portion 3).....	256
Table 96 – DL-conformance encoding (portion 4).....	256
Table 97 – Link-basic-parameters-reply SPDU.....	257
Table 98 – Link-master-parameters-reply SPDU	258
Table 99 – Token-hold-time-request SPDU	259
Table 100 – Token-hold-time-array SPDU.....	259
Table 101 – Sequence element header encoding	261
Table 102 – SHORT DL-address and duration sequence element	261
Table 103 – LONG DL-address and duration sequence element	262
Table 104 – Wakeup request sequence element	263
Table 105 – Schedule-request SPDU	264
Table 106 – Sequence type, schedule type and priority encoding	264
Table 107 – Scheduling-completed SPDU.....	266
Table 108 – Status and reason codes	266
Table 109 – Cancel-schedule SPDU	266
Table 110 – Schedule-cancelled SPDU.....	267
Table 111 – Link-schedule	268
Table 112 – Schedule-summary SPDU	268
Table 113 – Subschedule-SPDU reference	269
Table 114 – Subschedule SPDU	270
Table 115 – Sequence Sub-SPDU	271
Table 116 – Element-description.....	271
Table 117 – Schedule-summary-request SPDU.....	272
Table 118 – Subschedule-request SPDU	273
Table 119 – Parameter-list element-header encoding	273
Table 120 – Begin/end-of-list element.....	274

Table 121 – Continuation-of-list element	274
Table 122 – SHORT DL-address list element	274
Table 123 – LONG DL-address element	275
Table 124 – DLSAP-address-characteristics element	275
Table 125 – DLCEP-characteristics element	276
Table 126 – Address-query SPDU	276
Table 127 – Address-report SPDU	277
Table 128 – Address-list-query SPDU	278
Table 129 – DL-address selection criteria	279
Table 130 – Address-list-reply SPDU	280
Table 131 – Topology change notification BPDU format.....	328
Table 132 – Configuration BPDU format	328
Table 133 – Maximum permitted phase-tracking error in a DLE's sense of DL-time at the minimum requireable Time Distribution period.....	336
Table C.1 – Generic assignment of FC code points.....	393
Table C.2 – Individual assignment of FC code points	394
Table C.3 – Reply status for SR DLPDUs	397
Table C.4 – Reply status for unitdata-acknowledgment and exchange-unitdata-reply DT DLPDUs.....	398
Table C.5 – Approximate numeric significance of the bits of seven-octet DL-time	403
Table C.6 – Approximate numeric significance of the bits of N(NT), A...A, and three- octet C(NT).....	403
Table C.7 [Table 1] – Link node selector addressing	406
Table C.8 [Table 2] – Link-local node selector addressing	406
Table C.9 [Table 5] – Predefined flat non-local DL-addresses	407
Table C.10 [Table 6] – Predefined flat link-local DL-addresses	407
Table C.11 [Table 3] – Link-local node designators.....	408
Table C.12 [Table 4] – Node-local selector addressing	408
Table C.13 [Table 7] – Predefined node-local DL-addresses	408

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 4-1: Data-link layer protocol specification –
Type 1 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in IEC 61784-1 and IEC 61784-2.

International Standard IEC 61158-4-1 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This second edition cancels and replaces the first edition published in 2007. This edition constitutes a technical revision.

The main change with respect to the previous edition is listed below:

- Improved terms

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/762/FDIS	65C/772/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

NOTE 2 Slight variances from the directives have been allowed by the IEC Central Office to provide continuity of subclause numbering with prior editions.

A list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

0 INTRODUCTION

0.1 General

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

0.2 Nomenclature for references within this standard

Clauses, including annexes, can be referenced in their entirety, including any subordinate subclauses, as “Clause N” or “Annex N”, where N is the number of the clause or letter of the annex.

Subclauses can be referenced in their entirety, including any subordinate subclauses, as “N.M” or “N.M.P” and so forth, depending on the level of the subclause, where N is the number of the subclause or letter of the annex, and M, P and so forth represent the successive levels of subclause up to and including the subclause of interest.

When a clause or subclause contains one or more subordinate subclauses, the text between the clause or subclause heading and its first subordinate subclause can be referenced in its entirety as “N.0” or “N.M.0” or “N.M.P.0” and so forth, where N, M and P are as above. Stated differently, a reference ending with “.0” designates the text and figures between a clause or subclause header and its first subordinate subclause.

NOTE This nomenclature provides a means of referencing text in hanging clauses. Such clauses existed in earlier editions of IEC 61784-3, Type 1 clauses. Those hanging clauses are maintained in this edition to minimize the disruption to existing national and multi-national standards and consortia documents which reference that prior subclause numbering.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-1: Data-link layer protocol specification – Type 1 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides the data-link service by making use of the services available from the physical layer. The relationship between the International Standards for fieldbus data-link service, fieldbus data-link protocol, fieldbus physical service and systems management is described in IEC 61158-1.

This protocol provides communication opportunities to all participating data-link entities

- a) in a cyclic asynchronous manner, sequentially to each of those data-link entities, and
- b) in a synchronous manner, either cyclically or acyclically, according to a pre-established schedule.

The specified protocol also provides means of changing the set of participating data-link entities and of modifying the set of scheduled communications opportunities. When the set of scheduled communications opportunities is null, the distribution of communication opportunities to the participating data-link entities is completely asynchronous.

Thus this protocol can be characterized as one which provides access asynchronously but with a synchronous overlay.

1.2 Specifications

This standard specifies

- a) procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed data-link service provider;
- b) the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

NOTE In IEC 61158-4-1, gray boxes have been used in the tables to indicate that the specified field is not a conceptual part of the specific DLPDU.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as IEC 61784-1 and IEC 61784-2 are maintained simultaneously. Cross-references to these documents within the text therefore refer to the editions as dated in this list of normative references.

IEC 61158-1:2014, *Industrial communication networks – Fieldbus specifications – Part 1: Overview and guidance for the IEC 61158 and IEC 61784 series*

IEC 61158-2:2014, *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-1:2014, *Industrial communication networks – Fieldbus specifications – Part 3-1: Data link service definition – Type 1 elements*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC 8886, *Information technology – Open Systems Interconnection – Data link service definition*

ISO/IEC 10038:1993, *Information technology – Telecommunications and information exchange between systems – Local area networks – Media access control (MAC) bridges*

NOTE This edition has been withdrawn and replaced by ISO/IEC 15802-3:1998. However, the detailed references in this standard are to the 1993 edition.

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*