

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Fältbuss – Del 4-19: Specifikation av protokoll i datalänkskiktet – Delar i fältbuss, Typ 19

*Industrial communication networks –
Fieldbus specifications –
Part 4-19: Data-link layer protocol specification –
Type 19 elements*

Som svensk standard gäller europastandarden EN 61158-4-19:2014. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61158-4-19:2014.

Nationellt förord

Europastandarden EN 61158-4-19:2014

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61158-4-19, Third edition, 2014 - Industrial communication networks - Fieldbus specifications - Part 4-19: Data-link layer protocol specification - Type 19 elements**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 61158-4-19, utgåva 2, 2012, gäller ej fr o m 2017-09-19.

ICS 25.040.40; 35.100.20; 35.110.00

Denna standard är fastställd av SEK Svensk Elstandard, som också kan lämna upplysningar om **sakinnehållet** i standarden.
Postadress: Box 1284, 164 29 KISTA
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: www.elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

EUROPEAN STANDARD

EN 61158-4-19

NORME EUROPÉENNE

EUROPÄISCHE NORM

October 2014

ICS 25.040.40; 35.100.20; 35.110

Supersedes EN 61158-4-19:2012

English Version

**Industrial communication networks - Fieldbus specifications -
Part 4-19: Data-link layer protocol specification - Type 19
elements
(IEC 61158-4-19:2014)**

Réseaux de communication industriels - Spécifications des
bus de terrain - Partie 4-19: Spécification du protocole de la
couche liaison de données - Eléments de type 19
(CEI 61158-4-19:2014)

Industrielle Kommunikationsnetze - Feldbusse - Teil 4-19:
Protokollspezifikation des Data Link Layer
(Sicherheitsschicht) - Typ 19-Elemente
(IEC 61158-4-19:2014)

This European Standard was approved by CENELEC on 2014-09-19. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 65C/762/FDIS, future edition 3 of IEC 61158-4-19, prepared by SC 65C "Industrial networks" of IEC/TC 65 "Industrial-process measurement, control and automation" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61158-4-19:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-06-19
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-09-19

This document supersedes EN 61158-4-19:2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association.

Endorsement notice

The text of the International Standard IEC 61158-4-19:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for bibliography, the following notes have to be added for the standards indicated:

IEC 61131 Series	NOTE	Harmonised as EN 61131 Series
IEC 61158-1:2014	NOTE	Harmonised as EN 61158-1:2014
IEC 61158-3-19:2014	NOTE	Harmonised as EN 61158-3-19:2014
IEC 61158-5-16:2007	NOTE	Harmonised as EN 61158-5-16:2007
IEC 61158-5-19:2014	NOTE	Harmonised as EN 61158-5-19:2014
IEC 61158-6-16:2007	NOTE	Harmonised as EN 61158-6-16:2007
IEC 61158-6-19:2014	NOTE	Harmonised as EN 61158-6-19:2014
IEC 61784-1	NOTE	Harmonised as EN 61784-1
IEC 61784-2	NOTE	Harmonised as EN 61784-2
IEC 61800-7 Series	NOTE	Harmonised as EN 61800-7 Series
IEC 61800-7-201	NOTE	Harmonised as EN 61800-7-201
IEC 61800-7-202	NOTE	Harmonised as EN 61800-7-202
IEC 61800-7-203	NOTE	Harmonised as EN 61800-7-203
IEC 61800-7-204	NOTE	Harmonised as EN 61800-7-204

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61158-4-16	2007	Industrial communication networks - Fieldbus specifications Part 4-16: Data-link layer protocol specification - Type 16 elements	EN 61158-4-16	2008
ISO/IEC 7498-1	-	Information technology - Open Systems Interconnection - Basic reference model: The basic model	-	-
ISO/IEC 7498-3	-	Information technology - Open Systems Interconnection - Basic reference model: Naming and addressing	-	-
ISO 8601	-	Data elements and interchange formats - Information interchange - Representation of dates and times	-	-
ISO/IEC 8802-3	-	Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-
IEEE 802.3	-	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications	-	-
IETF RFC 879	-	The TCP Maximum Segment Size and Related Topics	-	-

CONTENTS

FOREWORD.....	21
INTRODUCTION.....	23
1 Scope.....	25
1.1 General.....	25
1.2 Specifications.....	25
1.3 Procedures.....	25
1.4 Applicability.....	25
1.5 Conformance.....	26
2 Normative references.....	26
3 Terms, definitions, symbols, acronyms, abbreviations and conventions.....	26
3.1 Reference model terms and definitions.....	26
3.2 Additional Type 19 terms and definitions.....	26
3.3 Symbols.....	30
3.4 Acronyms and abbreviations.....	31
3.5 Additional conventions.....	32
4 DL-protocol overview.....	33
4.1 Overview.....	33
4.2 General DLPDU identification.....	34
4.3 General DLPDU structure.....	35
4.4 DLPDU header.....	35
4.5 MDT DLPDU.....	36
4.6 AT DLPDU.....	48
4.7 Mechanisms of connections.....	59
5 DL management.....	69
5.1 Overview.....	69
5.2 Initialization of cyclic communication.....	69
5.3 Network topologies.....	91
5.4 Redundancy of RT communication with ring topology.....	102
5.5 Hot-plug procedure.....	105
5.6 Status procedures.....	110
6 Data transmission methods.....	111
6.1 Overview.....	111
6.2 Service channel (SVC).....	111
6.3 RT Channel.....	125
6.4 Transmission and activation of Type 19 time.....	125
6.5 Multiplexing of real-time data with data containers.....	127
6.6 Handling of Real-time bits.....	138
6.7 SMP.....	141
6.8 Oversampling.....	146
7 Telegram timing and DLPDU handling.....	151
7.1 Communication mechanisms.....	151
7.2 Synchronization.....	206
7.3 Processing methods of connection data.....	215
8 Communication Error handling and monitoring.....	218
8.1 Invalid telegrams.....	218

8.2	Response to MDT and AT telegram failure	218
8.3	Error counters in the slave	219
8.4	Status codes of Type 19 communication profile (SCP).....	219
8.5	Priority of diagnosis classes	222
Annex A	(normative) IDN – Identification numbers	223
A.1	IDN specification	223
A.1.1	Introduction	223
A.1.2	Element 1: structure of IDN	223
A.1.3	Element 2: structure of name.....	224
A.1.4	Element 3: structure of attribute.....	225
A.1.5	Element 4: structure of unit.....	227
A.1.6	Element 5: structure of minimum value	227
A.1.7	Element 6: structure of maximum value	228
A.1.8	Element 7: structure of operation data	228
A.1.9	Structure of Data status	230
A.2	Identification numbers in numerical orders	231
A.3	Detailed specification of communication-related IDNs	235
A.3.1	IDN S-0-0014 Interface status	235
A.3.2	IDN S-0-0021 IDN-list of invalid operation data for CP2	236
A.3.3	IDN S-0-0026 IDN allocation of producer RTB word container	237
A.3.4	IDN S-0-0027 IDN allocation of consumer RTB word container	238
A.3.5	IDN S-0-0127 CP3 transition check.....	239
A.3.6	IDN S-0-0128 CP4 transition check.....	239
A.3.7	IDN S-0-0144 Producer RTB word container	240
A.3.8	IDN S-0-0145 Consumer RTB word container	240
A.3.9	IDN S-0-0187 IDN-list of configurable data as producer	241
A.3.10	IDN S-0-0188 IDN-list of configurable data as consumer	242
A.3.11	IDN S-0-0328 Bit allocation of producer RTB word container.....	242
A.3.12	IDN S-0-0329 Bit allocation of consumer RTB word container	243
A.3.13	IDN S-0-0360 MDT data container A1	243
A.3.14	IDN S-0-0361 MDT data container B1	244
A.3.15	IDN S-0-0362 MDT data container A list index	245
A.3.16	IDN S-0-0363 MDT data container B list index	246
A.3.17	IDN S-0-0364 AT data container A1	247
A.3.18	IDN S-0-0365 AT data container B1	248
A.3.19	IDN S-0-0366 AT data container A list index	249
A.3.20	IDN S-0-0367 AT data container B list index	250
A.3.21	IDN S-0-0368 Data container A pointer	251
A.3.22	IDN S-0-0369 Data container B pointer	252
A.3.23	IDN S-0-0370 MDT data container A/B configuration list	254
A.3.24	IDN S-0-0371 AT data container A/B configuration list	254
A.3.25	IDN S-0-0394 List IDN	255
A.3.26	IDN S-0-0395 List index	255
A.3.27	IDN S-0-0396 Number of list elements	256
A.3.28	IDN S-0-0397 List segment	257
A.3.29	IDN S-0-0398 IDN list of configurable real-time bits as producer	258
A.3.30	IDN S-0-0399 IDN list of configurable real-time bits as consumer.....	258
A.3.31	IDN S-0-0444 IDN-list of configurable data in the AT data container.....	259

A.3.32	IDN S-0-0445 IDN-list of configurable data in the MDT data container.....	259
A.3.33	IDN S-0-0450 MDT data container A2	260
A.3.34	IDN S-0-0451 MDT data container A3	260
A.3.35	IDN S-0-0452 MDT data container A4	261
A.3.36	IDN S-0-0453 MDT data container A5	262
A.3.37	IDN S-0-0454 MDT data container A6	263
A.3.38	IDN S-0-0455 MDT data container A7	264
A.3.39	IDN S-0-0456 MDT data container A8	265
A.3.40	IDN S-0-0457 MDT data container A9	266
A.3.41	IDN S-0-0458 MDT data container A10	267
A.3.42	IDN S-0-0459 MDT data container B2	268
A.3.43	IDN S-0-0480 AT data container A2	269
A.3.44	IDN S-0-0481 AT data container A3	270
A.3.45	IDN S-0-0482 AT data container A4	271
A.3.46	IDN S-0-0483 AT data container A5	272
A.3.47	IDN S-0-0484 AT data container A6	273
A.3.48	IDN S-0-0485 AT data container A7	274
A.3.49	IDN S-0-0486 AT data container A8	275
A.3.50	IDN S-0-0487 AT data container A9	276
A.3.51	IDN S-0-0488 AT data container A10	277
A.3.52	IDN S-0-0489 AT data container B	278
A.3.53	IDN S-0-0490 MDT data container A2 configuration list.....	279
A.3.54	IDN S-0-0491 MDT data container A3 configuration list.....	280
A.3.55	IDN S-0-0492 MDT data container A4 configuration list.....	281
A.3.56	IDN S-0-0493 MDT data container A5 configuration list.....	281
A.3.57	IDN S-0-0494 MDT data container A6 configuration list.....	282
A.3.58	IDN S-0-0495 MDT data container A7 configuration list.....	283
A.3.59	IDN S-0-0496 MDT data container A8 configuration list.....	283
A.3.60	IDN S-0-0497 MDT data container A9 configuration list.....	284
A.3.61	IDN S-0-0498 MDT data container A10 configuration list.....	284
A.3.62	IDN S-0-0500 AT data container A2 configuration list.....	285
A.3.63	IDN S-0-0501 AT data container A3 configuration list.....	286
A.3.64	IDN S-0-0502 AT data container A4 configuration list.....	286
A.3.65	IDN S-0-0503 AT data container A5 configuration list.....	287
A.3.66	IDN S-0-0504 AT data container A6 configuration list.....	288
A.3.67	IDN S-0-0505 AT data container A7 configuration list.....	288
A.3.68	IDN S-0-0506 AT data container A8 configuration list.....	289
A.3.69	IDN S-0-0507 AT data container A9 configuration list.....	289
A.3.70	IDN S-0-0508 AT data container A10 configuration list.....	290
A.3.71	IDN S-0-1000.0.1 Active SCP Classes	291
A.3.72	IDN S-0-1000 SCP Type & Version	291
A.3.73	IDN S-0-1002 Communication cycle time	294
A.3.74	IDN S-0-1003 Allowed MST losses in CP3/CP4.....	294
A.3.75	IDN S-0-1005 Minimum feedback processing time (t_5)	295
A.3.76	IDN S-0-1006 AT transmission starting time (t_1)	296
A.3.77	IDN S-0-1007 Synchronization time (T_{sync})	297
A.3.78	IDN S-0-1008 Command value valid time (t_3).....	298
A.3.79	IDN S-0-1009 Device Control (C-DEV) offset in MDT	298

A.3.80	IDN S-0-1010 Lengths of MDTs	299
A.3.81	IDN S-0-1011 Device Status (S-DEV) offset in AT	301
A.3.82	IDN S-0-1012 Lengths of ATs	302
A.3.83	IDN S-0-1013 SVC offset in MDT	303
A.3.84	IDN S-0-1014 SVC offset in AT	304
A.3.85	IDN S-0-1015 Ring delay	305
A.3.86	IDN S-0-1016 Slave delay (P/S).....	306
A.3.87	IDN S-0-1017 UC channel transmission time.....	306
A.3.88	IDN S-0-1019 MAC address	307
A.3.89	IDN S-0-1020.0.1 Current IP address.....	308
A.3.90	IDN S-0-1020 IP address	309
A.3.91	IDN S-0-1021.0.1 Current subnet mask.....	310
A.3.92	IDN S-0-1021 Subnet mask.....	310
A.3.93	IDN S-0-1022.0.1 Current gateway address	311
A.3.94	IDN S-0-1022 Gateway address	312
A.3.95	IDN S-0-1023 SYNC jitter.....	313
A.3.96	IDN S-0-1024 SYNC delay measuring procedure command	314
A.3.97	IDN S-0-1026 Version of communication hardware	315
A.3.98	IDN S-0-1027.0.1 Requested MTU	315
A.3.99	IDN S-0-1027.0.2 Effective MTU	317
A.3.100	IDN S-0-1028 Error counter MST-P/S.....	317
A.3.101	IDN S-0-1031 Test pin assignment Port 1 & Port 2.....	318
A.3.102	IDN S-0-1034 PHY error counter Port 1 & Port 2.....	319
A.3.103	IDN S-0-1035 Error counter Port 1 & Port 2.....	320
A.3.104	IDN S-0-1036 Inter Frame Gap	322
A.3.105	IDN S-0-1037 Slave jitter	323
A.3.106	IDN S-0-1039.0.1 Current active hostname	323
A.3.107	IDN S-0-1039 Hostname	324
A.3.108	IDN S-0-1040 Sub-device address	325
A.3.109	IDN S-0-1041 AT Command value valid time (t9)	326
A.3.110	IDN S-0-1044 Device Control (C-DEV)	326
A.3.111	IDN S-0-1045 Device Status	327
A.3.112	IDN S-0-1047 Maximum Consumer Activation Time (t11)	329
A.3.113	IDN S-0-1048 Activate network settings	330
A.3.114	IDN S-0-1046 List of device addresses in device.....	331
A.3.115	IDN S-0-1050.x.1 Connection setup	332
A.3.116	IDN S-0-1050.x.2 Connection Number	333
A.3.117	IDN S-0-1050.x.3 Telegram assignment	334
A.3.118	IDN S-0-1050.x.4 Max. Length of Connection.....	335
A.3.119	IDN S-0-1050.x.5 Current length of connection	336
A.3.120	IDN S-0-1050.x.6 Configuration List.....	336
A.3.121	IDN S-0-1050.x.7 Assigned connection capability	337
A.3.122	IDN S-0-1050.x.8 Connection Control	338
A.3.123	IDN S-0-1050.x.10 Producer cycle time.....	338
A.3.124	IDN S-0-1050.x.11 Allowed Data Losses	339
A.3.125	IDN S-0-1050.x.12 Error Counter Data Losses	339
A.3.126	IDN S-0-1050.x.20 IDN Allocation of real-time bit.....	340
A.3.127	IDN S-0-1050.x.21 IDN Allocation of real-time bit.....	340
A.3.128	IDN S-0-1051 Image of connection setups	341

A.3.129	IDN S-0-1060.x.1 Default configuration	342
A.3.130	IDN S-0-1060.x.2 Configuration mask	342
A.3.131	IDN S-0-1060.x.3 Maximum quantity of this connection capability	343
A.3.132	IDN S-0-1060.x.4 Max. connection length of connection capability	343
A.3.133	IDN S-0-1060.x.6 Configurable IDNs of connection capability	344
A.3.134	IDN S-0-1060.x.7 Maximum processing time	344
A.3.135	IDN S-0-1060.x.10 Minimum producer cycle time	345
A.3.136	IDN S-0-1061 Maximum TSref-Counter	346
A.3.137	IDN S-0-1080.x.02 Producer RTB list container.....	346
A.3.138	IDN S-0-1080.x.03 IDN allocation of producer RTB list container	347
A.3.139	IDN S-0-1080.x.04 Bit allocation of producer RTB list container	348
A.3.140	IDN S-0-1081.x.02 Consumer RTB list container.....	348
A.3.141	IDN S-0-1081.x.03 IDN allocation of consumer RTB list container.....	349
A.3.142	IDN S-0-1081.x.04 Bit allocation of consumer RTB list container.....	349
A.3.143	IDN S-0-1099.0.1 Test-IDN Control for SCP Conformity Purpose	350
A.3.144	IDN S-0-1099.0.2 Test-IDN Container for SCP Conformity purpose.....	351
A.3.145	IDN S-0-1100.0.1 Diagnostic counter sent SMP fragments.....	352
A.3.146	IDN S-0-1100.0.2 Diagnostic counter received SMP fragments	352
A.3.147	IDN S-0-1100.0.3 Diagnostic counter discarded SMP fragments	353
A.3.148	IDN S-0-1101.x.1 SMP Container Data	353
A.3.149	IDN S-0-1101.x.2 List of session identifiers.....	354
A.3.150	IDN S-0-1101.x.3 List of session priorities	355
A.3.151	IDN S-0-1150.x.01 OVS Control (C-OVS).....	355
A.3.152	IDN S-0-1150.x.02 OVS Status (S-OVS)	356
A.3.153	IDN S-0-1150.x.03 OVS Container	357
A.3.154	IDN S-0-1150.x.04 Sample time	358
A.3.155	IDN S-0-1150.x.05 Phase shift.....	359
A.3.156	IDN S-0-1150.x.06 Configuration List OVS - IDNs	359
A.3.157	IDN S-0-1150.x.07 Configuration List OVS - Offset	360
A.3.158	IDN S-0-1150.x.08 Configuration List OVS - Length.....	361
A.3.159	IDN S-0-1150.x.09 Assigned Oversampling Capability	361
A.3.160	IDN S-0-1150.x.10 Number of Samples.....	362
A.3.161	IDN S-0-1151.x.01 Maximum number of samples	362
A.3.162	IDN S-0-1151.x.02 Internal resolution	363
A.3.163	IDN S-0-1151.x.03 Maximum quantity of this oversampling capability	364
A.3.164	IDN S-0-1151.x.04 Minimum sample time.....	364
A.3.165	IDN S-0-1151.x.06 Configurable IDNs of OVS capability	365
A.3.166	IDN S-0-1151.x.07 Configurable IDNs of OVS Capability - Offset.....	366
A.3.167	IDN S-0-1151.x.08 Configurable IDNs of OVS Capability - Length.....	366
A.3.168	IDN S-0-1153 Amount of OVS Domains	367
Annex B	(normative) SCP– Classification.....	368
B.1	General concept of profiling.....	368
B.2	Function Groups related to the SCP	369
B.2.1	FG SCP Identification	369
B.2.2	FG Timing	369
B.2.3	FG Telegram Setup	369
B.2.4	FG Control.....	370
B.2.5	FG Bus-Diagnosis	370

B.2.6	FG Connection	370
B.2.7	FG NRT	371
B.2.8	FG MUX	371
B.2.9	FG SMP	372
B.2.10	FG RTB	373
B.3	Type 19 communication classes	373
B.3.1	General	373
B.3.2	SCP_FixCFG	373
B.3.3	SCP_FixCFG_0x02	375
B.3.4	SCP_FixCFG_0x03	375
B.3.5	SCP_VarCFG	375
B.3.6	SCP_VarCFG_0x02	376
B.3.7	SCP_VarCFG_0x03	377
B.3.8	SCP_Sync	377
B.3.9	SCP_Sync	377
B.3.10	SCP_Sync_0x02	378
B.3.11	SCP_Sync_0x03	378
B.3.12	SCP_WD	378
B.3.13	SCP_WD_0x02	378
B.3.14	SCP_Diag	379
B.3.15	SCP_RTB	379
B.3.16	SCP_HP	379
B.3.17	SCP_SMP	379
B.3.18	SCP_Mux	380
B.3.19	SCP_Ext_Mux	380
B.3.20	SCP_NRT	380
B.3.21	SCP_Sig	381
B.3.22	SCP_ListSeg	381
B.3.23	SCP_IPS	381
B.3.24	SCP_Cap	381
B.3.25	SCP_RTBListProd	382
B.3.26	SCP_RTBListCons	382
B.3.27	SCP_SysTime	382
B.3.28	SCP_RTBWordProd	382
B.3.29	SCP_RTBWordCons	382
B.3.30	SCP_SafetyCon	383
B.3.31	SCP_OvS_Basic	383
B.3.32	SCP_NRTPC	384
B.3.33	SCP_Cyc	384
Annex C (normative)	GDP (Generic Device Profile)	385
C.1	General	385
C.2	Function Groups	385
C.2.1	Function Group Diagnosis	385
C.2.2	Function Group Archiving	387
C.2.3	Function Group Administration	387
C.2.4	Function Group Identification	387
C.2.5	Function Group State machine	388
C.2.6	Function Group Time	392
C.2.7	Function Group Conformance Test GDP	393

C.3	Classification.....	393
C.3.1	General	393
C.3.2	GDP_Basic.....	393
C.3.3	GDP_DiagT.....	393
C.3.4	GDP_DiagTAdv	394
C.3.5	GDP_LNg	394
C.3.6	GDP_PWD	394
C.3.7	GDP_Id	394
C.3.8	GDP_Rev	394
C.3.9	GDP_QA	395
C.3.10	GDP_CKs.....	395
C.3.11	GDP_CKsUser.....	395
C.3.12	GDP_StM	395
C.3.13	GDP_BKP	395
C.3.14	GDP_BKPAdv.....	396
C.3.15	GDP_RST	396
C.3.16	GDP_CIPSafetyDev.....	396
C.4	List of all GDP related IDNs.....	396
C.4.1	IDN specification	396
C.4.2	Identification numbers in numerical orders.....	396
C.4.3	Detailed specification of communication-related IDNs.....	398
C.5	GDP status codes	443
	Bibliography.....	445
	Figure 1 – Example of offsets within MDT payload	42
	Figure 2 – Example of Offsets within AT payload	54
	Figure 3 – Flow of application data	60
	Figure 4 – Telegram assignment and connection length.....	61
	Figure 5 – Connection control state machine producer.....	63
	Figure 6 – Connection control state machine consumer	66
	Figure 7 – Communication phase (CP) state machine.....	71
	Figure 8 – CPSwitch state machine master	78
	Figure 9 – CPSwitch state machine of the slave.....	83
	Figure 10 – Address allocation with line	90
	Figure 11 – Address allocation with ring.....	90
	Figure 12 – Address allocation with interrupted ring.....	91
	Figure 13 – Ring topology with P&S channel.....	92
	Figure 14 – Line topology with P channel (as example).....	93
	Figure 15 – Block diagram of a slave	93
	Figure 16 – Topology conditions of a slave	94
	Figure 17 – Addressing of multi-slave device	95
	Figure 18 – Multi-slave device in ring topology or not last in line topology.....	96
	Figure 19 – Multi-slave device as last in line topology.....	96
	Figure 20 – Multi-slave device in line (left).....	98
	Figure 21 – Multi-slave device in line (right).....	98
	Figure 22 – Multi-slave device in ring.....	98

Figure 23 – Topology state machine of a slave	99
Figure 24 – Ring without break	102
Figure 25 – Ring break	103
Figure 26 – Ring break on master	103
Figure 27 – Recovery of P channel (1)	104
Figure 28 – Recovery of P channel (2)	104
Figure 29 – Recovery of S channel (1)	105
Figure 30 – Recovery of S channel (2)	105
Figure 31 – Communication phase and hot-plug state machine	106
Figure 32 – Service channel handling diagram	112
Figure 33 – Communication step proceeding diagram	113
Figure 34 – State machine for procedure command execution	122
Figure 35 – Interaction of procedure command control and acknowledgement	123
Figure 36 – Procedure command execution without interrupt	124
Figure 37 – Procedure command execution with interrupt	124
Figure 38 – Procedure command execution with error message	125
Figure 39 – Type 19 Time Transmission	126
Figure 40 – Data container configuration without acknowledge (slave)	131
Figure 41 – Data container configuration with acknowledge (slave)	132
Figure 42 – Processing of list index in the MDT data	133
Figure 43 – Structure of extended data container	136
Figure 44 – Transport container	142
Figure 45 – UML Sequence Diagram: Multiplexing of two sessions (Example)	145
Figure 46 – Oversampling overview	147
Figure 47 – Oversampling timing input (producer)	147
Figure 48 – Oversampling timing output (consumer)	148
Figure 49 – Oversampling state machine	150
Figure 50 – Telegram timing reference	152
Figure 51 – Calculation of telegram length	153
Figure 52 – Calculation of t_1	154
Figure 53 – Determination of UC channel	156
Figure 54 – Timing diagram of CP0	156
Figure 55 – Timing diagram of CP1 and CP2 with 2 MDT, 2AT and UC channel	157
Figure 56 – Timing diagram of CP1 and CP2 with 4 MDT, 4 AT and UC channel	158
Figure 57 – Timing diagram of CP1 and CP2 with 2 MDT, UC channel and 2 AT	158
Figure 58 – Timing diagram of CP1 and CP2 with 4 MDT, UC channel and 4 AT	159
Figure 59 – Telegram sequence	160
Figure 60 – The two defined positions of the UC channel	161
Figure 61 – First and last transmit during UC channel	162
Figure 62 – Activated and deactivated collision buffer	163
Figure 63 – Time response of store and forward method	164
Figure 64 – Cut through forwarding	164
Figure 65 – Ethernet frame with payload	165

Figure 66 – Unhealed broken ring	168
Figure 67 – Broken ring with Type 19 slave in between.....	169
Figure 68 – S/IP busy response	174
Figure 69 – Client connection	175
Figure 70 – Server connection	175
Figure 71 – S/IP asynchronous request	176
Figure 72 – S/IP PDU	177
Figure 73 – S/IP error response	179
Figure 74 – UDP Browsing.....	183
Figure 75 – Sequence of setting a new network configuration on one device using UDP	186
Figure 76 – UDP Identification	191
Figure 77 – Usage UDP reset request.....	203
Figure 78 – Sequence for watchdog trigger service and client application timeout.....	204
Figure 79 – Synchronization timing	207
Figure 80 – Synchronization trigger	207
Figure 81 – Timing of TSref with ring and line	209
Figure 82 – Timing of TSref with interrupted ring	210
Figure 83 – Determination of the SYNC delay time	211
Figure 84 – Definition of TSref	213
Figure 85 – Timing with different cycle times	214
Figure 86 – Timing with the same cycle times	215
Figure 87 – Synchronous application data processing.....	216
Figure 88 – Cyclic application data processing.....	217
Figure 89 – Non-synchronous application data processing.....	218
Figure A.1 – IDN name structure.....	225
Figure A.2 – Unit structure	227
Figure A.3 – Structure of IDN operation data with variable length	229
Figure A.4 – Example of synchronization timing with different producer cycles.....	298
Figure A.5 – Definition of MDT length	300
Figure A.6 – Lengths of MDTs (example).....	301
Figure A.7 – Definition of AT length	303
Figure A.8 – Lengths of ATs (example)	303
Figure A.9 – Structure of MAC address.....	308
Figure A.10 – Structure of IP address	310
Figure A.11 – Structure of subnet mask	311
Figure A.12 – Structure of gateway address.....	313
Figure A.13 – Structure of List of Sub-device addresses	332
Figure A.14 – Definition of connection length	336
Figure A.15 – Synchronization with ring	345
Figure A.16 – Configuration example	358
Figure B.1 – Technical Profiling in Type 19.....	368
Figure C.1 – State machine without class GDP_StM	389
Figure C.2 – State machine without class GDP_StM	391

Figure C.3 – Password State Machine	406
Figure C.4 – Structure of Date information	425
Figure C.5 – Structure of QA date information.....	425
Figure C.6 – Structure of Service date information	427
Figure C.7 – Structure of Calibration date information.....	428
Figure C.8 – Structure of Calibration due date information	428
Figure C.9 – Mapping of data into the InputData and OutputData container	433
Table 1 – Ethernet DLPDU identification	34
Table 2 – Data structure in a DLPDU	35
Table 3 – DLPDU payload header	35
Table 4 – DLPDU type	36
Table 5 – MDT header	36
Table 6 – MDT header to be considered by the slave	36
Table 7 – MDT phase.....	37
Table 8 – MDT0 structure in CP0	38
Table 9 – Communication version	38
Table 10 – MDT0 in CP1 and CP2 (topology indices 0 to 127)	39
Table 11 – MDT1 in CP1 and CP2 (topology indices 128 to 255)	40
Table 12 – MDT2 in CP1 and CP2 (topology indices 256 to 383)	40
Table 13 – MDT3 in CP1 and CP2 (topology indices 384 to 511)	41
Table 14 – MDT data field.....	42
Table 15 – MDT hot-plug field.....	43
Table 16 – HP address in MDT-HP field.....	43
Table 17 – HP control field (in HP0 and HP1)	43
Table 18 – Extended Field (EF)	45
Table 19 – MDT service channel field	45
Table 20 – MDT SVC (for each slave).....	45
Table 21 – SVC control word (DLL).....	46
Table 22 – MDT device control	47
Table 23 – MDT application data.....	47
Table 24 – Device control field (C-DEV).....	47
Table 25 – AT MST header	48
Table 26 – AT header fields to be considered by the slave.....	48
Table 27 – AT0 structure in CP0	49
Table 28 – Topology address in AT0-CP0	50
Table 29 – AT0 in CP1 and CP2 (topology indices 0 to 127)	51
Table 30 – AT1 in CP1 and CP2 (topology indices 128 to 255)	51
Table 31 – AT2 in CP1 and CP2 (topology indices 256 to 383)	52
Table 32 – AT3 in CP1 and CP2 (topology indices 384 to 511)	52
Table 33 – AT data field.....	53
Table 34 – AT hot-plug field in HP0 and HP1	54
Table 35 – HP address in AT-HP field.....	55

Table 36 – HP status field (in HP0 and HP1).....	55
Table 37 – AT service channel field	56
Table 38 – AT SVC (for each slave).....	56
Table 39 – AT SVC status description (DLL)	56
Table 40 – AT device status.....	57
Table 41 – AT connection data	57
Table 42 – Device status field	58
Table 43 – Structure of the connection.....	61
Table 44 – Connection control (C-CON).....	61
Table 45 – Connection control combinations	63
Table 46 – States of the producer state machine	64
Table 47 – States of the producer sub-state machine.....	64
Table 48 – Producer transitions	64
Table 49 – States of the consumer state machine	66
Table 50 – States of the consumer sub-state machine	67
Table 51 – Consumer transitions.....	68
Table 52 – MDT hot-plug field in CP3 and after ring recovery	75
Table 53 – Transitions of CP state machine	76
Table 54 – States of master CPSwitch state machine	80
Table 55 – Transitions of master CPSwitch state machine	81
Table 56 – States of slave CPSwitch state machine.....	85
Table 57 – Transitions of slave CPSwitch state machine.....	85
Table 58 – Transitions of slave CPSwitch state machine (transitions with warning).....	86
Table 59 – Transitions of slave CPSwitch state machine (transitions with error)	86
Table 60 – Diagnostics of CPS state machine slave.....	87
Table 61 – Determination of the topology indices (1).....	96
Table 62 – Determination of the topology indices (2).....	96
Table 63 – Determination of the topology indices (3).....	97
Table 64 – Topology status of multi-slave device	97
Table 65 – Topology settings of multi-slave device	97
Table 66 – States of Topology state machine of slave.....	100
Table 67 – Transitions of Topology state machine	101
Table 68 – Transitions of Topology state machine (transitions with warning).....	101
Table 69 – Transitions of Topology state machine (transitions with error)	102
Table 70 – States of HP state machine	106
Table 71 – MDT hot-plug field in HP0	108
Table 72 – MDT hot-plug field in HP1	109
Table 73 – AT hot-plug field in HP1	109
Table 74 – Transitions of HP state machine.....	109
Table 75 – AT hot-plug field in HP1 (error).....	110
Table 76 – Condition for modifying data block elements.....	113
Table 77 – List of data block element and step numbers	113
Table 78 – SVC channel evaluation	115

Table 79 – Reaction to handshake timeout	116
Table 80 – Reaction to error message	116
Table 81 – Error messages	117
Table 82 – Structure of Procedure command control	120
Table 83 – Procedure command acknowledgment (data status)	120
Table 84 – List of valid standard data container combinations	129
Table 85 – Example of IDN and bit allocation of RTB container	141
Table 86 – Structure of the Session Control Header	142
Table 87 – Lists in S-0-1101.7.x	146
Table 88 – States of the oversampling state machine	150
Table 89 – Transitions of the oversampling state machine	151
Table 90 – Parameter for timing calculation	152
Table 91 – Default values of CP1/2 (case 1)	157
Table 92 – Default values of CP1/2 (case 2)	158
Table 93 – Structure of port/MAC table	167
Table 94 – Insertion of entry	167
Table 95 – Update of entries	167
Table 96 – Slave collision buffer	168
Table 97 – Physical topology Master (CP0)	169
Table 98 – Physical topology Master (CP 1-4)	170
Table 99 – Definition of data types	171
Table 100 – Overview on IP-based protocols	172
Table 101 – Message Types	177
Table 102 – User-specific Message Types	178
Table 103 – Common error codes	180
Table 104 – Nameplate IDs	192
Table 105 – IPS classes	205
Table 106 – Class TCP Basic	205
Table 107 – Class UDP Basic	206
Table 108 – Class Device Management	206
Table 109 – Explore & IP Configuration Services	206
Table 110 – Class Type 19 Parameter Access	206
Table 111 – SCP specific status codes	220
Table 112 – Overview on diagnosis classes	222
Table A.1 – Data block structure	223
Table A.2 – Parameter structure	224
Table A.3 – Element 3 of IDNs	225
Table A.4 – Valid combinations of the display formats	227
Table A.5 – Example of the structure of an IDN-list	230
Table A.6 – Data status structure	231
Table A.7 – List of relevant communication-related IDNs	231
Table A.8 – Attributes for IDN S-0-0014	235
Table A.9 – Structure of interface status	236

Table A.10 – Attributes for IDN S-0-0021	236
Table A.11 – Attributes for IDN S-0-0022	237
Table A.12 – Attributes for IDN S-0-0026	238
Table A.13 – Attributes for IDN S-0-0027	238
Table A.14 – Attributes for IDN S-0-0127	239
Table A.15 – Attributes for IDN S-0-0128	239
Table A.16 – Attributes for IDN S-0-0144	240
Table A.17 – Attributes for IDN S-0-0027	241
Table A.18 – Attributes for IDN S-0-0187	241
Table A.19 – Attributes for IDN S-0-0188	242
Table A.20 – Attributes for IDN S-0-0328	242
Table A.21 – Attributes for IDN S-0-0329	243
Table A.22 – Attributes for IDN S-0-0360	243
Table A.23 – Attributes for IDN S-0-0361	244
Table A.24 – Attributes for IDN S-0-0362	245
Table A.25 – List index of MDT data container A	246
Table A.26 – Attributes for IDN S-0-0363	246
Table A.27 – List index of MDT data container B	247
Table A.28 – Attributes for IDN S-0-0364	247
Table A.29 – Attributes for IDN S-0-0365	248
Table A.30 – Attributes for IDN S-0-0366	249
Table A.31 – List index of AT data container A	250
Table A.32 – Attributes for IDN S-0-0367	250
Table A.33 – List index of AT data container B	251
Table A.34 – Attributes for IDN S-0-0368	251
Table A.35 – Data container A pointer structure	252
Table A.36 – Attributes for IDN S-0-0369	253
Table A.37 – Data container B pointer structure	253
Table A.38 – Attributes for IDN S-0-0370	254
Table A.39 – Attributes for IDN S-0-0371	254
Table A.40 – Attributes for IDN S-0-0394	255
Table A.41 – Attributes for IDN S-0-0395	256
Table A.42 – Attributes for IDN S-0-0396	256
Table A.43 – Attributes for IDN S-0-0397	257
Table A.44 – Attributes for IDN S-0-0398	258
Table A.45 – Attributes for IDN S-0-0399	258
Table A.46 – Attributes for IDN S-0-0444	259
Table A.47 – Attributes for IDN S-0-0445	259
Table A.48 – Attributes for IDN S-0-0450	260
Table A.49 – Attributes for IDN S-0-0451	261
Table A.50 – Attributes for IDN S-0-0452	262
Table A.51 – Attributes for IDN S-0-0453	263
Table A.52 – Attributes for IDN S-0-0454	264

Table A.53 – Attributes for IDN S-0-0455	265
Table A.54 – Attributes for IDN S-0-0456	266
Table A.55 – Attributes for IDN S-0-0457	267
Table A.56 – Attributes for IDN S-0-0458	268
Table A.57 – Attributes for IDN S-0-0459	269
Table A.58 – Attributes for IDN S-0-0480	270
Table A.59 – Attributes for IDN S-0-0481	271
Table A.60 – Attributes for IDN S-0-0482	272
Table A.61 – Attributes for IDN S-0-0483	273
Table A.62 – Attributes for IDN S-0-0484	274
Table A.63 – Attributes for IDN S-0-0485	275
Table A.64 – Attributes for IDN S-0-0486	276
Table A.65 – Attributes for IDN S-0-0487	277
Table A.66 – Attributes for IDN S-0-0488	278
Table A.67 – Attributes for IDN S-0-0489	279
Table A.68 – Attributes for IDN S-0-0490	280
Table A.69 – Attributes for IDN S-0-0491	280
Table A.70 – Attributes for IDN S-0-0492	281
Table A.71 – Attributes for IDN S-0-0493	281
Table A.72 – Attributes for IDN S-0-0494	282
Table A.73 – Attributes for IDN S-0-0495	283
Table A.74 – Attributes for IDN S-0-0496	283
Table A.75 – Attributes for IDN S-0-0497	284
Table A.76 – Attributes for IDN S-0-0498	285
Table A.77 – Attributes for IDN S-0-0500	285
Table A.78 – Attributes for IDN S-0-0501	286
Table A.79 – Attributes for IDN S-0-0502	286
Table A.80 – Attributes for IDN S-0-0503	287
Table A.81 – Attributes for IDN S-0-0504	288
Table A.82 – Attributes for IDN S-0-0505	288
Table A.83 – Attributes for IDN S-0-0506	289
Table A.84 – Attributes for IDN S-0-0507	289
Table A.85 – Attributes for IDN S-0-0508	290
Table A.86 – Attributes of IDN S-0-1000.0.1	291
Table A.87 – Attributes of IDN S-0-1000	291
Table A.88 – SCP type and version	292
Table A.89 – Attributes of IDN S-0-1002	294
Table A.90 – Attributes of IDN S-0-1003	295
Table A.91 – Attributes of IDN S-0-1005	296
Table A.92 – Attributes of IDN S-0-1006	296
Table A.93 – Attributes for IDN S-0-1007	297
Table A.94 – Attributes for IDN S-0-1008	298
Table A.95 – Attributes of IDN S-0-1009	299

Table A.96 – C-DEV Offset in MDT	299
Table A.97 – Attributes of IDN S-0-1010	300
Table A.98 – Attributes of IDN S-0-1011	301
Table A.99 – S-DEV Offset in AT	302
Table A.100 – Attributes of IDN S-0-1012	302
Table A.101 – Attributes of IDN S-0-1013	303
Table A.102 – SVC Offset in MDT	304
Table A.103 – Attributes of IDN S-0-1014	304
Table A.104 – SVC Offset in AT	305
Table A.105 – Attributes of IDN S-0-1015	305
Table A.106 – Attributes of IDN S-0-1016	306
Table A.107 – Attributes of IDN S-0-1017	307
Table A.108 – Attributes of IDN S-0-1019	308
Table A.109 – Attributes of IDN S-0-1020.0.1	309
Table A.110 – Attributes of IDN S-0-1020	309
Table A.111 – Attributes of IDN S-0-1021.0.1	310
Table A.112 – Attributes of IDN S-0-1021	311
Table A.113 – Attributes of IDN S-0-1022.0.1	312
Table A.114 – Attributes of IDN S-0-1022	312
Table A.115 – Attributes of IDN S-0-1023	313
Table A.116 – Attributes of IDN S-0-1024	314
Table A.117 – Attributes of IDN S-0-1026	315
Table A.118 – Attributes of IDN S-0-1027.0.1	316
Table A.119 – Upper and lower Limit of MTU	317
Table A.120 – Attributes of IDN S-0-1027.0.2	317
Table A.121 – Attributes of IDN S-0-1028	318
Table A.122 – Attributes of IDN S-0-1031	318
Table A.123 – Structure of test pin assignment Port 1 & Port 2	319
Table A.124 – Selectable output signals	319
Table A.125 – Attributes of IDN S-0-1035	320
Table A.126 – Coding of PHY errors	320
Table A.127 – Attributes of IDN S-0-1035	321
Table A.128 – Checking of MAC telegrams	321
Table A.129 – Attributes of IDN S-0-1036	322
Table A.130 – Attributes of IDN S-0-1037	323
Table A.131 – Attributes of IDN S-0-1039.0.1	324
Table A.132 – Attributes of IDN S-0-1039	324
Table A.133 – Attributes of IDN S-0-1040	325
Table A.134 – Attributes of IDN S-0-1041	326
Table A.135 – Attributes of IDN S-0-1044	326
Table A.136 – Device control field (C-DEV)	327
Table A.137 – Attributes of IDN S-0-1045	328
Table A.138 – Device status field	328

Table A.139 – Attributes of IDN S-0-1047	330
Table A.140 – Attributes of IDN S-0-1048	330
Table A.141 – Attributes of IDN S-0-1046	331
Table A.142 – Attributes of IDN S-0-1050.x.1.....	332
Table A.143 – Connection setup	333
Table A.144 – Attributes of IDN S-0-1050.x.2.....	334
Table A.145 – Attributes of IDN S-0-1050.x.3.....	334
Table A.146 – Structure of telegram assignment.....	335
Table A.147 – Attributes of IDN S-0-1050.x.4.....	335
Table A.148 – Attributes of IDN S-0-1050.x.5.....	336
Table A.149 – Attributes of IDN S-0-1050.x.6.....	337
Table A.150 – Attributes of IDN S-0-1050.x.7.....	337
Table A.151 – Attributes of IDN S-0-1050.x.8.....	338
Table A.152 – Attributes of IDN S-0-1050.x.10.....	338
Table A.153 – Attributes of IDN S-0-1050.x.11.....	339
Table A.154 – Attributes of IDN S-0-1050.x.12.....	339
Table A.155 – Attributes of IDN S-0-1050.x.20.....	340
Table A.156 – Attributes of IDN S-0-1050.x.21.....	341
Table A.157 – Attributes of IDN S-0-1051	341
Table A.158 – Attributes of IDN S-0-1060.x.01.....	342
Table A.159 – Attributes of IDN S-0-1060.x.02.....	342
Table A.160 – Attributes of IDN S-0-1060.x.03.....	343
Table A.161 – Attributes of IDN S-0-1060.x.04.....	343
Table A.162 – Attributes of IDN S-0-1060.x.06.....	344
Table A.163 – Attributes of IDN S-0-1060.x.07.....	344
Table A.164 – Attributes of IDN S-0-1060.x.10.....	345
Table A.165 – Attributes of IDN S-0-1061	346
Table A.166 – Attributes of IDN S-0-1080.x.02.....	347
Table A.167 – Attributes of IDN S-0-1080.x.03.....	347
Table A.168 – Attributes of IDN S-0-1080.x.04.....	348
Table A.169 – Attributes of IDN S-0-1081.x.02.....	348
Table A.170 – Attributes of IDN S-0-1081.x.03.....	349
Table A.171 – Attributes of IDN S-0-1081.x.04.....	350
Table A.172 – Attributes of IDN S-0-1099.0.1	350
Table A.173 – Structure of Test-IDN control.....	351
Table A.174 – Attributes of IDN S-0-1099.0.2	351
Table A.175 – Attributes of IDN S-0-1100.0.1	352
Table A.176 – Attributes of IDN S-0-1100.0.2	352
Table A.177 – Attributes of IDN S-0-1100.0.3	353
Table A.178 – Attributes of IDN S-0-1101.x.1.....	354
Table A.179 – Attributes of IDN S-0-1101.x.2.....	354
Table A.180 – Attributes of IDN S-0-1101.x.3.....	355
Table A.181 – Attributes of IDN S-0-1150.x.01.....	355

Table A.182 – OVS Control structure	356
Table A.183 – Attributes of IDN S-0-1150.x.02.....	356
Table A.184 – OVS Status structure	357
Table A.185 – Attributes of IDN S-0-1150.x.03.....	357
Table A.186 – Configuration example	358
Table A.187 – Attributes of IDN S-0-1150.x.04.....	358
Table A.188 – Attributes of IDN S-0-1150.x.05.....	359
Table A.189 – Attributes of IDN S-0-1150.x.06.....	360
Table A.190 – Attributes of IDN S-0-1150.x.07.....	360
Table A.191 – Attributes of IDN S-0-1150.x.08.....	361
Table A.192 – Attributes of IDN S-0-1150.x.09.....	361
Table A.193 – Attributes of IDN S-0-1150.x.10.....	362
Table A.194 – Attributes of IDN S-0-1151.x.01.....	363
Table A.195 – Attributes of IDN S-0-1151.x.02.....	363
Table A.196 – Attributes of IDN S-0-1151.x.03.....	364
Table A.197 – Attributes of IDN S-0-1151.x.04.....	365
Table A.198 – Attributes of IDN S-0-1151.x.06.....	365
Table A.199 – Attributes of IDN S-0-1151.x.07.....	366
Table A.200 – Attributes of IDN S-0-1151.x.08.....	366
Table A.201 – Attributes of IDN S-0-1151.x.08.....	367
Table C.1 – Type 19 LED.....	386
Table C.2 – SDx LED	387
Table C.3 – List of relevant communication-related IDNs	396
Table C.4 – Attributes of IDN S-0-0000	398
Table C.5 – Attributes of IDN S-0-0017	399
Table C.6 – Attributes of IDN S-0-0025	399
Table C.7 – Attributes of IDN S-0-0095.....	400
Table C.8 – Attributes of IDN S-0-0099.....	400
Table C.9 – Attributes of IDN S-0-0192.....	401
Table C.10 – Attributes of IDN S-0-0262	401
Table C.11 – Attributes of IDN S-0-0263	402
Table C.12 – Attributes of IDN S-0-0264	403
Table C.13 – Attributes of IDN S-0-0265	403
Table C.14 – Language codes	404
Table C.15 – Attributes of IDN S-0-0266	404
Table C.16 – Attributes of IDN S-0-0267	405
Table C.17 – States of the password state machine.....	406
Table C.18 – Transitions of the password state machine.....	407
Table C.19 – Changing the password.....	407
Table C.20 – Attributes of IDN S-0-0269	408
Table C.21 – Structure of storage mode.....	408
Table C.22 – Attributes of IDN S-0-0270	409
Table C.23 – Attributes of IDN S-0-0279	409

Table C.24 – Attributes of IDN S-0-0293	410
Table C.25 – Attributes of IDN S-0-0326.x.00	410
Table C.26 – Attributes of IDN S-0-0327.x.00	411
Table C.27 – Attributes of IDN S-0-0390	412
Table C.28 – Prioritization of diagnostic events.....	412
Table C.29 – Transitions of the password state machine.....	413
Table C.30 – Attributes of IDN S-0-0420	414
Table C.31 – Attributes of IDN S-0-0422	414
Table C.32 – Attributes of IDN S-0-0423	415
Table C.33 – Attributes of IDN S-0-0425	416
Table C.34 – Structure of the sub-device state machine control	416
Table C.35 – Attributes of IDN S-0-0531	417
Table C.36 – Attributes of IDN S-0-1300.x.1	417
Table C.37 – Attributes of IDN S-0-1300.x.2	418
Table C.38 – Attributes of IDN S-0-1300.x.3	418
Table C.39 – Vendor code	419
Table C.40 – Attributes of IDN S-0-1300.x.4	419
Table C.41 – Attributes of IDN S-0-1300.x.5	420
Table C.42 – Attributes of IDN S-0-1300.x.6	420
Table C.43 – Attributes of IDN S-0-1300.x.7	421
Table C.44 – Attributes of IDN S-0-1300.x.8	421
Table C.45 – Attributes of IDN S-0-1300.x.9	422
Table C.46 – Attributes of IDN S-0-1300.x.10	422
Table C.47 – Attributes of IDN S-0-1300.x.11	423
Table C.48 – Attributes of IDN S-0-1300.x.12	424
Table C.49 – Attributes of IDN S-0-1300.x.13	424
Table C.50 – Attributes of IDN S-0-1300.x.14	425
Table C.51 – Attributes of IDN S-0-1300.x.20	426
Table C.52 – Attributes of IDN S-0-1300.x.21	426
Table C.53 – Attributes of IDN S-0-1300.x.22	427
Table C.54 – Attributes of IDN S-0-1300.x.23	428
Table C.55 – Attributes of IDN S-0-1301	429
Table C.56 – Structure of GDP classes & version	430
Table C.57 – Attributes of IDN S-0-1302.x.1	430
Table C.58 – Coding of S-1302.x.01	431
Table C.59 – Attributes of IDN S-0-1302.x.2	431
Table C.60 – Attributes of IDN S-0-1302.x.3	434
Table C.61 – Attributes of IDN S-0-1303.0.1	434
Table C.62 – Attributes of IDN S-0-1303.0.2	435
Table C.63 – Coding of S-1303.0.02	435
Table C.64 – Attributes of IDN S-0-1303.0.3	436
Table C.65 – Coding of S-1303.0.2	436
Table C.66 – Attributes of IDN S-0-1303.0.10	437

Table C.67 – Attributes of IDN S-0-1303.0.11	438
Table C.68 – Attributes of IDN S-0-1303.0.12	438
Table C.69 – Attributes of IDN S-0-1305.0.1	439
Table C.70 – Structure of Type 19 time	439
Table C.71 – Attributes of IDN S-0-1305.0.2	440
Table C.72 – Attributes of IDN S-0-1310	440
Table C.73 – Attributes of IDN S-0-1350	441
Table C.74 – Attributes of IDN S-0-1310	442
Table C.75 – Structure of Test IDN Diagnostic Event	443
Table C.76 – Status codes with the diagnosis class "operational state"	443
Table C.77 – Status codes with the diagnosis class "procedure command specific state"	444

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
FIELDBUS SPECIFICATIONS –****Part 4-19: Data-link layer protocol specification –
Type 19 elements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

Attention is drawn to the fact that the use of the associated protocol type is restricted by its intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a layer protocol type to be used with other layer protocols of the same type, or in other type combinations explicitly authorized by its intellectual-property-right holders.

NOTE Combinations of protocol types are specified in IEC 61784-1 and IEC 61784-2.

International Standard IEC 61158-4-19 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This third edition cancels and replaces the second edition published in 2010. This edition constitutes a technical revision. The main changes with respect to the previous edition are listed below:

- introducing connections based on a producer-consumer model;

- introducing additional mechanisms to realize features such as timestamping and oversampling;
- improving the hotplug and redundancy features;
- improving the phase switching and the error handling;
- editorial improvements.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/762/FDIS	65C/772/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

NOTE Attention is drawn to the fact that use of the associated protocol type(s) is restricted by its (their) intellectual-property-right holder(s). In all cases, the commitment to limited release of intellectual-property-rights made by the holder(s) of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the profile parts. Use of the various protocol type(s) in other combinations may require permission from their respective intellectual-property-right holders.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of patents concerning Type 19 elements and possibly other types given in this document as follows:

DE 102 00 502 4759.8-32	[BR]	Verfahren zur Laufzeitkorrektur in einer Kommunikationsstruktur
DE 102 37 097	[RI]	Korrektur von Signallaufzeiten in verteilten Kommunikationssystemen

IEC takes no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licenses either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights is registered with IEC. Information may be obtained from:

[BR] BoschRexrothAG
Zum Eisengiesser 1
D-97816 Lohr
Germany

[RI] Rexroth Indramat GmbH
Bgm.-Dr.-Nebel-Str. 2
D - 97816 Lohr
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (<http://patents.iec.ch>) maintain on-line databases of patents relevant to their standards. Users are encouraged to consult the databases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-19: Data-link layer protocol specification – Type 19 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities

- a) in a synchronously-starting cyclic manner, according to a pre-established schedule, and
- b) in a cyclic or acyclic asynchronous manner, as requested each cycle by each of those data-link entities.

Thus this protocol can be characterized as one which provides cyclic and acyclic access asynchronously but with a synchronous restart of each cycle.

1.2 Specifications

This standard specifies

- a) procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed data-link service provider;
- b) the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This part of this standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE All parts of the IEC 61158 series, as well as IEC 61784-1 and IEC 61784-2 are maintained simultaneously. Cross-references to these documents within the text therefore refer to the editions as dated in this list of normative references.

IEC 61158-4-16:2007, *Industrial communication networks – Fieldbus specifications – Part 4-16: Data-link layer protocol specification – Type 16 elements*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Part 1: Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Part 3: Basic Reference Model: Naming and addressing*

ISO/IEC 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

ISO 8601, *Data elements and interchange formats – Information interchange – Representation of dates and times*

IEEE 802.3: *IEEE Standard for Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer Specifications*

Internet Engineering Task Force (IETF), *Request for Comments (RFC): RFC 879, The TCP Maximum Segment Size and Related Topics* (available at <<http://www.ietf.org/rfc/rfc0879.txt>>)