

© Copyright SEK. Reproduction in any form without permission is prohibited.

Digitalt adresserbart gränssnitt för ljusarmaturer (DALI) – Del 101: Allmänna fordringar på systemkomponenter

*Digital addressable lighting interface –
Part 101: General requirements –
System components*

Som svensk standard gäller europastandarden EN 62386-101:2014. Den svenska standarden innehåller den officiella engelska språkversionen av EN 62386-101:2014.

Nationellt förord

Europastandarden EN 62386-101:2014

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 62386-101, Second edition, 2014 - Digital addressable lighting interface - Part 101: General requirements - System components**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 62386-101, utgåva 1, 2010, gäller ej fr o m 2017-12-12.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

EUROPEAN STANDARD

EN 62386-101

NORME EUROPÉENNE

EUROPÄISCHE NORM

December 2014

ICS 29.140; 29.140.50

Supersedes EN 62386-101:2009

English Version

**Digital addressable lighting interface -
Part 101: General requirements - System components
(IEC 62386-101:2014)**

Interface d'éclairage adressable numérique -
Partie 101: Exigences générales - Composants de système
(CEI 62386-101:2014)

Digital adressierbare Schnittstelle für die Beleuchtung -
Teil 101: Allgemeine Anforderungen - Systemkomponenten
(IEC 62386-101:2014)

This European Standard was approved by CENELEC on 2014-12-12. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

Foreword

The text of document 34C/1098/FDIS, future edition 2 of IEC 62386-101, prepared by SC 34C "Auxiliaries for lamps" of IEC/TC 34 "Lamps and related equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 62386-101:2014.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2015-09-12
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2017-12-12

This document supersedes EN 62386-101:2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 62386-101:2014 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

CISPR 15	NOTE	Harmonized as EN 55015.
IEC 61547	NOTE	Harmonized as EN 61547.
ISO/IEC 7498-1	NOTE	Harmonized as EN ISO/IEC 7498-1 ¹⁾ .

¹⁾ Withdrawn publication.

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61347	Series	Lamp controlgear	EN 61347	Series
IEC 61347-1	-	Lamp controlgear - Part 1: General and safety requirements	EN 61347-1	-
IEC 62386-102	2014	Digital addressable lighting interface - Part 102: General requirements - Control gear	EN 62386-102	2014
IEC 62386-103	2014	Digital addressable lighting interface - Part 103: General requirements - Control devices	EN 62386-103	2014
IEC 61000-4-11	-	Electromagnetic compatibility (EMC) - Part 4-11: Testing and measurement techniques - Voltage dips, short interruptions and voltage variations immunity tests	EN 61000-4-11	-

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
2 Normative references	10
3 Terms and definitions	10
4 General	15
4.1 Purpose	15
4.2 Version number	15
4.3 System structure and architecture.....	15
4.4 System information flow	16
4.5 Command types	16
4.6 Bus units.....	17
4.6.1 Transmitters and receivers in bus units.....	17
4.6.2 Control gear	17
4.6.3 Input device.....	17
4.6.4 Single master application controller	17
4.6.5 Multi-master application controller	18
4.6.6 Sharing an interface	18
4.7 Bus power supply and load calculations	19
4.7.1 Current demand coverage	19
4.7.2 Maximum signal current compliance	19
4.7.3 Simplified system calculation	19
4.8 Wiring	19
4.8.1 Wiring structure	19
4.8.2 Wiring specification	19
4.9 Insulation	20
4.10 Earthing of the bus.....	20
4.11 Power interruptions at bus units.....	20
4.11.1 Different levels of power interruptions.....	20
4.11.2 Short power interruptions of external power supply.....	20
4.11.3 External power cycle	21
4.11.4 Short interruptions of bus power supply	21
4.11.5 Bus power down	21
4.11.6 System start-up timing	21
5 Electrical specification	23
5.1 General.....	23
5.2 Marking of the interface	23
5.3 Capacitors between the interface and earth	23
5.4 Signal voltage rating	23
5.5 Signal current rating.....	24
5.6 Marking of bus powered bus unit.....	24
5.7 Signal rise time and fall time	24
6 Bus power supply	26
6.1 General.....	26
6.2 Marking of the bus power supply terminals.....	26
6.3 Capacitors between the interface and earth	26

6.4	Voltage rating	26
6.5	Current rating.....	26
6.5.1	General current rating.....	26
6.5.2	Single bus power supply current rating	27
6.5.3	Integrated bus power supply current rating	27
6.5.4	Dynamic behaviour of the bus power supply	27
6.6	Bus power supply timing requirements	28
6.6.1	Short power supply interruptions.....	28
6.6.2	Short circuit behaviour.....	29
7	Transmission protocol structure	29
7.1	General.....	29
7.2	Bit encoding.....	29
7.2.1	Start bit and data bit encoding	29
7.2.2	Stop condition encoding	30
7.3	Frame description	30
7.4	Frame types.....	30
7.4.1	16 bit forward frame.....	30
7.4.2	24 bit forward frame.....	30
7.4.3	Reserved forward frame	30
7.4.4	Backward frame.....	30
7.4.5	Proprietary forward frames	30
8	Timing	31
8.1	Transmitter timing.....	31
8.1.1	Transmitter bit timing	31
8.1.2	Transmitter frame sequence timing	32
8.2	Receiver timing.....	32
8.2.1	Receiver bit timing.....	32
8.2.2	Receiver bit timing violation	34
8.2.3	Receiver frame size violation	34
8.2.4	Receiver frame sequence timing.....	34
8.2.5	Reception of backward frames.....	35
8.3	Multi-master transmitter timing.....	35
8.3.1	Multi-master transmitter bit timing.....	35
8.3.2	Multi-master transmitter frame sequence timing.....	36
9	Method of operation.....	36
9.1	Collision avoidance, collision detection and collision recovery	36
9.1.1	General	36
9.1.2	Collision avoidance.....	37
9.1.3	Collision detection	37
9.1.4	Collision recovery	38
9.2	Transactions	39
9.3	Send-twice forward frames and send-twice commands	40
9.4	Command iteration.....	40
9.5	Usage of a shared interface	41
9.5.1	General	41
9.5.2	Backward frames	41
9.5.3	Forward frames	41
9.6	Use of multiple bus power supplies	41

9.7	Command execution	42
10	Declaration of variables	42
11	Definition of commands	42
12	Test procedures	42
12.1	General notes on test.....	42
12.1.1	Abbreviations.....	42
12.1.2	Ambient temperature	42
12.1.3	External power supply voltage and frequency	43
12.1.4	Measurement requirements	43
12.1.5	Test signal generators and bus voltage sources	43
12.1.6	Deviation from documentation	43
12.1.7	Test setup	43
12.1.8	Notation.....	43
12.2	General interface tests.....	49
12.2.1	Label and literature check.....	49
12.2.2	Interface marking check.....	49
12.2.3	Bus powered bus unit marking check.....	50
12.2.4	Bus power supply marking check.....	52
12.2.5	Insulation test.....	54
12.2.6	Capacitor check.....	55
12.3	Bus power supply tests	55
12.3.1	Voltage rating test	55
12.3.2	Voltage rise time test.....	56
12.3.3	Current rating test.....	56
12.3.4	Dynamic behaviour test	58
12.3.5	Power-on open circuit test	60
12.3.6	Power-on timing test.....	61
12.3.7	Power supply short interruptions test	62
12.3.8	Power supply short circuit test.....	63
12.3.9	Power supply current consumption test.....	64
12.4	Control device tests	65
12.5	Control gear tests	65
Annex A	(informative) Background information for systems.....	66
A.1	Wiring information.....	66
A.2	System architectures	67
A.2.1	General	67
A.2.2	Single master architecture	67
A.2.3	Multi-master architecture with one application controller	68
A.2.4	Multi-master architecture with more than one application controller	69
A.2.5	Multi-master architecture with integrated input device.....	70
A.2.6	Multi-master architecture with integrated input device and power supply.....	71
A.3	Collision detection	72
A.4	Timing definition explanations.....	73
A.4.1	General	73
A.4.2	Receiver timing.....	73
A.4.3	Transmitter timing.....	73
A.4.4	Grey areas	74
A.5	Maximum current consumption calculation explanation	74

A.5.1	Single bus power supply	74
A.5.2	Multiple bus power supplies	75
A.5.3	Redundant bus power supplies	76
A.6	Communication layer overview	77
A.6.1	General	77
A.6.2	Physical layer	77
A.6.3	Data link layer	77
A.6.4	Network layer	77
A.6.5	Transport layer	78
A.6.6	Session layer.....	78
A.6.7	Presentation layer	78
A.6.8	Application layer.....	78
Bibliography.....		79
Figure 1	– IEC 62386 graphical overview	9
Figure 2	– System structure example	16
Figure 3	– Communication between bus units (example).....	16
Figure 4	– Example of a shared interface	18
Figure 5	– Start up timing example	22
Figure 6	– Maximum signal rise and fall time measurements.....	25
Figure 7	– Minimum signal rise and fall time measurements.....	25
Figure 8	– Bus power supply current behaviour.....	28
Figure 9	– Bus power supply voltage behaviour	28
Figure 10	– Frame example	29
Figure 11	– Bi-phase encoded bits	30
Figure 12	– Bit timing example.....	31
Figure 13	– Settling time illustration	32
Figure 14	– Receiver timing decision example	34
Figure 15	– Collision detection timing decision example.....	38
Figure 16	– Collision recovery example.....	39
Figure 17	– Current rating test signal	57
Figure 18	– Dynamic behaviour test setup	58
Figure 19	– Dynamic behaviour test signal.....	59
Figure A.1	– Single master architecture example	68
Figure A.2	– Multi-master architecture example with one application controller	69
Figure A.3	– Multi-master architecture example with two application controllers.....	70
Figure A.4	– Multi-master architecture example with integrated input device	71
Figure A.5	– Multi-master architecture example with integrate input device and bus power supply	72
Figure A.6	– Collision detection timing diagram.....	73
Figure A.7	– Transmitter and receiver timing illustration.....	74
Figure A.8	– Bus power supply current values.....	75
Figure A.9	– Current demand coverage.....	75
Figure A.10	– Combination of 4 bus power supplies	76
Figure A.11	– Redundant bus power supplies	76

Table 1 – System components	15
Table 2 – Transmitters and receivers in bus units	17
Table 3 – Power-interruption timing of external power.....	20
Table 4 – Power-interruption timing of bus power.....	20
Table 5 – Short power interruptions	21
Table 6 – Start-up timing.....	22
Table 7 – System voltage levels.....	23
Table 8 – Receiver voltage levels	23
Table 9 – Transmitter voltage levels	24
Table 10 – Current rating	24
Table 11 – Signal rise and fall times	25
Table 12 – Bus power supply output voltage	26
Table 13 – Bus power supply current rating	27
Table 14 – Bus power supply dynamic behaviour	27
Table 15 – Short circuit timing behaviour	29
Table 16 – Transmitter bit timing.....	32
Table 17 – Transmitter settling time values	32
Table 18 – Receiver timing starting at the beginning of a logical bit	33
Table 19 – Receiver timing starting at an edge inside of a logical bit	33
Table 20 – Receiver settling time values	35
Table 21 – Multi-master transmitter bit timing.....	35
Table 22 – Multi-master transmitter settling time values	36
Table 23 – Checking a logical bit, starting at an edge at the beginning of the bit.....	37
Table 24 – Checking a logical bit, starting at an edge inside the bit	38
Table 25 – Collision recovery timing	39
Table 26 – Transmitter command iteration timing	41
Table 27 – Receiver command iteration timing.....	41
Table 28 – Function call keywords	44
Table 29 – Defined operators.....	47
Table A.1 – Maximum cable length	67
Table A.2 – OSI layer model of IEC 62386.....	77

INTERNATIONAL ELECTROTECHNICAL COMMISSION

DIGITAL ADDRESSABLE LIGHTING INTERFACE –**Part 101: General requirements –
System components**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62386-101 has been prepared by subcommittee 34C: Auxiliaries for lamps, of IEC technical committee 34: Lamps and related equipment.

This second edition cancels and replaces the first edition published in 2009. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) collection of all bus timing requirements defined in IEC 62386-101:2009 and IEC 62386-102:2009 and rework of the timing requirements to facilitate the preparation of a future control devices standard, taking particular account of the requirements for multi-master systems. The 10 % tolerances have been replaced by minimum and maximum timing values;
- b) integration of multi-master timing requirements;

- c) extension of the defined forward frames;
- d) addition of wiring requirements;
- e) improvement of the bus power supply requirements;
- f) improvement of test sequences and description of the test sequences in the form of pseudo code instead of flow charts.

The text of this standard is based on the following documents:

FDIS	Report on voting
34C/1098/FDIS	34C/1111/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This Part 101 is intended to be used in conjunction with:

- Part 102, which contains general requirements for the relevant product type (control gear), and with the appropriate Part 2xx (particular requirements for control gear);
- Part 103, which contains general requirements for the relevant product type (control devices), and the appropriate Part 3xx (particular requirements for control devices).

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 62386 series, under the general title: *Digital addressable lighting interface*, can be found on the IEC website

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 62386 contains several parts, referred to as series. The 1xx series includes the basic specifications. Part 101 contains general requirements for system components, Part 102 extends this information with general requirements for control gear and Part 103 extends it further with general requirements for control devices.

The 2xx parts extend the general requirements for control gear with lamp specific extensions (mainly for backward compatibility with Edition 1 of IEC 62386) and with control gear specific features.

The 3xx parts extend the general requirements for control devices with input device specific extensions describing the instance types as well as some common features that can be combined with multiple instance types.

This second edition of IEC 62386-101 is published in conjunction with IEC 62386-102:2014 and with the various parts that make up the IEC 62386-2xx series for control gear, together with IEC 62386-103:2014 and the various parts that make up the IEC 62386-3xx series of particular requirements for control devices. The division into separately published parts provides for ease of future amendments and revisions. Additional requirements will be added as and when a need for them is recognised.

The setup of the standard is graphically represented in Figure 1 below.




Figure 1 – IEC 62386 graphical overview

When this part of IEC 62386 refers to any of the clauses of the other two parts of the IEC 62386-1xx series, the extent to which such a clause is applicable and the order in which the tests are to be performed are specified. The other parts also include additional requirements, as necessary.

All numbers used in this International Standard are decimal numbers unless otherwise noted. Hexadecimal numbers are given in the format 0xVV, where VV is the value. Binary numbers are given in the format XXXXXXXXb or in the format XXXX XXXX, where X is 0 or 1, "x" in binary numbers means "don't care".

DIGITAL ADDRESSABLE LIGHTING INTERFACE –

Part 101: General requirements – System components

1 Scope

This part of IEC 62386 is applicable to system components in a bus system for control by digital signals of electronic lighting equipment. This electronic lighting equipment should be in line with the requirements of IEC 61347, with the addition of d.c. supplies.

NOTE Tests in this standard are type tests. Requirements for testing individual bus units during production are not included.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61347 (all parts), *Lamp controlgear*

IEC 61347-1, *Lamp controlgear – Part 1: General and safety requirements*

IEC 62386-102:2014, *Digital addressable lighting interface – Part 102: General requirements – Control gear*

IEC 62386-103:2014, *Digital addressable lighting interface – Part 103: General requirements – Control devices*

IEC 61000-4-11, *Electromagnetic compatibility (EMC) – Part 4-11: Testing and measurement techniques – Voltage dips, short interruptions and voltage variations immunity tests*