



Fastställd 2018-05-16

Utgåva 3 Sida 1 (1+49) Ansvarig kommitté SEK TK 101

© Copyright SEK. Reproduction in any form without permission is prohibited.

Elektrostatiska urladdningar – Del 4-4: Provningsmetoder för särskilda tillämpningar – Klassning av storsäckar (FIBC-behållare) med avseende på elektrostatiska egenskaper

Electrostatics -

Part 4-4: Standard test methods for specific applications – Electrostatic classification of flexible intermediate bulk containers (FIBC)

Som svensk standard gäller europastandarden EN IEC 61340-4-4:2018. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 61340-4-4:2018.

Nationellt förord

Europastandarden EN IEC 61340-4-4:2018

består av:

- europastandardens ikraftsättningsdokument, utarbetat inom CENELEC
- IEC 61340-4-4, Third edition, 2018 Electrostatics Part 4-4: Standard test methods for specific applications Electrostatic classification of flexible intermediate bulk containers (FIBC)

utarbetad inom International Electrotechnical Commission, IEC.

EN från CENELEC som är identiska med motsvarande IEC-standarder och som görs tillgängliga för nationalkommittéerna efter den 1 januari 2018 får en beteckning som inleds med EN IEC istället för som tidigare bara EN.

Tidigare fastställd svensk standard SS-EN 61340-4-4, utgåva 2, 2012 och SS-EN 61340-4-4/A1, utgåva 1, 2015, gäller ej fr o m 2021-03-06.

ICS 17.220.99; 29.020.00; 55.080.00

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284 164 29 Kista Tel 08-444 14 00 www.elstandard.se

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN IEC 61340-4-4

April 2018

ICS 17.220.99; 29.020; 55.080

Supersedes EN 61340-4-4:2012

English Version

Electrostatics - Part 4-4: Standard test methods for specific applications - Electrostatic classification of flexible intermediate bulk containers (FIBC) (IEC 61340-4-4:2018)

Electrostatique - Partie 4-4: Méthodes d'essai normalisées pour des applications spécifiques - Classification électrostatique des grands récipients pour vrac souples (GRVS)

(IEC 61340-4-4:2018)

Elektrostatik - Teil 4-4: Normprüfverfahren für spezielle Anwendungen - Einordnung flexibler Schüttgutbehälter (FIBC) in elektrostatischer Hinsicht (IEC 61340-4-4:2018)

This European Standard was approved by CENELEC on 2018-03-06. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2018 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

European foreword

The text of document 101/546/FDIS, future edition 3 of IEC 61340-4-4, prepared by IEC/TC 101 "Electrostatics" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61340-4-4:2018.

The following dates are fixed:

•	latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2018-12-06

 latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2021-03-06

This document supersedes EN 61340-4-4:2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61340-4-4:2018 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60079-32-2 NOTE Harmonized as EN 60079-32-2.
IEC 61340-2-1 NOTE Harmonized as EN 61340-2-1.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu,

Publication IEC 60079-10-1	<u>Year</u> -	Title Explosive atmospheres - Part 10-1: Classification of areas - Explosive gas atmospheres	<u>EN/HD</u> EN 60079-10-1	<u>Year</u> -
IEC 60079-10-2	-	Explosive atmospheres - Part 10-2: Classification of areas - Explosive dust atmospheres	EN 60079-10-2	-
IEC 60243-1	2013	Electric strength of insulating materials - Test methods Part 1: Tests at power frequencies	EN 60243-1	2013
IEC 60243-2	-	Electric strength of insulating materials - Test methods - Part 2: Additional requirements for tests using direct voltage	EN 60243-2	-
IEC 60417-DB	-	Graphical symbols for use on equipment	-	-
IEC 61340-2-3	-	Electrostatics - Part 2-3: Methods of test for determining the resistance and resistivity of solid materials used to avoid electrostatic charge accumulation	EN 61340-2-3	-
ISO 7000	-	Graphical symbols for use on equipment - Registered symbols	-	-
ISO 21898	-	Packaging - Flexible intermediate bulk containers (FIBCs) for non-dangerous goods	EN ISO 21898	-
ISO/IEC 80079-20-	-2-	Explosive atmospheres - Part 20-2: Material characteristics - Combustible dusts test methods	EN ISO/IEC 80079- 20-2	· -
ASTM E582	-	Standard test method for minimum ignition energy and quenching distance in gaseous mixtures		-

CONTENTS

FC	REWO	RD	5
IN	TRODU	CTION	7
1	Scop	e	8
2	Norm	ative references	9
3	Term	s and definitions	10
4	Class	sification	12
	4.1	Classification for FIBC	
	4.1.1	Principles of classification	
	4.1.2	·	
	4.1.3	• •	
	4.1.4		
	4.1.5	Type D	12
	4.2	Principles of classification and requirements for inner liners	12
	4.2.1	Components of inner liners	12
	4.2.2	Surface resistivity measurements for inner liners	13
	4.2.3	Breakdown voltage measurements for inner liners	13
	4.2.4	Type L1	14
	4.2.5	Type L1C	15
	4.2.6	Type L2	15
	4.2.7	. 7	
	4.3	Combination of FIBC and inner liners	
5		use of FIBC	
6	Labe	lling	19
7	Requ	irements for FIBC	22
	7.1	General remarks	22
	7.2	Requirements for dust environments with ignition energies greater than 3 mJ (apply to Type B FIBC, Type C FIBC and Type D FIBC)	22
	7.3	Requirements for vapour and gas atmospheres and for dust environments	
		with ignition energies of 3 mJ or less	
	7.3.1	Type C FIBC	
	7.3.2	71	
8	Atmo	sphere for conditioning, calibrating and testing	
	8.1	Conditioning time	24
	8.2	Electrical breakdown voltage, surface resistivity and resistance to	24
	0.2	groundable point testing	
	8.3 8.4	Surface resistivity testing	
9		procedures	
J			
	9.1 9.2	Sampling	
	9.2	Electrical breakdown voltage Ignition testing	
	9.3.1	Apparatus	
	9.3.1	Establishing correct charging current	
	9.3.2		
	9.4	Resistance to groundable point	
	9.4.1	Apparatus	

9.4.2 Test procedure	35
10 Test report	36
10.1 General	36
10.2 For all types of testing	37
10.3 For electrical breakdown voltage testing	37
10.4 For ignition testing	
10.5 For resistance to groundable point testing	37
10.6 For surface resistivity testing of inner liners, labels and document pockets	37
10.7 For test reports issued by accredited testing authorities	37
Annex A (informative) Electrical breakdown voltage – Typical voltage/time graphs	39
Annex B (normative) Polypropylene pellets for ignition testing	40
Annex C (informative) Guidance on test methods for manufacturing quality control	41
C.1 Introductory remarks	41
C.2 Test methods	41
C.2.1 Resistance measurements	41
C.2.2 Charge decay measurements	42
C.2.3 Charge transfer measurements	42
Annex D (normative) Classification of hazardous areas and zones	43
Annex E (informative) Risks associated with cone discharges	44
Annex F (informative) Explanation for resistance and resistivity limits, and thickness limits for insulating layers of inner liners	45
F.1 Resistance to groundable point limit for Type C FIBC	45
F.2 Resistivity of inner liners	45
F.3 Thickness of insulating layers of inner liners	45
Bibliography	47
Figure 1 – Examples of inner liners in FIBC	13
Figure 2 – Example of a label for Type B FIBC	20
Figure 3 – Example of a label for Type C FIBC	20
Figure 4 – Example of a label for Type D FIBC	
Figure 5 – Example of labels for Type C FIBC designated earth bonding points	
Figure 6 – Ignition probe	
Figure 7 – Perforated metal plate for use in ignition probe	
Figure 8 – Gas control and mixing apparatus (schematic)	
Figure 9 – FIBC filling rig (schematic)	
Figure 10 – Corona charging unit (schematic)	
Figure A.1 – Example of voltage/time graph for material showing distinct breakdown	39
Figure A.2 – Example of voltage/time graph for material showing reduction in rate of voltage rise because of conduction within the test material	39
Table 1 – Permissible configurations and requirements for Type L1 inner liners (without	
conductive internal layers)	14
Table 2 – Permissible configurations and requirements for Type L1C inner liners (with conductive internal layers ^a)	15
Table 3 – Permissible configurations and requirements for Type L2 inner liners	
Table 1 - Permissible configurations and requirements for Type I 3 inner liners	17

Table 5 – Use of different types of FIBC	17
Table 6 – Inner liners and FIBC: combinations that are permissible and not permissible in hazardous explosive atmospheres	18
Table 7 – Volume concentrations of flammable gas mixture	27
Table 8 – Example of full sample description to be included in the test report	38
Table B.1 – Particle size distribution of polypropylene pellets	40
Table D.1 – Classification of hazardous areas in IEC 60079-10-1 and IEC 60079-10-2	43
Table D.2 – Classification of zones in IEC 60079-10-1 and IEC 60079-10-2	43

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROSTATICS -

Part 4-4: Standard test methods for specific applications – Electrostatic classification of flexible intermediate bulk containers (FIBC)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61340-4-4 has been prepared by IEC technical committee 101: Electrostatics.

This third edition cancels and replaces the second edition, published in 2012, and Amendment 1:2014. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) in light of experimental evidence, the maximum resistance to ground limit for Type C FIBC, and corresponding resistance limits for inner liners used in Type C FIBC has been increased from $1.0 \times 10^7 \Omega$ to $1.0 \times 10^8 \Omega$;
- b) the classification of Type L1 inner liners has been revised and extended to include Type L1C inner liners made from multi-layer materials with a conductive internal layer;

c) a labelling requirement to include a reference to IEC TS 60079-32-1 for guidance on earthing has been added.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
101/546/FDIS	101/555/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 61340 series, published under the general title *Electrostatics*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- · reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Flexible intermediate bulk containers (FIBC) are widely used for the storage, transportation and handling of powdered, flaked or granular material. Typically, they are constructed from woven polypropylene fabric in the form of cubic bags of about 1 m³ volume, although they can vary in shape and in size from 0,25 m³ to 3 m³. The fabric used may be a single layer, a multi-layer laminate, or a coated fabric. Untreated polypropylene is an electrical insulator, as is often the case with the products placed in FIBC. There is ample opportunity for the generation of electrostatic charge during filling and emptying operations and in unprotected FIBC high levels of charge can quickly build up. In such cases, electrostatic discharges are inevitable and can be a severe problem when FIBC are used in hazardous explosive atmospheres.

A hazardous explosive atmosphere can be generated when handling fine powders that create dust clouds or thin layers of powder, both of which can be ignited by electrostatic discharges. A hazardous explosive atmosphere can also be generated when using gases or volatile solvents. In these industrial situations, there is clearly a need to eliminate incendive electrostatic discharges.

As with any industrial equipment, a thorough risk assessment should always be conducted before using FIBC in potentially hazardous situations. This part of IEC 61340 describes a system of classification, test methods, performance and design requirements and safe use procedures that can be used by manufacturers, specifiers and end-users as part of a risk assessment of any FIBC intended for use within a hazardous explosive atmosphere. However, it does not include procedures for evaluating the specific risks of electrostatic discharges arising from products within FIBC, for example cone discharges, from personnel or from equipment used near FIBC. Information on risks associated with cone discharges is given in Annex E.

CAUTION: The test methods specified in this document involve the use of high voltage power supplies and flammable gases that may present hazards if handled incorrectly, particularly by unqualified or inexperienced personnel. Users of this document are encouraged to carry out proper risk assessments and pay due regard to local regulations before undertaking any of the test procedures.

ELECTROSTATICS –

Part 4-4: Standard test methods for specific applications – Electrostatic classification of flexible intermediate bulk containers (FIBC)

1 Scope

This part of IEC 61340 specifies requirements for flexible intermediate bulk containers (FIBC) between $0.25~\text{m}^3$ and $3~\text{m}^3$ in volume, intended for use in hazardous explosive atmospheres. The explosive atmosphere can be created by the contents in the FIBC or can exist outside the FIBC.

The requirements include:

- classification and labelling of FIBC;
- classification of inner liners;
- specification of test methods for each type of FIBC, inner liner, labels and document pockets;
- design and performance requirements for FIBC, inner liners, labels and document pockets;
- safe use of FIBC (including those with inner liners) within different zones defined for explosion endangered environments, described for areas where combustible dusts are, or can be, present (IEC 60079-10-2), and for explosive gas atmospheres (IEC 60079-10-1);
- procedures for type qualification and certification of FIBC, including the safe use of inner liners.

NOTE 1 Guidance on test methods that can be used for manufacturing quality control is given in Annex C.

The requirements of this document are applicable to all types of FIBC and inner liners, tested as manufactured, prior to use and intended for use in hazardous explosive atmospheres: Zones 1 and 2 (Groups IIA and IIB only) and Zones 21 and 22 (see Annex D for classification of hazardous areas and explosion groups). For some types of FIBC, the requirements of this document apply only to use in hazardous explosive atmospheres with minimum ignition energy of 0,14 mJ or greater and where charging currents do not exceed 3,0 μ A.

NOTE 2

0,14 mJ represents a realistic minimum ignition energy for a Group IIB gas or vapour atmosphere. Although more sensitive materials exist, 0,14 mJ is the lowest minimum ignition energy of any material that is likely to be present when FIBC are emptied. 3,0 μ A is the highest charging current likely to be found in common industrial processes. This combination of minimum ignition energy and charging current represents the most severe conditions that might be expected in practice.

FIBC are not normally used in Zone 0 or Zone 20. If FIBC are used in Zone 0 or Zone 20, the requirements of this document are applicable, together with additional requirements that are beyond the scope of this document to define.

The volume contained within FIBC can be designated as Zone 20, in which case the requirements of this document are applicable.

Solids containing residual solvent can result in a hazardous explosive atmosphere within FIBC, possibly resulting in the volume being designated as Zone 1 or Zone 2; in which case the requirements of this document are applicable.

Compliance with the requirements specified in this document does not necessarily ensure that hazardous electrostatic discharges, for example cone discharges, will not be generated by the

contents in FIBC. Information on the risks associated with cone discharges is given in Annex E.

Compliance with the requirements of this document does not mitigate the need for full risk assessment. For example, metal and other conductive powders and toner powders can require additional precautions to prevent hazardous discharges from the powders.

NOTE 3 In the examples mentioned in the paragraph above, additional precautions can be necessary in the case of metal or other conductive powder because if the powder is isolated and becomes charged, incendiary sparks can occur, and in the case of toner powders, incendiary discharges can occur during rapid filling and emptying operations. IEC TS 60079-32-1 [1] gives guidance on additional precautions that can be necessary.

Test methods included in this document can be used in association with other performance requirements, for example when a risk assessment has shown the minimum ignition energy of concern is less than 0,14 mJ, charging currents are greater than 3,0 μ A, or the ambient conditions are outside of the range specified in this document.

Compliance with the requirements specified in this document does not necessarily ensure that electric shocks to personnel will not occur from FIBC during normal use.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-10-1, Explosive atmospheres – Part 10-1: Classification of areas – Explosive gas atmospheres

IEC 60079-10-2, Explosive atmospheres – Part 10-2: Classification of areas – Explosive dust atmospheres

IEC 60243-1:2013, Electric strength of insulating materials – Test methods – Part 1: Tests at power frequencies

IEC 60243-2, Electric strength of insulating materials – Test methods – Part 2: Additional requirements for tests using direct voltage

IEC 60417, Graphical symbols for use on equipment (available at: http://www.graphical-symbols.info/equipment)

IEC 61340-2-3, Electrostatics – Part 2-3: Methods of test for determining the resistance and resistivity of solid materials used to avoid electrostatic charge accumulation

ISO/IEC 80079-20-2, Explosive atmospheres – Part 20-2: Material characteristics – Combustible dusts test methods

ISO 7000, *Graphical symbols for use on equipment - Registered symbols* (available at: http://www.graphical-symbols.info/equipment)

ISO 21898, Packaging – Flexible intermediate bulk containers (FIBCs) for non-dangerous goods

¹ Numbers in square brackets refer to the Bibliography.

ASTM E582, Standard test method for minimum ignition energy and quenching distance in gaseous mixtures