

# SVENSK STANDARD SS-EN IEC 60079-0

FastställdUtgåvaSidaAnsvarig kommitté2018-09-1251 (1+147)SEK TK 31

© Copyright SEK. Reproduction in any form without permission is prohibited.

Explosiv atmosfär – Del 0: Utrustning – Allmänna fordringar

Explosive atmospheres – Part 0: Equipment – General requirements

Som svensk standard gäller europastandarden EN IEC 60079-0:2018. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 60079-0:2018.

### Nationellt förord

Europastandarden EN IEC 60079-0:2018

består av:

- europastandardens ikraftsättningsdokument, utarbetat inom CENELEC
- IEC 60079-0, Seventh edition, 2017 Explosive atmospheres Part 0: Equipment General requirements

utarbetad inom International Electrotechnical Commission, IEC.

EN från CENELEC som är identiska med motsvarande IEC-standarder och som görs tillgängliga för nationalkommittéerna efter den 1 januari 2018 får en beteckning som inleds med EN IEC istället för som tidigare bara EN.

Tidigare fastställd svensk standard SS-EN 60079-0, utgåva 4, 2012 och SS-EN 60079-0/A11, utgåva 1, 2013, gäller ej fr o m 2021-07-06.

#### ICS 29.260.20

Denna standard är fastställd av SEK Svensk Elstandard, som också kan lämna upplysningar om **sakinnehållet** i standarden. Postadress: Box 1284, 164 29 KISTA Telefon: 08 - 444 14 00. E-post: sek@elstandard.se. Internet: www.elstandard.se

### Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

### SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

### Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

### Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

### SEK Svensk Elstandard

Box 1284 164 29 Kista Tel 08-444 14 00 www.elstandard.se

# EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

# EN IEC 60079-0

July 2018

ICS 29.260.20

Supersedes EN 60079-0:2012

**English Version** 

# Explosive atmospheres - Part 0: Equipment - General requirements (IEC 60079-0:2017)

Atmosphères explosives - Partie 0: Matériel - Exigences générales (IEC 60079-0:2017) Explosionsgefährdete Bereiche - Teil 0: Betriebsmittel -Allgemeine Anforderungen (IEC 60079-0:2017)

This European Standard was approved by CENELEC on 2017-12-04. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2018 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. EN IEC 60079-0:2018 E

# European foreword

The text of document (31/1345/FDIS), future edition 7 of IEC 60079-0, prepared by IEC/TC 31 "Equipment for explosive atmospheres" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60079-0:2018.

The following dates are fixed:

•	latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2019-01-06
•	latest date by which the national standards conflicting with the	(dow)	2021-07-06

This document supersedes EN 60079-0:2012.

document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

## **Endorsement notice**

The text of the International Standard IEC 60079-0:2017 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC/TS 60034-25	NOTE	Harmonized as CLC/TS 60034-25.
IEC 60034-29	NOTE	Harmonized as EN 60034-29.
IEC 60079-2	NOTE	Harmonized as EN 60079-2.
IEC 60079-5	NOTE	Harmonized as EN 60079-5.
IEC 60079-6	NOTE	Harmonized as EN 60079-6.
IEC 60079-7	NOTE	Harmonized as EN 60079-7.
IEC 60079-10-1	NOTE	Harmonized as EN 60079-10-1.
IEC 60079-10-2	NOTE	Harmonized as EN 60079-10-2.
IEC 60079-11	NOTE	Harmonized as EN 60079-11.
IEC 60079-13	NOTE	Harmonized as EN 60079-13.
IEC 60079-14	NOTE	Harmonized as EN 60079-14.
IEC 60079-15	NOTE	Harmonized as EN 60079-15.
IEC 60079-17	NOTE	Harmonized as EN 60079-17.
IEC 60079-18	NOTE	Harmonized as EN 60079-18.
IEC 60079-19	NOTE	Harmonized as EN 60079-19.
IEC 60079-25	NOTE	Harmonized as EN 60079-25.
IEC 60079-28	NOTE	Harmonized as EN 60079-28.
IEC 60079-29-1	NOTE	Harmonized as EN 60079-29-1.

IEC 60079-29-4	NOTE	Harmonized as EN 60079-29-4.
IEC/IEEE 60079-30-	1 NOTE	Harmonized as EN 60079-30-1.
IEC 60079-31	NOTE	Harmonized as EN 60079-31.
IEC/TS 60079-32-1	NOTE	Harmonized as CLC/TR 60079-32-1.
IEC/TS 60079-39	NOTE	Harmonized as CLC/TS 60079-39 <sup>1</sup> ).
IEC 60254 (series)	NOTE	Harmonized in EN 60254 series.
IEC 60623	NOTE	Harmonized as EN 60623.
IEC 60896-11	NOTE	Harmonized as EN 60896-11.
IEC 60896-21	NOTE	Harmonized as EN 60896-21.
IEC 60952 (series)	NOTE	Harmonized in EN 60952 series.
IEC 61056-1	NOTE	Harmonized in EN 61056-1.
IEC 61427 (series)	NOTE	Harmonized in EN 61427 series.
IEC 61951-1	NOTE	Harmonized as EN 61951-1.
IEC 61951-2	NOTE	Harmonized as EN 61951-2.
IEC 61960 (series)	NOTE	Harmonized in EN 61960 series.
ISO/IEC 80079-20-2	NOTE	Harmonized as EN ISO/IEC 80079-20-2.
ISO/IEC 80079-34	NOTE	Harmonized as EN ISO/IEC 80079-34.
ISO/IEC 80079-36	NOTE	Harmonized as EN ISO/IEC 80079-36.
ISO/IEC 17000	NOTE	Harmonized as EN ISO/IEC 17000.

<sup>&</sup>lt;sup>1</sup>) Under preparation. Stage at the time of publication: CLC/FprTS 60079-39:2017.

# Annex ZA

(normative)

# Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: <a href="http://www.cenelec.eu">www.cenelec.eu</a>.

Publication	Year	<u>Title</u>	<u>EN/HD</u>	Year
IEC 60034-1	-	Rotating electrical machines - Part 1: Rating and performance	EN 60034-1 <sup>2</sup> )	-
IEC 60034-5	-	Rotating electrical machines - Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) - Classification	EN 60034-5	2001
IEC 60079-1	-	Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"	EN 60079-1	2014
IEC 60079-20-1	-	Explosive atmospheres - Part 20-1: Material characteristics for gas and vapour classification - Test methods and data	EN 60079-20-1	2010
IEC 60079-26	-	Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga	hEN 60079-26	2015
IEC 60079-35-1	-	Explosive atmospheres - Part 35-1: Caplights for use in mines susceptible to firedamp - General requirements - Construction and testing in relation to the risk of explosion	EN 60079-35-1	2011
			+AC	2011
IEC 60086-1 IEC 60192	-	Primary batteries - Part 1: General Low pressure sodium vapour lamps - Performance specifications	EN 60086-1 EN 60192	2015 2001
IEC 60216-1	-	Electrical insulating materials - Thermal endurance properties - Part 1: Ageing procedures and evaluation of test results	EN 60216-1	2013
IEC 60216-2	-	Electrical insulating materials - Thermal endurance properties - Part 2: Determination of thermal endurance properties of electrical insulating materials - Choice of test criteria	EN 60216-2	2005
IEC 60243-1	-	Electric strength of insulating materials - Test methods - Part 1: Tests at power frequencies	EN 60243-1	2013
IEC 60423	-	Conduit systems for cable management - Outside diameters of conduits for electrical installations and threads for conduits and fittings	EN 60423	2007
IEC 60529	-	Degrees of protection provided by enclosures (IF Code)	PEN 60529	1991
		,	+EN 60529:1991/corrig endum May 1993	1993

<sup>&</sup>lt;sup>2</sup>) Under preparation. Stage at the time of publication: FprEN 60034-1:2017.

IEC 60662 (mod)	-	High pressure sodium vapour lamps -	EN 60662	2012
		Performance specifications		0047
		la sulstina se sulla stina for services est mithis la c	+prAA	2017
IEC 60664-1	-	Insulation coordination for equipment within low- voltage systems - Part 1: Principles,	EIN 00004-1	2007
		requirements and tests		
IEC 60947-1	_	Low-voltage switchgear and controlgear - Part 1:	EN 60047-1	2007
120 00347-1	-	General rules	LN 00347-1	2007
IEC 62626-1	-	Low-voltage switchgear and controlgear	EN 62626-1	2014
120 02020 1		enclosed equipment - Part 1: Enclosed switch	211 02020 1	2011
		outside the scope of IEC 60947-3 for various		
		applications, to provide isolation of electrical		
		equipment during repair and maintenance work		
ISO 48	-	Rubber, vulcanized or thermoplastic	-	-
		Determination of hardness (hardness between 10	)	
		IRHD and 100 IRHD)		
ISO 178	-	Plastics - Determination of flexural properties	EN ISO 178	2010
ISO 179	series	Plastics - Determination of Charpy impact	EN ISO 179	series
100 000		properties		
ISO 262	-	ISO general purpose metric screw threads-	-	-
100 070		Selected sizes for screws, bolts and nuts		1001
ISO 273 ISO 527-2	-	Fasteners - Clearance holes for bolts and screws Plastics - Determination of tensile properties -	EN ISO 527-2	1991 2012
130 327-2	-	Part 2: Test conditions for moulding and	EN 130 527-2	2012
		extrusion plastics		
ISO 965-1	-	ISO general purpose metric screw threads -	-	-
		Tolerances – Part 1: Principles and basic data		
ISO 965-3	-	ISO general purpose metric screw threads-	-	-
		Tolerances – Part 3: Deviations for constructiona	I	
		screw threads		
ISO 3601-1	-	Fluid power systems - O-rings – Part 1: Inside	-	-
		diameters, cross-sections, tolerances and		
		designation codes		
ISO 3601-2	-	Fluid power systems - O-rings - Part 2: Housing	-	-
100 1011		dimensions for general applications		
ISO 4014	-	Hexagon head bolts - Product grades A and B	EN ISO 4014	2011
ISO 4017	-	Fasteners - Hexagon head screws - Product	EN ISO 4017	2014
ISO 4026		grades A and B	EN ISO 4026	2003
ISO 4020 ISO 4027	-	Hexagon socket set screws with flat point Hexagon socket set screws with cone point	EN ISO 4020 EN ISO 4027	2003
ISO 4028	-	Hexagon socket set screws with dog point	EN ISO 4027 EN ISO 4028	2003
ISO 4029	_	Hexagon socket set screws with dog point Hexagon socket set screws with cup point	EN ISO 4020 EN ISO 4029	2003
ISO 4032	-	Hexagon regular nuts (style 1) - Product grades	EN ISO 4032	2012
		A and B		
ISO 4762	-	Hexagon socket head cap screws	EN ISO 4762	2004
ISO 4892-2	-	Plastics - Methods of exposure to laboratory light	EN ISO 4892-2	2013
		sources - Part 2: Xenon-arc lamps		
ISO 7380	-	Hexagon socket button head screws	EN ISO 7380	2011
ISO 14583	-	Hexalobular socket pan head screws	EN ISO 14583	2011
ANSI/UL 746B	-	Polymeric Materials - Long-Term Property	-	-
		Evaluations		
ANSI/UL 746C	-	Standard for Polymeric Materials - Use in	-	-
		Electrical Equipment Evaluations		
ASTM D 5964	-	Standard Practice for Rubber IRM 901, IRM 902, and IRM 903 Replacement Oils for ASTM No. 1	-	-
		and IRM 903 Replacement Oils for ASTM No. 1, ASTM No. 2, ASTM No. 3 Oils, and IRM 905		
		formerly ASTM No. 5 Oil		

# CONTENTS

FC	DREWO	RD	8
1	Scop	e	15
2	Norm	ative references	16
3	Term	s and definitions	18
4	Equi	oment grouping	36
	4.1	General	
	4.2	Group I	
	4.3	Group II	36
	4.4	Group III	36
	4.5	Equipment for a particular explosive gas atmosphere	37
5	Tem	peratures	37
	5.1	Environmental influences	37
	5.1.1	Ambient temperature	37
	5.1.2	External source of heating or cooling	37
	5.2	Service temperature	37
	5.3	Maximum surface temperature	38
	5.3.1	Determination of maximum surface temperature	38
	5.3.2	Limitation of maximum surface temperature	38
	5.3.3	Small component temperature for Group I or Group II electrical equipment	39
	5.3.4	Component temperature of smooth surfaces for Group I or Group II electrical equipment	40
6	Reau	irements for all equipment	
-	6.1	General	
	6.2	Mechanical strength of equipment	
	6.3	Opening times	
	6.4	Circulating currents in enclosures (e.g. of large electric machines)	
	6.5	Gasket retention	
	6.6	Electromagnetic and ultrasonic energy radiating equipment	42
	6.6.1	General	42
	6.6.2	Radio frequency sources	42
	6.6.3	Ultrasonic sources	43
	6.6.4	Lasers, luminaires, and other non-divergent continuous wave optical sources	44
7	Non-	metallic enclosures and non-metallic parts of enclosures	
	7.1	General	44
	7.1.1	Applicability	
	7.1.2	Specification of materials	44
	7.2	Thermal endurance	45
	7.2.1	Tests for thermal endurance	45
	7.2.2	Material selection	46
	7.2.3	Alternative qualification of elastomeric sealing O-rings	46
	7.3	Resistance to ultraviolet light	46
	7.4	Electrostatic charges on external non-metallic materials	47
	7.4.1	Applicability	
	7.4.2	Avoidance of a build-up of electrostatic charge for Group I or Group II	47

7.4.3	Avoidance of a build-up of electrostatic charge for Group III	49
7.5	Attached external conductive parts	50
8 Meta	Illic enclosures and metallic parts of enclosures	51
8.1	Material composition	51
8.2	Group I	51
8.3	Group II	51
8.4	Group III	52
8.5	Copper Alloys	52
9 Fast	eners	52
9.1	General	52
9.2	Special fasteners	53
9.3	Holes for special fasteners	53
9.3.1	Thread engagement	53
9.3.2	2 Tolerance and clearance	53
9.4	Hexagon socket set screws	54
10 Inter	locking devices	54
11 Bush	nings	54
12 (Res	erved for future use)	54
``	omponents	
13.1	General	
13.1	Mounting	
13.2	Internal mounting	
13.4	External mounting	
13.4	Ex Component certificate	
	nection facilities	
14.1	General	
14.1	Type of protection	
14.2	Creepage and clearance	
	nection facilities for earthing or bonding conductors	
15.1	Equipment requiring earthing or bonding	
15.1	3	
15.1	5	
15.2	Equipment not requiring earthing	
15.3	Size of protective earthing conductor connection	
15.4	Size of equipotential bonding conductor connection	
15.5 15.6	Protection against corrosion Secureness of electrical connections	
15.6		
15.7	Internal earth continuity plate es into enclosures	
16.1	General	
16.2	Identification of entries	
16.3	Cable glands	
16.4	Blanking elements	
16.5	Thread adapters	
16.6	Temperature at branching point and entry point	
16.7	Electrostatic charges of cable sheaths	
	blementary requirements for electric machines	
17.1	General	60

17.2	Ventilation	
17.2	1 5	
17.2		
17.2		
17.2	,	
17.2	5	
17.3	Bearings	
18 Supp	plementary requirements for switchgear	62
18.1	Flammable dielectric	62
18.2	Disconnectors	62
18.3	Group I – Provisions for locking	63
18.4	Doors and covers	63
19 Rese	erved for future use	63
	elementary requirements for external plugs, socket outlets and connectors for wiring connection	63
	0	
20.1	General	
20.2	Explosive gas atmospheres	
20.3	Explosive dust atmospheres	
20.4	Energized plugs	
21 Supp	plementary requirements for luminaires	
21.1	General	64
21.2	Covers for luminaires of EPL Mb, EPL Gb, or EPL Db	64
21.3	Covers for luminaires of EPL Gc or EPL Dc	65
21.4	Sodium lamps	65
22 Supp	elementary requirements for caplights and handlights	65
22.1	Group I caplights	65
22.2	Group II and Group III caplights and handlights	65
00 E. '		
23 Equi	pment incorporating cells and batteries	
-		66
23.1	General	66 66
23.1 23.2	General Interconnection of cells to form batteries	66 66 66
23.1 23.2 23.3	General Interconnection of cells to form batteries Cell types	66 66 66 66
23.1 23.2 23.3 23.4	General Interconnection of cells to form batteries Cell types Cells in a battery	66 66 66 66 69
23.1 23.2 23.3 23.4 23.5	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries	66 66 66 69 69
23.1 23.2 23.3 23.4 23.5 23.6	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability	66 66 66 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries	66 66 66 69 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage	66 66 66 69 69 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections	66 66 66 69 69 69 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation	66 66 66 69 69 69 69 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries	66 66 69 69 69 69 69 69 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack	66 66 69 69 69 69 69 69 69 69 69 69 69
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Doct	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack	66 66 69 69 69 69 69 69 69 69 69 69 69 70
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Doct 25 Com	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack Imentation pliance of prototype or sample with documents	66 66 69 69 69 69 69 69 69 69 69 70 70 70
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Doct 25 Com	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack imentation pliance of prototype or sample with documents	66 66 69 69 69 69 69 69 69 69 69 70 70 70
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Doct 25 Com	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack Imentation pliance of prototype or sample with documents	66 66 69 69 69 69 69 69 69 69 69 70 70 70
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Doct 25 Com 26 Type	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack imentation pliance of prototype or sample with documents	66 66 69 69 69 69 69 69 69 69 70 70 70 70
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Docu 25 Com 26 Type 26.1	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack imentation pliance of prototype or sample with documents tests General	66 66 69 69 69 69 69 69 69 70 70 70 70 70
23.1 23.2 23.3 23.4 23.5 23.6 23.7 23.8 23.9 23.10 23.11 23.12 24 Doct 25 Com 26 Type 26.1 26.2	General Interconnection of cells to form batteries Cell types Cells in a battery Ratings of batteries Interchangeability Charging of primary batteries Leakage Connections Orientation Replacement of cells or batteries Replaceable battery pack umentation pliance of prototype or sample with documents tests General Test configuration	66 66 69 69 69 69 69 69 69 69 70 70 70 70 70 70 70

	26.4.	•	
	26.4.	•	
	26.4.		
	26.4.	5 1 ( ) , ,	
	26.5	Thermal tests	
	26.5.		
	26.5.		
	26.5.		
	26.6	Torque test for bushings	
	26.6.		
	26.6.		
	26.7	Non-metallic enclosures or non-metallic parts of enclosures	
	26.7.		
	26.7.		
	26.8	Thermal endurance to heat	
	26.9	Thermal endurance to cold	
		Resistance to UV light	
	26.10		
	26.10	5 1	82
	26.10	•	
	26.11	Resistance to chemical agents for Group I equipment	82
		Earth continuity	
	26.13	Surface resistance test of parts of enclosures of non-metallic materials	
	26.14	Measurement of capacitance	85
	26.14	4.1 General	85
	26.14	4.2 Test procedure	85
	26.15	Verification of ratings of ventilating fans	86
	26.17	Transferred charge test	86
	26.17	7.1 Test equipment	86
	26.17	7.2 Test sample	87
	26.17	7.3 Test procedure	87
27	7 Rout	tine tests	88
28	3 Manu	ufacturer's responsibility	88
	28.1	Conformity with the documentation	88
	28.2	Certificate	89
	28.3	Responsibility for marking	89
29	9 Mark	king	89
	29.1	Applicability	89
	29.2	Location	
	29.3	General	
	29.4	Ex marking for explosive gas atmospheres	
	29.5	Ex marking for explosive dust atmospheres	
	29.6	Combined types (or levels) of protection	
	29.7	Multiple types of protection	
	29.8	Ga equipment using two independent Gb types (or levels) of protection	
	29.9	Boundary wall	
	29.10	Ex Components	
	29.11	Small Ex Equipment and small Ex Components	

29.12	Extremely small Ex Equipment and extremely small Ex Components	96
29.13	Warning markings	96
29.14	Cells and batteries	97
29.15	Electric machines operated with a converter	
29.16	Examples of marking	98
30 Instr	uctions	.101
30.1	General	.101
30.2	Cells and batteries	.102
30.3	Electric machines	.103
30.4	Ventilating fans	.103
30.5	Cable glands	.104
Annex A	(normative) Supplementary requirements for cable glands	.105
A.1	General	. 105
A.2	Constructional requirements	.105
A.2.1	Cable sealing	.105
A.2.2	2 Filling compounds	.106
A.2.3	3 Clamping	.106
A.2.4	Lead-in of cable	.106
A.2.5	5 Release by a tool	.107
A.2.6	6 Fixing	.107
A.2.7	7 Degree of protection	.107
A.3	Type tests	. 107
A.3.1	Tests of clamping of non-armoured and braided cables	. 107
A.3.2	2 Tests of clamping of armoured cables	.110
A.3.3	3 Type test for resistance to impact	.111
A.3.4	Test for degree of protection (IP) of cable glands	.112
A.4	Marking	.113
A.4.1	Marking of cable glands	.113
A.4.2	2 Identification of cable-sealing rings	.113
A.5	Instructions	
Annex B	(normative) Requirements for Ex Components	.115
Annex C	(informative) Example of rig for resistance to impact test	.118
Annex D	(informative) Electric machines connected to converters	.119
	(informative) Temperature evaluation of electric machines	
Annex F	(informative) Guidance flowchart for tests of non-metallic enclosures or non- arts of enclosures (26.4)	
•	(informative) Guidance flowchart for tests of cable glands	
	(informative) Shaft voltages resulting in motor bearing or shaft brush	
	Discharge energy calculation	. 125
H.1	General	. 125
H.2	Assessment of the risk of ignition using ignition energy calculation	.125
H.3	Shaft voltage determination for a rotating machine	.126
H.4	Capacitance "C" calculation for a rotating machine	.126
H.5	Energy "E" calculation for a rotating machine	.129
H.6	Assessment using reference curves	
Bibliograp	bhy	. 131

Figure 1 – Typical battery example	es20

Figure 2 – Typical battery compartment	21
Figure 3 – Typical replaceable battery pack	22
Figure 4 – Tolerances and clearance for threaded fasteners	53
Figure 5 – Contact surface under head of fastener with a reduced shank	54
Figure 6 – Cable gland	59
Figure 7 – Conduit entry	59
Figure 8 – Assembly of test sample for earth-continuity test	84
Figure 9 – Test piece with painted electrodes	85
Figure 10 – Compression set of an O-ring	86
Figure A.1 – Illustration of the terms used for cable glands	106
Figure A.2 – Rounded edge of the point of entry of the flexible cable	107
Figure A.3 – Example of rig for resistance to impact test	112
Figure C.1 – Example of rig for resistance to impact test	118
Figure F.1 – Non-metallic enclosures or non-metallic parts of enclosures	123
Figure H.1 – Capacitance stored in bearing clearance of sleeve bearing Between journal and outer bearing housing	128
Figure H.2 – Air-gap between stator and rotor	
Figure H.3 – Typical surfaces that form capacitors from the motor shaft to ground	
Figure H.4 – Capacitive ignition curves	
Table 1 – Ambient temperatures in service and additional marking	37
Table 2 – Classification of maximum surface temperatures for Group II electrical	
equipment	38
Table 3 – Assessment of temperature classification according to component size	40
Table 4 – Assessment of temperature classification Component surface area $\geq$ 20 mm <sup>2</sup> .	40
Table 5 – Threshold power	43
Table 6 – Threshold energy	43
Table 7 – Limitation of surface areas	48
Table 8 – Maximum diameter or width	49
Table 9 – Limitation of thickness of non-metallic layer	49
Table 10 – Maximum acceptable transferred charge	49
Table 11 – Maximum capacitance of unearthed conductive parts	51
Table 12 – Minimum cross-sectional area of PE conductors	57
Table 13 – Primary cells	66
Table 14 – Secondary cells	68
Table 15 – Tests for resistance to impact	74
Table 16 – Torque to be applied to the stem of bushing used for connection facilities	79
Table 17 – Thermal endurance test	80
Table 18 – Text of warning markings	97
Table 19 – Example of type-test converter parameters	103
Table B.1 – Applicability of clauses to Ex Components	115
Table H.1 – Maximum permitted energy	126

- 8 -

### INTERNATIONAL ELECTROTECHNICAL COMMISSION

# **EXPLOSIVE ATMOSPHERES –**

## **Part 0: Equipment – General requirements**

### FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60079-0 has been prepared by IEC technical committee 31: Equipment for explosive atmospheres.

This seventh edition cancels and replaces the sixth edition, published in 2011. This edition constitutes a technical revision.

The significance of the changes between IEC Standard, IEC 60079-0, Edition 6 (2011) and IEC 60079-0, Edition 7 (2017) are as listed below:

		Туре		
Explanation of the significance of the changes	Clause	Minor and editorial changes	Extension	Major technical changes
Throughout document, "electrical equipment" replaced by "equipment" where appropriate.	Multiple	Х		
Scope	1	Х		
List of "Type of "Protection" and "Product" standards combined into one list.				
Definitions used in multiple sub-parts added.	3	Х		
Definitions harmonized across sub-parts and added to 60079-0 where appropriate.				
Battery definitions updated				
Clarification of the way that information on process temperature influences can be expressed.	5.1.2	Х		
Clarification regarding the determination of service temperatures when dust layers are present	5.2	Х		
Clarification on the need to provide service temperature information for Ex Components in the Schedule of Limitations	5.2	Х		
Relocation of EPL Da dust layer requirements from IEC 60079-18 & IEC 60079-31	5.3.2.3.1	A1		
Clarified that for EPL Db, a maximum specified dust layer of greater than 200 mm is not permitted as thicker layers have no additional effect on maximum surface temperature.	b)	х		
Added for EPL Db, a dust layer in a specified orientation, marked as $T_{\rm L}$	c)		Х	
Clarified that for EPL Dc, no dust layer tests are required.	5.3.2.3.3	Х		
Clarified that the "temperature" is the temperature of the air surrounding the component	5.3.3	Х		
Subdivided section dealing with higher permitted surface temperatures for "smooth" surfaces. Corrected area from 1 000 mm <sup>2</sup> to 10 000 mm <sup>2</sup> .	5.3.4	Х		
Clarified that the "Ex" requirements of IEC 60079 supplement those of the relevant industrial standards.	6.1	Х		
Added requirement that where an adhesive is used to secure a gasket, it shall be used within its COT and shall comply with the requirements for cements.	6.5			C1
Requirements relocated to IEC 60079-28	former 6.6.2	A2		
Ultrasonic requirements updated based on latest research work	6.6.3		Х	
Added reference to IEC 60079-28	6.6.4	A2		
Material identification parameters have been revised to reflect reasonably obtainable information	7.1.2.2	Х		
"RTI-mechanical" has been clarified to include "RTI- mechanical strength" and "RTI-mechanical impact"	7.1.2.2	Х		
Material identification parameters have been revised to reflect reasonably obtainable information	7.1.2.3	Х		
Relocated information on "cements" from Clause 12.	7.1.2.4	Х		
"RTI-mechanical" has been clarified to include "RTI- mechanical strength" and "RTI-mechanical impact". Requirements for cements aligned with the requirements for elastomers.	7.2.2	X		

		Туре		
Explanation of the significance of the changes	Clause	Minor and editorial changes	Extension	Major technical changes
Relocation of 10 K margin for EPL Gc or Dc from IEC 60079-15, IEC 60079-18 & IEC 60079-31	7.2.2	A3		
Added clarification with respect to gaskets and seals where only the outer edge is potentially exposed to light.	7.3	X		
Clarification added that one or more of the described techniques may be used	7.4.2	X		
Added additional relaxation for the case where a surface is in contact with an earthed surface on only two of four sides.	7.4.2 b)		Х	
Added reference to IEC 60243-1 and IEC 60243-2 for test method to require a 4 kV DC test	7.4.2.c)			C2
Additional guidance added with respect to the possible Specific Conditions of Use	7.4.2 e)	х		
New option added for portable, mains-powered equipment with earth-connected guard	7.4.2 f)		Х	
Added option for determination of maximum transferred	7.4.2 g)		Х	
charge.	Table 10			
Added missing limits (same as 7.4.2)	7.4.3 a)	Х		
Clarified that it is a dc test that is conducted	7.4.3 b)	Х		
Clarified that this requirement is not applied to personal or portable equipment	7.5	х		
Clarified Group I limits	8.2	Х		
Clarified Group II, EPL Ga limits	8.3	Х		
Added limitation for external surfaces of >65% copper	8.5			C3
Added clarification as to what is considered a tool	9.1	Х		
Clarified that the tolerance class of the set screw is not critical, only that it not protrude from the threaded hole after tightening.	9.4	Х		
Information on cements transferred to Clause 7	12	Х		
Required that Ex Component Certificates require a Schedule of Limitations in all cases	13.5		Х	
Revised to clarified that all connection facilities may not be a "Compartment".	14	Х		
Sub-clause split to separate the requirements for protective earthing and equipotential bonding into separate sections	15.3 15.4	Х		
Section split to separate secureness of electrical connections from the internal earth continuity plate.	15.6 15.7	Х		
Non-threaded Group I cable glands are no longer required to be Ex Components.	16.3		Х	
Non-threaded Group I blanking elements are no longer required to be Ex Components.	16.4		Х	
Scope of Clause 17 clarified to define applicability	17	Х		
Additional guidance notes added to address bearings	17.3	Х		
Clarified applicability to disconnectors, interlocks, and maintenance switches.	18.2	Х		
Fuse requirements deleted as they are addressed in the individual sub-parts	19	Х		
Added requirements for EPL Gc and Dc	20.1			C4

			Туре	
Explanation of the significance of the changes	Clause	Minor and editorial changes	Extension	Major technical changes
The test circuit requirements for a flameproof connection have been removed as they are more completely specified in IEC 60079-1.	20.2	х		
The impact test requirements for luminaires are relocated to Table 15	21.1 Table 15	х		
Clarified interlock switch operation for flameproof luminaires	21.2	х		
Clarified that some Types of Protection permit connection of cells in parallel	23.2	х		
New cell types and data added based on latest available data	Table 13		Х	
New cell types and data added based on latest available data	Table 14			C5
Clarification of what documentation is to be prepared regarding the explosion safety aspects of the equipment	24	х		
Clarification that the type tests are to take into consideration the installation instructions	26.2	Х		
Clarification that the "glass" requirements also apply to "ceramic" parts	26.4.1.1	х		
Added a permission to interchange the order of tests at the "lower test temperature" and the "upper test temperature".	26.4.1.2.2 26.4.1.2.3	X		
Clarified the construction of the impact test fixture	26.4.2	Х		
Clarified the impact tests for glass parts	26.4.2	Х		
Added clarification to deal with the new IPX9 ratings	26.4.5.1		Х	
Clarified the test voltage for maximum surface temperature	26.5.1.3	х		
Relocation of EPL Da dust layer requirements from IEC 60079-18 & IEC 60079-31	26.5.1.3	A1		
Relocation of EPL Db specified dust layer requirements from IEC 60079-31	26.5.1.3	A4		
Added for EPL Db, a dust layer in a specified orientation, marked as $T_{\rm L}$	26.5.1.3		B1	
Clarified that for EPL Dc, the testing is conducted without a dust layer.	26.5.1.3	X		
Relocation of thermal endurance to heat 10K relaxation for Gc equipment from IEC 60079-15, IEC 60079-18, & IEC 60079-31	Table 17	х		
Clarification of a consistent way to address elastomeric materials exposed to ultraviolet light	26.10	X		
Replacement of "oil No. 2" with the revised designation of "oil IRM 902".	26.11	Х		
Option added for testing at lower voltages when low resistance materials are encountered	26.13		Х	
Transferred charge test added based on IEC TS 60079-32-2	26.17		Х	
The reference to a specific instruction document instead of an "X" condition relocated to e) instead of a note giving a permission	29.3 e)	х		
Updated to reflect the additional levels of protection already shown in the sub-parts: "da", "dc", "eb", "ec", "oc", "op is", "op pr", "op sh", "pxb", "pyb", "pzc", "qb", "sa", "sb", and "sc".	29.4 b)	×		

- 12 -	
--------	--

			Туре	
Explanation of the significance of the changes	Clause	Minor and editorial changes	Extension	Major technical changes
Text added to address marking of "Ex associated equipment"	29.4		Х	
Updated to reflect the additional levels of protection already shown in the sub-parts: "ic", "op is", "op pr", "op sh", "pxb", "pyb", "pzc", "sa", "sb", and "sc".	29.5 b)	х		
Clarified marking of EPL Da, EPL Db with no dust layer, EPL Db with a specified dust layer, and EPL Dc.	29.5 d)	Х		
Introduced marking for EPL Db with a dust layer in a specified orientation	29.5 d)		Х	
Text added to address marking of "Ex associated equipment"	29.5		Х	
Text added to address marking of equipment intended to be installed in a boundary wall.	29.9		Х	
The marking of Ex Component enclosure was aligned with the marking requirements of IEC 60079-1 and IEC 60079-7	29.10	х		
The alternate marking of EPL has been deleted.	former 29.13			C6
Marking for electric machines operated with a converter clarified	29.15	Х		
Instruction material guidance clarified	30.1	Х		
Additional instruction material for electric machines added	30.3			C7
Additional instruction material for cable glands added	30.5			C8
	A.5			
Allow ISO 10807 hose assemblies to be used with cable glands.	A.1		Х	
Clarify testing with stainless steel mandrels	A.3	Х		
Reduction of the time / slippage permitted	A.3.1.1		Х	
Clarify impact testing of cable glands	A.3.3	Х		
	Figure A.3			
Clarified the order of tests	A.3.4	Х		
Clarified remarks	Annex B	Х		
Aligned Figure with text	Figure C.1	Х		
Clarified operation of electric machines from	Annex D	Х		
converters	(informative)			
Clarified temperature testing of electric machines	Annex E	Х		
	(informative)			
Flowchart for Cable Gland testing	Annex G	Х		
	(informative)			
Guidance of electric machine shaft voltages	Annex H	Х		
	(informative)			

NOTE The technical changes referred to include the significance of technical changes in the revised IEC Standard, but they do not form an exhaustive list of all modifications from the previous version. More guidance may be found by referring to the Redline Version of the standard.

IEC 60079-0:2017 © IEC 2017

Explanations:

### A) Definitions

Minor and editorial changes	clarification decrease of technical requirements minor technical change editorial corrections
	8

These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in level of existing requirement.

### Extension

addition of technical options

These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing requirements for equipment that was fully compliant with the previous standard. Therefore, these will not have to be considered for products in conformity with the preceding edition.

Major technical changes	addition of technical requirements
	increase of technical requirements

These are changes to technical requirements (addition, increase of the level or removal) made in a way that a product in conformity with the preceding edition will not always be able to fulfil the requirements given in the later edition. These changes have to be considered for products in conformity with the preceding edition. For these changes additional information is provided in clause B) below.

NOTE These changes represent current technological knowledge. However, these changes should not normally have an influence on equipment already placed on the market.

### B) Information about the background of changes

- A1 The dust layer requirements for EPL Da are unchanged from what previously existed in IEC 60079-18,Ed 4 and IEC 60079-31, Ed 2, but have been relocated to IEC 60079-0 to allow consistent application in all Types of Protection.
- A2 IEC 60079-28 now includes all requirements for optical radiation for all EPLs.
- A3 The COT requirements for EPL Gc or Dc are unchanged from what previously existed in IEC 60079-15, Ed 4, IEC 60079-18, Ed 4, and IEC 60079-31, Ed 2, but have been relocated to IEC 60079-0 to allow consistent application in all Types of Protection.
- A4 The dust layer requirements for EPL Db with a specified dust layer depth are unchanged from what previously existed in IEC 60079-31, Ed 2, but have been relocated to IEC 60079-0 to allow consistent application in all Types of Protection.
- B1 Dust layer requirements for EPL Db with a dust layer in a specified orientation have been added.
- C1 It is recognized that the new requirements were, in many cases, already applied. The change is to ensure that they are uniformly and consistently applied.
- C2 Require that the test be conducted at 4 kV DC.
- C3 The limitation applies to external surfaces of other than cable glands, blanking elements, thread adapters and bushings.
- C4 The added requirements for tool securing and marking are consistent with the approach in IEC 60079-15
- C5 Voltage values were changed following additional research due to the complicated assessment and sometimes unspecified construction of Li/Ion-cells. It was found that some voltage values previously stated were too low.

C6 The now required EPL marking may be other than that permitted by the Level of Protection to account for limiting restrictions of material or plastic material surface area.

– 14 –

- C7 Additional instruction material for electric machines required to facilitate selection, installation, and maintenance.
- C8 Additional instruction material for cable glands required to facilitate selection and installation.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
31/1345/FDIS	31/1356/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 60079 series, under the general title *Explosive atmospheres,* can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "http://webstore.iec.ch" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

## **EXPLOSIVE ATMOSPHERES –**

### **Part 0: Equipment – General requirements**

### 1 Scope

This part of IEC 60079 specifies the general requirements for construction, testing and marking of Ex Equipment and Ex Components intended for use in explosive atmospheres.

The standard atmospheric conditions (relating to the explosion characteristics of the atmosphere) under which it may be assumed that Ex Equipment can be operated are:

- temperature –20 °C to +60 °C;
- pressure 80 kPa (0,8 bar) to 110 kPa (1,1 bar); and
- air with normal oxygen content, typically 21 % v/v.

This part of IEC 60079 and other standards supplementing this standard specify additional test requirements for Ex Equipment operating outside the standard temperature range, but further additional consideration and additional testing may be required for Ex Equipment operating outside the standard atmospheric pressure range and standard oxygen content. Such additional testing may be particularly relevant with respect to Types of Protection that depend on quenching of a flame such as 'flameproof enclosures "d"' (IEC 60079-1) or limitation of energy, 'intrinsic safety "i" (IEC 60079-11).

NOTE 1 Although the standard atmospheric conditions above give a temperature range for the atmosphere of -20 °C to +60 °C, the normal ambient temperature range for the Ex Equipment is -20 °C to +40 °C, unless otherwise specified and marked. See 5.1.1. It is considered that -20 °C to +40 °C is appropriate for many items of Ex Equipment and that to manufacture all Ex Equipment to be suitable for a standard atmosphere upper ambient temperature of +60 °C would place unnecessary design constraints.

NOTE 2 Requirements given in this standard result from an ignition hazard assessment made on equipment. The ignition sources taken into account are those found associated with this type of equipment, such as hot surfaces, electromagnetic radiation, mechanically generated sparks, mechanical impacts resulting in thermite reactions, electrical arcing and static electric discharge in normal industrial environments.

NOTE 3 Where an explosive gas atmosphere and a combustible dust atmosphere are, or can be, present at the same time, the simultaneous presence of both often warrants additional protective measures. Additional guidance on the use of Ex Equipment in hybrid mixtures (mixture of a flammable gas or vapour with a combustible dust or combustible flyings) is given in IEC 60079-14.

IEC 60079 does not specify requirements for safety, other than those directly related to the explosion risk.

Ignition sources like adiabatic compression, shock waves, exothermic chemical reaction, selfignition of dust, naked flames and hot gases/liquids, are not addressed by this standard.

NOTE 4 Although outside the scope of this standard, such equipment would typically be subjected to a hazard analysis that identifies and lists all of the potential sources of ignition by the equipment and the measures to be applied to prevent them becoming effective. See ISO/IEC 80079-36.

This document is supplemented or modified by the following parts and technical specifications:

- IEC 60079-1: Gas Flameproof enclosures "d";
- IEC 60079-2: Gas and dust Pressurized enclosure "p";
- IEC 60079-5: Gas Powder filling "q";
- IEC 60079-6: Gas Liquid immersion "o";
- IEC 60079-7: Gas Increased safety "e";

- IEC 60079-11: Gas and dust Intrinsic safety "i";
- IEC 60079-13: Gas and dust Equipment protection by pressurized room "p" & artificially ventilated room "v";

- 16 -

- IEC 60079-15: Gas Type of protection "n";
- IEC 60079-18: Gas and dust Encapsulation "m";
- IEC 60079-25: Gas and dust Intrinsically safe electrical systems
- IEC 60079-26: Gas Equipment with equipment protection level (EPL) Ga
- IEC 60079-28: Gas and dust Protection of equipment and transmission systems using optical radiation
- IEC 60079-29-1: Gas detectors Performance requirements of detectors for flammable gases
- IEC 60079-29-4: Gas detectors Performance requirements of open path detectors for flammable gases
- IEC/IEEE 60079-30-1: Gas and dust Electrical resistance trace heating General and testing requirements.
- IEC 60079-31: Dust Protection by enclosure "t"
- IEC 60079-33: Gas and dust Special protection "s"
- IEC 60079-35-1: Caplights for use in mines susceptible to firedamp General requirements – Construction and testing in relation to the risk of explosion
- IEC TS 60079-39: Gas Intrinsically safe systems with electronically controlled spark duration limitation
- IEC TS 60079-40: Gas Requirements for process sealing between flammable process fluids and electrical systems
- ISO 80079-36: Gas and dust Non-electrical equipment for explosive atmospheres Basic method and requirements

This document, along with the additional parts of IEC 60079 mentioned above, is not applicable to the construction of

- electromedical apparatus,
- shot-firing exploders,
- test devices for exploders, and
- shot-firing circuits.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-1, Rotating electrical machines – Part 1: Rating and performance

IEC 60034-5, Rotating electrical machines – Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) – Classification

IEC 60079-1, *Explosive atmospheres – Part 1: Equipment protection by flameproof enclosures "d"* 

IEC 60079-20-1, *Explosive atmospheres – Part 20-1: Material characteristics for gas and vapour classification – Test methods and data* 

IEC 60079-0:2017 © IEC 2017

IEC 60079-26, Explosive atmospheres – Part 26: Equipment with Equipment Protection Level (EPL) Ga

IEC 60079-35-1, Explosive atmospheres – Part 35-1: Caplights for use in mines susceptible to firedamp – General requirements – Construction and testing in relation to the risk of explosion

IEC 60086-1, Primary batteries – Part 1: General

IEC 60192, Low-pressure sodium vapour lamps – Performance specifications

IEC 60216-1, *Electrical insulating materials – Thermal endurance properties – Part 1: Ageing procedures and evaluation of test results* 

IEC 60216-2, Electrical insulating materials – Thermal endurance properties – Part 2: Determination of thermal endurance properties of electrical insulating materials – Choice of test criteria

IEC 60243-1, *Electric strength of insulating materials – Test methods – Part 1: Tests at power frequencies* 

IEC 60423, Conduit systems for cable management – Outside diameters of conduits for electrical installations and threads for conduits and fittings

IEC 60529, Degrees of protection provided by enclosures (IP Code)

IEC 60662, *High-pressure sodium vapour lamps – Performance specifications* 

IEC 60664-1, Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements and tests

IEC 60947-1, Low-voltage switchgear and controlgear – Part 1: General rules

IEC 62626-1, Low-voltage switchgear and controlgear enclosed equipment – Part 1: Enclosed switch-disconnectors outside the scope of IEC 60947-3 to provide isolation during repair and maintenance work

ISO 48, Rubber, vulcanized or thermoplastic – Determination of hardness (hardness between 10 IRHD and 100 IRHD)

ISO 178, Plastics – Determination of flexural properties

ISO 179 (all parts), Plastics – Determination of Charpy impact properties

ISO 262, ISO general-purpose metric screw threads – Selected sizes for screws, bolts and nuts

ISO 273, Fasteners – Clearance holes for bolts and screws

ISO 527-2, Plastics – Determination of tensile properties – Part 2: Test conditions for moulding and extrusion plastics

ISO 965-1, ISO general-purpose metric screw threads – Tolerances – Part 1: Principles and basic data

ISO 965-3, ISO general-purpose metric screw threads – Tolerances – Part 3: Deviations for constructional screw threads

ISO 3601-1, Fluid power systems – O-rings – Part 1: Inside diameters, cross-sections, tolerances and designation codes

– 18 –

ISO 3601-2, Fluid power systems – O-rings – Part 2: Housing dimensions for general applications

ISO 4014, Hexagon head bolts - Product grades A and B

ISO 4017, Hexagon head screws – Product grades A and B

ISO 4026, Hexagon socket set screws with flat point

ISO 4027, Hexagon socket set screws with cone point

ISO 4028, Hexagon socket set screws with dog point

ISO 4029, Hexagon socket set screws with cup point

ISO 4032, Hexagon nuts, style 1 – Product grades A and B

ISO 4762, Hexagon socket head cap screws

ISO 4892-2, Plastics – Methods of exposure to laboratory light sources – Part 2: Xenon-arc lamps

ISO 7380, Hexagon socket button head screws

ISO 14583, Hexalobular socket pan head screws

ANSI/UL 746B, Polymeric Materials - Long-Term Property Evaluations

ANSI/UL 746C, Polymeric Materials – Used in Electrical Equipment Evaluations

ASTM D5964, Standard practice for rubber IRM 901, IRM 902, and IRM 903 replacement oils for ASTM No. 1, ASTM No. 2, and ASTM No. 3