

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Ljudanläggningar – Del 21: Mätning av akustiska egenskaper

*Sound system equipment –
Part 21: Acoustical (output-based) measurements*

Som svensk standard gäller europastandarden EN IEC 60268-21:2018. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 60268-21:2018.

Nationellt förord

Europastandarden EN IEC 60268-21:2018

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 60268-21, First edition, 2018 - Sound system equipment - Part 21: Acoustical (output-based) measurements**

utarbetad inom International Electrotechnical Commission, IEC.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English Version

**Sound system equipment - Part 21: Acoustical (output-based)
measurements
(IEC 60268-21:2018)**

Équipements pour systèmes électroacoustiques - Partie 21
: Mesures acoustiques (en sortie)
(IEC 60268-21:2018)

Elektroakustische Geräte - Teil 21:
Akustische(Ausgabebasierte) Messungen
(IEC 60268-21:2018)

This European Standard was approved by CENELEC on 2018-12-12. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 100/2957/CDV, future edition 1 of IEC 60268-21, prepared by IEC/TC 100 "Audio, video and multimedia systems and equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60268-21:2018.

The following dates are fixed:

- latest date by which the document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2019-09-12
- latest date by which the national standards conflicting with the document have to be withdrawn (dow) 2021-12-12

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 60268-21:2018 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60268-7:2010	NOTE	Harmonized as EN 60268-7:2011 (not modified)
IEC 62777	NOTE	Harmonized as EN 62777

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60263	-	Scales and sizes for plotting frequency characteristics and polar diagrams	-	-
IEC 60268-1	-	Sound system equipment. Part 1: General	HD 483.1 S2	-
IEC 60268-2	1987	Sound system equipment. Part 2: Explanation of general terms and calculation methods	HD 483.2 S2	1993
IEC 61094-4	-	Measurement microphones - Part 4: Specifications for working standard microphones	EN 61094-4	-
IEC 61260-1	-	Electroacoustics - Octave-band and fractional-octave-band filters - Part 1: Specifications	EN 61260-1	-
ISO 3	-	Preferred numbers - Series of preferred numbers	-	-
ISO 3741	2010	Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Precision methods for reverberation test rooms	EN ISO 3741	2010
ISO 3744	-	Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Engineering methods for an essentially free field over a reflecting plane	EN ISO 3744	-
ISO 3745	-	Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Precision methods for anechoic rooms and hemi-anechoic rooms	EN ISO 3745	-
CTA 2034-A	-	Standard Method of Measurement for In-Home Loudspeakers, Consumer Technology Association (Formerly CEA)	-	-
CTA 2010-B	-	Standard Method of Measurement for Powered Subwoofers, standard by Consumer Technology Association (Formerly CEA)	-	-

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references	11
3 Terms, definitions and abbreviated terms	12
3.1 Terms and definitions.....	12
3.2 Abbreviated terms.....	12
4 Type description	12
5 Physical characteristics	12
5.1 Marking of terminals and controls	12
5.2 Dimensions	12
5.3 Mass.....	12
5.4 Connectors and cable assemblies.....	13
6 Design data	13
7 Conditions	13
7.1 Rated conditions	13
7.2 Climatic conditions.....	13
7.3 Normal measuring conditions	13
8 Test signals	14
8.1 General.....	14
8.2 Sinusoidal chirp	14
8.3 Steady-state single-tone signal	15
8.4 Steady-state two-tone signal.....	15
8.5 Sparse multi-tone complex.....	15
8.6 Broadband noise signal.....	16
8.7 Narrow-band noise signal	16
8.8 Hann-burst signal.....	16
8.9 Impulsive signal	17
9 Acoustical environment.....	17
9.1 General.....	17
9.2 Free-field conditions	17
9.3 Half-space, free-field conditions.....	17
9.4 Simulated free-field conditions	17
9.5 Half-space simulated free-field conditions	17
9.6 Diffuse sound field conditions	18
9.7 Target application conditions	18
10 Positioning of the DUT.....	18
10.1 Rated geometrical conditions	18
10.1.1 General	18
10.1.2 Reference plane and normal vector	18
10.1.3 Reference point	18
10.1.4 Reference axis	19
10.1.5 Orientation vector	19
10.1.6 Evaluation point.....	19
10.1.7 Evaluation distance	19

10.2	Measuring distance between DUT and microphone	20
10.2.1	Far-field conditions	20
10.2.2	Near-field conditions	20
10.2.3	Diffuse field conditions	20
10.2.4	Target application condition	21
11	Measurement equipment and test results	21
12	Accuracy of the acoustical measurement	21
12.1	General	21
12.2	Measurement uncertainty	21
13	Mounting of the DUT	22
13.1	Mounting and acoustic loading of drive units	22
13.2	Mounting and acoustic loading of an electro-acoustic system	22
14	Preconditioning	23
15	Rated ambient conditions	23
15.1	Temperature ranges	23
15.1.1	Performance limited temperature range	23
15.1.2	Damage limited temperature range	23
15.2	Humidity ranges	23
15.2.1	Relative humidity range	23
15.2.2	Damage limited humidity range	23
16	Rated frequency range	23
17	Input signal	23
17.1	Rated maximum input value	23
17.1.1	Condition to be specified	23
17.1.2	Direct measurement	24
17.1.3	Indirect measurement based on SPL_{max}	25
17.2	Maximum input level	25
18	Sound-pressure output	26
18.1	Rated maximum sound pressure	26
18.1.1	Conditions to be specified	26
18.1.2	Direct measurement	26
18.1.3	Indirect measurement based on maximum input value	27
18.2	Rated maximum sound-pressure level	27
18.3	Short term maximum sound pressure level	27
18.3.1	Conditions to be specified	27
18.3.2	Method of measurement	28
18.4	Long term maximum sound pressure level	28
18.4.1	Conditions to be specified	28
18.4.2	Method of measurement	29
18.5	Sound pressure in a stated frequency band	29
18.5.1	Condition to be specified	29
18.5.2	Method of measurement	29
18.6	Sound-pressure level in a stated frequency band	30
18.7	Mean sound-pressure in a stated frequency range	30
18.7.1	Condition to be specified	30
18.7.2	Method of measurement	30
18.8	Mean sound-pressure level in a stated frequency range	30

19	Frequency response of the fundamental component	30
19.1	Transfer function	30
19.1.1	Conditions to be specified	30
19.1.2	Method of measurements	30
19.2	SPL frequency response	32
19.2.1	Conditions to be specified	32
19.2.2	Method of measurement	32
19.3	Time-varying amplitude compression of the fundamental component	33
19.3.1	General	33
19.3.2	Method of measurement	33
19.4	Amplitude compression at maximum input	33
19.4.1	Short term amplitude compression	33
19.4.2	Method of measurement	33
19.4.3	Long-term amplitude compression	34
19.4.4	Method of measurement	34
19.5	Corrections based on a free-field reference measurement	34
19.5.1	General	34
19.5.2	Correction of the measured sound pressure signal	34
19.5.3	Correction of the amplitude response	35
19.6	Effective frequency range	36
19.6.1	Conditions to be specified	36
19.6.2	Method of measurement	36
19.7	Internal latency	36
19.7.1	Conditions to be specified	36
19.7.2	Methods of measurement	36
20	Directional characteristics	37
20.1	General	37
20.2	Direct sound field in 3D space	37
20.2.1	Directional transfer function	37
20.2.2	Extrapolated far-field data	37
20.2.3	Parameters of the holographic sound field expansion	38
20.2.4	Extrapolated near-field data	39
20.3	Directional far field characteristics	39
20.3.1	Directional factor	39
20.3.2	Directional gain	41
20.3.3	Directivity factor	41
20.3.4	Directivity index	41
20.4	Acoustic output power	42
20.4.1	Conditions to be specified	42
20.4.2	Methods of measurement	42
20.5	Sound power level	44
20.6	Mean acoustic output power in a frequency band	44
20.6.1	Conditions to be specified	44
20.6.2	Method of measurement	44
20.7	Radiation angle	44
20.7.1	Conditions to be specified	44
20.7.2	Method of measurement	44

20.8	Coverage angle or angles	45
20.8.1	Conditions to be specified.....	45
20.8.2	Method of measurement	45
20.9	Mean sound pressure level in an acoustical zone.....	45
20.9.1	General	45
20.9.2	Method of measurement	45
21	Harmonic distortion.....	46
21.1	General.....	46
21.2	N^{th} -order harmonic component	46
21.2.1	Conditions to be specified.....	46
21.2.2	Method of measurement	46
21.3	Total harmonic components	47
21.3.1	Conditions to be specified.....	47
21.3.2	Method of measurement	47
21.4	Total harmonic distortion.....	47
21.4.1	Conditions to be specified.....	47
21.4.2	Method of measurement	47
21.5	Higher-order harmonic distortion	48
21.5.1	Conditions to be specified.....	48
21.5.2	Method of measurement	48
21.6	Maximum sound pressure level limited by total harmonic distortion	49
21.6.1	Conditions to be specified.....	49
21.6.2	Method of measurement	49
21.7	N^{th} -order equivalent input harmonic distortion component	50
21.7.1	Conditions to be specified.....	50
21.7.2	Method of measurement	50
21.8	Equivalent input total harmonic distortion	51
21.8.1	Conditions to be specified.....	51
21.8.2	Method of measurement	51
22	Two-tone distortion	52
22.1	Variation of excitation frequencies	52
22.2	Modulation distortion.....	52
22.2.1	Conditions to be specified.....	52
22.2.2	Method of measurement	52
22.3	Amplitude modulation distortion	53
22.3.1	Conditions to be specified.....	53
22.3.2	Method of measurement	54
23	Multi-tone distortion	54
23.1	Conditions to be specified	54
23.2	Method of measurement	55
24	Impulsive distortion.....	55
24.1	Impulsive distortion level.....	55
24.1.1	Conditions to be specified.....	55
24.1.2	Method of measurement	56
24.2	Maximum impulsive distortion ratio	56
24.2.1	Conditions to be specified.....	56
24.2.2	Method of measurement	56

24.3	Mean impulsive distortion level	57
24.3.1	Conditions to be specified.....	57
24.3.2	Method of measurement	57
24.4	Crest factor of impulsive distortion	57
24.4.1	Conditions to be specified.....	57
24.4.2	Method of measurement	57
25	Stray magnetic fields	58
25.1	General.....	58
25.2	Static component	58
25.2.1	Characteristic to be specified.....	58
25.2.2	Method of measurement	58
25.3	Dynamic components.....	59
25.3.1	Characteristics to be specified	59
25.3.2	Method of measurement	59
Annex A (informative) Uncertainty analysis		60
Annex B (normative) Transducer mounting		62
B.1	Standard baffle	62
B.2	Standard measuring enclosures	64
B.2.1	General	64
B.2.2	Type A.....	64
B.2.3	Type B.....	64
Annex C (normative) Simulated programme signal		66
Annex D (informative) Rating the maximum input and output values		68
Annex E (informative) Spherical wave expansion		70
E.1	Coefficients of spherical wave expansion	70
E.2	Directional factor.....	70
E.3	Directivity factor	71
E.4	Acoustic output power.....	71
Annex F (informative) Non-linearity		72
F.1	Equivalent harmonic input distortion.....	72
F.2	Two-tone intermodulation	72
F.3	Signal distortion generated in audio systems	73
Annex G (informative) Stray magnetic field		75
Bibliography.....		76

Figure 1	– Rated conditions used to describe the position of the DUT in the coordinate system	18
Figure 2	– Recommended position and orientation of the DUT	19
Figure 3	– Valid region of expansion of the sound pressure $p(r)$ at the observation point r at the distance $r > a$	39
Figure 4	– Measurement of the distortion generated by a multi-tone stimulus.....	55
Figure 5	– Measurement of impulsive distortion	56
Figure A.1	– Relationship between tolerance limits, corresponding acceptance intervals and the maximum permitted uncertainty of measurement, U_{MAX}	60
Figure B.1	– Standard baffle, dimensions.....	62
Figure B.2	– Standard baffle with chamfer	63
Figure B.3	– Standard baffle with sub-baffle.....	63

Figure B.4 – Standard measuring enclosure type A (net volume is about 600 l)	64
Figure B.5 – Standard measuring enclosure type B (net volume is about 450 l)	65
Figure C.1 – Block diagram of test setup for generating the simulated noise signal used for testing passive loudspeaker systems comprising a network filter	66
Figure F.1 – Signal flow chart of the electro-acoustical system	72
Figure F.2 – Variation of the frequencies of the two-tone stimulus in the intermodulation measurement	73
Figure F.3 – Generation of the signal distortion in audio systems	73
Figure G.1 – Measuring apparatus for stray magnetic field	75
 Table A.1 – Example uncertainty budget – acoustical loudspeaker evaluation	 61
Table C.1 – Power spectrum of simulated programme signal in 1/3 octave bands rated	67

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SOUND SYSTEM EQUIPMENT –**Part 21: Acoustical (output-based) measurements****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60268-21 has been prepared by IEC technical committee 100: Audio, video and multimedia systems and equipment.

The text of this standard is based on the following documents:

CDV	Report on voting
100/2957/CDV	100/3019/RVC

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60628, published under the general title *Sound system equipment*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Loudspeakers, headphones and other actuators have become more versatile and, as a result, new measurement techniques are required to evaluate these systems. The following is a list of examples where new measurement techniques are required:

- Limited access to the electrical terminals of the transducer
The higher integration of electrical, acoustical and mechanical elements limit the access to the electrical terminals of the transducer.
- Analogue or digital audio input signals
Audio inputs can accept analogue or digital signals in various formats.
- Latency and other kinds of distortion associated with digital signal processing
Digital signal processing is used to correct the transfer behaviour of the passive system and to generate a desired sound output and as a result, latency and other kinds of distortion not found in analogue equipment can be generated.
- Excessive equalization
Excessive equalization can force the transducer to operate in the large signal domain causing thermal and nonlinear effects.
- Active protection
Active protection attenuates the input signal to prevent a mechanical and thermal overload of the transducer and other components.
- Other transducer principles
Although most loudspeaker systems use a moving coil in an electro-dynamical transducer, there is a need to expand the application to electro-static, electro-magnetic or any other transduction principles.
- Other mechanical and acoustical elements
To improve sound radiation, vented enclosures, sealed enclosures, passive radiators, horns, wave guides, flat panels, and other mechanical and acoustical elements are implemented.
- Impulsive distortions
Defects in manufacturing (e.g. voice coil rubbing) or operating under overload conditions can create impulsive distortions, which have a high impact on perceived sound quality but cannot be detected by conventional measurements (e.g. total harmonic distortion).
- Directional characteristics and complex near field properties
The comprehensive evaluation of professional equipment, including directional characteristics, can be realized by considering the complex near-field properties as a supplement to the existing far-field measurement techniques. In addition, devices intended for use in the near field, such as hand-held personal audio devices (e.g. laptops, tablets, smart phones) and other portable sound systems, need to be evaluated in a manner appropriate to their intended use.

SOUND SYSTEM EQUIPMENT –

Part 21: Acoustical (output-based) measurements

1 Scope

This part of IEC 60268 specifies an acoustical measurement method that applies to electro-acoustical transducers and passive and active sound systems, such as loudspeakers, TV-sets, multi-media devices, personal portable audio devices, automotive sound systems and professional equipment. The device under test (DUT) can be comprised of electrical components performing analogue and digital signal processing prior to the passive actuators performing a transduction of the electrical input into an acoustical output signal. This document describes only physical measurements that assess the transfer behaviour of the DUT between an arbitrary analogue or digital input signal and the acoustical output at any point in the near and far field of the system. This includes operating the DUT in both the small and large signal domains. The influence of the acoustical boundary conditions of the target application (e.g. car interior) can also be considered in the physical evaluation of the sound system. This document does not assess the perception and cognitive evaluation of the reproduced sound and the impact of perceived sound quality.

NOTE Some measurement methods defined in this document can be applied to headphones, headsets, earphones and earsets in accordance with [1]¹. This document does not apply to microphones and other sensors. This document does not require access to the state variables (voltage, current) at the electrical terminals of the transducer. Sensitivity, electric input power and other characteristics based on the electrical impedance will be described in a separate future standard document, IEC 60268-22, dedicated to electrical and mechanical measurements.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60263, *Scales and sizes for plotting frequency characteristics and polar diagrams*

IEC 60268-1, *Sound system equipment – Part 1: General*

IEC 60268-2:1987, *Sound system equipment – Part 2: Explanation of general terms and calculation methods*

IEC 61094-4, *Measurement microphones – Part 4: Specifications for working standard microphones*

IEC 61260-1, *Electroacoustics – Octave-band and fractional-octave-band filters – Part 1: Specifications*

ISO 3, *Preferred numbers – Series of preferred numbers*

ISO 3741:2010, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Precision methods for reverberation test rooms*

¹ Numbers in square brackets refer to the Bibliography.

ISO 3744, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Engineering methods for an essentially free field over a reflecting plane*

ISO 3745, *Acoustics – Determination of sound power levels and sound energy levels of noise sources using sound pressure – Precision methods for anechoic rooms and hemi-anechoic rooms*

CTA 2034-A, *Standard Method of Measurement for In-Home Loudspeakers*, Consumer Technology Association (Formerly CEA), 02/01/2015

CTA 2010-B, *Standard Method of Measurement for Powered Subwoofers*, standard by Consumer Technology Association (Formerly CEA), 11/28/2014