

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Järnvägstillämpningar – Fasta installationer och rullande materiel – Kriterier för teknisk kompatibilitet mellan strömväxtagare och kontaktledning

Railway applications –

Fixed installations and rolling stock –

Criteria to achieve technical compatibility between pantographs and overhead contact line

Som svensk standard gäller europastandarden EN 50367:2020. Den svenska standarden innehåller den officiella engelska språkversionen av EN 50367:2020.

Nationellt förord

Tidigare fastställd svensk standard SS-EN 50367, utgåva 2, 2012, SS-EN 50367/AC1, utgåva 1, 2013 och SS-EN 50367/A1, utgåva 1, 2016, gäller ej fr o m 2023-07-27.

ICS 29.280.00

Denna standard är fastställd av SEK Svensk Elstandard,
som också kan lämna upplysningar om **sakinhålllet** i standarden.
Postadress: Box 1284, 164 29 KISTA
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: www.elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 50367

August 2020

ICS 29.280

Supersedes EN 50367:2012 and all of its amendments
and corrigenda (if any)

English Version

**Railway applications - Fixed installations and rolling stock -
Criteria to achieve technical compatibility between pantographs
and overhead contact line**

Applications ferroviaires - Systèmes de captage de courant
- Critères techniques d'interaction entre le pantographe et la
ligne aérienne de contact (réalisation du libre accès)

Bahnanwendungen - Zusammenwirken der Systeme -
Technische Kriterien für das Zusammenwirken zwischen
Stromabnehmer und Oberleitung für einen freien Zugang

This European Standard was approved by CENELEC on 2020-07-27. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2020 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. EN 50367:2020 E

Contents	Page
European foreword	6
1 Scope	7
2 Normative references.....	7
3 Terms and definitions.....	8
4 Symbols and abbreviations	11
5 Geometry.....	14
5.1 General.....	14
5.2 Overhead contact line characteristics	14
5.2.1 General.....	14
5.2.2 Infrastructure gauge for free passage of pantograph	14
5.2.3 Contact wire height.....	15
5.2.4 Contact wire gradient.....	15
5.2.5 Lateral deviation of contact wire.....	15
5.2.6 Contact wire uplift	18
5.2.7 Neutral sections.....	18
5.2.8 Change over area between pantograph profiles	19
5.3 Pantograph characteristics.....	19
5.3.1 General.....	19
5.3.2 Assessment of the pantograph head profile.....	20
5.3.3 Conducting range	23
6 Interface material	23
6.1 General.....	23
6.2 Contact wire.....	24
6.3 Contact strips.....	24
7 Interaction performance	24
7.1 General.....	24
7.2 Static contact forces and current capacity.....	24
7.3 Dynamic behaviour and quality of current collection.....	25
8 Operational requirements	28
8.1 Requirement for pantograph	28
8.2 Minimum and maximum distance between two operating pantographs.....	28
8.2.1 General.....	28
8.2.2 Design of overhead contact lines	28
8.2.3 Formation of train with multiple pantographs - Arrangement of pantographs	29
9 Assessment requirements - Dynamic behaviour and quality of current collection.....	29
9.1 General.....	29
9.2 Overhead contact line	30

9.2.1	Assessment of overhead contact line design	30
9.2.2	Integration of an assessed OCL into a network.....	30
9.3	Pantograph	31
9.3.1	Assessment of pantograph design.....	31
9.3.2	Integration of an assessed pantograph into a vehicle	31
	Annex A (normative) Special requirements	33
A.1	Neutral sections	33
A.1.1	Principle of neutral section.....	33
A.1.2	Long neutral section.....	33
A.1.3	Short neutral section	34
A.1.4	Split neutral section.....	34
A.1.5	Arrangement of pantographs on trains	35
A.2	Profiles for interoperable pantograph head	36
A.2.1	Pantograph head with length of 1 600 mm.....	36
A.2.2	Pantograph head with length of 1 950 mm.....	37
A.3	Additional tests for DC systems at standstill.....	37
A.3.1	General.....	37
A.3.2	Testing conditions.....	38
A.3.3	Testing method	38
A.3.4	Test results	40
A.4	Visualization of mean contact forces.....	41
	Annex B (informative) Data of existing networks	43
B.1	General.....	43
B.2	National characteristics.....	43
B.3	General characteristics of pantograph head.....	49
	Annex C (normative) Additional tests for DC at standstill – alternative method – Test method – Single strip configuration.....	56
	Annex D (informative) Specimen calculation for the permissible lateral deviation of the contact wire according to the requirements of 5.2.5 with typical values from the German network	57
D.1	Calculation Values	57
D.2	Calculation independent of type of pantograph	59
D.2.1	Calculation of reference height	59
D.2.2	Calculation of tolerances of track at the lower verification point	59
D.2.3	Calculation of tolerances of track at the upper verification point.....	59
D.2.4	Calculation of additional overthrow on the inside/outside of the curve for pantographs	59
D.2.5	Calculation of quasi static effect.....	60
D.3	Pantograph head with length of 1600 mm.....	60
D.3.1	Calculation of lateral movement of contact wire caused by forces from non-horizontal sections of pantograph head.....	60
D.3.2	Calculation of tolerances of overhead contact line	60

D.3.3 Calculation of width of mechanical kinematic pantograph gauge at minimum verification height of the pantograph gauge in a raised position	60
D.3.4 Calculation of width of mechanical kinematic pantograph gauge at maximum verification height of the pantograph gauge in a raised position	61
D.3.5 Calculation of width of mechanical kinematic pantograph gauge at reference height for interaction between contact wire and pantograph	61
D.3.6 permissible lateral deviation of the contact wire for stability against dewirement according to 5.2.5.2	61
D.3.7 Calculation of width of mechanical kinematic gauge for serviceability of overhead contact line at minimum verification height of the pantograph gauge in a raised position	62
D.3.8 Calculation of width of mechanical kinematic gauge for serviceability of overhead contact line at maximum verification height of the pantograph gauge in a raised position	62
D.3.9 Calculation of width of mechanical gauge for serviceability of overhead contact line gauge at reference height for interaction between contact wire and pantograph	62
D.3.10 Permissible lateral deviation of the contact wire from the track centre line to meet the serviceability limit state case according to 5.2.5.3	63
D.3.11 Permissible lateral deviation of the contact wire from the track centre line according to 5.2.5.3	63
D.4 Pantograph head with length of 1 950 mm	64
D.4.1 Calculation of lateral movement of contact wire caused by forces from non-horizontal sections of pantograph head	64
D.4.2 Calculation of tolerances of overhead contact line	64
D.4.3 Calculation of width of mechanical kinematic pantograph gauge at minimum verification height of the pantograph gauge in a raised position	64
D.4.4 Calculation of width of mechanical kinematic pantograph gauge at maximum verification height of the pantograph gauge in a raised position	64
D.4.5 Calculation of width of mechanical kinematic pantograph gauge at reference height for interaction between contact wire and pantograph	65
D.4.6 permissible lateral deviation of the contact wire for stability against dewirement according to 5.2.5.2	65
D.4.7 Calculation of width of mechanical kinematic gauge for serviceability of overhead contact line at minimum verification height of the pantograph gauge in a raised position	65
D.4.8 Calculation of width of mechanical kinematic gauge for serviceability of overhead contact line at maximum verification height of the pantograph gauge in a raised position	66
D.4.9 Calculation of width of mechanical gauge for serviceability of overhead contact line gauge at reference height for interaction between contact wire and pantograph	66
D.4.10 Permissible lateral deviation of the contact wire from the track centre line to meet the serviceability limit state case according to 5.2.5.3	66
D.4.11 Permissible lateral deviation of the contact wire from the track centre line according to 5.2.5.3	67
D.5 Illustration lateral deviation	68

Annex ZA (informative) Relationship between this European standard and the essential requirements of EU Directive 2016/797/EU [2016 OJ L138] aimed to be covered.....	72
Bibliography	74

European foreword

This document (EN 50367:2020) has been prepared by CLC/SC 9XC "Electric supply and earthing systems for public transport equipment and ancillary apparatus (Fixed installations)".

The following dates are fixed:

- latest date by which this document has (dop) 2021-07-27
to be implemented at national level by publication of an identical national standard or by endorsement
- latest date by which the national (dow) 2023-07-27
standards conflicting with this document have to be withdrawn

This document supersedes EN 50367:2012 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

Annex B gives some parameters for existing lines (informative).

Compared with the previous version, the most significant changes in this version are:

- Update of definitions;
- Changes to 5.2.5 concerning the lateral deviation on the basis of RfS 51 from the European Union Agency for Railways;
- Changes in 5.2.7;
- Revision of 5.3.2, including update of figures;
- Improvement of testing method for DC contact strips: 6.3, A.3;
- Addition of tunnel requirements in Clause 7;
- Revision of Table 9;
- Assessment requirements in Clause 9;
- Addition of an introduction for Annex B;
- Addition of Annex C;
- Addition of Annex D.

1 Scope

This document specifies requirements for the technical compatibility between pantographs and overhead contact lines, to achieve free access to the lines of the European railway network.

NOTE These requirements are defined for a limited number of pantograph types conforming to the requirements in 5.3, together with the geometry and characteristics of compatible overhead contact lines.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 15273-1:2013+A1:2016, *Railway applications - Gauges - Part 1: General - Common rules for infrastructure and rolling stock*

EN 15273-2:2013+A1:2016, *Railway applications - Gauges - Part 2: Rolling stock gauge*

EN 15273-3:2013+A1:2016, *Railway applications - Gauges - Part 3: Structure gauges*

EN 50119:2020, *Railway applications - Fixed installations - Electric traction overhead contact lines*

EN 50125-2:2002, *Railway applications - Environmental conditions for equipment - Part 2: Fixed electrical installations*

EN 50149:2012, *Railway applications - Fixed installations - Electric traction - Copper and copper alloy grooved contact wires*

EN 50206-1:2010, *Railway applications - Rolling stock - Pantographs: Characteristics and tests - Part 1: Pantographs for main line vehicles*

EN 50317:2012, *Railway applications - Current collection systems - Requirements for and validation of measurements of the dynamic interaction between pantograph and overhead contact line*

EN 50318:2018, *Railway applications - Current collection systems - Validation of simulation of the dynamic interaction between pantograph and overhead contact line*

EN 50388:2012, *Railway Applications - Power supply and rolling stock - Technical criteria for the coordination between power supply (substation) and rolling stock to achieve interoperability*

EN 50405:2015, *Railway applications – Current collection systems – Pantographs, testing methods for contact strips¹⁾*

IEC 60050-811:2017, *International Electrotechnical Vocabulary (IEV) - Part 811: Electric traction*

¹⁾ This standard is impacted by EN 50405:2015/A1:2016.