

© Copyright SEK. Reproduction in any form without permission is prohibited.

Explosiv atmosfär – Del 14: Konstruktion, val och utförande av elinstallationer

*Explosive atmospheres –
Part 14: Electrical installations design, selection and erection*

Som svensk standard gäller europastandarden EN 60079-14:2008. Den svenska standarden innehåller den officiella engelska språkversionen av EN 60079-14:2008.

Nationellt förord

Europastandarden EN 60079-14:2008

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 60079-14, Fourth edition, 2007 - Explosive atmospheres - Part 14: Electrical installations design, selection and erection**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 60079-14, utgåva 2, 2003, gäller ej fr o m 2011-07-01.

ICS 29.260.20

Denna standard är fastställd av SEK Svensk Elstandard, som också kan lämna upplysningar om **sakinnehållet** i standarden.
Postadress: SEK, Box 1284, 164 29 KISTA
Telefon: 08 - 444 14 00. Telefax: 08 - 444 14 30
E-post: sek@elstandard.se. Internet: www.elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Explosive atmospheres -
Part 14: Electrical installations design,
selection and erection
(IEC 60079-14:2007)**

Atmosphères explosives -
Partie 14: Conception,
sélection et construction
des installations électriques
(CEI 60079-14:2007)

Explosionsfähige Atmosphäre -
Teil 14: Projektierung,
Auswahl und Errichtung
elektrischer Anlagen
(IEC 60079-14:2007)

This European Standard was approved by CENELEC on 2008-07-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 31J/150/FDIS, future edition 4 of IEC 60079-14, prepared by SC 31J, Classification of hazardous areas and installation requirements, of IEC TC 31, Equipment for explosive atmospheres, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60079-14 on 2008-07-01.

This European Standard supersedes EN 60079-14:2003.

It constitutes a technical revision with respect to gases and vapours and incorporates the requirements for dusts from EN 61241-14:2004. The incorporation of requirements for dust is without technical change.

The significant technical changes with respect to EN 60079-14:2003 are as follows:

- knowledge, skills and competencies of "Responsible Persons", "Operatives" and "Designers" are explained in Annex F;
- Equipment Protection Levels (EPLs) have been introduced and are explained in the new Annex I;
- dust requirements included from EN 61241-14:2004.

NOTE Dust requirements are included as an interim presentation for the purpose of EN 60079-14:2008 and will be refined in a next edition with other required technical changes.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2009-05-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2011-07-01

Annexes ZA and ZB have been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60079-14:2007 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC/TS 60034-17	NOTE	Harmonized as CLC/TS 60034-17:2004 (not modified).
IEC/TS 60034-25	NOTE	Harmonized as CLC/TS 60034-25:2005 (not modified).
IEC 60332-2-2	NOTE	Harmonized as EN 60332-2-2:2004 (not modified)
IEC 60742	NOTE	Harmonized as EN 60742:1995 (modified). Superseded by EN 61558 series (partially modified)
IEC 61008-1	NOTE	Harmonized as EN 61008-1:2004 (modified)
IEC 61010-1	NOTE	Harmonized as EN 61010-1:2001 (not modified)
IEC 61024-1	NOTE	Superseded by IEC 62305-3, which is harmonized as EN 62305-3:2006 (modified)

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60034-1	– ¹⁾	Rotating electrical machines - Part 1: Rating and performance	EN 60034-1	2004 ²⁾
IEC 60034-5	– ¹⁾	Rotating electrical machines - Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) - Classification	EN 60034-5	2001 ²⁾
IEC 60050-826	– ¹⁾	International Electrotechnical Vocabulary (IEV) - Part 826: Electrical installations	–	–
IEC 60060-1	– ¹⁾	High-voltage test techniques - Part 1: General definitions and test requirements	HD 588.1 S1	1991 ²⁾
IEC 60079	Series	Explosive atmospheres	EN 60079	Series
IEC 60079-0 (mod)	– ¹⁾	Explosive atmospheres - Part 0: Equipment – General requirements	EN 60079-0	2006 ²⁾
IEC 60079-1	– ¹⁾	Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"	EN 60079-1	2007 ²⁾
IEC 60079-2	– ¹⁾	Explosive atmospheres - Part 2: Equipment protection by pressurized enclosure "p"	EN 60079-2	2007 ²⁾
IEC 60079-5	– ¹⁾	Explosive atmospheres - Part 5: Equipment protection by powder filling "q"	EN 60079-5	2007 ²⁾
IEC 60079-6	– ¹⁾	Explosive atmospheres - Part 6: Equipment protection by oil immersion "o"	EN 60079-6	2007 ²⁾
IEC 60079-7	– ¹⁾	Explosive atmospheres - Part 7: Equipment protection by increased safety "e"	EN 60079-7	2007 ²⁾
IEC 60079-11	– ¹⁾	Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"	EN 60079-11	2007 ²⁾
IEC/TR 60079-13	– ¹⁾	Electrical apparatus for explosive gas atmospheres - Part 13: Construction and use of rooms or buildings protected by pressurization	–	–

¹⁾ Undated reference.

²⁾ Valid edition at date of issue.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60079-15	- ¹⁾	Electrical apparatus for explosive gas atmospheres - Part 15: Construction, test and marking of type of protection "n" electrical apparatus	EN 60079-15	2005 ²⁾
IEC/TR 60079-16	- ¹⁾	Electrical apparatus for explosive gas atmospheres - Part 16: Artificial ventilation for the protection of analyzer(s) houses	-	-
IEC 60079-18	- ¹⁾	Electrical apparatus for explosive gas atmospheres - Part 18: Construction, test and marking of type of protection encapsulation "m" electrical apparatus	EN 60079-18 + corr. April	2004 ²⁾ 2006
IEC 60079-19	- ¹⁾	Explosive atmospheres - Part 19: Equipment repair, overhaul and reclamation	EN 60079-19	2007 ²⁾
IEC 60079-25	- ¹⁾	Electrical apparatus for explosive gas atmospheres - Part 25: Intrinsically safe systems	EN 60079-25 + corr. April	2004 ²⁾ 2006
IEC 60079-26	- ¹⁾	Explosive atmospheres - Part 26: Equipment with equipment protection level (EPL) Ga	EN 60079-26	2007 ²⁾
IEC 60079-27	- ¹⁾	Explosive atmospheres - Part 27: Fieldbus intrinsically safe concept (FISCO)	EN 60079-27	2008 ²⁾
IEC 60079-28	- ¹⁾	Explosive atmospheres - Part 28: Protection of equipment and transmission systems using optical radiation	EN 60079-28	2007 ²⁾
IEC 60079-29-1 (mod)	- ¹⁾	Explosive atmospheres - Part 29-1: Gas detectors - Performance requirements of detectors for flammable gases	EN 60079-29-1	2007 ²⁾
IEC 60079-29-2	- ¹⁾	Explosive atmospheres - Part 29-2: Gas detectors - Selection, installation, use and maintenance of detectors for flammable gases and oxygen	EN 60079-29-2 + corr. December	2007 ²⁾ 2007
IEC 60079-31	- ³⁾	Explosive Atmospheres - Part 31: Equipment dust ignition protection by enclosure "tD"	EN 60079-31	- ³⁾
IEC 60243-1	- ¹⁾	Electrical strength of insulating materials - Test methods - Part 1: Tests at power frequencies	EN 60243-1	1998 ²⁾
IEC 60332-1-2	- ¹⁾	Tests on electric and optical fibre cables under fire conditions - Part 1-2: Test for vertical flame propagation for a single insulated wire or cable - Procedure for 1 kW pre-mixed flame	EN 60332-1-2	2004 ²⁾
IEC 60364 (mod)	Series	Low-voltage electrical installations	HD 60364/ HD 384	Series

³⁾ To be published.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60364-4-41 (mod)	– ¹⁾	Low-voltage electrical installations - Part 4-41: Protection for safety - Protection against electric shock	HD 60364-4-41 + corr. July	2007 ²⁾ 2007
IEC 60529	– ¹⁾	Degrees of protection provided by enclosures (IP Code)	EN 60529 + corr. May	1991 ²⁾ 1993
IEC 60950 (mod)	Series	Information technology equipment - Safety	EN 60950	Series
IEC 61010-1	– ¹⁾	Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements	EN 61010-1 + corr. June	2001 ²⁾ 2002
IEC 61241	Series	Electrical apparatus for use in the presence of combustible dust	EN 61241	Series
IEC 61241-0 (mod)	– ¹⁾	Electrical apparatus for use in the presence of combustible dust - Part 0: General requirements	EN 61241-0	2006 ²⁾
IEC 61241-1	– ¹⁾	Electrical apparatus for use in the presence of combustible dust - Part 1: Protection by enclosures "tD"	EN 61241-1 + corr. December	2004 ²⁾ 2006
IEC 61241-2-1	– ¹⁾	Electrical apparatus for use in the presence of combustible dust - Part 2: Test methods - Section 1: Methods for determining the minimum ignition temperatures of dust	–	–
IEC 61241-4	– ¹⁾	Electrical apparatus for use in the presence of combustible dust - Part 4: Type of protection 'pD'	EN 61241-4	2006 ²⁾
IEC 61241-10	– ¹⁾	Electrical apparatus for use in the presence of combustible dust - Part 10: Classification of areas where combustible dusts are or may be present	EN 61241-10	2004 ²⁾
IEC 61241-11	– ¹⁾	Electrical apparatus for use in the presence of combustible dust - Part 11: Protection by intrinsic safety 'iD'	EN 61241-11	2006 ²⁾
IEC 61285	– ¹⁾	Industrial-process control - Safety of analyser houses	EN 61285	2004 ²⁾
IEC 61558-2-6	– ¹⁾	Safety of power transformers, power supply units and similar - Part 2-6: Particular requirements for safety isolating transformers for general use	EN 61558-2-6	1997 ²⁾
IEC 62305-3 (mod)	– ¹⁾	Protection against lightning - Part 3: Physical damage to structures and life hazard	EN 62305-3 + corr. September	2006 ²⁾ 2008
ISO 10807	– ¹⁾	Pipework - Corrugated flexible metallic hose assemblies for the protection of electric cables in explosive atmospheres	EN ISO 10807	1996 ²⁾

CONTENTS

INTRODUCTION.....	10
1 Scope.....	13
2 Normative references	13
3 Terms and definitions	16
3.1 General.....	16
3.2 Hazardous areas.....	16
3.3 Flameproof enclosure.....	17
3.4 Increased safety.....	17
3.5 Intrinsic safety - General	18
3.6 Intrinsic safety parameters	19
3.7 Pressurization	19
3.8 Type of protection 'n'.....	19
3.13 Electrical supply systems	20
3.14 Equipment.....	21
4 General	21
4.1 General requirements.....	21
4.2 Documentation	22
4.3 Assurance of conformity of equipment.....	23
4.3.1 Equipment with certificates according to IEC standards	23
4.3.2 Equipment without certificates according to IEC standards	23
4.3.3 Selection of repaired, second hand or existing equipment	23
4.4 Qualifications of personnel	23
5 Selection of equipment (excluding cables and conduits).....	24
5.1 Information requirements.....	24
5.2 Zones.....	24
5.3 Relationship between Equipment protection levels (EPLs) and zones.....	24
5.4 Selection of equipment according to EPLs.....	25
5.4.1 Relationship between EPLs and types of protection.....	25
5.4.2 Equipment for use in locations requiring EPL 'Ga' or 'Da'.....	26
5.4.3 Equipment for use in locations requiring EPL 'Gb' or 'Db'	26
5.4.4 Equipment for use in locations requiring EPL 'Gc' or 'Dc'.....	26
5.5 Selection according to equipment grouping	26
5.6 Selection according to the ignition temperature of the gas, vapour or dust and ambient temperature.....	27
5.6.1 General	27
5.6.2 Gas or Vapour	27
5.6.3 Dust	27
5.7 Selection of radiating equipment for dust.....	30
5.7.1 Ignition process	30
5.7.2 Safety measures in zone 20 or 21.....	30
5.7.3 Safety measures in zone 22	31
5.8 Selection of ultrasonic equipment for dust	31
5.8.1 Ignition process	31
5.8.2 Safety measures.....	31

5.9	External influences	31
5.10	Light metals as construction materials	32
5.10.1	Gas or vapour.....	32
5.10.2	Dust	32
5.11	Transportable, Portable and Personal equipment	33
5.11.1	General	33
5.11.2	Transportable and Portable equipment - Gas.....	33
5.11.3	Personal Equipment - Gas.....	33
5.11.4	Dust	33
5.12	Selection of rotating electrical machines.....	34
5.12.1	General	34
5.12.2	Motors fed from a converter supply.....	34
5.13	Luminaires	34
5.14	Plugs and socket outlets for dust.....	34
5.14.1	General	34
5.14.2	Mounting	34
5.14.3	Location	35
6	Protection from dangerous (incendive) sparking	35
6.1	Danger from live parts	35
6.2	Danger from exposed and extraneous conductive parts.....	35
6.2.1	TN type of system earthing.....	35
6.2.2	TT type of system earthing	35
6.2.3	IT type of system earthing	35
6.2.4	SELV and PELV systems.....	35
6.2.5	Electrical separation	36
6.2.6	Above hazardous areas	36
6.3	Potential equalization	36
6.3.1	General	36
6.3.2	Temporary bonding.....	37
6.4	Static electricity.....	37
6.4.1	Gas	37
6.4.2	Dust	38
6.5	Lightning protection.....	38
6.6	Electromagnetic radiation	38
6.7	Cathodically protected metallic parts	38
6.8	Ignition by optical radiation.....	39
7	Electrical protection.....	39
7.1	General.....	39
7.2	Rotating electrical machines.....	39
7.3	Transformers.....	39
7.4	Resistance heating devices	40
8	Emergency switch-off and electrical isolation.....	40
8.1	Emergency switch-off	40
8.2	Electrical isolation	40
9	Wiring systems	41
9.1	General.....	41
9.2	Aluminium conductors	41
9.3	Cables.....	41

9.3.1	Cables for fixed wiring	41
9.3.2	Cables supplying transportable and portable equipment	41
9.3.3	Flexible connections for dust	42
9.3.4	Flexible cables	42
9.3.5	Non-sheathed single cores	42
9.3.6	Overhead lines	42
9.3.7	Avoidance of damage	43
9.3.8	Cable surface temperature	43
9.3.9	Flame propagation.....	43
9.3.10	Connections of cables to equipment	43
9.4	Conduit systems.....	44
9.5	Cable and conduit systems.....	45
9.5.1	EPL 'Ga'	45
9.5.2	EPL 'Da'	45
9.5.3	Cable and conduit systems for EPL 'Gb', 'Gc', 'Db' and 'Dc'	45
9.6	Installation requirements	45
9.6.1	Circuits traversing a hazardous area	45
9.6.2	Protection of stranded ends.....	45
9.6.3	Unused cores	45
9.6.4	Unused openings.....	45
9.6.5	Fortuitous contact.....	45
9.6.6	Jointing	46
9.6.7	Openings in walls	46
9.6.8	Passage and collection of flammables	46
9.6.9	Static build-up for dust.....	46
9.6.10	Accumulation of combustible dust.....	46
10	Additional requirements for type of protection 'd' – Flameproof enclosures	47
10.1	General.....	47
10.2	Solid obstacles.....	47
10.3	Protection of flameproof joints	47
10.4	Cable entry systems.....	48
10.4.1	General	48
10.4.2	Selection of cable glands.....	48
10.5	Conduit systems.....	50
10.6	Motors.....	50
10.6.1	Motors with a converter supply	50
10.6.2	Reduced-voltage starting (soft starting)	50
11	Additional requirements for type of protection 'e' – Increased safety.....	51
11.1	Degree of ingress protection of enclosures (IEC 60034-5 and IEC 60529).....	51
11.2	Wiring systems.....	51
11.2.1	General	51
11.2.2	Cable glands	51
11.2.3	Conductor terminations.....	52
11.2.4	Combinations of terminals and conductors for general connection and junction boxes	52
11.3	Cage induction motors.....	52
11.3.1	Mains-operated	52
11.3.2	Winding temperature sensors	53
11.3.3	Machines with rated voltage greater than 1 kV.....	53

11.3.4	Motors with converter supply	54
11.3.5	Reduced-voltage starting (soft starting)	54
11.4	Luminaires	54
12	Additional requirements for types of protection 'i' – Intrinsic safety	54
12.1	Introductory remark	54
12.2	Installations to meet the requirements of EPL 'Gb' or 'Gc'	55
12.2.1	Equipment	55
12.2.2	Cables	56
12.2.3	Termination of intrinsically safe circuits	59
12.2.4	Earthing of intrinsically safe circuits	60
12.2.5	Verification of intrinsically safe circuits	61
12.3	Installations to meet the requirements of EPL 'Ga'	63
12.4	Special applications	64
13	Additional requirements for pressurized enclosures	65
13.1	Type of protection 'p'	65
13.1.1	General	65
13.1.2	Ducting	65
13.1.3	Action to be taken on failure of pressurization	66
13.1.4	Multiple pressurized enclosures with a common safety device	68
13.1.5	Purging	68
13.1.6	Protective gas	68
13.1.7	Wiring systems	69
13.2	Motors	69
13.2.1	Motors with a converter supply	69
13.2.2	Reduced-voltage starting (soft starting)	69
13.3	Type of protection 'pD'	69
13.3.1	Sources of protective gas	69
13.3.2	Automatic switch-off	70
13.3.3	Alarm	70
13.3.4	Common source of protective gas	70
13.3.5	Switching on electrical supply	70
13.3.6	Motors with a converter supply	71
13.4	Rooms for explosive gas atmosphere	71
13.4.1	Pressurized rooms and analyser houses	71
14	Additional requirements for type of protection 'n'	71
14.1	General	71
14.2	Degree of ingress protection of enclosures (IEC 60034-5 and IEC 60529)	72
14.3	Wiring systems	72
14.3.1	General	72
14.3.2	Cable glands	72
14.3.3	Conductor terminations	73
14.4	Motors	73
14.4.1	Machines with rated voltage greater than 1 kV	73
14.4.2	Motors with converter supply	73
14.4.3	Reduced-voltage starting (soft starting)	74
14.5	Luminaires	74
15	Additional requirements for type of protection 'o' – Oil immersion	74
16	Additional requirements for type of protection 'q' – Powder filling	74

17	Additional requirements for type of protection 'm' – Encapsulation.....	74
18	Additional requirements for type of protection 'tD' – Protection by enclosure	74
18.1	Practices A and B.....	74
18.2	Practice A	74
18.3	Practice B	75
18.4	Motors supplied at varying frequency and voltages.....	75
	Annex A (normative) Verification of intrinsically safe circuits with more than one associated apparatus with linear current/voltage characteristics	76
	Annex B (informative) Methods of determining the maximum system voltages and currents in intrinsically safe circuits with more than one associated apparatus with linear current/voltage characteristics (as required by Annex A)	77
	Annex C (informative) Determination of cable parameters.....	80
	Annex D (informative) Safe work procedure guidelines for explosive gas atmospheres	82
	Annex E (normative) Potential stator winding discharge risk assessment – Ignition risk factors	83
	Annex F (normative) Knowledge, skills and competencies of 'Responsible Persons', 'Operatives' and 'Designers'.....	84
	Annex G (informative) Examples of dust layers of excessive thickness	87
	Annex H (normative) Frictional sparking risks with light metals and their alloys.....	88
	Annex I (informative) Introduction of an alternative risk assessment method encompassing “equipment protection levels” for Ex equipment	89
	Bibliography.....	94
	Figure 1 – Correlation between the maximum permissible surface temperature and depth of dust layers	29
	Figure 2 – Selection chart for cable entry devices into flameproof enclosures for cables complying with item b) of 10.4.2	49
	Figure 3 – Earthing of conducting screens	57
	Figure B.1 – Series connection – Summation of voltage.....	78
	Figure B.2 – Parallel connection – Summation of currents	78
	Figure B.3 – Series and parallel connections – Summations of voltages and summations of currents.....	79
	Figure G.1a – Excessive layer on top of equipment.....	87
	Figure G.1b – Excessive layer on top of equipment due to low ignition temperature of the dust	87
	Figure G.1c – Excessive layer at the sides of equipment.....	87
	Figure G.1d – Completely submerged equipment	87
	Figure G.1 – Examples for dust layers of excessive thickness with the requirement of laboratory investigation.....	87
	Table 1 – Equipment protection levels (EPLs) where only zones are assigned	24
	Table 2 – Relationship between types of protection and EPLs	25
	Table 3 – Relationship between gas/vapour or dust subdivision and equipment group	26
	Table 4 – Relationship between gas or vapour ignition temperature and temperature class of equipment.....	27

Table 5 – Limitations of areas	38
Table 6 – Minimum distance of obstruction from the flameproof flange joints related to the gas group of the hazardous area.....	47
Table 7 – Assessment for T4 classification according to component size and ambient temperature	63
Table 8 – Determination of type of protection (with no flammable release within the enclosure).....	65
Table 9 – Use of spark and particle barriers.....	66
Table 10 – Action to be taken when the pressurization with the protective gas fails for electrical equipment without an internal source of release	67
Table 11 – Summary of protection requirements for enclosures	70
Table 12 – Dust tightness practice A.....	75
Table 13 – Dust tightness practice B.....	75
Table I.1 – Traditional relationship of EPLs to zones (no additional risk assessment)	91
Table I.2 – Description of risk of ignition protection provided	92

INTRODUCTION

Preventive measures to reduce the explosion risk from flammable materials are based on three principles, which shall be applied in the following order:

- 1) Substitution
- 2) Control
- 3) Mitigation

Substitution involves, for example, replacing a flammable material by one which is either not flammable or less flammable.

Control involves, for example:

- a) reducing the quantity of flammables;
- b) avoiding or minimising releases;
- c) controlling the release;
- d) preventing the formation of an explosive atmosphere;
- e) collecting and containing releases; and
- f) avoiding ignition sources.

NOTE 1 With the exception of item f), all of the above are part of the process of hazardous area classification.

Mitigation involves, for example:

- 1) reducing the number of people exposed;
- 2) providing measures to avoid the propagation of an explosion;
- 3) providing explosion pressure relief;
- 4) providing explosion pressure suppression; and
- 5) providing suitable personal protective equipment.

NOTE 2 The above items are part of consequence management when considering risk.

Once the principles of substitution and control (items a) to e)) have been applied, the remaining hazardous areas should be classified into zones according to the likelihood of an explosive atmosphere being present (see IEC 60079-10 or IEC 61241-10). Such classification, which may be used in conjunction with an assessment of the consequences of an ignition, allows equipment protection levels to be determined and hence appropriate types of protection to be specified for each location.

For an explosion to occur, an explosive atmosphere and a source of ignition need to co-exist. Protective measures aim to reduce, to an acceptable level, the likelihood that the electrical installation could become a source of ignition.

By careful design of the electrical installation, it is frequently possible to locate much of the electrical equipment in less hazardous or non-hazardous areas.

When electrical equipment is to be installed in areas where dangerous concentrations and quantities of flammable gases, vapours, mists or dusts may be present in the atmosphere, protective measures are applied to reduce the likelihood of explosion due to ignition by arcs, sparks or hot surfaces, produced either in normal operation or under specified fault conditions.

Many types of dust that are generated, processed, handled and stored, are combustible. When ignited they can burn rapidly and with considerable explosive force if mixed with air in the appropriate proportions. It is often necessary to use electrical apparatus in locations

where such combustible materials are present, and suitable precautions must therefore be taken to ensure that all such apparatus is adequately protected so as to reduce the likelihood of ignition of the external explosive atmosphere. In electrical apparatus, potential ignition sources include electrical arcs and sparks, hot surfaces and frictional sparks.

Areas where dust, flyings and fibres in air occur in dangerous quantities are classified as hazardous and are divided into three zones according to the level of risk.

Combustible dust can be ignited by equipment in several ways:

- by surfaces of the apparatus that are above the minimum ignition temperature of the dust concerned. The temperature at which a type of dust ignites is a function of the properties of the dust, whether the dust is in a cloud or layer, the thickness of the layer and the geometry of the heat source;
- by arcing or sparking of electrical parts such as switches, contacts, commutators, brushes, or the like;
- by discharge of an accumulated electrostatic charge;
- by radiated energy (e.g. electromagnetic radiation);
- by mechanical sparking or frictional sparking associated with the apparatus.

In order to avoid dust ignition hazards it is necessary that:

- the temperature of surfaces on which dust can be deposited, or which would be in contact with a dust cloud, is kept below the temperature limitation specified in this standard;
- any electrical sparking parts, or parts having a temperature above the temperature limit specified in this standard:
 - are contained in an enclosure which adequately prevents the ingress of dust, or
 - the energy of electrical circuits is limited so as to avoid arcs, sparks or temperatures capable of igniting combustible dust;
- any other ignition sources are avoided.

Several types of protection are available for electrical equipment in hazardous areas (see IEC 60079-0), and this standard gives the specific requirements for design, selection and erection of electrical installations in explosive atmospheres.

This part of IEC 60079 is supplementary to other relevant IEC standards, for example IEC 60364 series as regards electrical installation requirements. This part also refers to IEC 60079-0 and its associated standards for the construction, testing and marking requirements of suitable electrical equipment.

This standard is based on the assumption that electrical equipment is correctly installed, tested, maintained and used in accordance with its specified characteristics.

Inspection, maintenance and repair aspects play an important role in control of hazardous area installations and the user's attention is drawn to IEC 60079-17 and IEC 60079-19 for further information concerning these aspects.

In any industrial installation, irrespective of size, there may be numerous sources of ignition apart from those associated with electrical equipment. Precautions may be necessary to ensure safety from other possible ignition sources, but guidance on this aspect is outside the scope of this standard.

In IEC 61241-1, for protection by enclosure 'tD', two different types of practice, A and B, are specified and are intended to provide an equivalent level of protection.

Both of these practices are in common use and the requirements of each should be followed without mixing either the apparatus requirements or selection/installation requirements of the two practices. They adopt different methodology with the primary differences being:

Practice A	Practice B
Written principally as performance based requirements	Written as both performance and prescriptive based requirements
Maximum surface temperature is determined with 5 mm layer of dust and installation rules require 75 °C margin between the surface temperature and ignition temperature of the particular dust	Maximum surface temperature is determined with 12,5 mm layer of dust and installation rules require 25 °C margin between the surface temperature and ignition temperature of the particular dust
A method of achieving the required dust ingress protection by the use of resilient seals on joints and rubbing seals on rotating or moving shafts or spindles and determining dust ingress according to IEC 60529 -IP Code	A method of achieving the required dust ingress protection by specified widths and clearances between joint faces and, in the case of shafts and spindles, specified lengths and diametrical clearances between moving and stationary parts and determining dust ingress according to the heat cycling test

EXPLOSIVE ATMOSPHERES –

Part 14: Electrical installations design, selection and erection

1 Scope

This part of IEC 60079 contains the specific requirements for the design, selection and erection of electrical installations in hazardous areas associated with explosive atmospheres.

Where the equipment is required to meet other environmental conditions, for example, protection against ingress of water and resistance to corrosion, additional methods of protection may be necessary. The method used should not adversely affect the integrity of the enclosure.

The requirements of this standard apply only to the use of equipment under normal or near normal atmospheric conditions. For other conditions, additional precautions may be necessary. For example, most flammable materials and many materials which are normally regarded as non-flammable might burn vigorously under conditions of oxygen enrichment. Other precautions might also be necessary in the use of equipment under conditions of extreme temperature and pressure. Such precautions are beyond the scope of this standard.

These requirements are in addition to the requirements for installations in non-hazardous areas.

This standard applies to all electrical equipment including fixed, portable, transportable and personal, and installations, permanent or temporary.

It applies to installations at all voltages.

This standard does not apply to

- electrical installations in mines susceptible to firedamp;
NOTE This standard may apply to electrical installations in mines where explosive gas atmospheres other than firedamp may be formed and to electrical installations in the surface installation of mines.
- inherently explosive situations and dust from explosives or pyrophoric substances (for example explosives manufacturing and processing);
- rooms used for medical purposes;
- electrical installations in areas where the hazard is due to hybrid mixtures of combustible dust and explosive gas, vapour or mist.

This standard does not take into account of any risk due to an emission of flammable or toxic gas from the dust.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-1, *Rotating electrical machines – Part 1: Rating and performance*

IEC 60034-5, *Rotating electrical machines – Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) – Classification*

IEC 60050-826, *International Electrotechnical Vocabulary – Part 826: Electrical installations*

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60079 (all parts), *Explosive atmospheres*

IEC 60079-0, *Explosive atmospheres – Part 0: Equipment – General requirements*

IEC 60079-1, *Explosive atmospheres – Part 1: Equipment protection by flameproof enclosures “d”*

IEC 60079-2, *Explosive atmospheres – Part 2: Equipment protection by pressurized enclosure «p»*

IEC 60079-5, *Explosive atmospheres – Part 5: Equipment protection by powder filling «q»*

IEC 60079-6, *Explosive atmospheres – Part 6: Equipment protection by oil immersion “o”*

IEC 60079-7, *Explosive atmospheres – Part 7: Equipment protection by increased safety “e”*

IEC 60079-11, *Explosive atmospheres – Part 11: Equipment protection by intrinsic safety “i”*

IEC/TR 60079-13, *Electrical apparatus for explosive gas atmospheres – Part 13: Construction and use of rooms or buildings protected by pressurization*

IEC 60079-14, *Electrical apparatus for explosive gas atmospheres – Part 14: Electrical installations in hazardous areas (other than mines)*

IEC 60079-15, *Electrical apparatus for explosive gas atmospheres – Part 15: Construction, test and marking of type of protection “n” electrical apparatus*

IEC 60079-16, *Electrical apparatus for explosive gas atmospheres – Part 16: Artificial ventilation for the protection of analyzer(s) houses*

IEC 60079-18, *Electrical apparatus for explosive gas atmospheres – Part 18: Construction, test and marking of type of protection encapsulation “m” electrical apparatus*

IEC 60079-19, *Explosive atmospheres – Part 19: Equipment repair, overhaul and reclamation*

IEC 60079-25, *Electrical apparatus for explosive gas atmospheres – Part 25: Intrinsically safe systems*

IEC 60079-26, *Explosive atmospheres – Part 26: Equipment with equipment protection level (EPL) Ga*

IEC 60079-27, *Electrical apparatus for explosive gas atmospheres – Part 27: Fieldbus intrinsically safe concept (FISCO) and Fieldbus non-incendive concept (FNICO)*

IEC 60079-28, *Explosive atmospheres – Part 28: Protection of equipment and transmission systems using optical radiation*

IEC 60079-29-1, *Explosive atmospheres – Part 29-1: Gas detectors – Performance requirements of detectors for flammable gases*

IEC 60079-29-2, *Explosive atmospheres – Part 29-2: Gas detectors – Selection, installation, use and maintenance of detectors for flammable gases and oxygen*

IEC 60079-31, *Explosive atmospheres – Part 31: Equipment dust ignition protection by enclosure "tD"¹*

IEC 60243-1, *Electrical strength of insulating materials – Test methods – Part 1: Tests at power frequencies*

IEC 60332-1-2, *Tests on electric and optical cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable-Procedure for 1KW pre-mixed flame*

IEC 60364 (all parts) *Low-voltage electrical installations*

IEC 60364-4-41, *Low-voltage electrical installations – Part 4-41: Protection for safety – Protection against electric shock*

IEC 60529, *Degrees of protection provided by enclosure (IP code)*

IEC 60950 (all parts), *Information technology equipment – Safety*

IEC 61010-1, *Safety requirements for electrical equipment for measurement, control, and laboratory use - Part 1: General requirements*

IEC 61241 (all parts), *Electrical apparatus for use in the presence of combustible dust*

IEC 61241-0, *Electrical apparatus for use in the presence of combustible dust – Part 0: General requirements*

IEC 61241-1, *Electrical apparatus for use in the presence of combustible dust – Part 1: Protection by enclosures "tD"*

IEC 61241-2-1, *Electrical apparatus for use in the presence of combustible dust – Part 2: Test methods – Section 1: Methods for determining the minimum ignition temperatures of dust*

IEC 61241-4, *Electrical apparatus for use in the presence of combustible dust – Part 4: Type of protection "pD"*

IEC 61241-10, *Electrical apparatus for use in the presence of combustible dust – Part 10: Classification of areas where combustible dusts are or may be present*

IEC 61241-11, *Electrical apparatus for use in the presence of combustible dust – Part 11: Protection by intrinsic safety 'iD'*

IEC 61285, *Industrial process control – Safety of analyser houses*

IEC 61558-2-6, *Safety of power transformers, power supply units and similar – Part 2-6: Particular requirements for safety isolating transformers for general use*

IEC 62305-3, *Protection against lightning – Part 3 Physical damage to structures and life hazard*

ISO 10807, *Pipework – Corrugated flexible metallic hose assemblies for the protection of electric cables in explosive atmospheres*

¹ To be published