

SVENSK STANDARD SS-EN IEC 60947-4-2, utg 4:2023

Fastställd 2023-09-20

Sida 1 (118) Ansvarig kommitté SEK TK 121A

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Kopplingsapparater för högst 1000 V – Del 4-2: Kontaktorer och startkopplare – Halvledarbaserade mjukstartare och startkopplare för växelströmsmotorer

Low-voltage switchgear and controlgear –
Part 4-2: Contactors and motor-starters –
Semiconductor motor controllers, starters and soft-starters

Som svensk standard gäller europastandarden EN IEC 60947-4-2:2023. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 60947-4-2:2023.

Nationellt förord

Europastandarden EN IEC 60947-4-2:2023

består av:

- europastandardens ikraftsättningsdokument, utarbetat inom CENELEC

utarbetad inom International Electrotechnical Commission, IEC.

Standarden ska användas tillsammans med SS-EN IEC 60947-1, utg 6:2021.

Tidigare fastställd svensk standard SS-EN 60947-4-2, utg 3:2012 med eventuella tillägg, ändringar och rättelser, gäller ej fr o m 2026-01-11.

ICS 29.130.20

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284 164 29 Kista Tel 08-444 14 00 www.elstandard.se

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN IEC 60947-4-2

March 2023

ICS 29.130.20

Supersedes EN 60947-4-2:2012

English Version

Low-voltage switchgear and controlgear - Part 4-2: Contactors and motor-starters - Semiconductor motor controllers, starters and soft-starters

(IEC 60947-4-2:2020)

Appareillage à basse tension - Partie 4-2: Contacteurs et démarreurs de moteurs - Gradateurs, démarreurs et démarreurs progressifs à semiconducteurs de moteurs (IEC 60947-4-2:2020)

Niederspannungsschaltgeräte - Teil 4-2: Schütze und Motorstarter - Halbleiter-Motor-Steuergeräte, Starter und Sanftstarter (IEC 60947-4-2:2020)

This European Standard was approved by CENELEC on 2023-01-11. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2023 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. EN IEC 60947-4-2:2023 E

European foreword

The text of document 121A/353/FDIS, future edition 4 of IEC 60947-4-2, prepared by SC 121A "Low-voltage switchgear and controlgear" of IEC/TC 121 "Switchgear and controlgear and their assemblies for low voltage" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 60947-4-2:2023.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2023-10-11 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2026-01-11 document have to be withdrawn

This document supersedes EN 60947-4-2:2012 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a Standardization Request given to CENELEC by the European Commission and the European Free Trade Association.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 60947-4-2:2020 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 60034-30-1 NOTE Approved as EN 60034-30-1

IEC 60068-2-2:2007 NOTE Approved as EN 60068-2-2:2007 (not modified)

IEC 60079 (series) NOTE Approved as EN IEC 60079-7 (series)

IEC 60085:2007 NOTE Approved as EN 60085:2008 (not modified)

IEC 60269-1:2006 NOTE Approved as EN 60269-1:2007 (not modified)

IEC 60364-1 NOTE Approved as HD 60364-1

IEC 60664 (series) NOTE Approved as EN 60664 (series)

IEC 60947-2 NOTE Approved as EN 60947-2

IEC 60947-3 NOTE Approved as EN IEC 60947-3

IEC 60947-4-1 NOTE Approved as EN IEC 60947-4-1

IEC 60947-4-3 NOTE Approved as EN 60947-4-3

IEC 60990:2016 NOTE Approved as EN 60990:2016 (not modified)

IEC 61000-4 (series) NOTE Approved as EN 61000-4 (series)

IEC 61032 NOTE Approved as EN 61032

IEC 61800 (series) NOTE Approved as EN 61800 (series)

IEC 62443 (series) NOTE Approved as EN IEC 62443 (series)

IEC 62477-1:2012 NOTE Approved as EN 62477-1:2012 (not modified) +A11:2014

IEC 62683-1 NOTE Approved as EN 62683-1

IEC/TR 63201 NOTE Approved as CLC IEC/TR 63201

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 60034-1	2017	Rotating electrical machines - Part 1: Rating and performance	-	-
IEC 60445	-	Basic and safety principles for man- machine interface, marking and identification - Identification of equipment terminals, conductor terminations and conductors	EN IEC 60445	-
IEC 60715	-	Dimensions of low-voltage switchgear and controlgear - Standardized mounting on rails for mechanical support of switchgear, controlgear and accessories		-
IEC 60730-1	-	Automatic electrical controls - Part 1: General requirements	-	-
IEC 60947-1	2020	Low-voltage switchgear and controlgear - Part 1: General rules	EN IEC 60947-1	2021
IEC 61000-3-2	-	Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current 16 ≤ A per phase)		-
IEC 61000-3-3	Electromagnetic compatibility (EMC) - Part EN 61000-3-3 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection		-	
IEC 61000-3-11	-	Electromagnetic compatibility (EMC) - Part 3-12: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems - Equipment with rated current ≤ 75 A and subject to conditional connection		1 -

IEC 61000-3-12	-	Electromagnetic compatibility (EMC) - Part 3-12: Limits - Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current >16 A and ≤ 75 A per phase	t EN 61000-3-12	-
IEC 61140 2016 Protection against electric shock - EN 61140 Common aspects for installation and equipment		EN 61140	2016	
CISPR 11	2015	Industrial, scientific and medical equipment EN 55011 2 - Radio-frequency disturbance characteristics - Limits and methods of measurement		2016
+ A1	2016		+ A1	2017
-	-		+ A11	2020
ISO 2859-1	1999	Sampling procedures for inspection by attributes - Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection	-	-



Edition 4.0 2020-06

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Low-voltage switchgear and controlgear –
Part 4-2: Contactors and motor-starters – Semiconductor motor controllers, starters and soft-starters

Appareillage à basse tension -

Partie 4-2: Contacteurs et démarreurs de moteurs – Gradateurs, démarreurs et démarreurs progressifs à semiconducteurs de moteurs

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.130.20 ISBN 978-2-8322-8451-3

Warning! Make sure that you obtained this publication from an authorized distributor.

Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

Ε(DREWOR	D	7
IN	TRODUC	TION	g
1	Scope		10
2	•	tive references	
3	Terms	, definitions, symbols and abbreviated terms	12
		erms and definitions	
	3.1.1	Terms and definitions concerning the types of semiconductor motor controllers and starters	
	3.1.2	Terms and definitions concerning semiconductor motor controllers and starters	14
	3.1.3	Terms and definitions concerning safety aspects	17
	3.1.4	Alphabetical index of terms	
		Symbols and abbreviated terms	
4	Classi	fication	20
5	Chara	cteristics of semiconductor motor controllers and starters	20
	5.1	Summary of characteristics	20
	5.2	ype of equipment	21
	5.2.1	Kind of equipment	21
	5.2.2	Number of poles	21
	5.2.3	Kind of current	21
	5.2.4	Interrupting medium (air, vacuum, etc.)	21
	5.2.5	Operating conditions of the equipment	21
	5.3 F	Rated and limiting values for main circuits	22
	5.3.1	Rated voltages	22
	5.3.2	Currents	24
	5.3.3	Rated frequency	25
	5.3.4	Duty cycle values and sequences	25
	5.3.5	Normal load and overload characteristics	25
	5.3.6	Rated conditional short-circuit current	27
	5.3.7	Semiconductor motor controller power losses	27
	5.4 L	Itilization category	28
	5.4.1	General	28
	5.4.2	Assignment of ratings based on the results of tests	28
	5.5	Control circuits	29
	5.6 A	Auxiliary circuits	29
	5.7	Characteristics of relays and releases (overload relays)	29
	5.7.1	Summary of characteristics	29
	5.7.2	Types of relay or release	30
	5.7.3	Characteristic values	30
	5.7.4	Designation and current settings of overload relays	31
	5.7.5	Time-current characteristics of overload relays	31
	5.7.6	Influence of ambient air temperature	
	5.8	Coordination with short-circuit protective devices (SCPD)	32
6	Produc	ct information	32
	6.1 N	Nature of information	32
	6.2 N	Marking	34

	6.3	Instructions for installation, operation, maintenance, decommissioning and dismantling	34
	6.4	Environmental information	34
7	Norm	nal service, mounting and transport conditions	35
	7.1	Normal service conditions	35
	7.1.1		
	7.1.2	Altitude	35
	7.1.3	Atmospheric conditions	35
	7.1.4	Shock and vibrations	35
	7.2	Conditions during transport and storage	35
	7.3	Mounting	35
	7.4	Electrical system disturbances and influences	35
8	Cons	tructional and performance requirements	36
	8.1	Constructional requirements	36
	8.1.1	General	36
	8.1.2	Materials	36
	8.1.3	Current-carrying parts and their connections	37
	8.1.4	Clearances and creepage distances	37
	8.1.5	Actuator	37
	8.1.6	Indication of the contact position	37
	8.1.7	Additional requirements for equipment suitable for isolation	37
	8.1.8	Terminals	37
	8.1.9	Additional requirements for equipment provided with a neutral pole	38
	8.1.1	0 Provisions for protective earthing	38
	8.1.1	• •	
	8.1.1	2 Degrees of protection of enclosed equipment	38
	8.1.1	3 Conduit pull-out, torque and bending with metallic conduits	38
	8.1.1	3,	
	8.1.1	0 0,	
	8.1.1	6 Fault and abnormal conditions	40
	8.1.1	, ,	
	8.2	Performance requirements	
	8.2.1	Operating conditions	
	8.2.2	•	
	8.2.3	· ·	
	8.2.4	·	
	8.2.5	•	
	8.3	EMC requirements	
	8.3.1		
	8.3.2	•	
_	8.3.3		
9	Tests	S	
	9.1	Kinds of tests	
	9.1.1		
	9.1.2	31	
	9.1.3		
	9.1.4		
	9.1.5	•	
	9.2	Compliance with constructional requirements	58

9.2	.1	General	58
9.2	.2	Electrical performance of screwless-type clamping units	58
9.2	.3	Ageing test for screwless-type clamping units	59
9.2	.4	Limited energy source test	59
9.2	.5	Breakdown of components	59
9.2	.6	Wire flexing test	60
9.3	Com	pliance with performance requirements	60
9.3	.1	Test sequences	60
9.3	.2	General test conditions	61
9.3	.3	Performance under no load, normal load, and overload conditions	61
9.3	.4	Performance under short-circuit conditions	72
9.4	EMC	tests	75
9.4	.1	General	75
9.4	.2	EMC immunity tests	76
9.4	.3	EMC emission tests	76
9.5	Rout	ine and sampling tests	79
9.5	.1	General	79
9.5	.2	Operation and operating limits	79
9.5	.3	Dielectric tests	
Annex A	(norm	ative) Marking and identification of terminals	
A.1	•	eral	
A.2		ring and identification of terminals of semiconductor controllers and	
71.2		ers	81
A.2		Marking and identification of terminals of main circuits	
A.2	.2	Marking and identification of terminals of control circuits	
A.3	Mark	ring and identification of terminals of overload relays	81
Annex E	3 (xxx) .		82
		ative) Coordination at the crossover current between the starter and	
		PD	83
C.1	Gen	eral and definitions	83
C.1	.1	General	83
C.1	.2	Terms and definitions	83
C.2	Cond	dition for the test for the verification of coordination at the crossover	
	curre	ent by a direct method	83
C.3	Test	currents and test circuits	83
C.4	Test	procedure and results to be obtained	84
C.4	.1	Test procedure	84
C.4	.2	Results to be obtained	84
C.5	Verif	ication of coordination at the crossover current by an indirect method	84
C.5	5.1	General	84
C.5	5.2	Test for I _{cd}	84
C.5	5.3	Time-current characteristic withstand capability of controllers/starters	
Annex D) (xxx)		87
Annex E	(xxx)		88
	` '	native) Operating capability	
	•	mative) Rated operational currents and rated operational powers of	
		es for electrical motors	93
G.1	•	eral	
G.2		d operational powers and rated operational currents	
J.2		The first term of the first state of the first stat	

Annex H (xxx)	97
Annex I (normative) Modified test circuit for short-circuit testing of semiconductor motor controllers and starters	98
Annex J (xxx)	
Annex K (xxx)	101
Annex L (normative) Examples of overvoltage category reduction	102
L.1 General	102
L.2 Insulation to the surroundings	102
L.2.1 Circuits connected directly to the supply mains	
L.2.2 Insulation between circuits	
Annex M (xxx)	107
Annex N (normative) Additional requirements and tests for equipment with protective separation	108
N.1 General	108
N.2 Definitions	108
N.3 Requirements	108
N.3.1 Test method for implementing protective impedance	108
N.3.2 Touch current measurement	
Bibliography	111
Figure 1 – Semiconductor motor control devices	13
Figure 2 – Connecting methods	24
Figure 3 – Thermal memory test	44
Figure 4 – Multiple of current setting limits for ambient air temperature compensated time-delay overload relays	71
Figure C.1 – Examples of time-current withstand characteristic	
Figure F.1 – Thermal stability test profile	
Figure F.2 – Overload capability test profile	
Figure F.3 – Blocking and commutating capability test profile	
Figure I.1 – Modified circuit for short-circuit testing of semiconductor devices	
Figure I.2 – Time line for the short-circuit test of 9.3.4.1.6	
Figure L.1 – Basic insulation evaluation for circuits connected directly to the origin of	
the installation mains supply	102
Figure L.2 – Basic insulation evaluation for circuits connected directly to the mains supply	103
Figure L.3 – Basic insulation evaluation for equipment not permanently connected to the mains supply	103
Figure L.4 – Basic insulation evaluation for insulation between circuits connected directly to the origin of the installation mains supply and that are declared galvanically separated	104
Figure L.5 – Basic insulation evaluation for insulation between circuits connected directly to the mains supply and that are declared galvanically separated	104
Figure L.6 – Basic insulation evaluation for insulation between circuits not permanently connected directly to the mains supply and that are declared galvanically separated	105
Figure L.7 – Basic insulation evaluation for insulation between circuits connected directly to the origin of the installation mains supply and that are declared galvanically separated where internal SPDs are used	105

Figure L.8 – Basic insulation evaluation for insulation between circuits connected directly to the mains supply and that are declared galvanically separated where internal SPDs are used	106
Figure L.9 – Basic insulation evaluation for insulation between circuits connected directly to the mains supply and that are declared galvanically separated	106
Figure N.1 – Protection by means of protective impedance	109
Figure N.2 – Measuring instrument	110
Table 1 – Utilization categories	28
Table 2 – Relative levels of severity	29
Table 3 – Trip classes of overload relays	31
Table 19 – Limits for limited energy sources without an over-current protective device	39
Table 20 – Limits for limited energy sources with an over-current protective device	39
Table 21 – Limits for limited energy source with current limiting impedance	40
Table 4 – Limits of operation of time-delay overload relays when energized on all poles	43
Table 5 – Limits of operation of three-pole time-delay overload relays when energized on two poles only	45
Table 6 – Temperature-rise limits for insulated coils in air and in oil	47
Table 7 – Minimum overload current withstand time (T_{X}) in relation to overload current ratio (X) and corresponding to overload relay trip class (see Table 3)	49
Table 8 – Minimum requirements for thermal stability test conditions	50
Table 9 – Prospective locked rotor current by utilization categories	50
Table 10 – Minimum requirements for overload capability test conditions	51
Table 11 – Making and breaking capacity test; making and breaking conditions according to utilization categories for the mechanical switching device	52
Table 12 – Conventional operational performance making and breaking conditions according to utilization categories for the mechanical switching device	53
Table 13 – Specific performance criteria when EM disturbances are present	55
Table 14 – Thermal stability test specifications	66
Table 15 – Initial case temperature requirements	66
Table 16 – Minimum requirements and conditions for performance testing with an induction motor load	68
Table 17 – Terminal disturbance voltage limits for conducted radio-frequency emission (AC mains power port)	78
Table 18 – Radiated emissions test limits	79
Table A.1 – Main circuit terminal markings	81
Table C.1 – Test conditions	85
Table G.1 – Rated operational powers and rated operational currents of motors	94
Table L.1 – Drawing keys	102

INTERNATIONAL ELECTROTECHNICAL COMMISSION

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR -

Part 4-2: Contactors and motor-starters – Semiconductor motor controllers, starters and soft-starters

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 60947-4-2 has been prepared by subcommittee 121A: Low-voltage switchgear and controlgear, of IEC technical committee 121: Switchgear and controlgear and their assemblies for low voltage.

This fourth edition cancels and replaces the third edition published in 2011. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- scope exclusions;
- · editorial correction of notes and hanging paragraphs;
- reference to IEC 62683-1;

- safety aspects related to:
 - general aspects;
 - limited energy circuits;
 - electronic circuits;
- mention of dedicated wiring accessories;
- · power consumption measurement;
- alignment to IEC 60947-1:2020.

The provisions of the general rules dealt with IEC 60947-1 are applicable to this part of IEC 60947 series where specifically called for. Clauses and subclauses, tables, figures and annexes of the general rules thus applicable are identified by reference to IEC 60947-1:2020.

The text of this standard is based on the following documents:

FDIS	Report on voting
121A/353/FDIS	121A/360/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all the parts in the IEC 60947 series, under the general title *Low-voltage switchgear* and controlgear, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- · replaced by a revised edition, or
- amended.

INTRODUCTION

This document covers low-voltage semiconductor motor controllers, starters and soft-starters that have many capabilities and features beyond the simple starting and stopping of an induction motor, such as controlled starting and stopping, manoeuvring and controlled running.

The generic term "controller" is used in this document wherever reference is made to elements of power semiconductor switching devices.

The generic term "starter" is used in this document wherever reference is made to the elements of power semiconductor switching devices together with suitable overload protective devices.

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR -

Part 4-2: Contactors and motor-starters – Semiconductor motor controllers, starters and soft-starters

1 Scope

This part of IEC 60947 applies to semiconductor motor controllers, starters and soft-starters which can include a series mechanical switching device, intended to be connected to circuits the rated voltage of which does not exceed 1 000 V AC.

This document characterizes semiconductor motor controllers and starters with and without bypass means.

This document does not apply to:

- semiconductor motor controllers and starters used for continuous operation of AC motors at motor speeds other than the normal speed¹;
- electromechanical contactors and external overload relays (see IEC 60947-4-1);
- short-circuit protective device associated with semiconductor motor controllers and starters (see IEC 60947-4-1 (MPSD), IEC 60947-2 and IEC 60947-3);
- semiconductor equipment, including semiconductor contactors (3.4.13 of IEC 60947-1:2020) controlling non-motor loads (see IEC 60947-4-3);
- semiconductor motor controllers and starters used for rotor circuits¹;
- adjustable speed electrical power drive systems (see IEC 61800 series);
- use of the product within explosive atmospheres (see IEC 60079 series);
- software and firmware requirements¹;
 - NOTE 1 Guidance on embedded software is given in IEC TR 63201.
- cyber security aspects (see IEC TS 63208).

Contactors, overload relays and control circuit devices used in semiconductor motor controllers and starters are considered compliant with the requirements of their relevant product standard. Where mechanical switching devices are used, they are considered meeting the requirements of their own IEC product standard, and the additional requirements of this document.

The object of this document is to state as follows:

- the characteristics of semiconductor motor controllers, starters and soft-starters and associated equipment;
- the conditions with which semiconductor motor controllers, starters and soft-starters comply with reference to
 - a) their operation and behaviour in normal and abnormal operating conditions including overcurrent operating conditions;
 - b) their dielectric properties;
 - c) the degrees of protection provided by their enclosures where applicable;

¹ For this subject, the manufacturer is responsible for taking additional safety measures.

- d) their construction including safety measures against electric shock, fire hazard and mechanical hazard;
- the tests intended for confirming that these conditions have been met, and the methods to be adopted for these tests;
- the information to be given with the equipment, or in the manufacturer's literature.

NOTE 2 For the purpose of this document, the term "controller" is used instead of "semiconductor motor controller".

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-1:2017, Rotating electrical machines – Part 1: Rating and performance

IEC 60445, Basic and safety principles for man-machine interface, marking and identification – Identification of equipment terminals, conductor terminations and conductors

IEC 60715, Dimensions of low-voltage switchgear and controlgear – Standardized mounting on rails for mechanical support of switchgear, controlgear and accessories

IEC 60730-1, Automatic electrical controls – Part 1: General requirements

IEC 60947-1:2020, Low-voltage switchgear and controlgear - Part 1: General rules

IEC 61000-3-2, Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current ≤16 A per phase)

IEC 61000-3-3, Electromagnetic compatibility (EMC) – Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current \leq 16 A per phase and not subject to conditional connection

IEC 61000-3-11, Electromagnetic compatibility (EMC) – Part 3-11: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems – Equipment with rated current \leq 75 A and subject to conditional connection

IEC 61000-3-12, Electromagnetic compatibility (EMC) — Part 3-12: Limits — Limits for harmonic currents produced by equipment connected to public low-voltage systems with input current >16 A and \leq 75 A per phase

IEC 61140:2016, Protection against electric shock – Common aspects for installation and equipment

CISPR 11:2015, Industrial, scientific and medical equipment – Radio-frequency disturbance characteristics – Limits and methods of measurement CISPR 11:2015/AMD1:2016

ISO 2859-1:1999, Sampling procedures for inspection by attributes – Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection