

SVENSK STANDARD

SS-EN IEC 61000-4-6, utg 5:2024

2024-03-20

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

REDLINE VERSION

Elektromagnetisk kompatibilitet (EMC) – Del 4-6: Mät- och provningsmetoder – Immunitet mot ledningsbundna störningar orsakade av radiofrekventa fält

Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

En så kallad "Redline version" (RLV) innehåller både standarden som fastställts som SS och en ändringsmarkerad IEC-standard. Alla tillägg och borttagningar sedan den tidigare utgåvan av IEC-standarden är markerade med färg. Med en RLV sparar du mycket tid när du ska identifiera och bedöma aktuella ändringar i standarden. SEK Svensk Elstandard kan bara ge ut RLV i de fall den finns tillgänglig från IEC.





Edition 5.0 2023-06 REDLINE VERSION

INTERNATIONAL STANDARD



BASIC EMC PUBLICATION

Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.100.20 ISBN 978-2-8322-7130-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

F	DREWC	PRD	7
IN	TRODU	JCTION	9
1	Scop	re	10
2	Norm	native references	10
3	Term	is and definitions	10
4	Gene	eral	12
5		levels	
6		equipment and level adjustment procedure	
Ü	6.1	Test generator	
	6.2	Coupling and decoupling devices	
	6.2.1		
	6.2.2		
	6.2.3		
	6.2.4	Direct injection devices	30
	6.2.5	Decoupling networks	30
	6.3	Verification of the common-mode impedance at the EUT port of coupling and	
	0.0.4	decoupling devices	
	6.3.1		
	6.3.2	Insertion loss of the 150 Ω to 50 Ω adapters	
	6.4 6.4.1		
	6.4.2		
7	_	setup and injection methods	
•	7.1	Test setup	
	7.2	EUT comprising a single unit	
	7.3	EUT comprising several units	
	7.4	Rules for selecting injection methods and test points	
	7.4.1	General	44
	7.4.2	Injection method	44
	7.4.3	Ports to be tested	46
	7.5	CDN injection application	47
	7.6	Clamp injection application when the common mode impedance	
	7.7	requirements can be met	
	1.1	requirements cannot be met	
	7.6	Clamp injection application	52
	7.7	Direct injection application	53
8	Test	procedure	54
9	Eval	uation of the test results	55
10) Test	report	56
Ar	nnex A	(normative) EM and decoupling clamps	57
	A.1	EM clamps	
	A.1.1	·	
	A.1.2	2 Typical -Specification of EM clamps	57
	A.2	EM clamp characterization	60
	A.2.1	Specification of the clamp test jig	60

A.2.2	Clamp c	haracterization	0 1
A.3	Decoupling c	clamp characterization	66
A.3.1	General		66
A.3.2	Specific	ation of decoupling clamps	66
A.3.3	Impedar	nce	66
A.3.4	Decoupl	ling factor	67
Annex B (nformative)	Selection criteria for the frequency range of application	69
Annex C (informative)	Guidelines for selecting test levels	71
Annex D (informative)	Information on coupling and decoupling networks	72
D.1	Basic feature	es of the coupling and decoupling networks	72
D.2	Examples of	coupling and decoupling networks	72
Annex E (nformative)	Information for the test generator specification	77
Annex F (i	nformative)	Test setup for large EUTs	78
F.1	General		78
F.2	Test setup fo	or large EUTs	78
Annex G (informative)	Measurement uncertainty of the voltage test level	81
G.1	General		81
G.2	General sym	bols	81
G.3	Uncertainty b	oudgets for test methods	81
G.3.1	Definitio	on of the measurand	81
G.3.2	MU cont	tributors of the measurand	82
G.3.3	Input qu	antities and calculation examples for expanded uncertainty	83
G.4	•	of the calculated measurement uncertainty and its application	
C F	DOLLER CONTROL		
		Measurement of AE impedance	
Annex H (informative)		
Annex H (i <mark>nformative)</mark> informative) 1	Measurement of AE impedance	96
Annex H (informative) informative) 1 General	Measurement of AE impedance Testing with multiple signals	96
Annex H (Annex H (H.1 H.2	informative) informative) 1 General Intermodulati	Measurement of AE impedance Testing with multiple signals	96 96
Annex H (Annex H (H.1 H.2 H.3	informative) informative) T General Intermodulati Power requir	Measurement of AE impedance	96 96 96
Annex H (Annex H (H.1 H.2 H.3 H.4	informative) informative) General Intermodulati Power requir Level-setting	Measurement of AE impedance Testing with multiple signals ion ements	96 96 96 97
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5	informative) informative) General Intermodulati Power requir Level-setting Linearity che	Measurement of AE impedance Testing with multiple signals ion ements requirements	96 96 97 98
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6	informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform	Measurement of AE impedance Testing with multiple signals ion ements requirements eck and harmonics checks of the test generator	96 96 97 98 98
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6	informative) informative) Informative) Intermodulati Power requir Level-setting Linearity che EUT perform Iformative)	Measurement of AE impedance Testing with multiple signals ion ements requirements ck and harmonics checks of the test generator ance criteria with multiple signals	96 96 97 98 98 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (in	informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform nformative) General	Measurement of AE impedance. Testing with multiple signals	96 96 97 98 98 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (in	informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform nformative) F General Test setup fo	Measurement of AE impedance Testing with multiple signals	96 96 97 98 98 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (in	informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo	Measurement of AE impedance. Testing with multiple signals	96 96 97 98 98 98 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (in I.1 I.2 I.2.1	informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo Selectio Procedu	Measurement of AE impedance Testing with multiple signals ion rements requirements reck and harmonics checks of the test generator ance criteria with multiple signals Port-to-port injection or injection on identical ports	96 96 97 98 98 98 99 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (in I.1 I.2 I.2.1 I.2.2 Annex J (i	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) General Test setup fo Selectio Procedu	Measurement of AE impedance Testing with multiple signals ion ements requirements ck and harmonics checks of the test generator cance criteria with multiple signals Port-to-port injection or injection on identical ports and ports are for port-to-port injection	96 96 97 98 98 98 99 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (iii J.1	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo Selectio Procedu nformative) A	Measurement of AE impedance Testing with multiple signals ion rements requirements reck and harmonics checks of the test generator rance criteria with multiple signals Port-to-port injection or injection on identical ports re for port-to-port injection Amplifier compression and non-linearity	96 96 97 98 98 98 99 99 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (iii J.1 J.2	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) General Test setup fo Selectio Procedu nformative) Objective of I	Measurement of AE impedance Testing with multiple signals ion ements requirements ck and harmonics checks of the test generator cance criteria with multiple signals Port-to-port injection or injection on identical ports in of ports ire for port-to-port injection Amplifier compression and non-linearity limiting amplifier distortion	96 96 97 98 98 99 99 99 99 99
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (iii J.1 J.2	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo Selectio Procedu nformative) A Objective of I Possible prol	Measurement of AE impedance Testing with multiple signals ion ements requirements ck and harmonics checks of the test generator ance criteria with multiple signals Port-to-port injection or injection on identical ports and ports are for port-to-port injection Amplifier compression and non-linearity limiting amplifier distortion blems caused by harmonics and saturation	96 96 97 98 98 99 99 99 99 99 101
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (iii J.1 J.2 J.3	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo Selectio Procedu nformative) / Objective of I Possible prob	Measurement of AE impedance Testing with multiple signals ion ements requirements ck and harmonics checks of the test generator ance criteria with multiple signals Port-to-port injection or injection on identical ports in of ports are for port-to-port injection Amplifier compression and non-linearity limiting amplifier distortion blems caused by harmonics and saturation harmonic content in the disturbance signal	96 96 97 98 99 99 99 99 99 99 101 101
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (i J.1 J.2 J.3 J.4	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) General Test setup fo Selectio Procedu Informative) Objective of I Possible prob Limiting the R Effect of linear	Measurement of AE impedance. Testing with multiple signals	96 96 97 98 98 99 99 99 99 99 91 101 101 101
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (ii J.1 J.2 J.3 J.4 J.4.1 J.4.2	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo Selectio Procedu nformative) / Objective of I Possible prol Limiting the r Effect of linear General Evaluati	Measurement of AE impedance. Testing with multiple signals	96 96 97 98 98 99 99 99 99 101 101 101 101 102
Annex H (Annex H (H.1 H.2 H.3 H.4 H.5 H.6 Annex I (iii I.1 I.2 I.2.1 I.2.2 Annex J (ii J.1 J.2 J.3 J.4 J.4.1 J.4.2	informative) informative) informative) General Intermodulati Power requir Level-setting Linearity che EUT perform formative) F General Test setup fo Selectio Procedu nformative) / Objective of I Possible prol Limiting the r Effect of linear General Evaluati	Measurement of AE impedance Testing with multiple signals. ion	96 96 97 98 98 99 99 99 99 101 101 101 101 102

Figure 2 – Schematic setup for immunity test to RF conducted disturbances	15
Figure 2 - Open circuit waveforms at the EUT port of a coupling device for test level 1	
Figure 3 – Example of unmodulated and modulated RF signal	17
Figure 4 – Test generator setup	18
Figure 5 – Principle of coupling and decoupling – Symbols used for the indicated setup principles	21
Figure 6 – Principle of coupling and decoupling – Principle of direct injection to screened cables	22
Figure 7 – Principle of coupling and decoupling – Principle of coupling to unscreened cables according to the CDN method	23
Figure 8 – Principle of coupling and decoupling – Principle of decoupling	24
Figure 5 - Principle of coupling and decoupling according to the clamp injection	
method	
Figure 9 – Example of circuit for level-setting setup in a 150 Ω test jig	28
Figure 7 - Example circuit for evaluating the performance of the current clamp	
Figure 10 – Example of circuit for evaluating the performance transmission loss of the current clamp level-setting	29
Figure 11 – Example of the setup geometry to verify the impedance characteristics of the coupling and decoupling devices	32
Figure 12 – Setup principle to verify Z_{Ce} of the coupling and decoupling device	33
Figure 13 – Setup principle for measuring the insertion loss of two 150 Ω to 50 Ω adapters	33
Figure 8 — Details of setups and components to verify the essential characteristics of coupling and decoupling devices and the 150 Ω to 50 Ω adapters	
Figure 14 – Circuit and construction of the 150 Ω to 50 Ω adapter	34
Figure 15 – Definition of a common-mode point for unscreened and screened cables	37
Figure 16 – Setup for level-setting at the EUT port of the coupling/decoupling devices	38
Figure 17 – Example of test setup with a single unit EUT with only one CDN for injection (top view)	39
Figure 18 – Example of test setup with a single unit EUT (top view) using multiple CDNs	42
Figure 11 - Example of a test setup with a multi-unit EUT (top view)	
Figure 19 – Example of a test setup with a multi-unit EUT (top view)	
Figure 20 – Rules for selecting the injection method	
Figure 21 – Immunity test for two-port EUT (when only one CDN can be used)	
Figure 22 – General principle of a test setup using clamp injection devices	
Figure 23 – Example of the test unit locations on the ground plane when using injection clamps (top view)	
Figure A.1 – Example: Construction details of the EM clamp	
Figure A.1 – Example: Construction details of the EM clamp	59
Figure A.2 – Example: Concept of the EM clamp	59 60
·	59 60 61
Figure A.2 – Example: Concept of the EM clamp Figure A.3 – Dimension of a reference plane	59 60 61
Figure A.2 – Example: Concept of the EM clamp Figure A.3 – Dimension of a reference plane Figure A.4 – Test jig	59 60 61 61
Figure A.2 – Example: Concept of the EM clamp Figure A.3 – Dimension of a reference plane Figure A.4 – Test jig Figure A.5 – Test jig with inserted clamp	59 60 61 61 61

Figure A.9 – Normalization setup for coupling factor measurement	65
Figure A.10 – S ₂₁ coupling factor measurement setup	65
Figure A.11 – Typical examples for coupling factor, three typical clamps	66
Figure A.12 – Decoupling clamp characterization measurement setup	67
Figure A.13 – Typical examples for the decoupling clamp impedance	67
Figure A.14 – Typical examples for decoupling factors	68
Figure B.1 – Start frequency as function of cable length and equipment size	70
Figure D.1 – Example of a simplified diagram for the circuit of CDN-S1 used with screened cables (see 6.2.2.5)	73
Figure D.2 – Example of simplified diagram for the circuit of CDN-M1, CDN-M2 and CDN-M3 used with unscreened supply (mains) lines (see 6.2.2.2)	73
Figure D.3 – Example of a simplified diagram for the circuit of CDN-AF2 used with unscreened unbalanced lines (see 6.2.2.4)	74
Figure D.4 – Example of a simplified diagram for the circuit of CDN-T2, used with an unscreened balanced pair (see 6.2.2.3)	74
Figure D.5 – Example of a simplified diagram of the circuit of CDN-T4 used with unscreened balanced pairs (see 6.2.2.3)	75
Figure D.6 – Example of a simplified diagram of the circuit of CDN AF8 used with unscreened unbalanced lines (see 6.2.2.4)	75
Figure D.7 – Example of a simplified diagram of the circuit of CDN-T8 used with unscreened balanced pairs (see 6.2.2.3)	76
Figure F.1 – Example of large EUT test setup with elevated horizontal reference ground plane	79
Figure F.2 – Example of large EUT test setup with vertical reference ground plane	80
Figure G.1 – Example of influences upon voltage test level using CDN	82
Figure G.2 – Example of influences upon voltage test level using EM clamp	
Figure G.3 – Example of influences upon voltage test level using current clamp	
Figure G.4 – Example of influences upon voltage test level using direct injection	
Figure G.5 – Circuit for level-setting setup of CDN	84
Figure H.1 – Impedance measurement using a voltmeter	
Figure H.2 Impedance measurement using a current probe	
Figure H.1 – Test frequencies f_1 and f_2 and intermodulation frequencies of the second	00
and third order	
Figure I.1 – Example of setup, port-to-port injection	
Figure J.1 – Amplifier linearity measurement setup	
Figure J.2 – Linearity characteristic	
Figure J.3 – Measurement setup for modulation depth	
Figure J.4 – Spectrum of AM modulated signal	105
Table 1 – Test levels	
Table 2 – Characteristics of the test generator	
Table 3 – Main parameter of the combination of the coupling and decoupling device	
Table 4 – Usage of CDNs	25
Table B.1 – Main parameter of the combination of the coupling and decoupling device when the frequency range of the test is extended above 80 MHz	
Table E.1 – Required power amplifier output power to obtain a test level of 10 V	77

Table G.1 – CDN level-setting process	84
Table G.2 – CDN test process	84
Table G.3 – EM clamp level-setting process	87
Table G.4 – EM clamp test process	87
Table G.5 – Current clamp level-setting process	88
Table G.6 – Current clamp test process	89
Table G.7 – Direct injection level-setting process	90
Table G.8 – Direct injection test process	90
Table H.1 – Impedance requirements for the AE	
Table H.2 – Derived voltage division ratios for AE impedance measurements	
Table H.3 - Derived voltage ratios for AE impedance measurements	

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROMAGNETIC COMPATIBILITY (EMC) -

Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This redline version of the official IEC Standard allows the user to identify the changes made to the previous edition IEC 61000-4-6:2013. A vertical bar appears in the margin wherever a change has been made. Additions are in green text, deletions are in strikethrough red text.

IEC 61000-4-6 has been prepared by subcommittee 77B: High frequency phenomena, of IEC technical committee 77: Electromagnetic compatibility. It is an International Standard.

It forms Part 4-6 of IEC 61000. It has the status of a basic EMC publication in accordance with IEC Guide 107.

This fifth edition cancels and replaces the fourth edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) selection of injection devices revised;
- b) need of AE impedance check for clamp injection removed and Annex H deleted;
- c) saturation check revised;
- d) new Annex H on testing with multiple signals;
- e) level-setting only with feedback loop.

The text of this International Standard is based on the following documents:

Draft	Report on voting
77B/863/FDIS	77B/865/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61000 series, published under the general title *Electromagnetic* compatibility (EMC), can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed.
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

Part 1: General

General considerations (introduction, fundamental principles)

Definitions, terminology

Part 2: Environment

Description of the environment

Classification of the environment

Compatibility levels

Part 3: Limits

Emission limits

Immunity limits (in so far as they do not fall under the responsibility of the product committees)

Part 4: Testing and measurement techniques

Measurement techniques

Testing techniques

Part 5: Installation and mitigation guidelines

Installation guidelines

Mitigation methods and devices

Part 6: Generic standards

Part 9: Miscellaneous

Each part is further subdivided into several parts, published either as international standards or as technical specifications or technical reports, some of which have already been published as sections. Others will be published with the part number followed by a dash and a second number identifying the subdivision (example: IEC 61000-6-1).

This part is an international standard which gives immunity requirements and test procedures related to conducted disturbances induced by radio-frequency fields.

ELECTROMAGNETIC COMPATIBILITY (EMC) -

Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

1 Scope

This part of IEC 61000 relates to the conducted immunity requirements of electrical and electronic equipment to electromagnetic disturbances coming from intended radio-frequency (RF) transmitters in the frequency range 150 kHz up to 80 MHz.

NOTE 1 Product committees might decide to use the methods described in this document also for frequencies up to 230 MHz (see Annex B) although the methods and test instrumentation are intended to be used in the frequency range up to 80 MHz.

Equipment not having at least one conducting wire and/or cable (such as mains supply, signal line or earth connection) which can couple the equipment to the disturbing RF fields is excluded from the scope of this document.

NOTE 2 Test methods are defined specified in this part of IEC 61000 to assess the effect that conducted disturbing signals, induced by electromagnetic radiation, have on the equipment concerned. The simulation and measurement of these conducted disturbances are not adequately exact for the quantitative determination of effects. The test methods defined specified are structured for the primary objective of establishing adequate repeatability of results at various facilities for quantitative analysis of effects.

The object of this document is to establish a common reference for evaluating the functional immunity of electrical and electronic equipment when subjected to conducted disturbances induced by RF fields. The test method in this document describes a consistent method to assess the immunity of an equipment or system against a defined specified phenomenon.

NOTE 3 As described in IEC Guide 107, this document is a basic EMC publication for use by product committees of the IEC. As also stated in Guide 107, the IEC product committees are responsible for determining whether this immunity test standard should be applied or not, and if applied, they are responsible for determining the appropriate test levels and performance criteria.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050 (all parts), International Electrotechnical Vocabulary (IEV) (available at http://www.electropedia.org)

CISPR 16-1-2, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Coupling devices for conducted disturbance measurements



SVENSK STANDARD SS-EN IEC 61000-4-6, utg 5:2024

Fastställd 2024-03-20

Sida 1 (86) Ansvarig kommitté SEK TK EMC

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Elektromagnetisk kompatibilitet (EMC) – Del 4-6: Mät- och provningsmetoder – Immunitet mot ledningsbundna störningar orsakade av radiofrekventa fält

Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

Som svensk standard gäller europastandarden EN IEC 61000-4-6:2023. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 61000-4-6:2023.

Nationellt förord

Europastandarden EN IEC 61000-4-6:2023

består av:

- europastandardens ikraftsättningsdokument, utarbetat inom CENELEC

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 61000-4-6, utg 4:2014 med eventuella tillägg, ändringar och rättelser, gäller ej fr o m 2026-07-11.

ICS 33.100.20

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284 164 29 Kista Tel 08-444 14 00 www.elstandard.se

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN IEC 61000-4-6

July 2023

ICS 33.100.20

Supersedes EN 61000-4-6:2014; EN 61000-4-6:2014/AC:2015

English Version

Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields
(IEC 61000-4-6:2023)

Compatibilité électromagnétique (CEM) - Partie 4-6: Techniques d'essai et de mesure - Immunité aux perturbations conduites, induites par les champs aux fréquences radioélectriques (IEC 61000-4-6:2023) Elektromagnetische Verträglichkeit (EMV) - Teil 4-6: Prüfund Messverfahren - Störfestigkeit gegen leitungsgeführte Störgrößen, induziert durch hochfrequente Felder (IEC 61000-4-6:2023)

This European Standard was approved by CENELEC on 2023-07-11. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2023 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. EN IEC 61000-4-6:2023 E

European foreword

The text of document 77B/863/FDIS, future edition 5 of IEC 61000-4-6, prepared by SC 77B "High frequency phenomena" of IEC/TC 77 "Electromagnetic compatibility" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61000-4-6:2023.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2024-04-11 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2026-07-11 document have to be withdrawn

This document supersedes EN 61000-4-6:2014 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a standardization request addressed to CENELEC by the European Commission. The Standing Committee of the EFTA States subsequently approves these requests for its Member States.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 61000-4-6:2023 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 61000-4-3 NOTE Approved as EN IEC 61000-4-3

CISPR 16-1-4 NOTE Approved as EN IEC 55016-1-4

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
CISPR 16-1-2	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-2: Radio disturbance and immunity measuring apparatus - Coupling devices for conducted disturbance measurements	EN 55016-1-2	-



Edition 5.0 2023-06

INTERNATIONAL STANDARD



BASIC EMC PUBLICATION

Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 33.100.20 ISBN 978-2-8322-7076-9

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

Ε(DREWO	JRD	6
IN	TRODU	JCTION	8
1	Scop	De	g
2	•	native references	
3		ns and definitions	
4		eral	
5		levels	
6		equipment and level adjustment procedure	
	6.1 6.2	Test generator Coupling and decoupling devices	
	6.2.1		
	6.2.1		
	6.2.3		
	6.2.4		
	6.2.5	•	
	6.3	Verification of the common-mode impedance at the EUT port of coupling and	
	0.0	decoupling devices	22
	6.3.1	1 General	22
	6.3.2	Insertion loss of the 150 Ω to 50 Ω adapters	23
	6.4	Setting of the test generator	25
	6.4.1	1 General	25
	6.4.2	Setting of the output level at the EUT port of the coupling device	25
7	Test	setup and injection methods	27
	7.1	Test setup	27
	7.2	EUT comprising a single unit	28
	7.3	EUT comprising several units	30
	7.4	Rules for selecting injection methods and test points	31
	7.4.1	1 General	31
	7.4.2	2 Injection method	31
	7.4.3		
	7.5	CDN injection application	32
	7.6	Clamp injection application	34
	7.7	Direct injection application	36
8	Test	procedure	36
9	Evalı	uation of the test results	37
10	Test	report	38
Ar	nex A ((normative) EM and decoupling clamps	39
	A.1	EM clamps	39
	A.1.1	·	
	A.1.2	2 Specification of EM clamps	39
	A.2	EM clamp characterization	41
	A.2.1	·	
	A.2.2	·	
	A.3	Decoupling clamp characterization	47
	A.3.1	1 General	47
	A.3.2	2 Specification of decoupling clamps	47

A.3.3	Impedance	47
A.3.4	Decoupling factor	48
Annex B (informative) Selection criteria for the frequency range of application	50
Annex C (informative) Guidelines for selecting test levels	52
Annex D (informative) Information on coupling and decoupling networks	53
D.1	Basic features of the coupling and decoupling networks	53
D.2	Examples of coupling and decoupling networks	
Annex E (informative) Information for the test generator specification	58
Annex F (informative) Test setup for large EUTs	59
F.1	General	59
F.2	Test setup for large EUTs	59
Annex G (informative) Measurement uncertainty of the voltage test level	62
G.1	General	62
G.2	General symbols	62
G.3	Uncertainty budgets for test methods	62
G.3.1	Definition of the measurand	62
G.3.2	MU contributors of the measurand	63
G.3.3		
G.4	Expression of the calculated measurement uncertainty and its application	
Annex H (informative) Testing with multiple signals	
H.1	General	
H.2	Intermodulation	
H.3	Power requirements	
H.4	Level-setting requirements	
H.5	Linearity check and harmonics checks of the test generator	
H.6	EUT performance criteria with multiple signals	
	nformative) Port-to-port injection	
I.1	General	
1.2	Test setup for injection on identical ports	
1.2.1	Selection of ports	
1.2.2	Procedure for port-to-port injection	
	informative) Amplifier compression and non-linearity	
•		
J.1	Objective of limiting amplifier distortion	
J.2	Possible problems caused by harmonics and saturation	
J.3	Limiting the harmonic content in the disturbance signal	
J.4	Effect of linearity characteristic on the immunity test	
J.4.1	General	
J.4.2	Evaluation of the amplifier linearity characteristic	
Bibliograp	hy	83
	- Diagram showing EM fields near the EUT due to common-mode currents on	12
	- Schematic setup for immunity test to RF conducted disturbances	
•	- Example of unmodulated and modulated RF signal	
_	- Example of unmodulated and modulated KF signal	
•	-	
Figure 5 -	- Principle of coupling and decoupling – Symbols used for the indicated setup	17

Figure 6 – Principle of coupling and decoupling – Principle of direct injection to screened cables	17
Figure 7 – Principle of coupling and decoupling – Principle of coupling to unscreened cables according to the CDN method	18
Figure 8 – Principle of coupling and decoupling – Principle of decoupling	18
Figure 9 – Example of circuit for evaluating the transmission loss of the current clamp level-setting	21
Figure 10 – Example of circuit for level-setting setup in a 150 Ω test jig	21
Figure 11 – Example of the setup geometry to verify the impedance characteristics of the coupling and decoupling devices	23
Figure 12 – Setup principle to verify $Z_{ extsf{Ce}}$ of the coupling and decoupling device	24
Figure 13 – Setup principle for measuring the insertion loss of two 150 Ω to 50 Ω adapters	24
Figure 14 – Circuit and construction of the 150 Ω to 50 Ω adapter	24
Figure 15 – Definition of a common-mode point for unscreened and screened cables	26
Figure 16 – Setup for level-setting at the EUT port of the coupling/decoupling devices	27
Figure 17 – Example of test setup with a single unit EUT with only one CDN for injection (top view)	28
Figure 18 – Example of test setup with a single unit EUT (top view) using multiple CDNs	29
Figure 19 – Example of a test setup with a multi-unit EUT (top view)	30
Figure 20 – Rules for selecting the injection method	31
Figure 21 – Immunity test for two-port EUT (when only one CDN can be used)	34
Figure 22 – General principle of a test setup using clamp injection devices	35
Figure 23 – Example of the test unit locations on the ground plane when using injection clamps (top view)	36
Figure A.1 – Example: Construction details of the EM clamp	40
Figure A.2 – Example: Concept of the EM clamp	41
Figure A.3 – Dimension of a reference plane	42
Figure A.4 – Test jig	42
Figure A.5 – Test jig with inserted clamp	42
Figure A.6 – Impedance / decoupling factor measurement setup	43
Figure A.7 – Typical examples for clamp impedance, three typical clamps	45
Figure A.8 – Typical examples for decoupling factors, three typical clamps	45
Figure A.9 – Normalization setup for coupling factor measurement	46
Figure A.10 – S_{21} coupling factor measurement setup	46
Figure A.11 – Typical examples for coupling factor, three typical clamps	47
Figure A.12 – Decoupling clamp characterization measurement setup	48
Figure A.13 – Typical examples for the decoupling clamp impedance	48
Figure A.14 – Typical examples for decoupling factors	49
Figure B.1 – Start frequency as function of cable length and equipment size	51
Figure D.1 – Example of a simplified diagram for the circuit of CDN-S1 used with screened cables (see 6.2.2.5)	54
Figure D.2 – Example of simplified diagram for the circuit of CDN-M1, CDN-M2 and CDN-M3 used with unscreened supply (mains) lines (see 6.2.2.2)	54

Figure D.3 – Example of a simplified diagram for the circuit of CDN-AF2 used with unscreened unbalanced lines (see 6.2.2.4)	55
Figure D.4 – Example of a simplified diagram for the circuit of CDN-T2, used with an unscreened balanced pair (see 6.2.2.3)	55
Figure D.5 – Example of a simplified diagram of the circuit of CDN-T4 used with unscreened balanced pairs (see 6.2.2.3)	56
Figure D.6 – Example of a simplified diagram of the circuit of CDN AF8 used with unscreened unbalanced lines (see 6.2.2.4)	56
Figure D.7 – Example of a simplified diagram of the circuit of CDN-T8 used with unscreened balanced pairs (see 6.2.2.3)	57
Figure F.1 – Example of large EUT test setup with elevated horizontal reference ground plane	60
Figure F.2 – Example of large EUT test setup with vertical reference ground plane	61
Figure G.1 – Example of influences upon voltage test level using CDN	63
Figure G.2 – Example of influences upon voltage test level using EM clamp	63
Figure G.3 – Example of influences upon voltage test level using current clamp	63
Figure G.4 – Example of influences upon voltage test level using direct injection	64
Figure G.5 – Circuit for level-setting setup of CDN	65
Figure H.1 – Test frequencies $f_{f 1}$ and $f_{f 2}$ and intermodulation frequencies of the second and third order	73
Figure I.1 – Example of setup, port-to-port injection	77
Figure J.1 – Amplifier linearity measurement setup	80
Figure J.2 – Linearity characteristic	81
Figure J.3 – Measurement setup for modulation depth	81
Figure J.4 – Spectrum of AM modulated signal	82
Table 1 – Test levels	14
Table 2 – Characteristics of the test generator	15
Table 3 – Main parameter of the combination of the coupling and decoupling device	16
Table 4 – Usage of CDNs	19
Table B.1 – Main parameter of the combination of the coupling and decoupling device when the frequency range of the test is extended above 80 MHz	50
Table E.1 – Required power amplifier output power to obtain a test level of 10 V	58
Table G.1 – CDN level-setting process	65
Table G.2 – CDN test process	65
Table G.3 – EM clamp level-setting process	67
Table G.4 – EM clamp test process	68
Table G.5 – Current clamp level-setting process	69
Table G.6 – Current clamp test process	69
Table G.7 – Direct injection level-setting process	70
Table G.8 – Direct injection test process	71

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ELECTROMAGNETIC COMPATIBILITY (EMC) -

Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61000-4-6 has been prepared by subcommittee 77B: High frequency phenomena, of IEC technical committee 77: Electromagnetic compatibility. It is an International Standard.

It forms Part 4-6 of IEC 61000. It has the status of a basic EMC publication in accordance with IEC Guide 107.

This fifth edition cancels and replaces the fourth edition published in 2013. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) selection of injection devices revised;
- b) need of AE impedance check for clamp injection removed and Annex H deleted;
- c) saturation check revised;
- d) new Annex H on testing with multiple signals;

e) level-setting only with feedback loop.

The text of this International Standard is based on the following documents:

Draft	Report on voting
77B/863/FDIS	77B/865/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 61000 series, published under the general title *Electromagnetic* compatibility (EMC), can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 61000 is published in separate parts according to the following structure:

Part 1: General

General considerations (introduction, fundamental principles)

Definitions, terminology

Part 2: Environment

Description of the environment

Classification of the environment

Compatibility levels

Part 3: Limits

Emission limits

Immunity limits (in so far as they do not fall under the responsibility of the product committees)

Part 4: Testing and measurement techniques

Measurement techniques

Testing techniques

Part 5: Installation and mitigation guidelines

Installation guidelines

Mitigation methods and devices

Part 6: Generic standards

Part 9: Miscellaneous

Each part is further subdivided into several parts, published either as international standards or as technical specifications or technical reports, some of which have already been published as sections. Others will be published with the part number followed by a dash and a second number identifying the subdivision (example: IEC 61000-6-1).

This part is an international standard which gives immunity requirements and test procedures related to conducted disturbances induced by radio-frequency fields.

ELECTROMAGNETIC COMPATIBILITY (EMC) -

Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields

1 Scope

This part of IEC 61000 relates to the conducted immunity requirements of electrical and electronic equipment to electromagnetic disturbances coming from intended radio-frequency (RF) transmitters in the frequency range 150 kHz up to 80 MHz.

NOTE 1 Product committees might decide to use the methods described in this document also for frequencies up to 230 MHz (see Annex B) although the methods and test instrumentation are intended to be used in the frequency range up to 80 MHz.

Equipment not having at least one conducting wire or cable (such as mains supply, signal line or earth connection) which can couple the equipment to the disturbing RF fields is excluded from the scope of this document.

NOTE 2 Test methods are specified in this part of IEC 61000 to assess the effect that conducted disturbing signals, induced by electromagnetic radiation, have on the equipment concerned. The simulation and measurement of these conducted disturbances are not adequately exact for the quantitative determination of effects. The test methods specified are structured for the primary objective of establishing adequate repeatability of results at various facilities for quantitative analysis of effects.

The object of this document is to establish a common reference for evaluating the functional immunity of electrical and electronic equipment when subjected to conducted disturbances induced by RF fields. The test method in this document describes a consistent method to assess the immunity of an equipment or system against a specified phenomenon.

NOTE 3 As described in IEC Guide 107, this document is a basic EMC publication for use by product committees of the IEC. As also stated in Guide 107, the IEC product committees are responsible for determining whether this immunity test standard should be applied or not, and if applied, they are responsible for determining the appropriate test levels and performance criteria.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 16-1-2, Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-2: Radio disturbance and immunity measuring apparatus – Coupling devices for conducted disturbance measurements