

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

EMC – Utrustning och metoder för mätning av radiostörningar och immunitet – Del 4-4: Onoggrannhet vid EMC-mätningar och gränsvärdesmodellering – Klagomålsstatistik och en modell för beräkning av gränsvärden för skydd av radiotjänster

*Specification for radio disturbance and immunity measuring apparatus and methods –
Part 4-4: Uncertainties, statistics and limit modelling –
Statistics of complaints and a model for the calculation of limits for the protection of radio services
(CISPR/TR 16-4-4:2020)*

ISSN 1651-1417

ICS 33.100.10; 33.100.20

Upplysningar om **sakinnehållet** i rapporten lämnas av
SEK Svensk Elstandard.
Postadress: Box 1284, 164 29 KISTA
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: www.elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

FINAL VERSION



INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**Specification for radio disturbance and immunity measuring apparatus and methods –
Part 4-4: Uncertainties, statistics and limit modelling – Statistics of complaints and a model for the calculation of limits for the protection of radio services**

CONTENTS

FOREWORD.....	7
1 Scope.....	9
2 Normative references	9
3 Terms and definitions	9
3.1 Terms and definitions	9
3.2 Symbols and abbreviated terms.....	10
4 Statistics of complaints and sources of interference	11
4.1 Introduction and history	11
4.2 Relationship between radio frequency interference and complaints	11
4.2.1 Radio frequency interference to a fixed radio receiver	11
4.2.2 Radio frequency interference to a mobile radio receiver	11
4.2.3 Consequences of the move from analogue to digital radio systems.....	11
4.3 Towards the loss of a precious indicator: interference complaints.....	12
4.4 CISPR recommendations for collation of statistical data on interference complaints and classification of interference sources	12
4.5 Forms for statistics of interference complaints.....	13
5 A model for the calculation of limits	18
5.1 Introduction	18
5.1.1 Generation of EM disturbances.....	18
5.1.2 Immunity from EM disturbances.....	18
5.1.3 Planning a radio service	18
5.2 Probability of interference.....	19
5.2.1 Derivation of probability of interference	19
5.3 Circumstances of interferences	20
5.3.1 Close coupling and remote coupling	21
5.3.2 Measuring methods	22
5.3.3 Disturbance signal waveforms and associated spectra	24
5.3.4 Characteristics of interfered radio services	25
5.3.5 Operational aspects.....	26
5.3.6 Criteria for the determination of limits	27
5.4 A mathematical basis for the calculation of CISPR limits	31
5.4.1 Generation of EM disturbances (source of disturbance).....	31
5.4.2 Immunity from EM disturbances (victim receiver).....	32
5.5 Application of the mathematical basis.....	32
5.5.1 Radiation coupling	32
5.5.2 Wire-line coupling.....	34
5.6 Another suitable method for equipment in the frequency range 150 kHz to 1 GHz.....	42
5.6.1 Introduction	42
5.6.2 Derivation of limits.....	42
5.6.3 Application of limits	47
5.6.4 Overview of proposals for determination of disturbance limits for a given type of equipment.....	47
5.6.5 Rationale for determination of CISPR limits in the frequency range below 30 MHz.....	48

5.6.6	Model for limits for the magnetic component of the disturbance field strength for the protection of radio reception in the range below 30 MHz.....	54
5.7	Rational for determination of CISPR limits in the frequency range above 1 GHz.....	57
5.7.1	Introduction	57
5.7.2	Consideration and estimated values of μ_{P1} to μ_{P7}	59
5.7.3	Equivalent EMC environment below and above 1 GHz.....	64
5.7.4	Overview on parameters of radio communication services operating in the frequency range above 1 GHz and up to 16 GHz with effect to electromagnetic compatibility.....	65
Annex A	Excerpt from CISPR Report No. 31 Values of mains decoupling factor in the range 0,1 MHz to 200 MHz	69
Annex B (informative)	Conversion of H-field limits below 30 MHz for measurement distances	74
Annex C (informative)	Model for estimation of radiation from photovoltaic (PV) power generating systems.....	86
Annex D (informative)	Model for the estimation of radiation from in-house extra low voltage (ELV) lighting installations	119
Bibliography	133
Figure 1a	– Standard form for statistics on interference complaints recommended for radio services with analogue modulation and fixed or stationary radio reception	13
Figure 1b	– Standard form for statistics on interference complaints recommended for radio services with analogue modulation and mobile or portable radio reception	14
Figure 1c	– Standard form for statistics on interference complaints recommended for radio services with digital modulation and fixed or stationary radio reception	15
Figure 1d	– Standard form for statistics on interference complaints recommended for radio services with digital modulation and mobile or portable radio reception	16
Figure 1	– Standard forms for statistics on interference complaints.....	16
Figure 2	– Model for remote coupling situation derived disturbance field strength e_{ir} at receiving distance r	28
Figure 3	– Model for close coupling situations.....	30
Figure 4	– Example of conversion factors – field strength / common-mode voltage (in dB) – at feed point, found in practice	39
Figure 5	– Example of conversion factors – field strength generated by differential-mode voltage – at feed point, found in practice	40
Figure 6	– Example of conversion factors – field strength generated by differential-mode voltage – outside buildings and electrical substations, found in practice	41
Figure 7	– Example of conversion factors – field strength generated by differential-mode voltage – inside buildings, found in practice	42
Figure 8	– horizontal plane radiation pattern on a small purely magnetic antenna	50
Figure 9	– typical source of magnetic field disturbance	52
Figure 10	– Model for magnetic field limit at measuring equipment	55
Figure A.1	– Mains decoupling coefficient as measured by various authors	71
Figure A.2	– Median and minimum values of mains decoupling factor for the range 0,1 MHz to 200 MHz	72

Figure A.3 – Typical distributions of deviations from median value of decoupling factor as indicated in Figure A.2 72

Figure A.4 – Measurement of the mains decoupling factor 73

Figure B.1 – Commercial tool model for H-field conversion 74

Figure B.2 – Commercial tool model for the application of image theory..... 75

Figure B.3 – Photos of OATS measurement setup 76

Figure B.4 – Comparative simulation result with ground plane and with image theory 76

Figure B.5 – Comparison between the simulated conversion factors and the measurement results 77

Figure B.6 – Conversion factor C_{3_min} 78

Figure B.7 – Conversion factor C_{10_min} 79

Figure B.8 – Conversion factor C_{10-3_min} 81

Figure B.9 – Recommended conversion factor CF_{30m} to 3m 83

Figure B.10 – Recommended conversion factor CF_{30m} to 10m 84

Figure B.11 – Recommended conversion factor CF_{10m} to 3m 85

Figure C.1 – Schematic overview of the considered model influence factors 87

Figure C.2 – Schematic representation of probability of existence of PV generator groups in the field 90

Figure C.3 – Schematic representation of mean value \bar{C}_{PV} and variance σ_{CPV} 90

Figure C.4 – General model for coupling of CM disturbances of a GCPC to an attached photovoltaic power generating system (PV generator) 91

Figure C.5 – Geometric representation of a PV generator with 18 modules 93

Figure C.6 – Field strength determination by maximization (height scan) along a red line 94

Figure C.7 – Geometrical representation of Group A PV generators..... 101

Figure C.8 – Combined coupling factor $C_{PV_{GroupA\ sim}}$ for Group A PV generators ($r = 10m$)..... 101

Figure C.9 – Geometrical representation of Group B PV generators..... 102

Figure C.10 – Combined coupling factor $C_{PV_{GroupB\ sim}}$ for Group B PV generators ($r = 10 m$) 102

Figure C.11 – Geometrical representation of Group C PV generators..... 103

Figure C.12 – Combined coupling factor $C_{PV_{GroupC\ sim}}$ for Group C PV generators ($r = 10 m$)..... 103

Figure C.13 – Geometrical representation of Group D PV generators..... 104

Figure C.14 – Combined coupling factor $C_{PV_{GroupD\ sim}}$ for Group D PV generators ($r = 10 m$)..... 104

Figure C.15 – Measurement setup 106

Figure C.16 – Antenna orientations 106

Figure C.17 – Coupling factor $C_{PV_{GroupA\ meas}}$ for Group A PV generators..... 107

Figure C.18 – Coupling factor $C_{PV_{GroupC\ meas}}$ for Group C PV generators 108

Figure C.19 – Coupling factor $C_{PV_{GroupD\ meas}}$ for Group D PV generators 108

Figure C.20 – Ratio of registered PV power generating systems in Germany	110
Figure C.21 – Ratio of registered PV power generating systems in Sweden	111
Figure C.22 – Simulation results m_{TC} (test case)	113
Figure C.23 – Simulation results m_L (use case)	114
Figure C.24 – Overview of the calculated U_{TC} Limit values for radio services between 150 kHz and 30 MHz at a distance of $d = 10$ m	118
Figure D.1 – Application of ELV lamps	120
Figure D.2 – Typical components and wiring for an ELV lamp connected to a power source and the associated lumped-circuit model of the ELV part	121
Figure D.3 – Coupling scenarios	123
Figure D.4 – Two wire scenario	123
Figure D.5 – Field strength derived by Biot-Savart-law applied to a differential mode current in comparison with the values in CISPR 15:2018, Table 9 (3 m) converted to 10 m	125
Figure D.6 – Principal model used for the simulations	126
Figure D.7 – Electric field distribution (at 10 MHz) on a vertical plane at a distance of 10 m from the vertical two wire system	127
Figure D.8 – Coupling factor result for 3 different scenarios	128
Figure D.9 – Overview of the calculated U_{Limit} values for radio services between 150 kHz and 30 MHz	132
Table 1 – Classification of sources of radio frequency interference and other causes of complaint	17
Table 2 – Guidance survey of RFI measuring methods	24
Table 3 – Tabulation of the method of determining limits for equipment in the frequency range 0,150 MHz to 960 MHz	44
Table 4 – Calculation of permissible limits for disturbances at about 1 800 MHz from existing CISPR limits in the frequency range of 900 MHz	65
Table 5 – List of radio services, typical parameters, and influence factors	67
Table B.1 – Conversion factor C_{3_min}	78
Table B.2 – Conversion factor C_{10_min}	80
Table B.3 – Conversion factor C_{10-3_min}	82
Table B.4 – Recommended conversion factor $CF_{30m\ to\ 3m}$	83
Table B.5 – Recommended conversion factor $CF_{30m\ to\ 10m}$	84
Table B.6 – Recommended conversion factor $CF_{10m\ to\ 3m}$	85
Table C.1 – Coupling factors $C_{PV_{sim}}$	105
Table C.2 – Coupling factors $C_{PV_{meas}}$ and calibration factors	109
Table C.3 – Overview coupling factors C_{PV_i}	109
Table C.4 – Estimation of ρ_i	111
Table C.5 – Mismatch loss values m_L and m_{TC} determined by measurement and simulation	114

Table C.6 – Calculation of U_{TC} Limit for radio services between 150 kHz and 30 MHz
at a distance of $d = 10$ m 116

Table D.1 – Calculation of U_{Limit} for radio services between 150 kHz and 30 MHz..... 131

INTERNATIONAL ELECTROTECHNICAL COMMISSION
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY
MEASURING APPARATUS AND METHODS –**

**Part 4-4: Uncertainties, statistics and limit modelling –
Statistics of complaints and a model for the calculation of limits
for the protection of radio services**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER

This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of CISPR 16-4-4 bears the edition number 2.2. It consists of the second edition (2007-07) [documents CISPR/H/147/DTR and CISPR/H/153/RVC], its amendment 1 (2017-06) [documents CIS/H/313/DTR and CIS/H/319/RVC] and its amendment 2 (2020-04) [documents CIS/H/402/DTR and CIS/H/407A/RVDTR]. The technical content is identical to the base edition and its amendments.

This Final version does not show where the technical content is modified by amendments 1 and 2. A separate Redline version with all changes highlighted is available in this publication.

The main task of IEC technical committees is to prepare International Standards. However, a technical committee may propose the publication of a technical report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

This second edition of CISPR 16-4-4, which is a technical report, has been prepared by CISPR subcommittee H: Limits for the protection of radio services.

This second edition of CISPR 16-4-4 contains two thoroughly updated Clauses 4 and 5, compared with its first edition. It also contains, in its new Annex A, values of the classical CISPR mains decoupling factor which were determined by measurements in real LV AC mains grids in the 1960s. It is deemed that these mains decoupling factors are still valid and representative also for modern and well maintained LV AC mains grids around the world.

The information in Clause 4 – Statistics of complaints and sources of interference – was accomplished by the history and evolution of the CISPR statistics on complaints about radio frequency interference (RFI) and by background information on evolution in radio-based communication technologies. Furthermore, the forms for collation of actual RFI cases were detailed and structured in a way allowing for more qualified assessment and evaluation of compiled annual data in regard to the interference situation, as e.g. fixed or mobile radio reception, or analogue or digital modulation of the interfered with radio service or application concerned.

The information in Clause 5 – A model for the calculation of limits – was accomplished in several ways. The model itself was accomplished in respect of the remote coupling situation as well as the close coupling one. Further supplements of this model were incorporated regarding certain aspects of the coupling path via induction and wave propagation (radiation) of classical telecommunication networks. Furthermore, the calculation model on statistics and probability underwent revision and was brought in line with a more modern mathematical approach. Eventually the present model was extended for a possible determination of CISPR limits in the frequency range above 1 GHz.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 4-4: Uncertainties, statistics and limit modelling – Statistics of complaints and a model for the calculation of limits for the protection of radio services

1 Scope

This part of CISPR 16 contains a recommendation on how to deal with statistics of radio interference complaints. Furthermore it describes the calculation of limits for disturbance field strength and voltage for the measurement on a test site based on models for the distribution of disturbances by radiated and conducted coupling, respectively.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-161, *International Electrotechnical Vocabulary (IEV) – Part 161: Electromagnetic compatibility* (available at <http://www.electropedia.org>)

CISPR 11, *Industrial, scientific and medical equipment – Radio-frequency disturbance characteristics – Limits and methods of measurement*

CISPR 16-4-3, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-3: Uncertainties, statistics and limit modelling – Statistical considerations in the determination of EMC compliance of mass-produced products*

CISPR 15:2018, *Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment*