



Edition 3.1 2024-05 CONSOLIDATED VERSION

INTERNATIONAL STANDARD



Power cables with extruded insulation and their accessories for rated voltages from 1 kV ($U_m = 1,2 \text{ kV}$) up to 30 kV ($U_m = 36 \text{ kV}$) – Part 2: Cables for rated voltages from 6 kV ($U_m = 7,2 \text{ kV}$) up to 30 kV ($U_m = 36 \text{ kV}$)

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ICS 29.060.20

ISBN 978-2-8322-9033-0

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOF	REWORD)		11			
1	Scope			13			
2	Normati	ve referenc	es	13			
3	Terms and definitions						
	3.1	Definitions	of dimensional values (thicknesses, cross-sections, etc.)	15			
	3.2		concerning the tests				
4	Voltage	designation	ns and materials	16			
	4.1	Rated volt	ages	16			
	4.2	Insulating	compounds	17			
	4.3	Sheathing	compounds	18			
5	Conduc	tors		19			
6	Insulatio	on		19			
	6.1	Material		19			
	6.2	Insulation	thickness	19			
7	Screeni	ng		20			
	7.1	General					
	7.2	Conductor	screen	20			
	7.3		screen				
8	Assemb	ly of three-	core cables, inner coverings and fillers	21			
	8.1						
	8.2		rings and fillers				
		8.2.1	Construction				
		8.2.2	Material				
		8.2.3	Thickness of extruded inner covering				
	0.0	8.2.4 Cables her	Thickness of lapped inner covering				
	8.3 8.4		ving a collective metal layer (see Clause 9) ving a metal layer over each individual core (see Clause 10)				
9			gle-core and three-core cables				
10		-					
10			on				
	10.1 10.2		ents				
	10.2	•	ens not associated with semi-conducting layers				
11			or				
••	11.1		on				
	11.1		ents				
	11.3	•	٦				
12		• •					
	12.1	Lead shea	th	23			
	12.2		al sheaths				
13							
	13.1	Types of n	netal armour	24			
	13.2	• •					
	13.3	Application	n of armour	24			
		13.3.1	Single-core cables	24			
		13.3.2	Three-core cables	24			

IEC 60502-2:2014+AMD1:2024 CSV - 3 - © IEC 2024

I

		13.3.3	Separation sheath	24
		13.3.4	Lapped bedding under armour for lead sheathed cables	25
	13.4	Dimensior	ns of the armour wires, and armour tapes and armour strips	25
	13.5	Correlatio	n between cable diameters and armour dimensions	25
	13.6	Round or	flat wire armour	26
	13.7	Double ta	pe armour	26
	13.8	Interlock r	netal tape armour	27
14	Overshe	eath		27
	14.1	General		27
	14.2	Material		27
	14.3	Thickness		28
15	Test co	nditions		28
	15.1	Ambient te	emperature	28
	15.2		y and waveform of power frequency test voltages	
	15.3		of impulse test voltages	
	15.4		ation of the cable conductor temperature	
16	-			
10				
	16.1			
	16.2		resistance of conductors	
	16.3		charge test	
	16.4	•	est	
		16.4.1	General	
		16.4.2	Test procedure for single-core cables	
		16.4.3	Test procedure for three-core cables	
		16.4.4	Test voltage	
		16.4.5	Requirement	
	16.5		test on oversheath of the cable	
17	Sample	tests		30
	17.1	General		30
	17.2	Frequency	y of sample tests	31
		17.2.1	Conductor examination and check of dimensions	31
		17.2.2	Electrical and physical tests	31
	17.3	Repetition	of tests	31
	17.4	Conductor	r examination	31
	17.5		nent of thickness of insulation and of non-metal sheaths extruded separation sheaths, but excluding inner extruded	
)	31
		17.5.1	General	31
		17.5.2	Requirements for the insulation	31
		17.5.3	Requirements for the non-metal sheaths	32
	17.6	Measurem	nent of thickness of lead sheath	
		17.6.1	General	
		17.6.2	Strip method	
		17.6.3	king method	
	17.7		nent of armour wires, and tapes and armour strips	
		17.7.1	Measurement on wires	
		17.7.2	Measurement on tapes and armour strips	
		17.7.3	Requirements	
		· · · · • •		

	17.8	Measuren	nent of external diameter	33
	17.9	Voltage te	est for 4 h	33
		17.9.1	Sampling	33
		17.9.2	Procedure	33
		17.9.3	Test voltages	33
		17.9.4	Requirements	34
	17.10		st for EPR, HEPR and XLPE insulations and elastomeric	34
		17.10.1	Procedure	34
		17.10.2	Requirements	34
	17.11	Bending t	est on interlock armour cable followed by examination	34
18	Type te	sts, electric	cal	34
	18.1	General		34
	18.2		aving conductor screens and insulation screens	
	10.2	18.2.1	General	
		18.2.2	Sequence of tests	
		18.2.3	Special provisions	
		18.2.4	Bending test	
		18.2.4	-	
			Partial discharge test	30
		18.2.6	Tan δ measurement for cables of rated voltage 6/10 (12) kV and above	36
		18.2.7	Heating cycle test	
		18.2.8	Impulse test followed by a voltage test	
		18.2.9	Voltage test for 4 h	
		18.2.9	-	
	18.3		Resistivity of semi-conducting screens	
	10.3		rated voltage 3,6/6 (7,2) kV having unscreened insulation	
		18.3.1	General	
		18.3.2	Insulation resistance measurement at ambient temperature	38
		18.3.3	Insulation resistance measurement at maximum conductor temperature	
		18.3.4	Voltage test for 4 h	
		18.3.5	Impulse test	
19	Type te	sts, non-ele	ectrical	40
	19.1	General		40
	19.2	Measuren	nent of thickness of insulation	40
		19.2.1	Sampling	40
		19.2.2	Procedure	40
		19.2.3	Requirements	40
	19.3		nent of thickness of non-metal sheaths (including extruded n sheaths, but excluding inner coverings)	40
		19.3.1	Sampling	40
		19.3.2	Procedure	40
		19.3.3	Requirements	40
	19.4	Measuren	nent of thickness of lead sheath	
		19.4.1	Sampling	
		19.4.2	Procedure	
		19.4.3	Requirements	
	19.5		determining the mechanical properties of insulation before and	
			ng	40

IEC 60502-2:2014+AMD1:2024 CSV - 5 -© IEC 2024

I

	19.5.1	Sampling			
	19.5.2	Ageing treatments	41		
	19.5.3	Conditioning and mechanical tests	41		
	19.5.4	Requirements	41		
19.6		determining the mechanical properties of non-metal sheaths d after ageing	41		
	19.6.1	Sampling	41		
	19.6.2	Ageing treatments	41		
	19.6.3	Conditioning and mechanical tests	41		
	19.6.4	Requirements	41		
19.7	Additional	ageing test on pieces of completed cables	41		
	19.7.1	General	41		
	19.7.2	Sampling	41		
	19.7.3	Ageing treatment	41		
	19.7.4	Mechanical tests	42		
	19.7.5	Requirements	42		
19.8	Loss of m	ass test on PVC sheaths of type ST ₂	42		
	19.8.1	Procedure			
	19.8.2	Requirements			
19.9	Pressure	test at high temperature on insulations and non-metal sheaths			
	19.9.1	Procedure	42		
	19.9.2	Requirements	42		
19.10	Test on PVC insulation,-and PVC sheaths and halogen free sheaths at				
	low tempe	eratures	42		
	19.10.1	Procedure	42		
	19.10.2	Requirements	42		
19.11		esistance of PVC insulation and sheaths to cracking (heat shock	42		
	19.11.1	Procedure	42		
	19.11.2	Requirements	42		
19.12	Ozone res	sistance test for EPR and HEPR insulations	43		
	19.12.1	Procedure	43		
	19.12.2	Requirements	43		
19.13		st for EPR, HEPR and XLPE insulations and elastomeric	10		
10 14		sion test for elastomeric sheaths			
19.14	19.14.1	Procedure			
	19.14.1	Requirements			
19.15		sorption test on insulation			
19.15	19.15.1	Procedure			
	19.15.1	Requirements			
19.16		read test on single cables			
19.16		er fire conditions			
19.10	19.16.1				
	19.16.1 19.16.2	General			
	19.16.2	Flame spread test for single cables			
	19.16.3 19.16.4	Flame spread test for bunched cables Measurement of smoke density of cables burning under	44		
	19.10.4	defined conditions	44		

 19.16.5 Determination of acidity (by pH measurement) and conductivity of gases evolved during combustion of the n metallic materials in the cable. 19.16.6 Fire performance tests on halogen free oversheath mater ST₈. 19.16.7 Fire performance tests on halogen free oversheath mater ST₁₂. 19.16.8 Measurement of halogen content of gases evolved during combustion of the non-metallic materials in the cable. 19.17 Measurement of carbon black content of black PE oversheaths	44 rial 44
 ST₈ 19.16.7 Fire performance tests on halogen free oversheath mater ST₁₂ 19.16.8 Measurement of halogen content of gases evolved during combustion of the non-metallic materials in the cable 19.17 Measurement of carbon black content of black PE oversheaths 19.17 Procedure 19.17.2 Requirements 19.18 Shrinkage test for XLPE insulation 19.18.1 Procedure 19.18.2 Requirements 19.19 Thermal stability test for PVC insulation 19.19.1 Procedure 19.20.2 Requirements 19.20.2 Requirements 19.21 Determination of the elastic modulus of HEPR insulation 19.21.1 Procedure 19.22.2 Requirements 19.22.2 Requirements 	
 19.16.7 Fire performance tests on halogen free oversheath mater ST₁₂ 19.16.8 Measurement of halogen content of gases evolved during combustion of the non-metallic materials in the cable 19.17 Measurement of carbon black content of black PE oversheaths 19.17 Procedure	
 19.16.8 Measurement of halogen content of gases evolved during combustion of the non-metallic materials in the cable	
 19.17 Measurement of carbon black content of black PE oversheaths	g
 19.17.1 Procedure	
 19.17.2 Requirements	
 19.18 Shrinkage test for XLPE insulation	
 19.18.1 Procedure	
 19.18.2 Requirements 19.19 Thermal stability test for PVC insulation 19.19.1 Procedure 19.19.2 Requirements 19.20 Determination of hardness of HEPR insulation 19.20.1 Procedure 19.20.2 Requirements 19.21 Determination of the elastic modulus of HEPR insulation 19.21.1 Procedure 19.21.2 Requirements 19.22 Requirements 19.22 Requirements 19.21 Procedure 19.21.2 Requirements 19.22 Requirements 19.22 Requirements 19.22 Requirements 19.22 Requirements 	
 19.19 Thermal stability test for PVC insulation	
 19.19.1 Procedure	
 19.19.2 Requirements	
 19.20 Determination of hardness of HEPR insulation	
 19.20.1 Procedure	
 19.20.2 Requirements	-
 19.21 Determination of the elastic modulus of HEPR insulation	
19.21.1Procedure19.21.2Requirements19.22Shrinkage test for PE and halogen free oversheaths19.22.1Procedure19.22.2Requirements	
19.21.2Requirements19.22Shrinkage test for PE and halogen free oversheaths19.22.1Procedure19.22.2Requirements	
19.22Shrinkage test for PE and halogen free oversheaths19.22.1Procedure19.22.2Requirements	
19.22.1Procedure19.22.2Requirements	
19.22.2 Requirements	
	46
19.23 Strippability test for insulation screen	
· · · · · · · · · · · · · · · · · · ·	47
19.23.1 General	47
19.23.2 Procedure	47
19.23.3 Requirements	47
19.24 Water penetration test	47
19.25 Additional tests on halogen free oversheath of type ST ₈	
19.25.1 General	
19.25.2 Water absorption test for halogen free oversheath of type	∋ ST ₈ 48
19.25.3 Abrasion test on halogen free oversheath of type ST ₈	0
19.26 Bending test on interlock armour	
20 Electrical tests after installation	
20.1 General	
20.1 DC voltage test of the oversheath	
20.3 Insulation test AC voltage test of the insulation	
5	
Annex A (normative) Fictitious calculation method for determination of dimensions protective coverings	
A.1 General	58
A.2 Method	58
A.2.1 Conductors	58
A.2.2 Cores	59
A.2.3 Diameter over laid-up cores	59
A.2.4 Inner coverings	59
A.2.5 Concentric conductors and metal screens	

IEC 60502-2:2014+AMD1:2024 CSV - 7 - © IEC 2024

	A.2.6	Lead sheath	61
	A.2.7	Separation sheath	
	A.2.8	Lapped bedding	
	A.2.9	Additional bedding for tape-armoured cables (provided over	-
		the inner covering)	62
	A.2.10	Armour	62
		abulated continuous current ratings for cables having extruded	
		oltage from 3,6/6 kV up to 18/30 kV	
B.1			
B.2		structions	
B.3	•	ires	
B.4		al resistivity	
B.5		f installation	
	B.5.1	General	
	B.5.2	Single-core cables in air	
	B.5.3	Single-core cables buried direct	
	B.5.4	Single-core cables in earthenware ducts	
	B.5.5	Three-core cables	
B.6	Screen bo	nding	66
B.7	Cable load	ling	66
B.8	-	tors for grouped circuits	
B.9	Correction	factors	66
Annex C (no	rmative) Ro	ounding of numbers	82
C.1	Rounding	of numbers for the purpose of the fictitious calculation method	82
C.2	Rounding	of numbers for other purposes	82
Annex D (no	rmative) M	ethod of measuring resistivity of semi-conducting screens	83
Annex E (no	rmative) De	etermination of hardness of HEPR insulations	86
E.1	Test piece	•	86
E.2	Test proce	dure	86
	E.2.1	General	86
	E.2.2	Surfaces of large radius of curvature	86
	E.2.3	Surfaces of small radius of curvature	86
	E.2.4	Conditioning and test temperature	86
	E.2.5	Number of measurements	87
Annex F (noi	rmative) W	ater penetration test	88
F.1	Test piece		88
F.2	Test		88
F.3	Requireme	ents	89
Annex G (inf	ormative) [Determination of the cable conductor temperature	90
G.1	Purpose		90
G.2	Calibratior	n of the temperature of the main test loop	90
	G.2.1	General	90
	G.2.2	Installation of cable and temperature sensors	90
	G.2.3	Calibration method	
G.3	Heating fo	r the test	93
	G.3.1	Method 1 – Test using a reference cable	93
	G.3.2	Method 2 – Test using conductor temperature calculations	
		and measurement of the surface temperature	93

REDLINE	/ERSION	- 8 -	IEC 60502-2:2014+AMD1:20 © IE	24 CSV C 2024
Annex H (n	ormative) Test for wate	er penetration in the c	conductor	95
H.1	General	•		
H.2	Test piece			
H.3				
H.4	Requirements			
			ed value of halogen content of	97
l.1			e when the halogen content of	97
1.2			ement of halogen content on a materials in the cable	97
Bibliograph				
Figure B.1	 Single-core cables in 	air		64
Figure B.2	- Single-core cables bu	iried direct		65
-	-			
•	-			
Figure D.1	- Preparation of sample	es for measurement c	f resistivity of conductor and	
			re	
-		-	re	
-			penetration test	
-	-	• •	' Ind the main test loop	
Figure G.2	- Example of an arrang	ement of the tempera	ature sensors on the conductor	
	– Schematic diagram o		penetration test in the	
	U 1			
Table 3 – N	Maximum conductor tem	peratures for differen	t types of insulating compound.	
Table 4 – N	Maximum conductor tem	peratures for differen	t types of sheathing compound	l 18
Table 5 – N	Nominal thickness of PV	C/B insulation		
Table 6 – N	Nominal thickness of cro	oss-linked polyethylen	e (XLPE) insulation	19
			er (EPR) and hard ethylene	20
Table 8 – T	Thickness of extruded in	iner covering		21
Table 9 – N	Nominal diameter of rou	nd armour wires		26
Table 10 –	Nominal thickness of a	rmour tapes		26
Table 24 –	Nominal thickness of a	rmour strips		
Table 11 –	Routine test voltages			
Table 12 –	Number of samples for	sample tests		
			ng compounds	
Table 16 –	Non-electrical type test	s (see Table 17 to Ta	ble 23 and Table 25)	50

IEC 60502-2:2014+AMD1:2024 CSV -9-REDLINE VERSION © IEC 2024 Table 17 – Test requirements for mechanical characteristics of insulating compounds Table 18 – Test requirements for particular characteristics for PVC insulating Table 19 – Test requirements for particular characteristics of various crosslinked Table 20 – Test requirements for mechanical characteristics of sheathing compounds Table 21 – Test requirements for particular characteristics for PVC sheathing Table 22 – Test requirements for particular characteristics of PE (thermoplastic polyethylene) sheathing compounds55 Table 23 – Test requirements for particular characteristics of elastomeric sheathing Table 25 – Test requirements for particular characteristics of halogen free sheathing

 Table B.1 – Nominal screen cross-sectional areas
 63

 Table B.2 – Current ratings for single-core cables with XLPE insulation – Rated voltage Table B.3 – Current ratings for single-core cables with XLPE insulation – Rated voltage Table B.4 – Current ratings for single-core cables with EPR insulation – Rated voltage Table B.5 – Current ratings for single-core cables with EPR insulation – Rated voltage 3,6/6 kV to 18/30 kV * – Aluminium conductor......70 Table B.6 – Current rating for three-core XLPE insulated cables – Rated voltage Table B.7 – Current rating for three-core XLPE insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * – Aluminium conductor, armoured and unarmoured......72 Table B.8 – Current rating for three-core EPR insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * - Copper conductor, armoured and unarmoured73 Table B.9 – Current rating for three-core EPR insulated cables – Rated voltage 3,6/6 kV to 18/30 kV * - Aluminium conductor, armoured and unarmoured......74 Table B.11 – Correction factors for ambient ground temperatures other than 20 °C75 Table B.12 – Correction factors for depths of laying other than 0.8 m for direct buried Table B.13 – Correction factors for depths of laying other than 0.8 m for cables in Table B.14 – Correction factors for soil thermal resistivities other than 1.5 K·m/W for Table B.15 – Correction factors for soil thermal resistivities other than 1,5 K·m/W Table B.16 – Correction factors for soil thermal resistivities other than 1.5 K·m/W for

Table B.17 – Correction factors for soil thermal resistivities other than 1,5 K·m/W for three-core cables in ducts	77
Table B.18 – Correction factors for groups of three-core cables in horizontal formation laid direct in the ground	78
Table B.19 – Correction factors for groups of three-phase circuits of single-core cables laid direct in the ground	78
Table B.20 – Correction factors for groups of three-core cables in single way ducts in horizontal formation	79
Table B.21 – Correction factors for groups of three-phase circuits of single-core cables in single-way ducts	79
Table B.22 – Reduction factors for groups of more than one multi-core cable in air – To be applied to the current-carrying capacity for one multi-core cable in free air	80
Table B.23 – Reduction factors for groups of more than one circuit of single-corecables (Note 2) – To be applied to the current-carrying capacity for one circuit ofsingle-core cables in free air	81

INTERNATIONAL ELECTROTECHNICAL COMMISSION

POWER CABLES WITH EXTRUDED INSULATION AND THEIR ACCESSORIES FOR RATED VOLTAGES FROM 1 kV ($U_m = 1,2$ kV) UP TO 30 kV ($U_m = 36$ kV) –

Part 2: Cables for rated voltages from 6 kV $(U_m = 7,2 \text{ kV})$ up to 30 kV $(U_m = 36 \text{ kV})$

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60502-2 edition 3.1 contains the third edition (2014-02) [documents 20/1469A/FDIS and 20/1472/RVD] and its amendment 1 (2024-05) [documents 20/2166/FDIS and 20/2181/RVD].

In this Redline version, a vertical line in the margin shows where the technical content is modified by amendment 1. Additions are in green text, deletions are in strikethrough red text. A separate Final version with all changes accepted is available in this publication.

International Standard IEC 60502-2 has been prepared by IEC technical committee 20: Electric cables.

This third edition cancels and replaces the second edition, published in 2005, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) a simplified calculation procedure for the thickness of the lead sheath and the oversheath;
- b) a new subclause for the determination of the cable conductor temperature;
- c) a modified procedure for the routine voltage test;
- d) a new subclause for a routine electrical test on oversheath;
- e) modified requirements for the non-metal sheaths including semi-conductive layer;
- f) modified tolerances for the bending test cylinder;
- g) the inclusion of a 0,1Hz test after installation.

In addition, the modified structure of the IEC 60811 series has been adopted for this third edition.

The following editorial changes have been made within the English version:

- 'metallic' has been replaced by 'metal';
- 'thermosetting' has been replaced by 'crosslinked'.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60502 series, published under the general title *Power cables with* extruded insulation and their accessories for rated voltages from 1kV ($U_m = 1,2 \text{ kV}$) up to 30 kV ($U_m = 36 \text{ kV}$), can be found on the IEC website.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under <u>webstore.iec.ch</u> in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

POWER CABLES WITH EXTRUDED INSULATION AND THEIR ACCESSORIES FOR RATED VOLTAGES FROM 1 kV ($U_m = 1,2$ kV) UP TO 30 kV ($U_m = 36$ kV) –

Part 2: Cables for rated voltages from 6 kV $(U_{\rm m} = 7,2 \text{ kV})$ up to 30 kV $(U_{\rm m} = 36 \text{ kV})$

1 Scope

This part of IEC 60502 specifies the construction, dimensions and test requirements of power cables with extruded solid insulation from 6 kV up to 30 kV for fixed installations such as distribution networks or industrial installations.

When determining applications, it is recommended that the possible risk of radial water ingress is considered. Cable designs with barriers claimed to prevent longitudinal water penetration and an associated test are included in this part of IEC 60502.

Cables for special installation and service conditions are not included, for example cables for overhead networks, the mining industry, nuclear power plants (in and around the containment area) nor for submarine use or shipboard application.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60038, IEC standard voltages

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60060-3, High-voltage test techniques – Part 3: Definitions and requirements for on-site testing

IEC 60183, Guide to the selection of high-voltage cables

IEC 60228, Conductors of insulated cables

IEC 60229:2007, Tests on cable oversheaths which have a special protective function and are applied by extrusion

IEC 60230, Impulse tests on cables and their accessories

IEC 60287-3-1, Electric cables – Calculation of the current rating – Part 3: Sections on operating conditions – Section 1: Reference operating conditions and selection of cable type

IEC 60332-1-2, Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW premixed flame **REDLINE VERSION**

IEC 60332-3-24, Tests on electric and optical fibre cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C

IEC 60684-2, Flexible insulating sleeving – Part 2: Methods of test

IEC 60754-1, Test on gases evolved during combustion of materials from cables – Part 1: Determination of the halogen acid gas content

IEC 60754-2, Test on gases evolved during combustion of materials from cables – Part 2: Determination of acidity (by pH measurement) and conductivity

IEC 60754-3, Test on gases evolved during combustion of materials from cables – Part 3: Measurement of low level of halogen content by ion chromatography

IEC 60811 (all parts), *Electric and optical fibre cables – Test methods for non-metallic materials*

IEC 60811-201, Electric and optical fibre cables – Test methods for non-metallic materials – Part 201: General tests – Measurement of insulation thickness

IEC 60811-202, Electric and optical fibre cables – Test methods for non-metallic materials – Part 202: General tests – Measurement of thickness of non-metallic sheath

IEC 60811-203, Electric and optical fibre cables – Test methods for non-metallic materials – Part 203: General tests – Measurement of overall dimensions

IEC 60811-401, Electric and optical fibre cables – Test methods for non-metallic materials – Part 401: Miscellaneous tests – Thermal ageing methods – Ageing in an air oven

IEC 60811-402, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 402: Miscellaneous tests – Water absorption tests*

IEC 60811-403, Electric and optical fibre cables – Test methods for non-metallic materials – Part 403: Miscellaneous tests – Ozone resistance test on cross-linked compounds

IEC 60811-404, Electric and optical fibre cables – Test methods for non-metallic materials – Part 404: Miscellaneous tests – Mineral oil immersion tests for sheaths

IEC 60811-405, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 405: Miscellaneous tests – Thermal stability test for PVC insulations and PVC sheaths*

IEC 60811-409, Electric and optical fibre cables – Test methods for non-metallic materials – Part 409: Miscellaneous tests – Loss of mass test for thermoplastic insulations and sheaths

IEC 60811-501, Electric and optical fibre cables – Test methods for non-metallic materials – Part 501: Mechanical tests – Tests for determining the mechanical properties of insulating and sheathing compounds

IEC 60811-502, Electric and optical fibre cables – Test methods for non-metallic materials – Part 502: Mechanical tests – Shrinkage test for insulations

IEC 60811-503, Electric and optical fibre cables – Test methods for non-metallic materials – Part 503: Mechanical tests – Shrinkage test for sheaths

IEC 60811-504, Electric and optical fibre cables – Test methods for non-metallic materials – Part 504: Mechanical tests – Bending tests at low temperature for insulation and sheaths

IEC 60502-2:2014+AMD1:2024 CSV © IEC 2024

IEC 60811-505, Electric and optical fibre cables – Test methods for non-metallic materials – Part 505: Mechanical tests – Elongation at low temperature for insulations and sheaths

- 15 -

IEC 60811-506, Electric and optical fibre cables – Test methods for non-metallic materials – Part 506: Mechanical tests – Impact test at low temperature for insulations and sheaths

IEC 60811-507, Electric and optical fibre cables – Test methods for non-metallic materials – Part 507: Mechanical tests – Hot set test for cross-linked materials

IEC 60811-508, Electric and optical fibre cables – Test methods for non-metallic materials – Part 508: Mechanical tests – Pressure test at high temperature for insulation and sheaths

IEC 60811-509, Electric and optical fibre cables – Test methods for non-metallic materials – Part 509: Mechanical tests – Test for resistance of insulations and sheaths to cracking (heat shock test)

IEC 60811-605, Electric and optical fibre cables – Test methods for non-metallic materials – Part 605: Physical tests – Measurement of carbon black and/or mineral filler in polyethylene compounds

IEC 60811-606, Electric and optical fibre cables – Test methods for non-metallic materials – Part 606: Physical tests – Methods for determining the density

IEC 60853 (all parts), Calculation of the cyclic and emergency current rating of cables

IEC 60853-2, Calculation of the cyclic and emergency current rating of cables – Part 2: Cyclic rating of cables greater than 18/30 (36) kV and emergency ratings for cables of all voltages

IEC 60885-3, *Electrical test methods for electric cables – Part 3: Test methods for partial discharge measurements on lengths of extruded power cables*

IEC 60986, Short-circuit temperature limits of electric cables with rated voltages from 6 kV $(U_m = 7, 2 \text{ kV})$ up to 30 kV $(U_m = 36 \text{ kV})$

IEC 61034-2, Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements

ISO 48, Rubber, vulcanized or thermoplastic – Determination of hardness (hardness between 10 IRHD and 100 IRHD)

CONTENTS

FOF	REWORD)		11			
1	Scope			13			
2	Normati	Normative references					
3	Terms a	and definitio	ns	15			
	3.1	Definitions of dimensional values (thicknesses, cross-sections, etc.)					
	3.2 Definitions concerning the tests						
4	Voltage		ns and materials				
	4.1	Rated volt	ages	16			
	4.2		compounds				
	4.3	Sheathing	compounds	18			
5	Conduc	tors		19			
6	Insulatio	on		19			
	6.1	Material		19			
	6.2	Insulation	thickness	19			
7	Screeni	ng		20			
	7.1	General					
	7.2	Conductor	screen	20			
	7.3	Insulation	screen	20			
8	Assemb	ly of three-	core cables, inner coverings and fillers	21			
	8.1	General					
	8.2	Inner cove	erings and fillers	21			
		8.2.1	Construction	21			
		8.2.2	Material	21			
		8.2.3	Thickness of extruded inner covering				
		8.2.4	Thickness of lapped inner covering				
	8.3		ving a collective metal layer (see Clause 9)				
-	8.4		ving a metal layer over each individual core (see Clause 10)				
9		•	gle-core and three-core cables				
10							
			on				
	10.2	•	ents				
	10.3		ens not associated with semi-conducting layers				
11			tor				
	11.1		on				
	11.2	•	ents				
4.0	11.3	••	n				
12							
	12.1						
4.0	12.2		al sheaths				
13							
	13.1		netal armour				
	13.2						
	13.3		n of armour				
		13.3.1	Single-core cables				
		13.3.2	Three-core cables	24			

IEC 60502-2:2014+AMD1:2024 CSV - 3 -© IEC 2024

		13.3.3	Separation sheath	
		13.3.4	Lapped bedding under armour for lead sheathed cables	
	13.4		is of the armour wires, armour tapes and armour strips	
	13.5	Correlation	n between cable diameters and armour dimensions	25
	13.6		flat wire armour	
	13.7	Double tap	be armour	26
	13.8	Interlock n	netal tape armour	27
14	Overshe	eath		27
	14.1	General		27
	14.2	Material		27
	14.3	Thickness		28
15	Test cor	nditions		28
	15.1	Ambient te	emperature	28
	15.2	Frequency	and waveform of power frequency test voltages	28
	15.3		of impulse test voltages	
	15.4		tion of the cable conductor temperature	
16	Routine		·	
	16.1			
	16.2		resistance of conductors	
	16.3		charge test	
	16.4		st	
	10.4	16.4.1	General	
		16.4.2	Test procedure for single-core cables	
		16.4.3	Test procedure for three-core cables	
		16.4.4	Test voltage	
		16.4.5	Requirement	
	16.5		test on oversheath of the cable	
17				
17	•			
	17.1			
	17.2	. ,	of sample tests	
		17.2.1	Conductor examination and check of dimensions	
	47.0	17.2.2	Electrical and physical tests	
	17.3	•	of tests	
	17.4		examination	31
	17.5	(including	ent of thickness of insulation and of non-metal sheaths extruded separation sheaths, but excluding inner extruded	31
		17.5.1	General	
		17.5.2	Requirements for the insulation	
		17.5.3	Requirements for the non-metal sheaths	
	17.6		ent of thickness of lead sheath	
		17.6.1	General	
		17.6.2	Strip method	
		17.6.3	Ring method	
	17.7		ient of armour wires, tapes and armour strips	
		17.7.1	Measurement on wires	
		17.7.2	Measurement on tapes and armour strips	
		17.7.3	Requirements	

			• · _ ·	
	17.8	Measure	ment of external diameter	33
	17.9	Voltage t	est for 4 h	33
		17.9.1	Sampling	33
		17.9.2	Procedure	33
		17.9.3	Test voltages	33
		17.9.4	Requirements	33
	17.10		est for EPR, HEPR and XLPE insulations and elastomeric	
				-
		17.10.1	Procedure	
		17.10.2	Requirements	34
	17.11	Bending	test on interlock armour cable followed by examination	34
18	Type te	sts, electri	cal	34
	18.1	General		34
	18.2	Cables ha	aving conductor screens and insulation screens	34
		18.2.1	General	34
		18.2.2	Sequence of tests	34
		18.2.3	Special provisions	35
		18.2.4	Bending test	35
		18.2.5	Partial discharge test	36
		18.2.6	Tan δ measurement for cables of rated voltage 6/10 (12) kV	
			and above	
		18.2.7	Heating cycle test	36
		18.2.8	Impulse test followed by a voltage test	36
		18.2.9	Voltage test for 4 h	37
		18.2.10	Resistivity of semi-conducting screens	37
	18.3	Cables of	f rated voltage 3,6/6 (7,2) kV having unscreened insulation	37
		18.3.1	General	37
		18.3.2	Insulation resistance measurement at ambient temperature	38
		18.3.3	Insulation resistance measurement at maximum conductor temperature	38
		18.3.4	Voltage test for 4 h	
		18.3.5	Impulse test	
19	Type te		ectrical	
10	19.1			
	19.1		ment of thickness of insulation	
	19.2	19.2.1		
			Sampling	
		19.2.2	Procedure	
	10.0	19.2.3	Requirements	40
	19.3		ment of thickness of non-metal sheaths (including extruded on sheaths, but excluding inner coverings)	40
		19.3.1	Sampling	
		19.3.2	Procedure	
		19.3.3	Requirements	
	19.4		ment of thickness of lead sheath	
		19.4.1	Sampling	
		19.4.2	Procedure	
		19.4.3	Requirements	
	19.5		determining the mechanical properties of insulation before and	
			ing	40

IEC 60502-2:2014+AMD1:2024 CSV - 5 -© IEC 2024

	19.5.1	Sampling	40			
	19.5.2	Ageing treatments				
	19.5.3	Conditioning and mechanical tests	40			
	19.5.4	Requirements				
19.6	Tests for	determining the mechanical properties of non-metal sheaths				
		d after ageing	41			
	19.6.1	Sampling	41			
	19.6.2	Ageing treatments	41			
	19.6.3	Conditioning and mechanical tests	41			
	19.6.4	Requirements	41			
19.7	Additiona	I ageing test on pieces of completed cables	41			
	19.7.1	General	41			
	19.7.2	Sampling	41			
	19.7.3	Ageing treatment	41			
	19.7.4	Mechanical tests	41			
	19.7.5	Requirements	41			
19.8	Loss of m	ass test on PVC sheaths of type ST2	42			
	19.8.1	Procedure	42			
	19.8.2	Requirements	42			
19.9	Pressure	test at high temperature on insulations and non-metal sheaths	42			
	19.9.1	Procedure	42			
	19.9.2	Requirements	42			
19.10	Test on PVC insulation, PVC sheaths and halogen free sheaths at low					
	temperati	ıres				
	19.10.1	Procedure	42			
	19.10.2	Requirements	42			
19.11	Test for resistance of PVC insulation and sheaths to cracking (heat shock					
	,					
	19.11.1	Procedure				
40.40	19.11.2	Requirements				
19.12		sistance test for EPR and HEPR insulations				
	19.12.1	Procedure				
	19.12.2	Requirements	42			
19.13		est for EPR, HEPR and XLPE insulations and elastomeric	43			
19.14		sion test for elastomeric sheaths				
10.11	19.14.1	Procedure				
	19.14.2	Requirements				
19.15		sorption test on insulation				
	19.15.1	Procedure				
	19.15.2	Requirements				
19.16		er fire conditions				
	19.16.1	General				
	19.16.2	Flame spread test for single cables				
	19.16.3	Flame spread test for bunched cables				
	19.16.4	Measurement of smoke density of cables burning under				
		defined conditions	43			
	19.16.5	Determination of acidity (by pH measurement) and				
		conductivity of gases evolved during combustion of the non- metallic materials in the cable	44			

		19.16.6	Fire performance tests on halogen free oversheath material ST8	44
		19.16.7	Fire performance tests on halogen free oversheath material ST ₁₂	
		19.16.8	Measurement of halogen content of gases evolved during combustion of the non-metallic materials in the cable	
	19.17	Measuren	nent of carbon black content of black PE oversheaths	45
		19.17.1	Procedure	45
		19.17.2	Requirements	
	19.18	Shrinkage	e test for XLPE insulation	
		19.18.1	Procedure	
		19.18.2	Requirements	45
	19.19	Thermal s	stability test for PVC insulation	
		19.19.1	Procedure	
		19.19.2	Requirements	46
	19.20	Determina	ation of hardness of HEPR insulation	46
		19.20.1	Procedure	46
		19.20.2	Requirements	
	19.21		ation of the elastic modulus of HEPR insulation	
		19.21.1	Procedure	
		19.21.2	Requirements	
	19.22		e test for PE and halogen free oversheaths	
	-	19.22.1	Procedure	
		19.22.2	Requirements	
	19.23		ity test for insulation screen	
		19.23.1	, General	
		19.23.2	Procedure	
		19.23.3	Requirements	
	19.24		netration test	
	19.25		l tests on halogen free oversheath of type ST ₈	
		19.25.1	General	
		19.25.2	Water absorption test for halogen free oversheath of type ST8	
		19.25.3	Abrasion test on halogen free oversheath of type ST ₈	
	19.26		est on interlock armour	
20	Electric	•	er installation	
	20.1			
	20.1		e test of the oversheath	
	20.2		e test of the insulation	
Δnr		-	ictitious calculation method for determination of dimensions of	
	· ·	,		57
•	A.1	•		
	A.2			
		A.2.1	Conductors	
		A.2.2	Cores	
		A.2.3	Diameter over laid-up cores	
		A.2.4	Inner coverings	
		A.2.5	Concentric conductors and metal screens	
		A.2.6	Lead sheath	
		A.2.7	Separation sheath	
			1	

IEC 60502-2:2014+AMD1:2024 CSV - 7 - © IEC 2024

A.2.8	Lapped bedding	60					
A.2.9	Additional bedding for tape-armoured cables (provided over						
	the inner covering)	61					
A.2.10	Armour	61					
Annex B (informative) Tabulated continuous current ratings for cables having extrue							
nd a rated v	oltage from 3,6/6 kV up to 18/30 kV	62					
General		62					
Cable constructions							
Temperate	ures	62					
Soil thermal resistivity							
Methods of installation							
B.5.1	General	63					
B.5.2	Single-core cables in air	63					
B.5.3	Single-core cables buried direct	63					
B.5.4	Single-core cables in earthenware ducts	64					
B.5.5	5						
Screen bo	ondina	65					
	5						
	0						
-							
,	-						
-							
-							
,							
Test piece	3	85					
Test proce	edure	85					
E.2.1	General	85					
E.2.2	Surfaces of large radius of curvature	85					
E.2.3	Surfaces of small radius of curvature	85					
E.2.4	Conditioning and test temperature	85					
E.2.5	Number of measurements	86					
rmative) W	/ater penetration test	87					
Test piece	9	87					
Test							
	ents	87					
Requirem	ents	87 88					
Requirem formative)	ents Determination of the cable conductor temperature	87 88 89					
Requirem ormative) Purpose	ents Determination of the cable conductor temperature	87 88 89 89					
Requirem formative) Purpose Calibration	ents Determination of the cable conductor temperature n of the temperature of the main test loop	87 88 89 89 89					
Requirem formative) Purpose Calibration G.2.1	ents Determination of the cable conductor temperature n of the temperature of the main test loop General	87 88 89 89 89 89 89					
Requirem formative) Purpose Calibration G.2.1 G.2.2	ents Determination of the cable conductor temperature n of the temperature of the main test loop General Installation of cable and temperature sensors	87 88 89 89 89 89 89 89					
Requirem formative) Purpose Calibration G.2.1 G.2.2 G.2.3	ents Determination of the cable conductor temperature n of the temperature of the main test loop General Installation of cable and temperature sensors Calibration method	87 88 89 89 89 89 89 91					
Requirem formative) Purpose Calibration G.2.1 G.2.2 G.2.3 Heating fo	ents Determination of the cable conductor temperature n of the temperature of the main test loop General Installation of cable and temperature sensors Calibration method or the test	87 89 89 89 89 89 91 91					
Requirem formative) Purpose Calibration G.2.1 G.2.2 G.2.3 Heating for G.3.1	ents Determination of the cable conductor temperature n of the temperature of the main test loop General Installation of cable and temperature sensors Calibration method or the test Method 1 – Test using a reference cable	87 89 89 89 89 89 91 91					
Requirem formative) Purpose Calibration G.2.1 G.2.2 G.2.3 Heating fo	ents Determination of the cable conductor temperature n of the temperature of the main test loop General Installation of cable and temperature sensors Calibration method or the test	87 89 89 89 89 89 91 92 92					
Requirem formative) Purpose Calibration G.2.1 G.2.2 G.2.3 Heating for G.3.1 G.3.2	ents Determination of the cable conductor temperature n of the temperature of the main test loop General Installation of cable and temperature sensors Calibration method or the test Method 1 – Test using a reference cable Method 2 – Test using conductor temperature calculations	87 89 89 89 89 91 92 92 92					
	A.2.9 A.2.10 ormative) d a rated v General Cable con Temperati Soil therm Methods of B.5.1 B.5.2 B.5.3 B.5.4 B.5.5 Screen bo Cable load Rating fac Correction rmative) R Rounding Rounding rmative) N rest piece E.2.1 E.2.2 E.2.3 E.2.4 E.2.5 rmative) W	A.2.9 Additional bedding for tape-armoured cables (provided over the inner covering). A.2.10 Armour. ormative) Tabulated continuous current ratings for cables having extruded da rated voltage from 3,6/6 kV up to 18/30 kV. General. Gable constructions Temperatures Temperatures Soil thermal resistivity. Methods of installation B.5.1 General B.5.2 Single-core cables in air B.5.3 Single-core cables buried direct. B.5.4 Single-core cables in earthenware ducts. B.5.5 Three-core cables. Screen bonding. Cable loading. Rating factors for grouped circuits Correction factors Rounding of numbers for the purpose of the fictitious calculation method. Rounding of numbers for other purposes rmative) Determination of hardness of HEPR insulations Test piece Test piece Test piece Test piece Test piece Test piece of large radius of curvature E.2.3 Surfaces of large radius of curvature E.2.4 Conditioning and test temperature E.2.5 Number of measurements Further and test temperature E.2.5 Number of me					

H.2	Test piece	94				
H.3	Test					
H.4	Requirements	94				
Annex I (normative) Methods of determining the weighted value of halogen content of the non-metallic materials in the cable						
l.1	Calculating the weighted value of the cable when the halogen content of individual materials is tested	96				
1.2	Preparation of the test sample for measurement of halogen content on a sample representative of the non-metallic materials in the cable	96				
Bibliography	· · ·					
Figure B.1 –	Single-core cables in air	63				
Figure B.2 –	Single-core cables buried direct	64				
	Single-core cables in earthenware ducts					
0	Three-core cables					
Figure D.1 –	Preparation of samples for measurement of resistivity of conductor and reens					
	Test on surfaces of large radius of curvature					
•	Test on surfaces of small radius of curvature					
	Schematic diagram of apparatus for water penetration test					
•	Typical test set-up for the reference loop and the main test loop					
Figure G.2 -	Example of an arrangement of the temperature sensors on the conductor nce loop					
	•					
	Schematic diagram of apparatus for water penetration test in the	95				
conductor						
conductor Table 1 – Re		17				
conductor Table 1 – Re Table 2 – Ins	commended rated voltages U ₀	17 17				
Conductor Table 1 – Re Table 2 – Ins Table 3 – Ma	ecommended rated voltages U ₀	17 17 18				
Conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound	17 17 18 18				
Conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation	17 17 18 18 19				
conductor Table $1 - Re$ Table $2 - Ins$ Table $3 - Ma$ Table $4 - Ma$ Table $5 - Na$ Table $6 - Na$ Table $7 - Na$	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene	17 17 18 18 19 19				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 7 – No	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene bber (HEPR) insulation	17 17 18 18 19 19 20				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 7 – No propylene ru Table 8 – Th	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene bber (HEPR) insulation	17 17 18 18 19 19 20 21				
conductor Table $1 - Re$ Table $2 - Ins$ Table $3 - Ma$ Table $4 - Ma$ Table $5 - Na$ Table $5 - Na$ Table $6 - Na$ Table $7 - Na$ propylene ru Table $8 - Th$ Table $9 - Na$	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene bber (HEPR) insulation ickness of extruded inner covering	17 18 18 19 19 19 20 21 26				
conductor Table $1 - Re$ Table $2 - Ins$ Table $3 - Ms$ Table $3 - Ms$ Table $4 - Ms$ Table $5 - Nc$ Table $6 - Nc$ Table $7 - Nc$ propylene ru Table $8 - Th$ Table $9 - Nc$	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene bber (HEPR) insulation ickness of extruded inner covering ominal diameter of round armour wires	17 18 18 19 19 20 21 26 26				
conductor Table $1 - Re$ Table $2 - Ins$ Table $3 - Ma$ Table $4 - Ma$ Table $5 - Na$ Table $6 - Na$ Table $6 - Na$ Table $7 - Na$ propylene ru Table $8 - Th$ Table $9 - Na$ Table $10 - Na$	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene bber (HEPR) insulation ickness of extruded inner covering ominal diameter of round armour wires lominal thickness of armour tapes	17 18 18 19 19 20 21 26 26 26				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 7 – No propylene ru Table 8 – Th Table 9 – No Table 10 – N Table 24 – N	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation ominal thickness of cross-linked polyethylene (XLPE) insulation ominal thickness of ethylene propylene rubber (EPR) and hard ethylene bber (HEPR) insulation ickness of extruded inner covering ominal diameter of round armour wires lominal thickness of armour tapes coutine test voltages	17 18 18 19 19 20 21 26 26 26 26 30				
conductor Table $1 - Re$ Table $2 - Ins$ Table $2 - Ins$ Table $3 - Ma$ Table $4 - Ma$ Table $5 - Na$ Table $5 - Na$ Table $6 - Na$ Table $7 - Na$ propylene ru Table $8 - Th$ Table $9 - Na$ Table $9 - Na$ Table $10 - Na$ Table $24 - Na$ Table $24 - Na$ Table $11 - F$	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation	17 18 19 19 19 20 21 26 26 26 26 26 30 31				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 7 – No propylene ru Table 8 – Th Table 9 – No Table 9 – No Table 10 – N Table 24 – N Table 11 – F Table 12 – N	ecommended rated voltages U ₀ sulating compounds aximum conductor temperatures for different types of insulating compound aximum conductor temperatures for different types of sheathing compound ominal thickness of PVC/B insulation	17 18 18 19 19 20 21 26 26 26 30 31 33				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 6 – No Table 7 – No propylene ru Table 8 – Th Table 9 – No Table 9 – No Table 10 – N Table 24 – N Table 11 – F Table 12 – N Table 13 – S Table 14 – In	ecommended rated voltages U ₀	17 18 19 19 19 20 21 26 26 26 26 30 31 33 37				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 6 – No Table 7 – No propylene ru Table 8 – Th Table 9 – No Table 10 – N Table 10 – N Table 11 – F Table 12 – N Table 13 – S Table 13 – S	ecommended rated voltages U ₀	17 18 18 19 19 20 21 26 26 26 26 30 31 33 37 49				
conductor Table 1 – Re Table 2 – Ins Table 3 – Ma Table 4 – Ma Table 5 – No Table 6 – No Table 7 – No propylene ru Table 8 – Th Table 9 – No Table 10 – N Table 11 – F Table 12 – N Table 13 – S Table 13 – S Table 14 – In Table 15 – E Table 16 – N	ecommended rated voltages U ₀	17 18 18 19 19 20 21 26 26 26 26 30 31 33 37 49				

IEC 60502-2:2014+AMD1:2024 CSV © IEC 2024	- 9 -	FINAL VERSION
Table 18 – Test requirements for particular compound		
Table 19 – Test requirements for particularinsulating compounds		
Table 20 – Test requirements for mechanica (before and after ageing)		
Table 21 – Test requirements for particular compounds		
Table 22 – Test requirements for particularpolyethylene) sheathing compounds		
Table 23 – Test requirements for particular compound		
Table 25 – Test requirements for particular compounds	5	5
Table A.1 – Fictitious diameter of conductor	٢	58
Table A.2 – Increase of diameter for concer	ntric conductors and metal screer	ıs59
Table A.3 – Increase of diameter for additio	nal bedding	61
Table A.4 – Increase of diameter over interl	ocked armour	61
Table B.1 – Nominal screen cross-sectional		
Table B.2 – Current ratings for single-core of 3,6/6 kV to 18/30 kV * – Copper conductor	cables with XLPE insulation – Ra	ted voltage 66
Table B.3 – Current ratings for single-core of 3,6/6 kV to 18/30 kV * – Aluminium conduct		
Table B.4 – Current ratings for single-core of 3,6/6 kV to 18/30 kV * – Copper conductor		
Table B.5 – Current ratings for single-core of 3,6/6 kV to 18/30 kV * – Aluminium conduct		
Table B.6 – Current rating for three-core XL 3,6/6 kV to 18/30 kV * – Copper conductor,	PE insulated cables – Rated volt armoured and unarmoured	age 70
Table B.7 – Current rating for three-core XL 3,6/6 kV to 18/30 kV * – Aluminium conduct		
Table B.8 – Current rating for three-core EF 3,6/6 kV to 18/30 kV * – Copper conductor,		
Table B.9 – Current rating for three-core EF 3,6/6 kV to 18/30 kV * – Aluminium conduct		
Table B.10 – Correction factors for ambient	air temperatures other than 30 °	C73
Table B.11 – Correction factors for ambient	ground temperatures other than	20 °C74
Table B.12 – Correction factors for depths of cables		
Table B.13 – Correction factors for depths of ducts		
Table B.14 – Correction factors for soil ther direct buried single-core cables		
Table B.15 – Correction factors for soil thersingle-core cables in buried ducts		
Table B.16 – Correction factors for soil ther direct buried three-core cables		
Table B.17 – Correction factors for soil ther three-core cables in ducts		

Table B.18 – Correction factors for groups of three-core cables in horizontal formation laid direct in the ground	77
Table B.19 – Correction factors for groups of three-phase circuits of single-core cables laid direct in the ground	77
Table B.20 – Correction factors for groups of three-core cables in single way ducts in horizontal formation	78
Table B.21 – Correction factors for groups of three-phase circuits of single-core cables in single-way ducts	78
Table B.22 – Reduction factors for groups of more than one multi-core cable in air – To be applied to the current-carrying capacity for one multi-core cable in free air	79
Table B.23 – Reduction factors for groups of more than one circuit of single-core cables (Note 2) – To be applied to the current-carrying capacity for one circuit of single-core cables in free air	80

INTERNATIONAL ELECTROTECHNICAL COMMISSION

POWER CABLES WITH EXTRUDED INSULATION AND THEIR ACCESSORIES FOR RATED VOLTAGES FROM 1 kV ($U_m = 1,2$ kV) UP TO 30 kV ($U_m = 36$ kV) –

Part 2: Cables for rated voltages from 6 kV $(U_m = 7,2 \text{ kV})$ up to 30 kV $(U_m = 36 \text{ kV})$

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

This consolidated version of the official IEC Standard and its amendment has been prepared for user convenience.

IEC 60502-2 edition 3.1 contains the third edition (2014-02) [documents 20/1469A/FDIS and 20/1472/RVD] and its amendment 1 (2024-05) [documents 20/2166/FDIS and 20/2181/RVD].

This Final version does not show where the technical content is modified by amendment 1. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 60502-2 has been prepared by IEC technical committee 20: Electric cables.

This third edition cancels and replaces the second edition, published in 2005, and constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) a simplified calculation procedure for the thickness of the lead sheath and the oversheath;
- b) a new subclause for the determination of the cable conductor temperature;
- c) a modified procedure for the routine voltage test;
- d) a new subclause for a routine electrical test on oversheath;
- e) modified requirements for the non-metal sheaths including semi-conductive layer;
- f) modified tolerances for the bending test cylinder;
- g) the inclusion of a 0,1Hz test after installation.

In addition, the modified structure of the IEC 60811 series has been adopted for this third edition.

The following editorial changes have been made within the English version:

- 'metallic' has been replaced by 'metal';
- 'thermosetting' has been replaced by 'crosslinked'.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 60502 series, published under the general title *Power cables with* extruded insulation and their accessories for rated voltages from 1kV ($U_m = 1,2 \text{ kV}$) up to 30 kV ($U_m = 36 \text{ kV}$), can be found on the IEC website.

The committee has decided that the contents of this document and its amendment will remain unchanged until the stability date indicated on the IEC website under <u>webstore.iec.ch</u> in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

POWER CABLES WITH EXTRUDED INSULATION AND THEIR ACCESSORIES FOR RATED VOLTAGES FROM 1 kV ($U_m = 1,2$ kV) UP TO 30 kV ($U_m = 36$ kV) –

Part 2: Cables for rated voltages from 6 kV $(U_{\rm m} = 7,2 \text{ kV})$ up to 30 kV $(U_{\rm m} = 36 \text{ kV})$

1 Scope

This part of IEC 60502 specifies the construction, dimensions and test requirements of power cables with extruded solid insulation from 6 kV up to 30 kV for fixed installations such as distribution networks or industrial installations.

When determining applications, it is recommended that the possible risk of radial water ingress is considered. Cable designs with barriers claimed to prevent longitudinal water penetration and an associated test are included in this part of IEC 60502.

Cables for special installation and service conditions are not included, for example cables for overhead networks, the mining industry, nuclear power plants (in and around the containment area) nor for submarine use or shipboard application.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60038, IEC standard voltages

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60060-3, High-voltage test techniques – Part 3: Definitions and requirements for on-site testing

IEC 60183, Guide to the selection of high-voltage cables

IEC 60228, Conductors of insulated cables

IEC 60229:2007, Tests on cable oversheaths which have a special protective function and are applied by extrusion

IEC 60230, Impulse tests on cables and their accessories

IEC 60287-3-1, Electric cables – Calculation of the current rating – Part 3: Sections on operating conditions – Section 1: Reference operating conditions and selection of cable type

IEC 60332-1-2, Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW premixed flame FINAL VERSION

IEC 60332-3-24, Tests on electric and optical fibre cables under fire conditions – Part 3-24: Test for vertical flame spread of vertically-mounted bunched wires or cables – Category C

IEC 60684-2, Flexible insulating sleeving – Part 2: Methods of test

IEC 60754-1, Test on gases evolved during combustion of materials from cables – Part 1: Determination of the halogen acid gas content

IEC 60754-2, Test on gases evolved during combustion of materials from cables – Part 2: Determination of acidity (by pH measurement) and conductivity

IEC 60754-3, Test on gases evolved during combustion of materials from cables – Part 3: Measurement of low level of halogen content by ion chromatography

IEC 60811 (all parts), *Electric and optical fibre cables – Test methods for non-metallic materials*

IEC 60811-201, Electric and optical fibre cables – Test methods for non-metallic materials – Part 201: General tests – Measurement of insulation thickness

IEC 60811-202, Electric and optical fibre cables – Test methods for non-metallic materials – Part 202: General tests – Measurement of thickness of non-metallic sheath

IEC 60811-203, Electric and optical fibre cables – Test methods for non-metallic materials – Part 203: General tests – Measurement of overall dimensions

IEC 60811-401, Electric and optical fibre cables – Test methods for non-metallic materials – Part 401: Miscellaneous tests – Thermal ageing methods – Ageing in an air oven

IEC 60811-402, Electric and optical fibre cables – Test methods for non-metallic materials – Part 402: Miscellaneous tests – Water absorption tests

IEC 60811-403, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 403: Miscellaneous tests – Ozone resistance test on cross-linked compounds*

IEC 60811-404, Electric and optical fibre cables – Test methods for non-metallic materials – Part 404: Miscellaneous tests – Mineral oil immersion tests for sheaths

IEC 60811-405, Electric and optical fibre cables – Test methods for non-metallic materials – Part 405: Miscellaneous tests – Thermal stability test for PVC insulations and PVC sheaths

IEC 60811-409, Electric and optical fibre cables – Test methods for non-metallic materials – Part 409: Miscellaneous tests – Loss of mass test for thermoplastic insulations and sheaths

IEC 60811-501, Electric and optical fibre cables – Test methods for non-metallic materials – Part 501: Mechanical tests – Tests for determining the mechanical properties of insulating and sheathing compounds

IEC 60811-502, Electric and optical fibre cables – Test methods for non-metallic materials – Part 502: Mechanical tests – Shrinkage test for insulations

IEC 60811-503, Electric and optical fibre cables – Test methods for non-metallic materials – Part 503: Mechanical tests – Shrinkage test for sheaths

IEC 60811-504, Electric and optical fibre cables – Test methods for non-metallic materials – Part 504: Mechanical tests – Bending tests at low temperature for insulation and sheaths

IEC 60502-2:2014+AMD1:2024 CSV © IEC 2024

IEC 60811-505, Electric and optical fibre cables – Test methods for non-metallic materials – Part 505: Mechanical tests – Elongation at low temperature for insulations and sheaths

- 15 -

IEC 60811-506, Electric and optical fibre cables – Test methods for non-metallic materials – Part 506: Mechanical tests – Impact test at low temperature for insulations and sheaths

IEC 60811-507, Electric and optical fibre cables – Test methods for non-metallic materials – Part 507: Mechanical tests – Hot set test for cross-linked materials

IEC 60811-508, Electric and optical fibre cables – Test methods for non-metallic materials – Part 508: Mechanical tests – Pressure test at high temperature for insulation and sheaths

IEC 60811-509, Electric and optical fibre cables – Test methods for non-metallic materials – Part 509: Mechanical tests – Test for resistance of insulations and sheaths to cracking (heat shock test)

IEC 60811-605, Electric and optical fibre cables – Test methods for non-metallic materials – Part 605: Physical tests – Measurement of carbon black and/or mineral filler in polyethylene compounds

IEC 60811-606, Electric and optical fibre cables – Test methods for non-metallic materials – Part 606: Physical tests – Methods for determining the density

IEC 60853 (all parts), Calculation of the cyclic and emergency current rating of cables

IEC 60853-2, Calculation of the cyclic and emergency current rating of cables – Part 2: Cyclic rating of cables greater than 18/30 (36) kV and emergency ratings for cables of all voltages

IEC 60885-3, *Electrical test methods for electric cables – Part 3: Test methods for partial discharge measurements on lengths of extruded power cables*

IEC 60986, Short-circuit temperature limits of electric cables with rated voltages from 6 kV $(U_m = 7, 2 \text{ kV})$ up to 30 kV $(U_m = 36 \text{ kV})$

IEC 61034-2, Measurement of smoke density of cables burning under defined conditions – Part 2: Test procedure and requirements

ISO 48, Rubber, vulcanized or thermoplastic – Determination of hardness (hardness between 10 IRHD and 100 IRHD)