

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Åskskydd – Del 4: Skydd av elektriska och elektroniska system i byggnader

*Protection against lightning –
Part 4: Electrical and electronic systems within structures*

Som svensk standard gäller europastandarden EN IEC 62305-4:2024. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 62305-4:2024.

Nationellt förord

Europastandarden EN IEC 62305-4:2024

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 62305-4, Third edition, 2024 - Protection against lightning – Part 4: Electrical and electronic systems within structures**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 62305-4, utg 2:2011 med eventuella tillägg, ändringar och rättelser gäller ej fr o m 2027-10-31.

ICS 29.020.00; 91.120.40

Denna standard är fastställd av SEK Svensk Elstandard, som också kan lämna upplysningar om **sakinnehållet** i standarden.
Postadress: Box 1042, 172 21 Sundbyberg
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1042
172 21 Sundbyberg
Tel 08-444 14 00
elstandard.se

English Version

**Protection against lightning - Part 4: Electrical and electronic systems within structures
(IEC 62305-4:2024)**

Protection contre la foudre - Partie 4: Réseaux de puissance et de communication dans les structures
(IEC 62305-4:2024)

Blitzschutz - Teil 4: Elektrische und elektronische Systeme in baulichen Anlagen
(IEC 62305-4:2024)

This European Standard was approved by CENELEC on 2024-10-17. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 81/733/FDIS, future edition 3 of IEC 62305-4, prepared by TC 81 "Lightning protection" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62305-4:2024.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2025-10-31 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2027-10-31 document have to be withdrawn

This document supersedes EN 62305-4:2011 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 62305-4:2024 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 60364-4-43	NOTE	Approved as HD 60364-4-43
IEC 60364-4-44:2007	NOTE	Approved as HD 60364-4-444:2010
IEC 60364-4-44:2007/A1:2015	NOTE	Approved as HD 60364-4-443:2016
IEC 61000 series	NOTE	Approved as EN IEC 61000 series
IEC 62475	NOTE	Approved as EN 62475
IEC 60060 series	NOTE	Approved as EN 60060 series
IEC 62793	NOTE	Approved as EN IEC 62793
IEC 60038	NOTE	Approved as EN 60038
IEC 61643-351	NOTE	Approved as EN 61643-351
IEC 61643-352	NOTE	Approved as EN IEC 61643-352

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60364-5-53	2019	Low-voltage electrical installations -- Part 5-53: Selection and erection of electrical equipment - Protection, isolation, switching, control and monitoring	-	-
IEC 60664-1	-	Insulation coordination for equipment within low-voltage supply systems - Part 1: Principles, requirements and tests	EN IEC 60664-1	-
IEC 61000-4-5	-	Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test	EN 61000-4-5	-
IEC 61000-4-9	-	Electromagnetic compatibility (EMC) – Part 4-9: Testing and measurement techniques – Impulse magnetic field immunity test	EN 61000-4-9	-
IEC 61000-4-10	-	Electromagnetic compatibility (EMC) – Part 4-10: Testing and measurement techniques – Damped oscillatory magnetic field immunity test	EN 61000-4-10	-
IEC 61643-11 (mod)	2011	Low-voltage surge protective devices - Part 11: Surge protective devices connected to low-voltage power systems - Requirements and test methods	EN 61643-11	2012
-	-		+ A11	2018
IEC 61643-12	2020	Low-voltage surge protective devices - Part 12: Surge protective devices connected to low-voltage power systems - Selection and application principles	-	-
IEC 61643-21	-	Low voltage surge protective devices - Part 21: Surge protective devices connected to telecommunications and signalling networks - Performance requirements and testing methods	EN 61643-21	-

EN IEC 62305-4:2024 (E)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61643-22	-	Low-voltage surge protective devices - Part 22: Surge protective devices connected to telecommunications and signalling networks - Selection and application principles	CLC/TS 61643-22	-
IEC 61643-31	-	Low-voltage surge protective devices – Part 31: Requirements and test methods for SPDs for photovoltaic installations	EN 61643-31	-
IEC 61643-32	2017	Low-voltage surge protective devices – Part 32: Surge protective devices connected to the d.c. side of photovoltaic installations – Selection and application principles	-	-
IEC 62305-1	2024	Protection against lightning - Part 1: General principles	EN IEC 62305-1	2024
IEC 62305-2	2024	Protection against lightning - Part 2: Risk management	EN IEC 62305-2	2024
IEC 62305-3	2024	Protection against lightning - Part 3: Physical damage to structures and life hazard	EN IEC 62305-3	2024
IEC 62561	series	Lightning protection system components (LPSC) - Part 1: Requirements for connection components	EN IEC 62561	series



IEC 62305-4

Edition 3.0 2024-09

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Protection against lightning –
Part 4: Electrical and electronic systems within structures**

**Protection contre la foudre –
Partie 4: Réseaux de puissance et de communication dans les structures**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.020, 91.120.40

ISBN 978-2-8322-7933-5

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

FOREWORD.....	8
INTRODUCTION.....	10
1 Scope.....	11
2 Normative references	11
3 Terms and definitions	12
4 Design and installation of SPM	16
4.1 General.....	16
4.2 Design of SPM.....	20
4.3 Lightning protection zones (LPZs).....	20
4.3.1 General	20
4.3.2 Outer zones.....	20
4.3.3 Inner zones	21
4.4 Basic SPM	23
5 Earthing and bonding networks.....	24
5.1 General.....	24
5.2 Earth-termination system	25
5.3 Bonding network	26
5.4 Bonding bars	31
5.5 Bonding at the boundary of an LPZ.....	32
5.6 Material and dimensions of bonding components	32
6 Magnetic shielding and line routing.....	33
6.1 General.....	33
6.2 Spatial shielding	33
6.3 Shielding of internal lines.....	33
6.4 Routing of internal lines	34
6.5 Shielding of external lines	34
6.6 Material and dimensions of magnetic shields	34
7 Coordinated SPD system.....	34
8 Isolating interfaces	35
9 SPM management	35
9.1 General.....	35
9.2 SPM management plan	36
9.3 Inspection of SPM.....	38
9.3.1 General	38
9.3.2 Inspection procedure	38
9.3.3 Inspection documentation	39
9.4 Maintenance	39
Annex A (informative) Basis of electromagnetic environment evaluation in an LPZ	40
A.1 General.....	40
A.2 Damaging effects on electrical and electronic systems due to lightning.....	40
A.2.1 Sources of damage.....	40
A.2.2 Object of damage	40
A.2.3 Withstand of equipment signal ports	40
A.2.4 Withstand of equipment power ports	41
A.2.5 Relationship between the object of damage and the source of damage.....	42
A.3 Spatial shielding, line routing and line shielding	42

A.3.1	General	42
A.3.2	Grid-like spatial shields	45
A.3.3	Line routing and line shielding	47
A.4	Magnetic field inside LPZ	51
A.4.1	Approximation for the magnetic field inside LPZ	51
A.4.2	Numerical magnetic field calculation in case of direct lightning strikes	57
A.4.3	Experimental evaluation of the magnetic field due to a direct lightning strike	61
A.5	Calculation of induced voltages and currents	62
A.5.1	General	62
A.5.2	Situation inside LPZ 1 in the case of a direct lightning strike	62
A.5.3	Situation inside LPZ 1 in the case of a nearby lightning strike	65
A.5.4	Situation inside LPZ 2 and higher	66
Annex B (informative)	Implementation of SPM for an existing structure	67
B.1	General	67
B.2	Checklists	67
B.3	Design of SPM for an existing structure	68
B.4	Design of basic protection measures for LPZs	70
B.4.1	Design of basic protection measures for LPZ 1	70
B.4.2	Design of basic protection measures for LPZ 2	70
B.4.3	Design of basic protection measures for LPZ 3	71
B.5	Improvement of an existing LPS using spatial shielding of LPZ 1	71
B.6	Establishment of LPZs for electrical and electronic systems	71
B.7	Protection using a bonding network	74
B.8	Protection by surge protective devices	74
B.9	Protection by isolating interfaces	75
B.10	Protection measures by line routing and shielding	75
B.11	Protection measures for externally installed equipment	77
B.11.1	General	77
B.11.2	Protection of external equipment	77
B.11.3	Protection by maintaining electrical insulation to the LPS	79
B.11.4	Reduction of overvoltages in cables	80
B.12	Improving interconnections between structures	81
B.12.1	General	81
B.12.2	Isolating lines	81
B.12.3	Metallic lines	81
B.13	Integration of new internal systems into existing structures	81
B.14	Overview of possible protection measures	82
B.14.1	Power supply	82
B.14.2	Surge protective devices	83
B.14.3	Isolating interfaces	83
B.14.4	Line routing and shielding	83
B.14.5	Spatial shielding	83
B.14.6	Bonding	83
B.15	Upgrading a power supply and cable installation inside the structure	83
Annex C (informative)	Selection and installation of a coordinated SPD system	84
C.1	General	84
C.2	Selection of SPDs	85
C.2.1	Location of SPDs according to source of damage	85

C.2.2	Selection with regard to lightning current I	86
C.2.3	Selection with regard to voltage protection level U_p	87
C.2.4	SPD arrangements	92
C.2.5	Equipment protection by two SPDs	92
C.2.6	Equipment connected to two different services	93
C.2.7	Selection with regard to location and discharge current	93
C.2.8	Coordination of the SPD with back-up overcurrent protective device (OCPD)	96
C.3	Installation of a coordinated SPD system	97
C.3.1	General	97
C.3.2	Installation location of SPDs	97
C.3.3	Connecting conductors	98
C.3.4	Coordination of SPDs	98
C.3.5	Procedure for installation of a coordinated SPD system	98
Annex D (informative)	Factors to be considered in the selection of SPDs	99
D.1	General	99
D.2	Factors determining the stress experienced by an SPD	99
D.3	Quantifying the statistical threat level to an SPD	101
D.3.1	General	101
D.3.2	Installation factors effecting current distribution	101
D.3.3	Considerations in the selection of SPD ratings: I_{imp} , $[I_{max}]$, I_n , U_{OC}	102
Annex E (informative)	Lightning current sharing using simulation modelling	104
E.1	General	104
E.1.1	Overview	104
E.1.2	Methods to determine the lightning current distribution	104
E.2	Lightning current parameters for SPDs	105
E.2.1	Lightning current parameters in accordance with IEC 62305-1	105
E.2.2	Conclusion on lightning current sharing from numerical modelling	105
E.3	Distribution of lightning currents in power supply systems	106
E.3.1	Influencing factors	106
E.3.2	Considerations in lightning current sharing using numerical modelling	108
E.4	Current distribution in structures	111
E.4.1	General	111
E.4.2	Structures with externally installed equipment and non-isolated LPS	112
E.4.3	Tall buildings	113
E.4.4	Transformer located inside a structure	114
Annex F (informative)	Lightning current sharing in photovoltaic installations	115
F.1	General	115
F.2	Structures with roof-mounted PV systems	117
F.2.1	Description and assumptions	117
F.2.2	Simplified calculation for the lightning current flowing in DC conductors	117
F.3	Outside free-field power plant with a non-isolated LPS	119
F.3.1	General	119
F.3.2	Finding the lightning current flowing through the DC conductor via the SPD	120
F.3.3	Results	120
Annex G (informative)	Testing system level behaviour under lightning discharge conditions	122
G.1	General	122

G.2	SPD discharge current test under normal service conditions	122
G.3	Induction test due to lightning currents.....	122
G.4	Recommended test classification of system level immunity (IEC 61000-4-5)	122
Annex H (informative)	Induced voltage in the circuits protected by an SPD	124
H.1	General.....	124
H.2	Direct flashes to the structure (Figure H.1).....	124
H.3	Flashes near the structure (Figure H.2).....	125
H.4	Flashes to the service	126
Annex I (informative)	Isolation interfaces using surge isolation transformers (SITs)	128
I.1	SIT for low-voltage power distribution system	128
I.2	SIT for communication systems	128
I.3	SIT surge mitigation performance (low-voltage power distribution systems)	128
Bibliography	130
Figure 1	– General principle for the division into different LPZs	17
Figure 2	– Examples of possible SPM (LEMP protection measures).....	19
Figure 3	– Examples of interconnected LPZs	22
Figure 4	– Examples of extended lightning protection zones	23
Figure 5	– Example of a three-dimensional earthing system consisting of the bonding network interconnected with the earth-termination system	25
Figure 6	– Meshed earth-termination system of a plant.....	26
Figure 7	– Utilization of reinforcing rods of a structure as a protection measure against LEMP and for equipotential bonding.....	28
Figure 8	– Equipotential bonding in a structure with steel reinforcement	29
Figure 9	– Integration of conductive parts of internal systems into the bonding network	30
Figure 10	– Combinations of integration methods of conductive parts of internal systems into the bonding network	31
Figure A.1	– LEMP situation due to lightning strike to the structure.....	42
Figure A.2	– Simulation of the rise of the field of the subsequent stroke (0,25/100 μ s) by damped 1 MHz oscillations (multiple impulses 0,2/0,5 μ s)	45
Figure A.3	– Large volume shield built by metal reinforcement and metal frames	46
Figure A.4	– Volume for electrical and electronic systems inside an inner LPZ n	47
Figure A.5	– Reducing induction effects by line routing and shielding measures	48
Figure A.6	– Example of SPM for an office building.....	50
Figure A.7	– Evaluation of the magnetic field values in case of a direct lightning strike	51
Figure A.8	– Evaluation of the magnetic field values in case of a nearby lightning strike	53
Figure A.9	– Distance s_a depending on rolling sphere radius and structure dimensions.....	56
Figure A.10	– Types of structure geometries with different volume shields.....	58
Figure A.11	– Magnetic field strength $H_{1/MAX}$ inside a grid-like shield for the cubic structure shown in Figure A.10 [14].....	59
Figure A.12	– Magnetic field strength $H_{1/MAX}$ inside a grid-like shield for the cubic structure according to mesh width.....	60
Figure A.13	– Low-level test to evaluate the magnetic field inside a shielded structure	61
Figure A.14	– Voltages and currents induced into a loop formed by lines	62
Figure B.1	– SPM design steps for an existing structure	70
Figure B.2	– Methods of establishing LPZs in existing structures	73

Figure B.3 – Reduction of loop area using shielded cables close to a metal plate	76
Figure B.4 – Example of a metal plate for additional shielding	76
Figure B.5 – Protection of aerials and other external equipment	78
Figure B.6 – Separation distance maintained or not maintained	79
Figure B.7 – Inherent shielding provided by bonded ladders and pipes	80
Figure B.8 – Ideal positions for lines on a mast (cross-section of steel lattice mast).....	80
Figure B.9 – Upgrading of the SPM in existing structures.....	82
Figure C.1 – Selection of SPDs by source of damage	86
Figure C.2 – Example of installation of an SPD to reduce the effect of SPD lead length.....	88
Figure C.3 – Surge voltage between live conductor and bonding bar	91
Figure C.4 – Equipment with two ports and SPDs on both services bonded to two different earthing points of a non-equipotential earthing system.....	93
Figure D.1 – Installation example of SPD test class I, class II and class III in a TN system.....	100
Figure D.2 – Basic example of different sources of damage to a structure and lightning current distribution within a system	101
Figure D.3 – Example of the simplified current distribution in a TN power distribution system.....	102
Figure E.1 – Approach to computer simulation used to analyse lightning current sharing	105
Figure E.2 – MEN earthing system.....	108
Figure E.3 – Parallel connected structures.....	109
Figure E.4 – Influence of lightning current flow in parallel connected structures	109
Figure E.5 – Influence of lightning current flow in star connected structures	110
Figure E.6 – Influence of other metallic conductive services on lightning current sharing	110
Figure E.7 – Influence of lightning current flow from S3 events	111
Figure E.8 – Structures with externally installed equipment and non-isolated LPS	112
Figure E.9 – Protection of internally located sub-station transformers	114
Figure F.1 – Current sharing between LPS down conductors and the internal cabling of a PV system in which the separation distance s has not been maintained	116
Figure F.2 – Protection of a roof-mounted PV system	117
Figure F.3 – Free-field PV power plant with multiple earthing and meshed earthing system.....	120
Figure G.1 – Example circuit of an SPD discharge current test under service conditions.....	123
Figure G.2 – Example circuit of an induction test due to lightning currents.....	123
Figure H.1 – Induced loop by a lightning current on the structure.....	125
Figure H.2 – Induced loop by a lightning current near the structure.....	125
Figure I.1 – Use of SPDs to protect windings of SIT.....	129
Table 1 – Minimum cross-sections for bonding components.....	33
Table 2 – SPM management plan for new buildings and for extensive changes in construction or use of existing buildings.....	37
Table A.1 – Rated impulse voltage of equipment per IEC 60364-4-44:2007, Clause 443 and IEC 60364-4-44:2007/AMD1:2015, Clause 443	41
Table A.2 – Parameters relevant to source of harm and equipment.....	43

Table A.3 – Examples for $I_{0/MAX} = 100$ kA and $w_m = 2$ m	53
Table A.4 – Attenuation of the magnetic field of grid-like spatial shields for a plane wave	54
Table A.5 – Rolling sphere radius corresponding to maximum lightning current	56
Table A.6 – Examples for $I_{0/MAX} = 100$ kA and $w_m = 2$ m corresponding to $SF = 12,6$ dB	57
Table B.1 – Structural characteristics and surroundings	67
Table B.2 – Installation characteristics	68
Table B.3 – Equipment characteristics	68
Table B.4 – Other questions to be considered for the protection concept	68
Table B.5 – Type of LPS	68
Table C.1 – Required rated impulse voltage of equipment	87
Table C.2 – Connection of the SPD dependent on supply system	94
Table C.3 – Selection of impulse discharge current (I_{imp}) where the building is protected against direct lightning strike (S1) based on simplified rules	95
Table C.4 – Nominal discharge current (I_n) in kA depending on supply system and connection type	95
Table C.5 – Selection of impulse discharge current (I_{imp}) where the building is protected from direct strikes to the line (S3)	96
Table D.1 – Preferred values of I_{imp}	99
Table E.1 – General trends associated with protection installations for different power distribution systems	107
Table F.1 – Simplified calculated values of I_{imp} ($I_{10/350}$) and I_n ($I_{8/20}$) for voltage-limiting SPDs on the DC side of a PV installation mounted on the roof of a building with an external LPS if the separation distance is not maintained (see Figure F.1)	118
Table F.2 – Simplified calculated values of I_{imp} ($I_{10/350}$) for voltage switching SPDs on the DC side of a PV installation mounted on the roof of a building with an external LPS if the separation distance is not maintained (see Figure F.1)	119
Table F.3 – Simplified calculated values of $I_{10/350}$ and $I_{8/20}$ for SPDs intended to be used in free-field PV power plants with multiple earthing and a meshed earthing system based on Figure F.3	121
Table H.1 – Flashes near the structure: induced voltage per square metre q as a function of LPL	126
Table H.2 – Values of k_C	127
Table H.3 – Values of k_{S1} and k_{S2} for some copper shields	127

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROTECTION AGAINST LIGHTNING –

Part 4: Electrical and electronic systems within structures

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62305-4 has been prepared by IEC technical committee 81: Lightning protection. It is an International Standard.

This third edition cancels and replaces the second edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) addition of new informative Annex E and Annex F on the determination of current sharing using modelling and current sharing in PV installations respectively;
- b) addition of a new informative Annex G on methods of testing of system level behaviour;
- c) addition of a new informative Annex H on induced voltages in SPD-protected installations.

The text of this International Standard is based on the following documents:

Draft	Report on voting
81/733/FDIS	81/752/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62305 series, published under the general title *Protection against lightning*, can be found on the IEC website.

The following differing practices of a less permanent nature exist in the countries indicated below.

- 1) Subclause 5.6: In Japan, the minimum values of the cross-section are reduced from:
 - 16 mm² to 14 mm² for copper and 25 mm² to 22 mm² for aluminium, for bonding conductors connecting different bonding bars and conductors connecting the bars to the earth-termination system;
 - 6 mm² to 5 mm² for copper, 10 mm² to 8 mm² for aluminium and 16 mm² to 14 mm² for steel, for bonding conductors connecting internal metal installations to the bonding bars;
 - 16 mm² to 14 mm², 6 mm² to 5 mm² and 2,5 mm² to 2 mm² for copper, for earthing conductors to the SPD, conductors connecting SPDs and overcurrent protective devices to live conductors.
- 2) Subclause E.3.2.3: In South Africa SANS 10142-1:2020, Clause 6.1.6 [1]¹ states that 'The neutral conductor shall not be connected direct to earth or to the earth continuity conductor on the load side of the point of control'.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

¹ Numbers in square brackets refer to the Bibliography.

INTRODUCTION

Lightning as a source of harm is a very high energy phenomenon. Lightning flashes release many hundreds of mega-joules of energy. When compared with the milli-joules of energy that can be enough to cause damage to sensitive electronic equipment in electrical and electronic systems within a structure, additional protection measures will be necessary to protect some of this equipment.

The need for this International Standard has arisen due to the increasing cost of failures of electrical and electronic systems, caused by electromagnetic effects of lightning. Of importance are electronic systems used in data processing and storage as well as process control and safety for plants of considerable capital cost, size and complexity (for which plant outages are very undesirable for cost and safety reasons).

Lightning can cause different types of damage in a structure, as defined in IEC 62305-1.

IEC 62305-3 deals with the protection measures to reduce the risk of physical damage and life hazard but does not cover the protection of electrical and electronic systems.

This part of IEC 62305 therefore provides information on protection measures to reduce the risk of permanent failures of electrical and electronic systems within structures.

Permanent failure of electrical and electronic systems can be caused by the lightning electromagnetic impulse (LEMP) via:

- conducted and induced surges transmitted to equipment via connecting wiring;
- the effects of radiated electromagnetic fields directly into equipment itself.

Surges to the structure can originate from sources external to the structure or from within the structure itself:

- surges which originate externally from the structure are created by lightning flashes striking incoming lines or the nearby ground, and are transmitted to electrical and electronic systems within the structure via these lines;
- surges which originate internally within the structure are created by lightning flashes striking the structure itself or the nearby ground.

NOTE 1 Surges can also originate internally within the structure, from switching effects, e.g. switching of inductive loads, tripping of circuit breakers, blowing of fuses.

NOTE 2 Further information about the protection against switching overvoltages created within structures can be found in IEC 60364-4-43 [2], IEC 60364-5-53 and IEC 61643-12.

Coupling can arise from different mechanisms, namely:

- resistive coupling (e.g. the earth impedance of the earth-termination system or the cable shield resistance);
- magnetic field coupling (e.g. caused by wiring loops in the electrical and electronic system or by inductance of bonding conductors);
- electric field coupling (e.g. caused by rod antenna reception).

NOTE 3 The effects of electric field coupling are generally very small when compared to the magnetic field coupling and can be disregarded.

Radiated electromagnetic fields can be generated via

- the direct lightning current flowing in the lightning channel;
- the partial lightning current flowing in conductors (e.g. in the down conductors of an external LPS, or its natural components, in accordance with IEC 62305-3 or in an external spatial shield in accordance with this document).

PROTECTION AGAINST LIGHTNING –

Part 4: Electrical and electronic systems within structures

1 Scope

This part of IEC 62305 provides requirements for the design, installation, inspection, maintenance, and testing of surge protection measures (SPM) for electrical and electronic systems to reduce the risk of permanent failures due to lightning electromagnetic impulse (LEMP) within a structure.

This document does not cover protection against electromagnetic interference due to lightning, which can cause malfunctioning of internal systems. However, the information reported in Annex A can also be used to evaluate such disturbances. Protection measures against electromagnetic interference are covered in IEC 60364-4-44 [3] and in the IEC 61000 series [4].

This document provides guidelines for cooperation between the designer of the electrical and electronic system and the designer of the protection measures, in order to achieve optimum protection effectiveness.

This document does not deal with detailed design of the electrical and electronic systems themselves.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60364-5-53:2019, *Low-voltage electrical installations – Part 5-53: Selection and erection of electrical equipment – Devices for protection for safety, isolation, switching, control and monitoring*

IEC 60664-1, *Insulation coordination for equipment within low-voltage systems – Part 1: Principles, requirements, and tests*

IEC 61000-4-5, *Electromagnetic compatibility (EMC) – Part 4-5: Testing and measurement techniques – Surge immunity test*

IEC 61000-4-9, *Electromagnetic compatibility (EMC) – Part 4-9: Testing and measurement techniques – Impulse magnetic field immunity test*

IEC 61000-4-10, *Electromagnetic compatibility (EMC) – Part 4-10: Testing and measurement techniques – Damped oscillatory magnetic field immunity test*

IEC 61643-11:2011, *Low-voltage surge protective devices– Part 11: Surge protective devices connected to low-voltage power systems – Requirements and test methods*

IEC 61643-12:2020, *Low-voltage surge protective devices – Part 12: Surge protective devices connected to low-voltage power systems – Selection and application principles*

IEC 61643-21, *Low-voltage surge protective devices – Part 21: Surge protective devices connected to telecommunications and signalling networks – Performance requirements and testing methods*

IEC 61643-22, *Low-voltage surge protective devices – Part 22: Surge protective devices connected to telecommunications and signalling networks – Selection and application principles*

IEC 61643-31, *Low-voltage surge protective devices – Part 31: Requirements and test methods for SPDs for photovoltaic installations*

IEC 61643-32:2017, *Low-voltage surge protective devices – Part 32: Surge protective devices connected to the d.c. side of photovoltaic installations – Selection and application principles*

IEC 62305-1:2024, *Protection against lightning – Part 1: General principles*

IEC 62305-2:2024, *Protection against lightning – Part 2: Risk management*

IEC 62305-3:2024, *Protection against lightning – Part 3: Physical damage to structures and life hazard*

IEC 62561 (all parts), *Lightning protection system components (LPSC)*