

SVENSK STANDARD SS-EN IEC 62305-3, utg 3:2024

Fastställd

Sida

Ansvarig kommitté

2024-12-18

1 (140)

SEK TK 81

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Åskskydd –

Del 3: Skydd mot skador på byggnader och personer

Protection against lightning -

Part 3: Physical damage to structures and life hazard

Som svensk standard gäller europastandarden EN IEC 62305-3:2024. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 62305-3:2024.

Nationellt förord

Europastandarden EN IEC 62305-3:2024

består av:

- europastandardens ikraftsättningsdokument, utarbetat inom CENELEC
- IEC 62305-3, Third edition, 2024 Protection against lightning Part 3: Physical damage to structures and life hazard

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 62305-3, utg 2:2011 med eventuella tillägg, ändringar och rättelser gäller ej fr o m 2027-10-31.

ICS 29.020.00: 91.120.40

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1042 172 21 Sundbyberg Tel 08-444 14 00 elstandard.se

EUROPEAN STANDARD NORME EUROPÉENNE

EUROPÄISCHE NORM

EN IEC 62305-3

October 2024

ICS 29.020; 91.120.40

Supersedes EN 62305-3:2011

English Version

Protection against lightning - Part 3: Physical damage to structures and life hazard (IEC 62305-3:2024)

Protection contre la foudre - Partie 3: Dommages physiques sur les structures et risques humains (IEC 62305-3:2024) Blitzschutz - Teil 3: Schutz von baulichen Anlagen und Personen (IEC 62305-3:2024)

This European Standard was approved by CENELEC on 2024-10-17. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2024 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Ref. No. EN IEC 62305-3:2024 E

European foreword

The text of document 81/764/FDIS, future edition 3 of IEC 62305-3, prepared by TC 81 "Lightning protection" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 62305-3:2024.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2025-10-31 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2027-10-31 document have to be withdrawn

This document supersedes EN 62305-3:2011 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 62305-3:2024 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 61400-24	NOTE	Approved as EN IEC 61400-24
ISO 1182	NOTE	Approved as EN ISO 1182
ISO 11925-2	NOTE	Approved as EN ISO 11925-2
IEC 60071-2	NOTE	Approved as EN IEC 60071-2
IEC 60079-17	NOTE	Approved as EN IEC 60079-17
IEC 62858	NOTE	Approved as EN IEC 62858

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 60079-10-1	2020	Explosive atmospheres - Part 10-1: Classification of areas - Explosive gas atmospheres	EN IEC 60079-10-1	2021
IEC 60079-10-2	2015	Explosive atmospheres - Part 10-2: Classification of areas - Explosive dust atmospheres	EN 60079-10-2	2015
IEC 60079-14	-	Explosive atmospheres - Part 14: Electrical installation design, selection and installation of equipment, including initial inspection	EN IEC 60079-14	-
IEC 60364-5-53	-	Low-voltage electrical installations Part 5-53: Selection and erection of electrical equipment - Protection, isolation, switching, control and monitoring	-	-
IEC 61643-11	-	Low-voltage surge protective devices - Par 11: Surge protective devices connected to low-voltage power systems - Requirements and test methods		-
IEC 61643-21	-	Low voltage surge protective devices - Part 21: Surge protective devices connected to telecommunications and signalling networks - Performance requirements and testing methods	EN 61643-21	-
IEC 62305-1	2024	Protection against lightning - Part 1: General principles	EN IEC 62305-1	2024
IEC 62305-2	2024	Protection against lightning - Part 2: Risk management	EN IEC 62305-2	2024
IEC 62305-4	2024	Protection against lightning - Part 4: Electrical and electronic systems within structures	EN IEC 62305-4	2024
IEC 62561	series	Lightning protection system components (LPSC) - Part 1: Requirements for connection components	EN IEC 62561	series

EN IEC 62305-3:2024 (E)

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 62561-1	2017	Lightning protection system components (LPSC)	EN 62561-1	2017
IEC/TS 62561-8	2018	Lightning protection system components (LPSC) - Part 8: Requirements for components for isolated LPS	-	-
ISO 3864-1	-	Graphical symbols - Safety colours and safety signs - Part 1: Design principles for safety signs and safety markings	-	-



Edition 3.0 2024-09

INTERNATIONAL STANDARD

NORME INTERNATIONALE



Protection against lightning –
Part 3: Physical damage to structures and life hazard

Protection contre la foudre -

Partie 3: Dommages physiques sur les structures et risques humains

INTERNATIONAL ELECTROTECHNICAL COMMISSION

COMMISSION ELECTROTECHNIQUE INTERNATIONALE

ICS 29.020, 91.120.40 ISBN 978-2-8322-9059-0

Warning! Make sure that you obtained this publication from an authorized distributor. Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.

CONTENTS

FC	REWOR	D	7
IN	TRODUC	TION	10
1	Scope		12
2	•	tive references	
3		and definitions	
4		ng protection system (LPS)	
_	•	Class of LPS	
		Design of the LPS	
5		al lightning protection system	
J		Seneral	
	5.1.1	Application of an external LPS	
	5.1.1	Application of an isolated LPS or an electrically insulated LPS	
	5.1.3	Use of natural components	
		Air-termination systems	
	5.2.1	General	
	5.2.2	Positioning	
	5.2.3	Air terminations against flashes to the side of tall structures	
	5.2.4	Construction	
	5.2.5	Natural components	26
	5.3 E)own-conductor systems	29
	5.3.1	General	29
	5.3.2	Positioning of an isolated LPS	29
	5.3.3	Positioning of an attached LPS	29
	5.3.4	Construction	30
	5.3.5	Natural components	32
	5.3.6	Test joints and test points	33
	5.4 E	Earth-termination system	
	5.4.1	General	
	5.4.2	Earthing arrangement in general conditions	
	5.4.3	Installation of earth electrodes	
	5.4.4	Natural earth electrodes	
		Components	
	5.5.1	General	
	5.5.2	Fixing	
	5.5.3	Connections	
	5.5.4 5.6 N	Components of an electrically insulated LPS Materials and dimensions	
	5.6.1	Materials	
	5.6.2	Dimensions	
6		al lightning protection system	
Ü		Seneral	
		ightning equipotential bonding	
	6.2.1	General	
	6.2.2	Lightning equipotential bonding for metal installations	
	6.2.3	Lightning equipotential bonding for external conductive parts	
	6.2.4	Lightning equipotential bonding for internal systems	
		G G - 4	

	6.2.5	Lightning equipotential bonding for lines connected to the structure to be protected	44
	6.3	Separation distance	
	6.3.1	General approach	45
	6.3.2	• •	
7		enance and inspection of an LPS	
	7.1	General	
	7.2	Maintenance	
	7.3	Objective of inspections	
	7.3 7.4	Need for inspection	
8		·	40
0		ction measures against injury to human beings due to touch and step ges	48
	8.1	Protection measures against touch voltages	
	8.2	Protection measures against step voltages	
Λr		normative) Minimum cross-section of the entering cable screen to avoid	
		s sparking	50
	•	informative) Evaluation of the separation distance s	
	,	normative) Additional requirements for LPSs in the case of structures with a	
		plosion	56
	C.1	General	
	C.2	Basic requirements	
	C.2.1	·	
	C.2.1		
	C.2.2	•	
	C.3	ů .	
		Structures containing solid explosive material	
	C.4	Structures with hazardous areas	
	C.4.1		
	C.4.2		
	C.4.3		
	C.4.4		
	C.4.5	1 11	
_	C.5	Maintenance and inspection	59
		informative) Explanatory text concerning the design, construction, nce and inspection of lightning protection systems	60
1114			
	D.1	General	
	D.2	Structure of Annex D.	
	D.3	Additional information	
	D.4	Design of lightning protection systems (LPSs)	
	D.4.1		
	D.4.2	3	
	D.5	External lightning protection system	
	D.5.1		
	D.5.2	•	
	D.5.3	•	
	D.5.4	Earth-termination systems	108
	D.5.5	Components	117
	D.5.6	Materials and dimensions	117
	D.6	Internal lightning protection system	122
	D 6 1	Conoral	122

D.6.2 L	ightning equipotential bonding (EB)	122
D.6.3 E	Electrical isolation of the external LPS	128
D.6.4 F	Protection against effects of induced currents in internal systems	132
D.7 Maint	enance and inspection of the LPS	132
D.7.1 C	General	132
D.7.2	nspection	132
D.7.3 T	esting	134
D.7.4 N	Maintenance	135
Bibliography		136
Figure 1 – Prote	ction angle corresponding to the class of LPS	22
Figure 2 – Conta	acting the rolling sphere with the structure to be protected	23
Figure 3 – Appli	cation of the protection angle method	24
Figure 4 – Loop	in a down conductor	31
Figure 5 – Minin	num length $l_{f 1}$ of each earth electrode according to the class of LPS	34
_	lues of coefficient k_{C} in the case of a wire air-termination system	
Figure B.2 – Val	lues of coefficient $k_{\mathbf{C}}$ in the case of a multiple down-conductor system	52
-	lues of coefficients k_{C} in the case of multiple down conductors with an	
interconnecting	ring of down conductors at each level	53
=	ues of coefficient $k_{\mathbf{C}}$ in the case of a meshed air-termination system,	
with a multiple of	lown-conductor system	54
Figure D.1 – LP	S design flow diagram	61
	ace protected by two parallel air-termination horizontal wires or two	60
	ods $(r > d/2)$	
-	signing the protection volume of catenary wire	
=	rizontal section of the protected area at a given height	71
	ree examples of design of attached LPS air termination according to dair-termination design	72
	-	73
	eral protected volume constructed from the rolling sphere and the name and the name and the sphere	74
•	plication of the protection angle method for lateral impact with heights	
		75
Figure D.8 – Air	termination and visually concealed conductors for buildings less than	
	sloping roofs	76
	nstruction of an LPS using natural components on the roof of the	
structure		78
	ositioning of the external LPS on a structure made of insulating	
	ood or bricks) with a height up to 60 m with flat roof and with roof	70
	onnection of natural air-termination rod to air-termination conductor	
· ·		01
	onstruction of the bridging between the segments of the metallic	82
·	ir-termination rod used for protection of a metallic roof fixture with	•
•	estallations which are not bonded to the air-termination system	83
Figure D.14 – M	ethod of achieving electrical continuity on metallic parapet capping	84
_	xamples of air termination for a house with an antenna using an	
		86

Figure D.16 – Installation of external LPS on a structure of insulating material with different roof levels	90
Figure D.17 – LPS design for a cantilevered part of a structure	
Figure D.18 – Use of a metallic facade covering as a natural down-conductor system on a structure of steel-reinforced concrete	
Figure D.19 – Use of metallic facade as natural down-conductor system and connection of facade supports	94
Figure D.20 – Connection of the continuous strip windows to a metal facade covering	95
Figure D.21 – Measuring the overall electrical resistance of steel reinforcement	96
Figure D.22 – Equipotential bonding in a structure with a steel reinforcement	98
$ \label{eq:constraint} \textbf{Figure D.23-Typical methods of joining reinforcing rods in concrete (where permitted)} \\$	99
Figure D.24 – Examples of clamps used as joints between reinforcing rods and conductors	100
Figure D.25 – Examples of connection points to the reinforcement in a reinforced concrete wall	101
Figure D.26 – Internal down conductors in industrial structures	104
Figure D.27 – Installation of bonding conductors on plate-like prefabricated reinforced concrete parts by means of bolted or welded conductor links	106
Figure D.28 – Installation of bonding conductors in reinforced concrete structures and flexible bonds between two reinforced concrete parts	107
Figure D.29 – Combined foundation earth electrode	112
Figure D.30 – Construction of foundation earth ring for structures of different foundation design	113
Figure D.31 – Example of a Type A earthing arrangement with a vertical conductor type electrode	114
Figure D.32 – Example of a Type A earthing arrangement with a vertical rod type electrode	115
Figure D.33 – Meshed earth-termination system of a plant	118
Figure D.34 – Example of an equipotential bonding arrangement	124
Figure D.35 – Example of bonding arrangement in a structure with multiple entry points of external conductive parts using a ring electrode for interconnection of bonding bars	125
Figure D.36 – Example of bonding in the case of multiple entry points of external conductive parts and an electric power or communication line, using an internal ring conductor for interconnection of the bonding bars	126
Figure D.37 – Example of bonding arrangement in a structure with multiple entry points of external conductive parts entering the structure above ground level	127
Figure D.38 – Directions for calculations of the separation distance, s , for a worse case lightning interception point at a distance, l , from the reference point according to 6.3	130
Table 1 – Relation between lightning protection levels (LPL) and class of LPS (see IEC 62305-1)	18
Table 2 – Values of rolling sphere radius, mesh size and protection angle corresponding to the class of LPS	21
Table 3 – Minimum thickness of metal sheets or metal pipes in air-termination systems	27
Table 4 – Maximum temperature rises ΔT (K) of inner surface and time duration t_{50} (s) for different thickness t'' (mm) and long strokes according to LPL I (Q_{LONG} = 200 C)	28
Table 5 – Preferred values of the distance between down conductors by LPS according to the class of LPS	30

Table 6 – LPS materials and conditions of use	37
Table 7 – Material, configuration and minimum cross-sectional area of air-termination conductors, air-termination rods, earth lead-in conductors and down conductors	39
Table 8 – Material, configuration and minimum dimensions of earth electrodes	40
Table 9 – Minimum dimensions of conductors connecting different bonding bars or connecting bonding bars to the earth-termination system	42
Table 10 – Minimum dimensions of conductors connecting internal metal installations to the bonding bar	42
Table 11 – Separation distance – Values of coefficient k_{j}	45
Table 12 – Separation distance – Values of coefficient k_{m}	45
Table 13 – Separation distance – Approximated values of coefficient $k_{ extsf{C}}$	47
Table A.1 – Cable length to be considered according to the condition of the screen	50
Table D.1 – Suggested fixing centres	75

INTERNATIONAL ELECTROTECHNICAL COMMISSION

PROTECTION AGAINST LIGHTNING -

Part 3: Physical damage to structures and life hazard

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at https://patents.iec.ch. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62305-3 has been prepared by IEC technical committee 81: Lightning protection. It is an International Standard.

This third edition cancels and replaces the second edition published in 2010. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Minimum thicknesses of metal sheets or metal pipes are given in Table 4 for air-termination systems where it is necessary to prevent hot-spot problems. Maximum temperature rises ΔT (K) and time duration t_{50} (s) for different thicknesses and long strokes are also given.
- b) Cross-reference to the IEC 62561 series is made for the use of reliable, stable, safe and appropriate LPS components.

- c) The application of two methods general and simplified for separation distance calculation is clarified.
- d) Some changes to the requirements for continuity of steel reinforcement are made.
- e) Annex C is revised to address comments from IEC subcommittee 31J.
- f) Revision of positioning of air-termination conductors are modified according to the three accepted methods. A more precise description of the methods for positioning of the airtermination systems is made according to the complexity of structures to be protected. The main text has been simplified, Annex A has been deleted and all detailed information has been moved to Annex D.
- g) Information on the protection of green roofs is introduced in Annex D.
- h) Information on the protection of protruding parts on facades of tall buildings is introduced in Annex D:
- i) a new definition of "electrically insulated LPS" has been introduced to distinguish it from an LPS both electrically and physically isolated from the structure, with a slight modification of the other LPS definitions.

The text of this International Standard is based on the following documents:

Draft	Report on voting
81/764/FDIS	81/767/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this International Standard is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62305 series, published under the general title *Protection against lightning*, can be found on the IEC website.

The following differing practices of a less permanent nature exist in the countries indicated below.

In Austria, Annex C shall not be applied and is replaced by the National standard ÖVE/ÖNORM EN 62305-3 Beiblatt 1:2013-11-01 Blitzschutz – Teil 3: Schutz von baulichen Anlagen und Personen – Beiblatt 1: Zusätzliche Informationen für bauliche Anlagen mit explosionsgefährdeten Bereichen. In Austria, Annex C shall be classified as "Informative".

In Germany, the need for lightning protection is determined by, and the class of required LPS shall be selected according to, a national annex to the third edition of IEC 62305-1 (including an option for a risk assessment following the third edition of IEC 62305-2).

In Germany, for a metallic or electrically-continuous connected reinforced concrete framework, in addition, DIN EN 62305-3 Beiblatt 1 shall be applied.

In Germany, 8.1 condition b) is not applied – see DIN EN 62305-3 Beiblatt 1. Instead, the alternate measures, as described in DIN EN 62305-3 Beiblatt 1, shall be applied.

In Germany, for 8.2, the alternate measures, as described in DIN EN 62305-3 Beiblatt 1, shall be applied.

In Japan, when using country-specific lightning protection components, the manufacturer and/or lightning protection designer shall explain that the component will withstand the electromagnetic effects of lightning currents and possible accidental stresses without damage.

In Italy, a separation distance is not required in structures with metallic or electrically-continuous connected reinforced concrete framework according to 5.3.5.

In Italy, in reinforced concrete structures, the reinforcement may be used for equipotential bonding. In this case, if a ring electrode is not yet installed and connected to the reinforcement steels, a ring conductor welded or bolted to the steel reinforcement will be installed, to which the bonding bars should be connected via welded conductors.

In the Netherlands, in some situations, special fasteners which are necessary and which are not available on the commercial market and are not tested according to IEC 62561-4 (because of a small number of required special fasteners), must comply with the lateral and axial test mentioned in IEC 62561-4. A written statement of passing these lateral and axial tests must be issued by the designer and/or the installer of the LPS and must be a part of the commissioning documents.

In South Africa, the class of required LPS shall be selected on the basis of a risk assessment of either the second edition of IEC 62305-2 or the third edition of IEC 62305-2. This note applies also for D.4.1 and D.4.2.1.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- · withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

This part of IEC 62305 deals with the protection, in and around a structure, against physical damage and injury to human beings due to touch and step voltages.

The main and most effective measure for protection of structures and its content against physical damage is considered to be a lightning protection system (LPS). It usually consists of both external and internal lightning protection measures.

An external LPS is intended to

- a) intercept a lightning flash to the structure (with an air-termination system),
- b) conduct the lightning current safely towards earth (using a down-conductor system),
- c) disperse the lightning current into the earth (using an earth-termination system).

NOTE The purpose of the external LPS is to protect the structure from a direct lightning strike by providing the preferred attachment points, conducting and dispersing the lightning current. It will not significantly influence the attachment process between the structure and the lightning to increase or reduce the number of direct lightning strikes (S1) to the structure.

An internal LPS prevents dangerous sparking within the structure using either equipotential bonding or a separation distance (and hence isolation) between the external LPS (as defined in 3.2) and other electrically conducting elements internal to the structure.

Main protection measures against injury to human beings due to touch and step voltages are intended to:

- 1) reduce dangerous current flowing through bodies by either insulating exposed conductive parts, or by increasing the surface soil resistivity, or both,
- 2) reduce the occurrence of dangerous touch and step voltages by either physical restrictions or warning notices, or both.

The type and location of an LPS should be carefully considered in the initial design of a new structure, thereby enabling maximum advantage to be taken of the electrically conductive parts of the structure. By so doing, design and construction of an integrated installation is made easier, the overall aesthetic aspects can be improved, and the effectiveness of the LPS can be increased at minimum cost and effort.

Access to the ground and the proper use of foundation steelwork for the purpose of forming an effective earth termination may well be impossible once construction work on a site has commenced. Therefore, soil resistivity and the nature of the earth should be considered at the earliest possible stage of a project. This information is fundamental to the design of an earth-termination system and can influence the foundation design work for the structure.

Regular consultation between LPS designers and installers, architects and builders is essential in order to achieve the best result at minimum cost.

If lightning protection is to be added to an existing structure, every effort should be made to ensure that it conforms to the principles of this document. The design of the type and location of an LPS should take into account the features of the existing structure.

When safety is involved and significant changes are made to the structure or its use changes, consideration of updating the lightning protection installation to the present edition of this document is recommended.

National or local laws and regulations can provide guidance or minimum requirements on the application of this document. This includes specifying the class of a required LPS for specific applications without a risk assessment, the conditions of separation and bonding of other earth-termination systems, the additional information given in Annex C for LPSs in case of structures with a risk of explosion, and the mandatory requirements for inspection, testing and maintenance of LPSs given in Clause 7.

PROTECTION AGAINST LIGHTNING -

Part 3: Physical damage to structures and life hazard

1 Scope

This part of IEC 62305 provides the requirements for protection of a structure against physical damage by means of a lightning protection system (LPS), and for protection against injury to human beings due to touch and step voltages in the vicinity of an LPS (see IEC 62305-1).

This document is applicable to the:

- a) design, installation, inspection and maintenance of an LPS for structures without limitation of their height,
- b) establishment of measures for protection against injury to human beings primarily due to touch and step voltages.

NOTE 1 Specific requirements for an LPS in structures dangerous to their surroundings due to the risk of explosion are provided in Annex C.

NOTE 2 This document is not intended to provide protection against failures of electrical and electronic systems due to overvoltages. Specific requirements for such cases are provided in IEC 62305-4.

NOTE 3 Specific requirements for the protection against lightning of wind turbines are reported in IEC 61400-24 [1] 1.

NOTE 4 Specific requirements for the protection against overvoltage of photovoltaic systems are reported in IEC 61643-32 [2] and in IEC 62305-4:2024, Annex F.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60079-10-1:2020, Explosive atmospheres – Part 10-1: Classification of areas – Explosive gas atmospheres

IEC 60079-10-2:2015, Explosive atmospheres – Part 10-2: Classification of areas – Explosive dust atmospheres

IEC 60079-14, Explosive atmospheres – Part 14: Electrical installations design, selection and erection

IEC 60364-5-53, Low-voltage electrical installations – Part 5-53: Selection and erection of electrical equipment – Devices for protection for safety, isolation, switching, control and monitoring

IEC 61643-11, Low-voltage surge protective devices – Part 11: Surge protective devices connected to low-voltage power systems – Requirements and test methods

Numbers in square brackets refer to the Bibliography.

IEC 61643-21, Low-voltage surge protective devices – Part 21: Surge protective devices connected to telecommunications and signalling networks – Performance requirements and testing methods

IEC 62305-1:2024, Protection against lightning - Part 1: General principles

IEC 62305-2:—2, Protection against lightning – Part 2: Risk management

IEC 62305-4:2024, Protection against lightning – Part 4: Electrical and electronic systems within structures

IEC 62561 (all parts), Lightning protection system components (LPSC)

IEC 62561-1:2017³, Lightning protection system components (LPSC) – Part 1: Requirements for connection components

IEC TS 62561-8:2018, Lightning protection system components (LPSC) – Part 8: Requirements for components for isolated LPS

ISO 3864-1, Graphical symbols – Safety colours and safety signs – Part 1: Design principles for safety signs and safety markings

Third edition under preparation. Stage at the time of publication IEC FDIS 62305-2:2024.

³ Withdrawn.