

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Measurement procedures for materials used in photovoltaic modules – Part 8-1: Electrically conductive adhesive (ECA) – Measurement of material properties

(IEC TS 62788-8-1:2024)

Nationellt förord

En teknisk specifikation, TS, utarbetad inom IEC är avsedd att ge vägledning beträffande specifikationer eller provningsmetoder eller ge specifikationer för teknikområden under snabb utveckling. Ett förslag till internationell standard, som det inte varit möjligt att nå tillräcklig enighet kring, kan också fastställas som TS, för att användas på försök (som förstandard) och för att efter eventuella justeringar eller bearbetningar senare fastställas som internationell standard. En teknisk specifikation ska omprövas inom tre år.

ICS 27.160.00

Detta dokument är fastställt av SEK Svensk Elstandard, som också kan lämna upplysningar om **säkerheten**.
Postadress: Box 1042, 172 21 Sundbyberg
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1042
172 21 Sundbyberg
Tel 08-444 14 00
elstandard.se

TECHNICAL SPECIFICATION



**Measurement procedures for materials used in photovoltaic modules –
Part 8-1: Electrically conductive adhesive (ECA) – Measurement of material
properties**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 27.160

ISBN 978-2-8322-8735-4

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope.....	7
2 Normative references	7
3 Terms and definitions	8
4 Test procedures	12
4.1 General.....	12
4.2 General characteristics	12
4.2.1 Visual inspection	12
4.2.2 Density	12
4.2.3 Viscosity.....	13
4.2.4 Thixotropic index	14
4.2.5 Fineness.....	15
4.3 Mechanical characteristics	16
4.3.1 Tensile strength / elongation at break	16
4.3.2 Storage normal modulus and loss normal modulus.....	19
4.4 Adhesive characteristics	21
4.4.1 Lap shear strength.....	21
4.4.2 Peel strength	23
4.5 Electrical characteristics	25
4.5.1 Volume resistivity	25
4.5.2 Contact resistivity	28
4.6 Thermal characteristics	32
4.6.1 Coefficient of thermal expansion (CTE).....	32
4.6.2 Solids content.....	34
4.7 Conditions of use	35
4.7.1 General	35
4.7.2 Shelf life	35
4.7.3 Pot life	36
5 Uniform characterization form (UCF)	37
5.1 Purpose	37
5.2 Details of the UCF	37
5.3 Reporting requirements.....	38
6 Data sheet.....	38
6.1 Purpose	38
6.2 Details of the data sheet	38
6.3 Reporting requirements.....	39
7 Product identification sheet (label).....	39
Annex A (normative) Sampling for lap shear strength test.....	40
A.1 Sampling for on-line test	40
A.2 Sampling for off-line test.....	41
Annex B (normative) Sampling for volume resistivity test	42
Annex C (normative) Sampling of contact resistivity between silver electrode and ECA	44
Annex D (normative) Sampling of contact resistivity between PV ribbon and ECA.....	46
Annex E (informative) Estimate of deviation and elimination of outliers	49

E.1	General.....	49
E.2	Estimate of deviation	49
E.3	Z score	49
E.4	Outliers elimination	49
	Bibliography.....	51
	Figure 1 – Shape of dumb-bell test specimen (ISO 37:2017).....	16
	Figure 2 – Die for dumb-bell test specimen	16
	Figure 3 – Schematic diagram of tensile strength and elongation at break test.....	18
	Figure 4 – Schematic diagram of modulus specimen installation	20
	Figure 5 – Schematic diagram of lap shear strength test.....	22
	Figure 6 – Schematic diagram of peel strength test (180° peel)	24
	Figure 7 – Schematic diagram of volume resistivity test tooling.....	26
	Figure 8 – Schematic diagram of volume resistivity test	27
	Figure 9 – Schematic diagram of contact resistivity test between ECA and silver electrode	30
	Figure 10 – Schematic diagram of contact resistivity test between ECA and PV ribbon	31
	Figure 11 – LR scatter plot and linear fit curve	31
	Figure 12 – Schematic diagram of ECA life time at various stages	35
	Figure A.1 – Schematic sampling diagram of lap shear strength test (on-line).....	40
	Figure A.2 – Picture of ECA on the top of the electrode of a solar cell	40
	Figure A.3 – Picture of a final specimen slice cut from the bonded assembly	41
	Figure A.4 – Schematic sampling diagram of lap shear strength test (off-line).....	41
	Figure B.1 – Schematic sampling diagram of volume resistivity test	42
	Figure B.2 – Picture of a volume resistivity test specimen after curing	43
	Figure C.1 – Schematic sampling diagram of ECA and silver electrode contact resistivity test.....	44
	Figure C.2 – Schematic of an EVA and electrode contact resistivity test specimen	45
	Figure D.1 – Schematic sampling diagram of ECA and PV ribbon contact resistivity test.....	47
	Figure D.2 – Schematic of an ECA and PV ribbon contact resistivity test specimen	48
	Table 1 – Dimensions of dies for dumb-bell test specimens	17
	Table 2 – Uniform characterization form (UCF) for an ECA	37
	Table 3 – Minimum required characteristics for the datasheet	39
	Table E.1 – Contact resistance between ECA and silver electrode.....	49
	Table E.2 – Contact resistance between ECA and silver electrode with z scores.....	50

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MEASUREMENT PROCEDURES FOR MATERIALS USED
IN PHOTOVOLTAIC MODULES –****Part 8-1: Electrically conductive adhesive (ECA) –
Measurement of material properties**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC TS 62788-8-1 has been prepared by IEC technical committee 82: Solar photovoltaic energy systems. It is a Technical Specification.

The text of this Technical Specification is based on the following documents:

Draft	Report on voting
82/2200/DTS	82/2241/RVDTS

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this Technical Specification is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

A list of all parts in the IEC 62788 series, published under the general title *Measurement procedures for materials used in photovoltaic modules*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

IMPORTANT – The "colour inside" logo on the cover page of this document indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Electrically conductive adhesive (ECA) is a material composed of conductive fillers blended with an organic adhesive polymer matrix. Already widely used as an interconnect material in electronic packaging and interconnection technologies for electronic devices, ECA is beginning to replace metallic solders as an innovative interconnection method in recent designs of photovoltaic (PV) modules. In a typical shingled PV module, solar cells are cut into strips and these solar cell strips overlap each other. ECA is applied in between the top electrode of one cell strip and the bottom electrode of the adjacent cell strip to form the electric interconnection. In some back-contact PV module designs, ECA allows the interconnection of solar cells' rear busbars to a conductive backsheet. In some PV modules where the solar cells are sensitive to high soldering temperatures, ECA is used to connect PV ribbons to the electrodes of the solar cells. The solar cell interconnections based on ECA can effectively reduce mechanical stress, shading loss and interconnect ohmic loss, and have been profiled as a promising alternative to traditional soldering process.

ECA can be used for wiring and surface assembly in PV modules. Initial performance and environmental endurance in application are highly dependent on its inherent material characteristics. For instance, adhesive properties are the primary requirement for ECA. Good adhesion between ECA and the adherends enables the structural integrity and long-term durability of the bonded joint over its service lifetime. Furthermore, the electrical performances of ECA, including volume resistance and contact resistance, are essential for the output performance and field durability of PV modules. Other characteristics such as viscosity, fineness, and conditions of use have a significant impact on the process conditions in manufacturing.

It is impractical to perform all the tests on ECA at the PV module level. Evaluation of the inherent material characteristics of ECA is highly desirable for pre-qualification of materials. This document defines test methods for key characteristics of ECA intended for use in photovoltaic modules.

The material property tests in this document cover general characteristics, mechanical characteristics, adhesion characteristics, electrical characteristics, thermal characteristics and the conditions of use.

MEASUREMENT PROCEDURES FOR MATERIALS USED IN PHOTOVOLTAIC MODULES –

Part 8-1: Electrically conductive adhesive (ECA) – Measurement of material properties

1 Scope

This document defines test methods and datasheet reporting requirements for key characteristics of ECA used in photovoltaic modules, involving mechanical characteristics, adhesive characteristics, electrical characteristics, thermal characteristics, etc.

The object of this document is to offer a standard test procedure to ECA manufacturers for product design, production and quality control, and to PV module manufacturers for the purpose of material screening, material inspection, process control, and failure analysis.

This document is intended to be applied to ECA used in solar PV modules.

For non-conductive adhesives or tapes used in PV modules, the applicable test methods except for electrical characteristics in this document may be used.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60068-1, *Environmental testing – Part 1: General and guidance*

IEC TS 61836, *Solar photovoltaic energy systems – Terms, definitions and symbols*

IEC TS 62788-2, *Measurement procedures for materials used in photovoltaic modules – Part 2: Polymeric materials – Frontsheets and backsheets*

ISO/IEC Guide 98-3:2008, *Uncertainty of measurement – Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

ISO 37:2017, *Rubber, vulcanized or thermoplastic – Determination of tensile stress-strain properties*

ISO 291, *Plastics – Standard atmospheres for conditioning and testing*

ISO 1524:2020, *Paints, varnishes and printing inks – Determination of fineness of grind*

ISO 2393, *Rubber test mixes – Preparation mixing and vulcanization – Equipment and procedures*

ISO 2811-1, *Paints and varnishes – Determination of density – Part 1: Pycnometer method*

ISO 4587, *Adhesives – Determination of tensile lap-shear strength of rigid-to-rigid bonded assemblies*

ISO 4664-1:2022, *Rubber, vulcanized or thermoplastic – Determination of dynamic properties – Part 1: General guidance*

ISO 5893, *Rubber and plastics test equipment – Tensile, flexural and compression types (constant rate of traverse) – Specification*

ISO 7500-2, *Metallic materials – Verification of static uniaxial testing machines – Part 2: Tension creep testing machines – Verification of the applied force*

ISO 7886-1, *Sterile hypodermic syringes for single use – Part 1: Syringes for manual use*

ISO 8510-2, *Adhesives – Peel test for a flexible-bonded-to-rigid test specimen assembly – Part 2: 180 degree peel*

ISO 10365, *Adhesives – Designation of main failure patterns*

ISO 11358-1, *Plastics – Thermogravimetry (TG) of polymers – Part 1: General principles*

ISO 11358-2, *Plastics – Thermogravimetry (TG) of polymers – Part 2: Determination of activation energy*

ISO 11359-1, *Plastics – Thermomechanical analysis (TMA) – Part 1: General principles*

ISO 11359-2:2021, *Plastics – Thermomechanical analysis (TMA) – Part 2: Determination of coefficient of linear thermal expansion and glass transition temperature*

ISO 16525-1:2014, *Adhesives – Test methods for isotropic electrically conductive adhesives – Part 1: General test methods*

ISO 16525-2:2014, *Adhesives – Test methods for isotropic electrically conductive adhesives – Part 2: Determination of electrical characteristics for use in electronic assemblies*

ISO 17212, *Structural adhesives – Guidelines for surface preparation of metals and plastics prior to adhesive bonding*

ISO 23529:2016, *Rubber – General procedures for preparing and conditioning test pieces for physical test methods*

ASTM D1337-10, *Standard practice for storage life of adhesives by viscosity and bond strength*

ASTM D4287-00, *Standard Test Method for High – Shear Viscosity Using a Cone/Plate Viscometer*