

© Copyright SEK Svensk Elstandard. Reproduction in any form without permission is prohibited.

Ultraljud – Kirurgiska system – Mätning och angivande av grundläggande egenskaper

*Ultrasonics –
Surgical systems –
Measurement and declaration of the basic output characteristics*

Som svensk standard gäller europastandarden EN IEC 61847:2025. Den svenska standarden innehåller den officiella engelska språkversionen av EN IEC 61847:2025.

Nationellt förord

Europastandarden EN IEC 61847:2025

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61847, Second edition, 2025 - Ultrasonics – Surgical systems – Measurement and declaration of the basic output characteristics**

utarbetad inom International Electrotechnical Commission, IEC.

Tidigare fastställd svensk standard SS-EN 61847, utg 1:1998 med eventuella tillägg, ändringar och rättelser gäller ej fr o m 2028-07-31.

ICS 11.040.01; 17.140.50

Denna standard är fastställd av SEK Svensk Elstandard, som också kan lämna upplysningar om **sakinnehållet** i standarden.
Postadress: Box 1042, 172 21 Sundbyberg
Telefon: 08 - 444 14 00.
E-post: sek@elstandard.se. Internet: elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a mätning, säkerhet och provning och för utförande, skötsel och dokumentation av elprodukter och elanläggningar.

Genom att utforma sådana standarder blir säkerhetsfordringar tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1042
172 21 Sundbyberg
Tel 08-444 14 00
elstandard.se

English Version

Ultrasonics - Surgical systems - Measurement and declaration of the basic output characteristics (IEC 61847:2025)

Ultrasons - Systèmes chirurgicaux - Mesurage et
déclaration des caractéristiques d'émission de base
(IEC 61847:2025)

Ultraschall - Chirurgische Systeme - Messung und
Deklaration der grundlegenden Ausgangsgrößen
(IEC 61847:2025)

This European Standard was approved by CENELEC on 2025-06-24. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Türkiye and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

European foreword

The text of document 87/894/FDIS, future edition 2 of IEC 61847, prepared by TC 87 "Ultrasonics" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN IEC 61847:2025.

The following dates are fixed:

- latest date by which the document has to be implemented at national (dop) 2026-07-31 level by publication of an identical national standard or by endorsement
- latest date by which the national standards conflicting with the (dow) 2028-07-31 document have to be withdrawn

This document supersedes EN 61847:1998 and all of its amendments and corrigenda (if any).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

Any feedback and questions on this document should be directed to the users' national committee. A complete listing of these bodies can be found on the CENELEC website.

Endorsement notice

The text of the International Standard IEC 61847:2025 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standard indicated:

IEC 60601-1 NOTE Approved as EN 60601-1

IEC 80601-2-58 NOTE Approved as EN IEC 80601-2-58

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 Where an International Publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Up-to-date information on the latest versions of the European Standards listed in this annex is available here: www.cencenelec.eu.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60500	-	Underwater acoustics - Hydrophones - Properties of hydrophones in the frequency range 1 Hz to 500 kHz	EN 60500	-

INTERNATIONAL STANDARD

NORME INTERNATIONALE

Ultrasonics – Surgical systems – Measurement and declaration of the basic output characteristics

Ultrasons – Systèmes chirurgicaux – Mesurage et déclaration des caractéristiques d'émission de base

CONTENTS

FOREWORD.....	4
INTRODUCTION	6
1 Scope.....	7
2 Normative references.....	8
3 Terms and definitions.....	8
4 List of symbols	12
5 General measurement requirements	13
5.1 Operating conditions	13
5.2 Test conditions for the measurement of acoustic power	13
5.2.1 General.....	13
5.2.2 For systems which make direct contact with tissue	13
5.2.3 For systems which make minimal contact with tissue	14
5.2.4 For systems which make no contact with tissue.....	14
5.3 Preparation for measurements	14
5.3.1 Preparation of the applicator	14
5.3.2 Preparation of the water	14
5.3.3 Preparation of the system	14
6 Measurement procedures	14
6.1 Primary tip vibration excursion	14
6.1.1 General.....	14
6.1.2 Optical microscope method	14
6.1.3 Laser vibrometer method	15
6.1.4 Feedback voltage method.....	15
6.2 Secondary tip vibration excursion	15
6.2.1 General.....	15
6.2.2 Optical microscope.....	15
6.3 Drive frequency	16
6.3.1 General.....	16
6.3.2 Frequency counter method.....	16
6.3.3 Spectrum analyser method.....	16
6.4 Tip vibration frequency	16
6.4.1 General.....	16
6.4.2 Vibrometer method.....	16
6.4.3 Hydrophone method	16
6.5 Output acoustic power.....	17
6.5.1 General.....	17
6.5.2 Output acoustic power – Hydrophone method	17
6.5.3 Output acoustic power – Calorimeter method	18
6.6 Directivity pattern	18
6.7 Primary tip vibration excursion modulation	19
6.7.1 General.....	19
6.7.2 Laser vibrometer method	19
6.8 Duty cycle.....	19
6.9 Primary acoustic output area	20
6.10 Secondary acoustic output area	20
7 Declaration of output characteristics	20

Annex A (informative) Measurement methods and conditions	25
A.1 Optical microscope method.....	25
A.2 Vibrometer method	25
A.3 Output acoustic power using the calorimeter method	25
A.4 Output acoustic power using the pressure method	26
A.4.1 General.....	26
A.4.2 Measurement experience with ultrasonic surgical systems	26
A.5 Feedback voltage method.....	27
A.6 Influence of air bubbles and contaminations	27
A.7 Test tank	27
A.8 Derivation of formula for output acoustic power for the case of a dipole.....	27
Annex B (informative) Theory of operation of ultrasonic surgical systems	30
B.1 Overview	30
B.2 System description	30
B.3 Possible mechanisms of tissue interaction.....	31
B.4 Typical values of output and discussion of parameters	31
B.5 Operating conditions	32
Bibliography.....	33
Figure 1 – Measuring the primary and secondary tip vibration excursion	22
Figure 2 – Example of a primary acoustic output area	23
Figure 3 – Measuring the pressure field	23
Figure 4 – Illustration of the method of determining duty cycle from an oscilloscope trace	24
Figure A.1 – A typical relationship between tip vibration amplitude and acoustic output	29
Figure A.2 – Schematic diagram of the theoretical model geometry for the tip immersed below the surface of the water	29

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**ULTRASONICS – SURGICAL SYSTEMS –
MEASUREMENT AND DECLARATION OF
THE BASIC OUTPUT CHARACTERISTICS****FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) IEC draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). IEC takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, IEC had not received notice of (a) patent(s), which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at <https://patents.iec.ch>. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 61847 has been prepared by IEC technical committee 87: Ultrasonics. It is an International Standard.

This second edition cancels and replaces the first edition published in 1998. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) The upper frequency covered by this document has been raised from 60 kHz to 120 kHz.
- b) The hydrophone method of measuring ultrasound power is now normative. Because of difficulties in using the calorimetry method of measuring ultrasound power, it is no longer the primary approach.

- c) It is recognised that some systems can have more than one mode of vibration under user control, and the measurement techniques and declarations have been updated to address this.
- d) The high-frequency component, which relates to **cavitation** developed at the **applicator tip** and the vibration amplitude at which **cavitation** occurs is addressed.
- e) Specific requirements for measurement at excursion levels where no **cavitation** is present, and extrapolation to maximum excursion level(s) are described.
- f) Guidance is provided to adapt the methodology described to more complex designs and vibration patterns, excursion directions, and their output characteristics.
- g) Guidance is provided with respect to measurement tank arrangements for different types of systems.
- h) The list of ultrasound methods and systems not covered by this document was extended to incorporate recent developments.
- i) Definitions for **cavitation** related terms were added.
- j) Requirements for the measurement of directivity characteristics of the **applicator tip** were changed.
- k) Annex A was modified and Figure A.1 was added.
- l) New literature was added, and the references to other standards were updated.

The text of this document is based on the following documents:

Draft	Report on voting
87/894/FDIS	87/900/RVD

Full information on the voting for its approval can be found in the report on voting indicated in the above table.

The language used for the development of this document is English.

This document was drafted in accordance with ISO/IEC Directives, Part 2, and developed in accordance with ISO/IEC Directives, Part 1 and ISO/IEC Directives, IEC Supplement, available at www.iec.ch/members_experts/refdocs. The main document types developed by IEC are described in greater detail at www.iec.ch/publications.

In this document the following print types are used:

- Requirements: in roman type.
- *Test specifications: in italic type.*
- Notes: in small roman type.
- Words in **bold** in the text are defined in Clause 3.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under webstore.iec.ch in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn, or
- revised.

INTRODUCTION

Ultrasonic surgical systems, operating in the 20 kHz to 120 kHz range, are used widely in ophthalmology and neurosurgery to fragment or disintegrate and aspirate unwanted tissue. Their commercial use in ophthalmology started in 1970. Their application in neurosurgery followed about 10 years later. Ultrasonic surgical systems are also widely used in oncology surgery. The use of these systems has expanded to areas such as liposuction and wound treatments.

This document defines the parameters which characterize the output and performance of open and closed site ultrasonic surgical systems and indicates which parameters should be declared. In addition, measurement procedures are described so that technically qualified people will be able to report on the parameters in a uniform and understandable fashion. An open surgical site is one in which the area of use is large relative to the size of the **applicator tip** being inserted thus precluding any increase in pressure of the organ due to an imbalance of irrigant flow and suction flow. An example of a closed surgical site is an eye where the incision is closely controlled.

This document does not provide any guidance on what is the resultant safety or efficacy of systems described by these parameters. While available data indicate that **inertial cavitation** is an important component of efficacy for certain applications, other effects such as acoustic streaming can be more important in other applications. Overall, it is important that manufacturers provide users with quantified acoustic and vibrational output metrics, so that systems can be properly compared, and so that users can improve their surgical technique by minimizing output while maintaining surgical efficacy.

It is recognized that manufacturers can develop systems with complicated vibrational patterns and **applicator tip** geometries. In order to properly compare acoustic output dynamics of such system, this document describes acoustic pressure measurements to be taken, which, when combined with excursion and frequency information, allow for the derivation of the effective acoustic output area. This area is fundamental to the operation of ultrasound surgical systems and is a key metric for system and **applicator tip** comparison.

It is recognized that there are difficulties performing acoustic measurements when **cavitation**, either inertial or non-inertial, occurs. Therefore, this document describes measurements performed at low vibration excursion levels when no **cavitation** is present, with the acoustic output at higher excursions linearly extrapolated from the low-level measurements. The excursion level at which **cavitation** is first detected is also important information for the user. Cavitation measurement techniques are discussed in other standards currently under development.

ULTRASONICS – SURGICAL SYSTEMS – MEASUREMENT AND DECLARATION OF THE BASIC OUTPUT CHARACTERISTICS

1 Scope

This document specifies:

- the essential non-thermal output characteristics of ultrasonic surgical units;

NOTE 1 One of the parameters of interest is **output acoustic power**. This document primarily addresses the low-frequency (under 120 kHz) component of the total delivered energy. The high-frequency component, which relates to **cavitation** developed at the tip, is discussed in Clause A.4.

- methods of measurement of these output characteristics;
- those characteristics to be declared by the manufacturers of such equipment.

NOTE 2 In the interest of clarity, a straight tubular shape is used in the basic description of the parameters and measurements to be made. Guidance is provided to the user of this document to adapt the basic methodology described to more complex designs as required. It is recognized that complex designs and vibration patterns are design features of many surgical systems, and therefore it is important that output characteristics be declared for those conditions.

This document is applicable to equipment which meets the criteria of a), b) and c) below:

- a) ultrasonic surgical systems operating in the frequency range 20 kHz to 120 kHz; and
- b) ultrasonic surgical systems whose use is the fragmentation, emulsification, debridement, or cutting of human tissue, whether or not those effects are delivered in conjunction with tissue removal or coagulation; and
- c) ultrasonic surgical systems in which an acoustic wave is conducted by means of a specifically designed wave guide to deliver energy to the surgical site.

NOTE 3 Examples of these types of systems are surgical aspirators, phacoemulsifiers, intracorporeal lithotripters, end-cutting systems, ultrasonic liposuction systems, etc.

NOTE 4 The upper frequency limit has been set to accommodate more recently developed systems operating at higher frequencies than IEC 61847:1998. The techniques of this document are also useful for systems operating at higher frequencies that use the same mechanisms of action.

This document is not applicable to:

- lithotripsy equipment which uses extracorporeally induced pressure pulses, focused through liquid conducting media and the soft tissues of the body;
- surgical systems used as part of the therapeutic process (hyperthermia systems);
- surgical systems whose mechanism of action is through frictional heat generated by tissue in contact with the wave guide, e.g. clamp coagulators or clamping vibrational cutters;
- surgical systems whose mechanism of action is through focused ultrasound for either thermal degradation (high intensity focused ultrasound – HIFU or HITU) or **cavitation** erosion (Histotripsy) of tissue remote from the ultrasound transducer;
- surgical systems whose mechanism of action is through erosion of hard tissues in contact with the **applicator tip**, e.g. bone cutting or drilling.

NOTE 5 Limited declaration requirements for surgical systems whose mechanism of action is through erosion of hard tissues in contact with the **applicator tip** are listed in Clause 7.

This document does not deal with the effectiveness or safety of ultrasonic surgical systems. This document does not deal with airborne noise from the systems, which can affect operators and patients.

NOTE 6 Airborne noise levels are addressed in IEC 60601-1 [1]¹.

NOTE 7 The safety of ultrasonic surgical systems for ophthalmic applications are addressed in IEC 80601-2-58 [2].

NOTE 8 Throughout this document, the term accuracy means the overall uncertainty expressed at the 95 % confidence level.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60500, *Underwater acoustics – Hydrophones – Properties of hydrophones in the frequency range 1 Hz to 500 kHz*

¹ Numbers in square brackets refer to the Bibliography.