



IEC 61800-7-1

Edition 1.0 2007-11

INTERNATIONAL STANDARD

**Adjustable speed electrical power drive systems –
Part 7-1: Generic interface and use of profiles for power drive systems –
Interface definition**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE

XD

ICS 29.200; 35.100.05

ISBN 2-8318-9365-8

CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	12
2 Normative references	12
3 Terms, definitions and abbreviated terms	13
3.1 Preamble.....	13
3.2 General definitions	13
3.3 Specific definitions	17
3.3.1 Common definitions	17
3.3.2 Definitions for Annex A	17
3.3.3 Definitions for Annex B	18
3.3.4 Definitions for Annex C	19
3.3.5 Definitions for Annex D	20
3.4 Abbreviated terms	22
3.4.1 Common abbreviations	22
3.4.2 Abbreviations for Annex A	22
3.4.3 Abbreviations for Annex B	22
3.4.4 Abbreviations for Annex C	22
3.4.5 Abbreviations for Annex D	22
3.5 Conventions	23
4 General architecture	23
4.1 Generic PDS interface.....	23
4.2 Typical structure of automation systems	27
4.3 Structure of the logical PDS	28
4.4 Use cases of the PDS	30
4.4.1 General	30
4.4.2 Use case engineering	31
4.4.3 Use case operation-control	31
5 Functional elements	32
5.1 Device identification FE.....	32
5.1.1 General	32
5.1.2 Parameters.....	32
5.2 Device Control FE	33
5.2.1 General	33
5.2.2 I/O data	33
5.2.3 States.....	34
5.2.4 Parameters.....	35
5.3 Communication FE	35
5.3.1 General	35
5.3.2 I/O data	36
5.3.3 States.....	36
5.3.4 Parameters.....	38
5.4 Basic drive FE	38
5.4.1 General	38
5.4.2 I/O data	39

5.4.3	States.....	40
5.4.4	Parameters.....	41
5.5	Optional application FE	42
6	Application modes	42
6.1	General.....	42
6.2	Torque control.....	43
6.3	Velocity control.....	44
6.4	Position control	45
7	Profile specific extensions	46
8	Structure for annexes	46
8.1	General.....	46
8.2	Structure of the annexes	47
Annex A (normative) Mapping to Profile CiA 402 drive and motion control		50
Annex B (normative) Mapping to profile CIP Motion™		62
Annex C (normative) Mapping to profile PROFIdrive		74
Annex D (normative) Mapping to Profile SERCOS		87
Bibliography.....		100
Figure 1 – Structure of IEC 61800-7.....		11
Figure 2 – Definition of power drive system.....		23
Figure 3 – Example of system structures for position-control applications		24
Figure 4 – Examples of system structures for velocity-control applications.....		25
Figure 5 – Examples of system structures for torque-control applications		26
Figure 6 – Typical structure of automation systems (adapted from IEC/TR 62390).....		27
Figure 7 – Structure of the PDS with functional elements.....		29
Figure 8 – Functional Elements (FE) in the logical PDS		30
Figure 9 – Use case for the generic PDS interface.....		31
Figure 10 – The generic interface in the use case operation		32
Figure 11 – Device control FE state-chart diagram.....		34
Figure 12 – Device control FE state transition table		35
Figure 13 – Communication FE state-chart diagram.....		37
Figure 14 – Communication FE state transition table		37
Figure 15 – Optional communication FE state-chart diagram.....		38
Figure 16 – Optional communication FE state transition table		38
Figure 17 – Basic drive FE state-chart diagram.....		40
Figure 18 – Basic drive FE state transition table		40
Figure 19 – Optional basic drive FE state-chart diagram		41
Figure 20 – Optional basic drive FE state transition table		41
Figure 21 – Torque control application mode		43
Figure 22 – Torque control with velocity feedback application mode		43
Figure 23 – Velocity preset application mode.....		44
Figure 24 – Velocity control application mode		44

Figure 25 – Velocity control with position feedback application mode.....	45
Figure 26 – Position preset application mode.....	45
Figure 27 – Position control application mode.....	46
Figure A.1 – CiA 402 logical power drive system model	51
Figure B.1 – Object structure of the logical PDS	63
Figure B.2 – Object structure of the logical PDS	63
Figure B.3 – Motion Axis Object state machine	66
Figure C.1 – Overview of communication devices and services in PROFIdrive	75
Figure C.2 – Structure of the PROFIdrive device.....	76
Figure C.3 – PROFIdrive Axis type Drive Object	77
Figure C.4 – Functional block diagram of the PROFIdrive Axis type DO	78
Figure C.5 – Mapping of communication FE states.....	81
Figure D.1 – Topology example	88
Figure D.2 – State machine of Basic Drive FE	93
Table 1 – Structures within the scope of this part of IEC 61800-7	27
Table 2 – Parameters in the device identification FE.....	33
Table 3 – Status values for the device control FE	34
Table 4 – Command values for the device control FE.....	34
Table 5 – Parameters in the device control FE.....	35
Table 6 – Status values for the communication FE (see Figure 13)	36
Table 7 – Command values for the communication FE (see Figure 13)	36
Table 8 – Status values for the optional communication FE (see Figure 15).....	36
Table 9 – Command values for the optional communication FE (see Figure 15)	36
Table 10 – Status values of the basic drive FE.....	39
Table 11 – Optional status values for the basic drive FE	39
Table 12 – Command values for basic drive FE	39
Table 13 – Optional command values for the basic drive FE	40
Table 14 – Possible generic application modes.....	42
Table 15 – Set-point values for generic application modes.....	42
Table 16 – Mapping of names to profiles.....	46
Table 17 – Structure of annexes	47
Table 18 – Profile specific terms	48
Table 19 – Supported application modes	48
Table 20 – I/O data for profile torque mode.....	48
Table 21 – I/O data for profile velocity mode.....	49
Table 22 – I/O data for profile position mode	49
Table A.1 – Profile specific terms.....	50
Table A.2 – Drive device identification parameters.....	52
Table A.3 – Status values for the device control FE	52
Table A.4 – Command values for the device control FE	52
Table A.5 – Parameters in the device control FE.....	53
Table A.6 – Status values for the communication FE	53

Table A.7 – Command values for the communication FE	53
Table A.8 – Status values for the basic drive FE	54
Table A.9 – Command values for the basic drive FE	54
Table A.10 – Basic drive FE parameters	55
Table A.11 – Optional application functions FE parameters	55
Table A.12 – Supported application modes	56
Table A.13 – I/O data for profile torque mode	56
Table A.14 – Parameter for profile torque mode	56
Table A.15 – I/O data for cyclic sync torque mode	57
Table A.16 – Parameter for cyclic sync torque mode	57
Table A.17 – I/O data for velocity mode	57
Table A.18 – Parameter for velocity mode	57
Table A.19 – I/O data for profile velocity mode	58
Table A.20 – Parameter for profile velocity mode	58
Table A.21 – I/O data for cyclic sync velocity mode	58
Table A.22 – Parameter for cyclic sync velocity mode	58
Table A.23 – I/O data for profile position mode	59
Table A.24 – Parameter for profile position mode	59
Table A.25 – I/O data for interpolated position mode	60
Table A.26 – Parameter for interpolated position mode	60
Table A.27 – I/O data for cyclic sync position mode	60
Table A.28 – Parameter for cyclic sync position mode	61
Table B.1 – Profile specific terms	62
Table B.2 – Mapping of parameters for the device identification FE	65
Table B.3 – Mapping of status values for the device control FE	65
Table B.4 – Mapping of command values for the device control FE	65
Table B.5 – Mapping of parameters for the device control FE	67
Table B.6 – Mapping of status values for the communication FE	67
Table B.7 – Mapping of command values for the communication FE	68
Table B.8 – Mapping of status values for the optional communication FE	68
Table B.9 – Mapping of command values for the optional communication FE	68
Table B.10 – Status values for the basic drive FE	69
Table B.11 – Command values for the basic drive FE	69
Table B.12 – Drive Control Mode values for the basic drive FE	69
Table B.13 – Command Data Set values for the basic drive FE	70
Table B.14 – Actual Data Set values for the basic drive FE	70
Table B.15 – Status Data Set values for the basic drive FE	71
Table B.16 – Supported application modes	72
Table B.17 – Set-point values for the generic application modes	72
Table B.18 – I/O data for profile torque mode	72
Table B.19 – I/O data for profile velocity mode	73
Table B.20 – I/O data for profile position mode	73
Table C.1 – Profile specific terms	74

Table C.2 – Parameters for device identification	79
Table C.3 – Status values for the device control FE	80
Table C.4 – Command values for the device control FE	80
Table C.5 – Device control parameters	80
Table C.6 – Status values of the basic drive FE	82
Table C.7 – Command values of the basic drive FE	82
Table C.8 – Status values for the optional basic drive FE	83
Table C.9 – Command values for the optional basic drive FE	83
Table C.10 – Device control parameters	83
Table C.11 – Supported application modes	84
Table C.12 – I/O data for profile velocity mode	85
Table C.13 – I/O data for profile velocity control mode with position feedback	85
Table C.14 – I/O data for profile velocity control mode (process technology)	86
Table C.15 – I/O data for profile position preset	86
Table C.16 – I/O data for profile position mode	86
Table D.1 – Profile specific terms	87
Table D.2 – Device identification parameters	90
Table D.3 – Status values for the device control FE	90
Table D.4 – Command values for the device control FE	91
Table D.5 – Parameters for the device control FE	91
Table D.6 – Status values for the basic drive and communication FE	93
Table D.7 – Command values for the basic drive and communication FE	94
Table D.8 – IDN for operation modes	94
Table D.9 – Supported application modes	95
Table D.10 – Additional application modes	96
Table D.11 – I/O data for profile torque mode	96
Table D.12 – Configuration data for torque control	96
Table D.13 – I/O data for profile velocity mode	97
Table D.14 – Configuration data for velocity control	97
Table D.15 – I/O data for profile position mode	98
Table D.16 – Configuration data for position control	98

INTERNATIONAL ELECTROTECHNICAL COMMISSION

ADJUSTABLE SPEED ELECTRICAL POWER DRIVE SYSTEMS –**Part 7-1: Generic interface and use of profiles
for power drive systems –
Interface definition**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

The International Standard IEC 61800-7-1 has been prepared by subcommittee SC 22G: Adjustable speed electric drive systems incorporating semiconductor power converters, of IEC technical committee TC 22: Power electronic systems and equipment.

The text of this standard is based on the following documents:

FDIS	Report on voting
22G/183/FDIS	22G/191/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of the IEC 61800 series, under the general title *Adjustable speed electrical power drive systems*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

The IEC 61800 series is intended to provide a common set of specifications for adjustable speed electrical power drive systems.

IEC 61800-7 describes a generic interface between control systems and power drive systems. This interface can be embedded in the control system. The control system itself can also be located in the drive (sometimes known as "smart drive" or "intelligent drive").

A variety of physical interfaces is available (analogue and digital inputs and outputs, serial and parallel interfaces, fieldbuses and networks). Profiles based on specific physical interfaces are already defined for some application areas (e.g. motion control) and some device classes (e.g. standard drives, positioner). The implementations of the associated drivers and application programmers interfaces are proprietary and vary widely.

IEC 61800-7 defines a set of common drive control functions, parameters, and state machines or description of sequences of operation to be mapped to the drive profiles.

IEC 61800-7 provides a way to access functions and data of a drive that is independent of the used drive profile and communication interface. The objective is a common drive model with generic functions and objects suitable to be mapped on different communication interfaces. This makes it possible to provide common implementations of motion control (or velocity control or drive control applications) in controllers without any specific knowledge of the drive implementation.

There are several reasons to define a generic interface:

For a drive device manufacturer

- Less effort to support system integrators
- Less effort to describe drive functions because of common terminology
- The selection of drives does not depend on availability of specific support

For a control device manufacturer

- No influence of bus technology
- Easy device integration
- Independent of a drive supplier

For a system integrator

- Less integration effort for devices
- Only one understandable way of modeling
- Independent of bus technology

Much effort is needed to design a motion control application with several different drives and a specific control system. The tasks to implement the system software and to understand the functional description of the individual components may exhaust the project resources. In some cases, the drives do not share the same physical interface. Some control devices just support a single interface which will not be supported by a specific drive. On the other hand, the functions and data structures are often specified with incompatibilities. This requires the system integrator to write special interfaces for the application software and this should not be his responsibility.

Some applications need device exchangeability or integration of new devices in an existing configuration. They are faced with different incompatible solutions. The efforts to adopt a solution to a drive profile and to manufacturer specific extensions may be unacceptable. This will reduce the degree of freedom to select a device best suited for this application to the selection of the unit which will be available for a specific physical interface and supported by the controller.

This part of IEC 61800-7 is divided into a generic part and several annexes as shown in Figure 1. The drive profiles types for CiA 402¹, CIP Motion^{TM2}, PROFIdrive³ and SERCOS interface^{TM4} are mapped to the generic interface in the corresponding annex. The annexes have been submitted by open international network or fieldbus organizations which are responsible for the content of the related annex and use of the related trademarks.

The different profile types 1, 2, 3 and 4 are specified in IEC 61800-7-201, IEC 61800-7-202, IEC 61800-7-203 and IEC 61800-7-204.

IEC 61800-7-301, IEC 61800-7-302, IEC 61800-7-303 and IEC 61800-7-304 specify how the profile types 1, 2, 3 and 4 are mapped to different network technologies (such as CANopen⁵, EtherCAT^{TM6}, Ethernet Powerlink^{TM7}, DeviceNet^{TM8}, ControlNet^{TM9}, EtherNet/IP^{TM10}, PROFIBUS¹¹, PROFINET¹² and SERCOS interface).

-
- 1 CiA 402 is a trade name of CAN in Automation, e.V. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade name holder or any of its products. Compliance to this profile does not require use of the trade name CiA 402.
 - 2 CIP MotionTM is a trade name of Open DeviceNet Vendor Association, Inc. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name CIP MotionTM. Use of the trade name CIP MotionTM requires permission of Open DeviceNet Vendor Association, Inc.
 - 3 PROFIdrive is a trade name of PROFIBUS International. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade name holder or any of its products. Compliance to this profile does not require use of the trade name PROFIdrive. Use of the trade name PROFIdrive requires permission of PROFIBUS International.
 - 4 SERCOSTM and SERCOS interfaceTM are trade names of SERCOS International e.V. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade name holder or any of its products. Compliance to this profile does not require use of the trade names SERCOS or SERCOS interface. Use of the trade names SERCOS and SERCOS interface requires permission of the trade name holder.
 - 5 CANopen is an acronym for Controller Area Network *open* and is used to refer to EN 50325-4.
 - 6 EtherCATTM is a trade name of Beckhoff, Verl. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name EtherCATTM. Use of the trade name EtherCATTM requires permission of the trade name holder.
 - 7 Ethernet PowerlinkTM is a trade name of B&R, control of trade name use is given to the non profit organization EPSG. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name Ethernet PowerlinkTM. Use of the trade name Ethernet PowerlinkTM requires permission of the trade name holder.
 - 8 DeviceNetTM is a trade name of Open DeviceNet Vendor Association, Inc. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name DeviceNetTM. Use of the trade name DeviceNetTM requires permission of Open DeviceNet Vendor Association, Inc.
 - 9 ControlNetTM is a trade name of ControlNet International, Ltd. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name ControlNetTM. Use of the trade name ControlNetTM requires permission of ControlNet International, Ltd.
 - 10 EtherNet/IPTM is a trade name of ControlNet International, Ltd. and Open DeviceNet Vendor Association, Inc. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trademark holder or any of its products. Compliance to this profile does not require use of the trade name EtherNet/IPTM. Use of the trade name EtherNet/IPTM requires permission of either ControlNet International, Ltd. or Open DeviceNet Vendor Association, Inc.
 - 11 PROFIBUS is a trade name of PROFIBUS International. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade name holder or any of its products. Compliance to this profile does not require use of the trade name PROFIBUS. Use of the trade name PROFIBUS requires permission of PROFIBUS International.
 - 12 PROFINET is a trade name of PROFIBUS International. This information is given for the convenience of users of this International Standard and does not constitute an endorsement by IEC of the trade name holder or any of its products. Compliance to this profile does not require use of the trade name PROFINET. Use of the trade name PROFINET requires permission of PROFIBUS International.




Figure 1 – Structure of IEC 61800-7

ADJUSTABLE SPEED ELECTRICAL POWER DRIVE SYSTEMS –

Part 7-1: Generic interface and use of profiles for power drive systems – Interface definition

1 Scope

IEC 61800-7 specifies profiles for power drive systems (PDS) and their mapping to existing communication systems by use of a generic interface model.

The functions specified in this part of IEC 61800-7 are not intended to ensure functional safety. This requires additional measures according to the relevant standards, agreements and laws.

This part of IEC 61800-7 specifies a generic interface between power drive system(s) (PDS) and the application control program in a controller. The generic PDS interface is not specific to any particular communication network technology. Annexes of this part of IEC 61800-7 specify the mapping of the different drive profiles types onto the generic PDS interface.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-5-2, *Industrial communication networks – Fieldbus specifications – Part 5-2: Application layer service definition – Type 2 elements*

IEC 61158-5-3, *Industrial communication networks – Fieldbus specifications – Part 5-3: Application layer service definition – Type 3 elements*

IEC 61158-5-10, *Industrial communication networks – Fieldbus specifications – Part 5-10: Application layer service definition – Type 10 elements*

IEC 61158-6-2, *Industrial communication networks – Fieldbus specifications – Part 6-2: Application layer protocol specification – Type 2 elements*

IEC 61158-6-3, *Industrial communication networks – Fieldbus specifications – Part 6-3: Application layer protocol specification – Type 3 elements*

IEC 61158-6-10, *Industrial communication networks – Fieldbus specifications – Part 6-10: Application layer protocol specification – Type 10 elements*

IEC 61800-7 (all parts), *Adjustable speed electrical power drive systems – Generic interface and use of profiles for power drive systems*

IEC 61800-7-1, *Adjustable speed electrical power drive systems – Part 7-1: Generic interface and use of profiles for power drive systems – Interface definition*

IEC 61800-7-201, *Adjustable speed electrical power drive systems – Part 7-201: Generic interface and use of profiles for power drive systems – Profile type 1 specification*

IEC 61800-7-202, *Adjustable speed electrical power drive systems – Part 7-202: Generic interface and use of profiles for power drive systems – Profile type 2 specification*

IEC 61800-7-203, *Adjustable speed electrical power drive systems – Part 7-203: Generic interface and use of profiles for power drive systems – Profile type 3 specification*

IEC 61800-7-204, *Adjustable speed electrical power drive systems – Part 7-204: Generic interface and use of profiles for power drive systems – Profile type 4 specification*

IEC 61800-7-301, *Adjustable speed electrical power drive systems – Part 7-301: Generic interface and use of profiles for power drive systems – Mapping of profile type 1 to network technologies*

IEC 61800-7-302, *Adjustable speed electrical power drive systems – Part 7-302: Generic interface and use of profiles for power drive systems – Mapping of profile type 2 to network technologies*

IEC 61800-7-303, *Adjustable speed electrical power drive systems – Part 7-303: Generic interface and use of profiles for power drive systems – Mapping of profile type 3 to network technologies*

IEC 61800-7-304, *Adjustable speed electrical power drive systems – Part 7-304: Generic interface and use of profiles for power drive systems – Mapping of profile type 4 to network technologies*

IEC/TR 62390:2005, *Common automation device – Profile guideline*

EN 50325-4, *Industrial communications subsystem based on ISO 11898 (CAN) for controller-device interfaces – Part 4: CANopen*