

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Fältbuss – Del 6-10: Specifikation av protokoll i applikationsskiktet – Delar i fältbuss, Typ 10

*Industrial communication networks –
Fieldbus specifications –
Part 6-10: Application layer protocol specification –
Type 10 elements*

Som svensk standard gäller europastandarden EN 61158-6-10:2008. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61158-6-10:2008.

Nationellt förord

Europastandarden EN 61158-6-10:2008

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61158-6-10, First edition, 2007 - Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 61158-6, ersätter SS-EN 61158-6, utgåva 1, 2004.

Tidigare fastställd svensk standard SS-EN 61158-6, utgåva 1, 2004, gäller ej fr o m 2011-02-01.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Industrial communication networks -
Fieldbus specifications -
Part 6-10: Application layer protocol specification -
Type 10 elements
(IEC 61158-6-10:2007)**

Réseaux de communication industriels -
Spécifications des bus de terrain -
Partie 6-10: Spécification des services
des couches d'application -
Éléments de type 10
(CEI 61158-6-10:2007)

Industrielle Kommunikationsnetze -
Feldbusse -
Teil 6-10: Protokollspezifikation
des Application Layer
(Anwendungsschicht) -
Typ 10-Elemente
(IEC 61158-6-10:2007)

This European Standard was approved by CENELEC on 2008-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 65C/476/FDIS, future edition 1 of IEC 61158-6-10, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61158-6-10 on 2008-02-01.

This and the other parts of the EN 61158-6 series supersede EN 61158-6:2004.

With respect to EN 61158-6:2004 the following changes were made:

- deletion of Type 6 fieldbus for lack of market relevance;
- addition of new fieldbus types;
- partition into multiple parts numbered 6-2, 6-3, ...6-20.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-11-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-02-01

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in type combinations as specified explicitly in the EN 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

IEC and CENELEC draw attention to the fact that it is claimed that compliance with this standard may involve the use of patents as follows, where the [xx] notation indicates the holder of the patent right:

The following patent rights for Type 10 have been announced by [HI]:

WO publication	Title (WO)
WO 99/046908	Local network, especially ethernet network, with redundancy properties and redundancy manager

The following patent rights for Type 10 have been announced by [SI]:

WO publication	Title (WO)
WO 00/026731	Automation system and method for accessing the functionality of hardware components
WO 02/043336	System and method for the parallel transmission of real-time critical and non real-time critical data via switched data networks especially ethernet
WO 02/076033	Synchronous, clocked communication system with local input/output components and method for integrating local input/output components into such a system
WO 03/028258	Method for synchronising nodes of a communication system
WO 03/028259	Communications system and method for synchronising a communications cycle
WO 04/030284	Method for permanent redundant transmission of data telegrams in communication systems
EP 1453230	Synchronisation in einem schaltbaren Datennetz

IEC and CENELEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights are registered with IEC. Information may be obtained from:

[HI]: Hirschmann Automation and Control GmbH
Stuttgarter Straße 45-51
D-72654 Neckartenzlingen
Germany

[SI]: Siemens AG
CT IP L&T
Hr. Hans-Jörg Müller
Otto-Hahn-Ring 6
D-81739 Munich
Germany

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC and CENELEC shall not be held responsible for identifying any or all such patent rights.

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 61158-6-10:2007 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61158-3-3	NOTE Harmonized as EN 61158-3-3:2008 (not modified).
IEC 61158-4-3	NOTE Harmonized as EN 61158-4-3:2008 (not modified).
IEC 61784-1	NOTE Harmonized as EN 61784-1:2008 (not modified).
IEC 61784-2	NOTE Harmonized as EN 61784-2:2008 (not modified).

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60559	- ¹⁾	Binary floating-point arithmetic for microprocessor systems	HD 592 S1	1991 ²⁾
IEC 61158-5-10	- ¹⁾	Industrial communication networks - Fieldbus specifications - Part 5-10: Application layer service definition - Type 10 elements	EN 61158-5-10	2008 ²⁾
IEC 61784-3-3	- ¹⁾	Industrial communication networks - Profiles - Part 3-3: Functional safety fieldbuses - Additional specifications for CPF 3	EN 61784-3-3	2008 ²⁾
ISO/IEC 646	1991	Information technology - ISO 7-bit coded character set for information interchange	-	-
ISO/IEC 7498-1	- ¹⁾	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	EN ISO/IEC 7498-1	1995 ²⁾
ISO/IEC 8822	- ¹⁾	Information technology - Open Systems Interconnection - Presentation service definition	-	-
ISO/IEC 8824-2	- ¹⁾	Information technology - Abstract Syntax Notation One (ASN.1): Information object specification	-	-
ISO/IEC 9545	- ¹⁾	Information technology - Open Systems Interconnection - Application Layer structure	-	-
ISO/IEC 10731	- ¹⁾	Information technology - Open Systems Interconnection - Basic reference model - Conventions for the definition of OSI services	-	-
ISO 8601	- ¹⁾	Data elements and interchange formats - Information interchange - Representation of dates and times	EN 28601	1992 ²⁾
IEEE 802	2001	IEEE Standard for Local and Metropolitan Area Networks: Overview and Architecture	-	-
IEEE 802.1AB	2005	IEEE Standard for Local and Metropolitan Area Networks: Station and Media Access Control Connectivity Discovery	-	-

¹⁾ Undated reference.

²⁾ Valid edition at date of issue.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEEE 802.1D	2004	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	2005	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-
IEEE 802.3	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and Metropolitan Area Networks - Specific requirements - Part 3: Carrier Sense Multiple Access with Collision Detection	-	-
IEEE 802.11	1999 ³⁾	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 11: Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications	-	-
IEEE 802.15.1	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and Metropolitan Area Networks - Specific requirements - Part 15.1: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Wireless Personal Area Networks (WPANs)	-	-
IETF RFC 768	- ¹⁾	User Datagram Protocol	-	-
IETF RFC 791	- ¹⁾	Internet Protocol	-	-
IETF RFC 792	- ¹⁾	Internet Control Message Protocol	-	-
IETF RFC 826	- ¹⁾	Ethernet Address Resolution Protocol	-	-
IETF RFC 1034	- ¹⁾	Domain names - concepts and facilities	-	-
IETF RFC 1112	- ¹⁾	Host Extensions for IP Multicasting	-	-
IETF RFC 2131	- ¹⁾	Dynamic Host Configuration Protocol	-	-
IETF RFC 2132	- ¹⁾	DHCP Options and BOOTP Vendor Extensions	-	-
IETF RFC 2365	- ¹⁾	Administratively Scoped IP Multicast	-	-
IETF RFC 2474	- ¹⁾	Definition of the Differentiated Services Field (DS Field) in the IPv4 and IPv6 Headers	-	-
IETF RFC 2674	- ¹⁾	Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions	-	-
IETF RFC 2737	- ¹⁾	Entity MIB (Version 2)	-	-

³⁾ IEEE 802.11:1999 is superseded by IEEE 802.11:2007.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IETF RFC 2863	- ¹⁾	The Interfaces Group MIB	-	-
IETF RFC 3418	- ¹⁾	Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)	-	-
IETF RFC 3490	- ¹⁾	Internationalizing Domain Names in Applications (IDNA)	-	-
IETF RFC 3621	- ¹⁾	Power Ethernet MIB	-	-
IETF RFC 3636	- ¹⁾	Definitions of Managed Objects for IEEE 802.3-Medium Attachment Units (MAUs)	-	-
The Open Group C706	- ¹⁾	CAE Specification DCE11: Remote Procedure Call	-	-

CONTENTS

INTRODUCTION.....	20
1 Scope.....	21
1.1 General.....	21
1.2 Specifications.....	21
1.3 Conformance.....	21
2 Normative references	22
3 Terms, definitions, abbreviations, symbols and conventions	24
3.1 Referenced terms and definitions	24
3.2 Additional terms and definitions for distributed automation	24
3.3 Additional terms and definitions for decentralized periphery	26
3.4 Additional abbreviations and symbols for distributed automation	33
3.5 Additional abbreviations and symbols for decentralized periphery	34
3.6 Additional abbreviations and symbols for media redundancy	35
3.7 Conventions	35
3.8 Conventions used in state machines	42
4 Application layer protocol specification for common protocols.....	45
4.1 FAL syntax description	45
4.2 Transfer syntax	48
4.3 Discovery and basic configuration	57
4.4 Precision time control.....	79
4.5 Media redundancy.....	147
4.6 Real-time cyclic.....	175
4.7 Real-time acyclic.....	192
4.8 Remote procedure call	203
4.9 Link layer discovery.....	218
4.10 MAC bridges	226
4.11 Virtual bridges	249
4.12 IP suite.....	256
4.13 Domain name system	259
4.14 Dynamic host configuration	259
4.15 Simple network management.....	259
4.16 Common DLL mapping protocol machines (DMPM)	269
5 Application layer protocol specification for distributed automation	279
5.1 FAL syntax description	279
5.2 Transfer syntax	303
5.3 FAL protocol state machines	305
5.4 AP context state machine	306
5.5 FAL service protocol machines (FSPM).....	306
5.6 Application relationship protocol machine (ARPM).....	390
5.7 DLL mapping protocol machines (DMPMs)	394
5.8 Protocol options	398
6 Application layer protocol specification for decentralized periphery.....	399
6.1 FAL syntax description	399
6.2 Transfer syntax	408
6.3 FAL protocol state machines	526

6.4	AP-Context state machine	527
6.5	FAL service protocol machines (FSPMs)	527
6.6	Application relationship protocol machines (ARPMs)	592
6.7	DLL mapping protocol machines (DMPMs)	683
Annex A (informative)	Filtering data base (FDB)	684
Annex B (informative)	Establishing of a companion AR	687
Annex C (informative)	Establishing of a device access AR	688
Annex D (informative)	Establishing of an AR (simple procedure)	689
Annex E (informative)	Establishing of an AR (accelerated procedure)	690
Annex F (informative)	Establishing of an AR (fast startup procedure)	692
Annex G (informative)	Example of the upload, storage, and retrieval procedure	693
Bibliography		695
Figure 1	– Common structure of specific fields	39
Figure 2	– Common structure of specific fields for octet 1 (high)	40
Figure 3	– Common structure of specific fields for octet 2 (low)	40
Figure 4	– Common structure of specific fields for octet 1 (high)	41
Figure 5	– Common structure of specific fields for octet 2	41
Figure 6	– Common structure of specific fields for octet 3	41
Figure 7	– Common structure of specific fields for octet 4 (low)	42
Figure 8	– Coding of the data type BinaryDate	49
Figure 9	– Encoding of Time Of Day value	50
Figure 10	– Encoding of Time Difference value	50
Figure 11	– Encoding of Network Time value	51
Figure 12	– Encoding of Network Time Difference value	51
Figure 13	– Timescale correspondence between PTCP_Time and CycleCounter	85
Figure 14	– Message timestamp point	88
Figure 15	– Four message timestamps	88
Figure 16	– Line delay protocol with follow up	89
Figure 17	– Line delay protocol without follow up	89
Figure 18	– Line delay measurement	91
Figure 19	– Model parameter for GSDML usage	92
Figure 20	– Bridge delay measurement	93
Figure 21	– Delay accumulation	93
Figure 22	– Worst case accumulated time deviation of synchronization	94
Figure 23	– Scheme for measurement of deviation	94
Figure 24	– Measurement of deviation	95
Figure 25	– Sending Sync-Frame without Follow Up-Frame	95
Figure 26	– Sending Sync-Frame with FollowUp-Frame	96
Figure 27	– Forwarding Sync- and FollowUp-Frame	96
Figure 28	– Transition between Synchronization Variants	97
Figure 29	– State transition diagram of delay request	98
Figure 30	– State transition diagram of delay response	106
Figure 31	– Overview of PTCP	112

Figure 32 – State transition diagram of BMA	113
Figure 33 – State transition diagram of MSM	130
Figure 34 – State transition diagram of BRC	140
Figure 35 – State transition diagram of SRX	144
Figure 36 – MRM protocol machine for MRP	152
Figure 37 – MRC protocol machine	158
Figure 38 – MRM protocol machine.....	167
Figure 39 – MRC protocol machine for MRRT	173
Figure 40 – Structure of the CycleCounter	177
Figure 41 – Structuring of the protocol machines within the DMPM (bridge)	270
Figure 42 – Error message structure	279
Figure 43 – Coding scheme of ITEMQUALITYDEF	284
Figure 44 – Relationship among protocol machines	306
Figure 45 – State transition diagram of FSPM	320
Figure 46 – State transition diagram of ARPM	392
Figure 47 – State transition diagram of DMPM	397
Figure 48 – Classification of diagnosis, maintenance and qualified	473
Figure 49 – Definition of PLL window	486
Figure 50 – Detection of dropped frames — appear	495
Figure 51 – Detection of dropped frames — disappear.....	495
Figure 52 – Relationship among Protocol Machines	526
Figure B.1 – Establishing of a companion AR	687
Figure C.1 – Establishing of a device access AR	688
Figure D.1 – Accelerated establishing of an IOAR (simple procedure).....	689
Figure E.1 – Accelerated establishing of an IOAR without error	690
Figure E.2 – Accelerated establishing of an IOAR with “late” error	691
Figure F.1 – Establishing of an IOAR using fast startup	692
Figure G.1 – Example of upload with storage.....	693
Figure G.2 – Example of retrieval with storage.....	694
Table 1 – State machine description elements	42
Table 2 – Description of state machine elements	43
Table 3 – Conventions used in state machines	43
Table 4 – IEEE 802.3 DLPDU syntax	45
Table 5 – IEEE 802.11 DLPDU syntax	46
Table 6 – IEEE 802.15.1 DLPDU syntax	46
Table 7 – SourceAddress.....	52
Table 8 – DCP_MulticastMACAdd	52
Table 9 – PTCP_MulticastMACAdd	53
Table 10 – MRP OUI.....	53
Table 11 – MRPMulticastMACAdd	54
Table 12 – MRRTMulticastMACAdd	54
Table 13 – LT (Length/Type).....	54

Table 14 – TagControllInformation.Priority	55
Table 15 – FrameID range 1	55
Table 16 – FrameID range 2	55
Table 17 – FrameID range 3	56
Table 18 – FrameID range 4	56
Table 19 – FrameID range 5	56
Table 20 – FrameID range 6	56
Table 21 – FrameID range 7	57
Table 22 – FrameID range 8	57
Table 23 – FrameID range 9	57
Table 24 – DCP APDU syntax	58
Table 25 – DCP substitutions	59
Table 26 – ServiceID	61
Table 27 – ServiceType for request	61
Table 28 – ServiceType for response	61
Table 29 – List of options	62
Table 30 – List of suboptions	63
Table 31 – SuboptionDHCP	65
Table 32 – BlockQualifier with option IP	66
Table 33 – BlockQualifier with option DeviceProperties, DHCP, and ManufacturerSpecific	66
Table 34 – BlockError	66
Table 35 – BlockInfo for SuboptionIPParameter	67
Table 36 – Bit 1 and Bit 0 of BlockInfo for SuboptionIPParameter	67
Table 37 – Bit 7 of BlockInfo for SuboptionIPParameter	67
Table 38 – BlockInfo for all other suboptions	67
Table 39 – DeviceInitiativeValue	67
Table 40 – SignalValue	68
Table 41 – DeviceRoleDetails	69
Table 42 – IPAddress	69
Table 43 – Subnetmask	70
Table 44 – StandardGateway	70
Table 45 – DCPUCS state table	73
Table 46 – DCPUCR state table	75
Table 47 – DCPMCS state table	77
Table 48 – DCPMCR state table	79
Table 49 – PTCP APDU syntax	80
Table 50 – PTCP substitutions	80
Table 51 – PTCP_TLVHeader.Type	81
Table 52 – PTCP_Delay10ns	81
Table 53 – PTCP_Delay1ns.Value	82
Table 54 – PTCP_Delay1ns.Sign	82
Table 55 – PTCP_CumulativeFrequencyOffset	82

Table 56 – PTCP_SequenceID	83
Table 57 – PTCP_SubType for OUI (=00-0E-CF)	83
Table 58 – PTCP_NanoSeconds	83
Table 59 – PTCP_Flags.LeapSecond	84
Table 60 – Timescale correspondence between MJD, UTC, and PTCP_EPOCHNumber	84
Table 61 – Timescale correspondence between PTCP_EPOCHNumber, PTCP_Second, PTCP_Nanosecond, CycleCounter, and SendClockFactor	84
Table 62 – PTCP_ClockStratum	86
Table 63 – PTCP_ClockRole	86
Table 64 – PTCP_RequestPortID	87
Table 65 – PTCP_SyncID	87
Table 66 – PTCP_T2TimeStamp	87
Table 67 – DelayRequest state table	100
Table 68 – Macros used by DelayRequest	104
Table 69 – Functions used by DelayRequest	105
Table 70 – DelayResponse state table	107
Table 71 – Macros used by DelayResponse	110
Table 72 – Functions used by DelayResponse	111
Table 73 – BMA state table	115
Table 74 – BMA state table – check remote	122
Table 75 – BMA state table – check local vs. remote	123
Table 76 – Macros used by BMA	125
Table 77 – Functions used by BMA	127
Table 78 – BMA_Sync_Ind	127
Table 79 – BMA_Announce_Ind	128
Table 80 – MSM state table	131
Table 81 – Macros used by MSM	136
Table 82 – Functions used by MSM	137
Table 83 – MSM_Role_Ind	137
Table 84 – MSM_Sync	138
Table 85 – MSM_Announce	139
Table 86 – BRC state table	141
Table 87 – Macros used by BRC	143
Table 88 – Macros used by the BRC	143
Table 89 – BRC_Sync_Ind	143
Table 90 – SRX state table	145
Table 91 – Functions used by SRX	146
Table 92 – MRP APDU syntax	147
Table 93 – MRP substitutions	147
Table 94 – MRP_TLVHeader.Type	148
Table 95 – MRP_Prio	148
Table 96 – MRP_PortRole	148
Table 97 – MRP_RingState	149

Table 98 – MRP_Interval	149
Table 99 – MRP_Transition.....	149
Table 100 – MRP_TimeStamp	149
Table 101 – MRP_DomainUUID	150
Table 102 – MRRT APDU syntax	150
Table 103 – MRRT substitutions	150
Table 104 – MRRT_TLVHeader.Type.....	151
Table 105 – MRRT_DomainUUID.....	151
Table 106 – Local variables of MRM protocol machine.....	153
Table 107 – MRM state machine.....	153
Table 108 – Local variables of MRC protocol machine	159
Table 109 – MRC state machine	159
Table 110 – Functions	164
Table 111 – FDB Clear Timer	166
Table 112 – Topology Change Timer	166
Table 113 – Local variables of MRM Protocol Machine for MRRT Activation	168
Table 114 – MRM state machine for MRRT Activation.....	168
Table 115 – MRC state machine for MRRT Activation	174
Table 116 – MRM and MRC functions	175
Table 117 – RTC APDU syntax.....	176
Table 118 – RTC substitutions	176
Table 119 – CycleCounter Difference.....	177
Table 120 – DataStatus.State	178
Table 121 – DataStatus.DataValid	178
Table 122 – DataStatus.ProviderState	178
Table 123 – DataStatus.StationProblemIndicator	178
Table 124 – TransferStatus for RT_CLASS_3	179
Table 125 – IOxS.Extension.....	180
Table 126 – IOCS.Instance	180
Table 127 – IOxS.DataState	180
Table 128 – PPM state table.....	182
Table 129 – Functions used by the PPM	185
Table 130 – CPM state table.....	186
Table 131 – Functions used by the CPM.....	192
Table 132 – RTA APDU syntax	192
Table 133 – RTA substitutions	193
Table 134 – PDUType.Type	193
Table 135 – PDUType.Version.....	194
Table 136 – APMS state table.....	196
Table 137 – Functions used by the APMS and APMR	199
Table 138 – A_Timer_add.....	199
Table 139 – A_Timer_event	200
Table 140 – A_Timer_remove	200

Table 141 – APMR state table	201
Table 142 – RPC APDU syntax	203
Table 143 – RPC substitutions	204
Table 144 – RPCPacketType	205
Table 145 – RPCFlags	205
Table 146 – RPCFlags2	206
Table 147 – RPCDRep.Character- and IntegerEncoding	206
Table 148 – RPCDRep Octet 2 – Floating Point Representation	206
Table 149 – RPCObjectUUID.Data4	207
Table 150 – RPCObjectUUID – defined values	207
Table 151 – RPCInterfaceUUID – defined values	208
Table 152 – RPCOperationNmb (IO device, controller and supervisor)	209
Table 153 – RPCOperationNmb for endpoint mapper	209
Table 154 – RPCDataRepresentationUUID – defined values	211
Table 155 – RPCInquiryType	212
Table 156 – RPCEPMapStatus	214
Table 157 – Values of NCAFaultStatus	216
Table 158 – Values of NCARrejectStatus	217
Table 159 – LLDP APDU syntax	218
Table 160 – LLDP substitutions	219
Table 161 – LLDP_PNIO_SubType	220
Table 162 – PTCP_PortRxDelayLocal	221
Table 163 – PTCP_PortRxDelayRemote	221
Table 164 – PTCP_PortTxDelayLocal	221
Table 165 – PTCP_PortTxDelayRemote	221
Table 166 – CableDelayLocal	222
Table 167 – RTClass2_PortStatus.State	222
Table 168 – RTClass3_PortStatus.State	222
Table 169 – RTClass3_PortStatus.Mode	223
Table 170 – MRRT_PortStatus.State	223
Table 171 – LLDP_RedPeriodBegin.Offset	223
Table 172 – LLDP_RedPeriodBegin.Valid	223
Table 173 – LLDP_OrangePeriodBegin.Offset	224
Table 174 – LLDP_OrangePeriodBegin.Valid	224
Table 175 – LLDP_GreenPeriodBegin.Offset	224
Table 176 – LLDP_GreenPeriodBegin.Valid	224
Table 177 – LLDP_LengthOfPeriod.Length	225
Table 178 – LLDP_LengthOfPeriod.Valid	225
Table 179 – IFW state table	227
Table 180 – IFW function table	233
Table 181 – S_FW state table	235
Table 182 – S_FW function table	238
Table 183 – S_FU_FW state table	241

Table 184 – S_FU_FW function table	245
Table 185 – Primitives issued by LMPM to MMAC	249
Table 186 – Primitives issued by MMAC to LMPM	249
Table 187 – Primitives issued by MMAC to MAC	249
Table 188 – Primitives issued by MAC to MMAC	250
Table 189 – MMAC state table	251
Table 190 – MMAC function table	255
Table 191 – IP/UDP APDU syntax	257
Table 192 – IP/UDP substitutions	257
Table 193 – UDP_SrcPort	258
Table 194 – UDP_DstPort	258
Table 195 – IP_DstIPAddress	258
Table 196 – IP Multicast DstIPAddress according to RFC 2365	258
Table 197 – Enterprise number	259
Table 198 – LMPM state table	271
Table 199 – LMPM macros table	275
Table 200 – LMPM function table	279
Table 201 – Error messages	280
Table 202 – VARTYPE values	283
Table 203 – ITEMQUALITYDEF values	284
Table 204 – STATEDEF values	287
Table 205 – GROUPEXCEPTIONDEF values	287
Table 206 – ACCESSRIGHTSDEF values	288
Table 207 – PERSISTDEF values	288
Table 208 – UUID values	291
Table 209 – Data format for serialized connection data	304
Table 210 – Calculation of the RT reference data size	305
Table 211 – Primitives issued by FAL User to FSPM	307
Table 212 – Primitives issued by FSPM to FAL User	314
Table 213 – FSPM state descriptions	320
Table 214 – FSPM state table	321
Table 215 – Primitives issued by FSPM to ARPM	391
Table 216 – Primitives issued by ARPM to FSPM	391
Table 217 – Parameters used with primitives exchanged between FSPM and ARPM	392
Table 218 – ARPM state descriptions	392
Table 219 – ARPM state table	393
Table 220 – Primitives issued by ARPM to DMPM	394
Table 221 – Primitives issued by DMPM to ARPM	395
Table 222 – Parameters used with primitives exchanged between ARPM and DMPM	395
Table 223 – Primitives issued by DMPM to ORPC model	396
Table 224 – Primitives issued by ORPC model to DMPM	396
Table 225 – Parameters used with primitives exchanged between DMPM and ORPC model	397

Table 226 – DMPM state descriptions	397
Table 227 – DMPM state table	398
Table 228 – IO APDU substitutions	399
Table 229 – BlockType	409
Table 230 – AlarmType	413
Table 231 – AlarmSpecifier.ChannelDiagnosis	414
Table 232 – AlarmSpecifier.ManufacturerSpecificDiagnosis	414
Table 233 – AlarmSpecifier.SubmoduleDiagnosisState	414
Table 234 – AlarmSpecifier.ARDiagnosisState	415
Table 235 – SlotNumber	415
Table 236 – SubslotNumber	415
Table 237 – Grouping of DiagnosisData	418
Table 238 – Index (user specific)	418
Table 239 – Index (subslot specific)	419
Table 240 – Index (slot specific)	420
Table 241 – Index (AR specific)	421
Table 242 – Index (API specific)	422
Table 243 – Index (device specific)	423
Table 244 – ARTYPE	423
Table 245 – IOCRMulticastMACAdd	424
Table 246 – Type 10 OUI	424
Table 247 – ARProperties.State	425
Table 248 – ARProperties.SupervisorTakeoverAllowed	425
Table 249 – ARProperties.ParametrizationServer	425
Table 250 – ARProperties.DataRate	425
Table 251 – ARProperties.DeviceAccess	426
Table 252 – ARProperties.CompanionAR	426
Table 253 – ARProperties.AcknowledgeCompanionAR	426
Table 254 – ARProperties.PullModuleAlarmAllowed	426
Table 255 – IOCRProperties.RTClass	427
Table 256 – IOCRProperties.MediaRedundancy	427
Table 257 – IOCRTagHeader.IOCRVLANID	428
Table 258 – IOCRTagHeader.IOUserPriority	428
Table 259 – IOCRTYPE	428
Table 260 – CMInitiatorActivityTimeoutFactor with ARProperties.DeviceAccess:=0	428
Table 261 – CMInitiatorActivityTimeoutFactor with ARProperties.DeviceAccess:=1	429
Table 262 – LengthIOCS	429
Table 263 – LengthIOPS	430
Table 264 – AlarmCRProperties.Priority	430
Table 265 – AlarmCRProperties.Transport	430
Table 266 – AlarmCRTagHeaderHigh.AlarmCRVLANID	431
Table 267 – AlarmCRTagHeaderHigh.AlarmUserPriority	431
Table 268 – AlarmCRTagHeaderLow.AlarmCRVLANID	431

Table 269 – AlarmCRTagHeaderLow.AlarmUserPriority	431
Table 270 – AlarmSequenceNumber	432
Table 271 – AlarmCRType	432
Table 272 – RTATimeoutFactor	432
Table 273 – RTARetries	432
Table 274 – AddressResolutionProperties.Protocol	433
Table 275 – AddressResolutionProperties.Factor	433
Table 276 – MCITimeoutFactor	434
Table 277 – ModuleIdentNumber	434
Table 278 – SubmoduleIdentNumber	435
Table 279 – ControlBlockProperties in conjunction with ControlCommand.ApplicationReady	436
Table 280 – ControlBlockProperties in conjunction with the other values of the field ControlCommand	436
Table 281 – ControlCommand.PrmEnd	436
Table 282 – ControlCommand.ApplicationReady	436
Table 283 – ControlCommand.Release	437
Table 284 – ControlCommand.Done	437
Table 285 – ControlCommand.ReadyForCompanion	437
Table 286 – DataDescription.Type	437
Table 287 – Values of ReductionRatio	439
Table 288 – Values of Phase	439
Table 289 – Values of Sequence	440
Table 290 – DataHoldFactor	440
Table 291 – WatchdogFactor	441
Table 292 – Values of FrameSendOffset	441
Table 293 – Values of ErrorCode for negative responses	442
Table 294 – Values of ErrorDecode	442
Table 295 – Coding of ErrorCode1 with ErrorDecode PNIORW	443
Table 296 – Values of ErrorCode1 and ErrorCode2 for ErrorDecode with the value PNIO	444
Table 297 – Values of ErrorCode2 for ErrorCode1 = RPC	450
Table 298 – ModuleState	450
Table 299 – SubmoduleState.AddInfo	450
Table 300 – SubmoduleState.QualifiedInfo	451
Table 301 – SubmoduleState.MaintenanceRequired	451
Table 302 – SubmoduleState.MaintenanceDemanded	451
Table 303 – SubmoduleState.DiagInfo	451
Table 304 – SubmoduleState.ARInfo	452
Table 305 – SubmoduleState.IdentInfo	452
Table 306 – SubmoduleState.FormatIndicator	452
Table 307 – SubmoduleState.Detail	453
Table 308 – SubmoduleProperties.Type	453
Table 309 – SubmoduleProperties.SharedInput	454

Table 310 – SubmoduleProperties.ReduceInputSubmoduleDataLength	454
Table 311 – SubmoduleProperties.ReduceOutputSubmoduleDataLength	454
Table 312 – SubmoduleProperties.DiscardIOXS	454
Table 313 – SubstitutionMode	455
Table 314 – SubstituteActiveFlag	455
Table 315 – InitiatorUDPRTPort	455
Table 316 – ResponderUDPRTPort	456
Table 317 – InitiatorRPCServerPort	456
Table 318 – ResponderRPCServerPort	456
Table 319 – IM_Hardware_Revision	457
Table 320 – IM_SWRevision_Functional_Enhancement	457
Table 321 – IM_SWRevision_Bug_Fix	457
Table 322 – IM_SWRevision_Internal_Change	457
Table 323 – IM_Revision_Counter	457
Table 324 – IM_Profile_ID	458
Table 325 – IM_Profile_Specific_Type	458
Table 326 – IM_Version_Major	458
Table 327 – IM_Version_Minor	458
Table 328 – IM_Date	460
Table 329 – UserStructureIdentifier	460
Table 330 – ChannelErrorType	462
Table 331 – ChannelNumber	463
Table 332 – ChannelProperties.Type	464
Table 333 – Valid combinations within ChannelProperties	465
Table 334 – Valid combinations for Alarmnotification and RecordDataRead(DiagnosisData)	466
Table 335 – ChannelProperties.Specifier	467
Table 336 – ChannelProperties.Direction	467
Table 337 – ExtChannelErrorType	467
Table 338 – ExtChannelErrorType for ChannelErrorType 0 – 0x7FFF	467
Table 339 – ExtChannelErrorType for ChannelErrorType “Data transmission impossible”	468
Table 340 – ExtChannelErrorType for ChannelErrorType “Remote mismatch”	468
Table 341 – ExtChannelErrorType for ChannelErrorType “Media redundancy mismatch”	468
Table 342 – ExtChannelErrorType for ChannelErrorType “Sync mismatch” and for ChannelErrorType “Time mismatch”	469
Table 343 – ExtChannelErrorType for ChannelErrorType “Isochronous mode mismatch”	469
Table 344 – ExtChannelErrorType for ChannelErrorType “Multicast CR mismatch”	469
Table 345 – ExtChannelErrorType for ChannelErrorType “Fiber optic mismatch”	470
Table 346 – ExtChannelErrorType for ChannelErrorType “Network component function mismatch”	470
Table 347 – Values for Accumulative Info	470
Table 348 – Values for “Fiber optic mismatch” – “Power Budget”	471

Table 349 – Values for “Network component function mismatch” – “Frame dropped”	471
Table 350 – Values for “Remote mismatch” – “Peer CableDelay mismatch”	471
Table 351 – Values for QualifiedChannelQualifier	472
Table 352 – Values for MaintenanceStatus	472
Table 353 – URRecordIndex	473
Table 354 – URRecordLength	473
Table 355 – LineDelay.Value with LineDelay.FormatIndicator == 0	474
Table 356 – LineDelay.Value with LineDelay.FormatIndicator == 1	474
Table 357 – LineDelay.FormatIndicator	475
Table 358 – RxPort	475
Table 359 – NumberOfTxPortGroups	475
Table 360 – TxPortEntry	476
Table 361 – FrameDetails.SyncFrame	477
Table 362 – FrameDetails.MeaningFrameSendOffset	477
Table 363 – MAUType	478
Table 364 – Valid combinations between MAUType and PortState	479
Table 365 – CheckSyncMode.CableDelay	479
Table 366 – CheckSyncMode.SyncMaster	480
Table 367 – MAUTypeMode.Check	480
Table 368 – DomainBoundary	480
Table 369 – MulticastBoundary	481
Table 370 – PortState	481
Table 371 – MediaType	481
Table 372 – MaxBridgeDelay	482
Table 373 – NumberOfPorts	482
Table 374 – MaxPortTxDelay	482
Table 375 – MaxPortRxDelay	482
Table 376 – SyncProperties.Role	483
Table 377 – SyncProperties.SyncClass in conjunction with Clock Master	483
Table 378 – SyncProperties.SyncClass in conjunction with Clock Slave	483
Table 379 – SyncSendFactor	484
Table 380 – SyncFrameAddress.MulticastSelection for RTASyncPDU	484
Table 381 – SyncFrameAddress.MulticastSelection for RTCSyncPDU	484
Table 382 – SyncFrameAddress.PDUType	485
Table 383 – PTCPTimeoutFactor	485
Table 384 – PLLWindow	485
Table 385 – TimeDataCycle	486
Table 386 – TimeIOInput	486
Table 387 – TimeIOOutput	487
Table 388 – TimeIOInputValid	487
Table 389 – TimeIOOutputValid	487
Table 390 – ControllerApplicationCycleFactor	487
Table 391 – MRP_Role	488

Table 392 – MRP_RTMode.RTClass1_2	488
Table 393 – MRP_RTMode.RTClass3	488
Table 394 – MRRT_TSTdefaultT	489
Table 395 – MRP_TOPchgT	489
Table 396 – MRP_TOPNRmax	489
Table 397 – MRP_TSTshortT	490
Table 398 – MRP_TSTdefaultT	490
Table 399 – MRP_TSTNRmax	490
Table 400 – MRRT_TSTNRmax	491
Table 401 – MRP_LNKdownT	491
Table 402 – MRP_LNKupT	491
Table 403 – MRP_LNKNRmax	492
Table 404 – MRP_RTState	492
Table 405 – MRP_Check.MediaRedundancyManager	492
Table 406 – MRP_Check.MRP_DomainUUID	492
Table 407 – VendorBlockType	493
Table 408 – FiberOpticType	493
Table 409 – FiberOpticCableType	493
Table 410 – FiberOpticPowerBudgetType.Value	494
Table 411 – FiberOpticPowerBudgetType.CheckEnable	494
Table 412 – NCDropBudgetType.Value	494
Table 413 – NCDropBudgetType.CheckEnable	494
Table 414 – FSHelloMode.Mode	495
Table 415 – FSHelloInterval	496
Table 416 – FSHelloRetry	496
Table 417 – FSHelloDelay	497
Table 418 – FSPParameterMode.Mode	497
Table 419 – FSPParameterUUID	497
Table 420 – FSMode.Mode	498
Table 421 – ArgsLength check	499
Table 422 – ARBlockReq – request check	500
Table 423 – IOCRBlockReq – request check	501
Table 424 – AlarmCRBlockReq – request check	504
Table 425 – ExpectedSubmoduleBlockReq – request check	505
Table 426 – PrmServerBlock – request check	506
Table 427 – MCRBlockReq – request check	507
Table 428 – ARRPCBlockReq – request check	507
Table 429 – ArgsLength check	508
Table 430 – ARBlockRes – response check	508
Table 431 – IOCRBlockRes – response check	509
Table 432 – AlarmCRBlockRes – response check	509
Table 433 – ModuleDiffBlock – response check	510
Table 434 – ArgsLength check	511

Table 435 – ControlBlockConnect – request check	511
Table 436 – ControlBlockPlug – request check	512
Table 437 – ArgsLength check.....	512
Table 438 – ControlBlockConnect – response check.....	513
Table 439 – ControlBlockPlug – response check.....	514
Table 440 – ArgsLength check.....	514
Table 441 – ControlBlockConnect – request check	515
Table 442 – ControlBlockPlug – request check	515
Table 443 – ArgsLength check.....	516
Table 444 – ControlBlockConnect – response check.....	516
Table 445 – ControlBlockPlug – response check.....	517
Table 446 – ArgsLength check.....	517
Table 447 – ReleaseBlock – request check.....	518
Table 448 – ArgsLength check.....	518
Table 449 – ReleaseBlock – response check	519
Table 450 – ArgsLength check.....	519
Table 451 – IODWriteReqHeader – request check	520
Table 452 – ArgsLength check.....	520
Table 453 – IODWriteResHeader – response check.....	521
Table 454 – ArgsLength check.....	521
Table 455 – ArgsLength check.....	522
Table 456 – ArgsLength check.....	523
Table 457 – IODReadReqHeader – request check	524
Table 458 – RecordDataReadQuery – request check	524
Table 459 – ArgsLength check.....	525
Table 460 – IODReadResHeader – response check.....	525
Table 461 – Primitives issued by AP-Context (FAL user) to FSPMDEV	528
Table 462 – Primitives issued by FSPMDEV to AP-Context (FAL user)	536
Table 463 – FSPMDEV protocol machine for multicast communication	543
Table 464 – Functions used by AP-Context (FAL user) to FSPMDEV	550
Table 465 – Function used by FSPMDEV to AP-Context (FAL user)	554
Table 466 – Primitives issued by AP-Context (FAL user) to FSPMCTL.....	561
Table 467 – Primitives issued by FSPMCTL to AP-Context (FAL user).....	566
Table 468 – Function used by AP-Context (FAL user) to FSPMCTL	574
Table 469 – Functions used by FSPMCTL to AP-Context (FAL user)	584
Table 470 – Primitives issued by FSPMDEV or FSPMCTL to ALPMI.....	592
Table 471 – Primitives issued by ALPMI to FSPMDEV or FSPMCTL	592
Table 472 – Primitives issued by CMDEV or CMCTL to ALPMI	593
Table 473 – Primitives issued by ALPMI to CMCTL or CMDEV	593
Table 474 – Primitives issued by APMR to ALPMI.....	594
Table 475 – Primitives issued by ALPMI to APMR.....	594
Table 476 – Primitives issued by APMS to ALPMI.....	595
Table 477 – Primitives issued by ALPMI to APMS.....	595

Table 478 – ALPMI state table	596
Table 479 – Primitives issued by FSPMDEV or FSPMCTL to ALPMR	599
Table 480 – Primitives issued by ALPMR to FSPMDEV or FSPMCTL	599
Table 481 – Primitives issued by CMDEV or CMCTL to ALPMR	599
Table 482 – Primitives issued by ALPMR to CMCTL or CMDEV	600
Table 483 – Primitives issued by APMR to ALPMR	600
Table 484 – Primitives issued by ALPMR to APMR	600
Table 485 – Primitives issued by APMS to ALPMR	601
Table 486 – Primitives issued by ALPMR to APMS	601
Table 487 – ALPMR state table	602
Table 488 – Primitives issued by CMCTL to NRPM	606
Table 489 – Primitives issued by NRPM to CMCTL	607
Table 490 – Primitives issued by other machines to NRPM	608
Table 491 – Primitives issued by NRPM to other machines	609
Table 492 – NRPM state table	610
Table 493 – Functions used by the NRPM and RMPM	616
Table 494 – Primitives issued by CMDEV to RMPM	617
Table 495 – Primitives issued by RMPM to CMDEV	618
Table 496 – Primitives issued by RPC to RMPM	618
Table 497 – Primitives issued by RMPM to RPC	619
Table 498 – Primitives issued by other machines to RMPM	619
Table 499 – Primitives issued by RMPM to other machines	620
Table 500 – RMPM state table	621
Table 501 – Primitives issued by FSPMDEV to CMDEV	631
Table 502 – Primitives issued by CMDEV to FSPMDEV	632
Table 503 – CMDEV state table	633
Table 504 – Macros used by CMDEV	652
Table 505 – Primitives issued by CMDEV to NRMC	653
Table 506 – Primitives issued by NRMC to CMDEV	653
Table 507 – Primitives issued by CPM to NRMC	653
Table 508 – Primitives issued by NRMC to CPM	654
Table 509 – Primitives issued by other machines to NRMC	654
Table 510 – Primitives issued by NRMC to other machines	655
Table 511 – NRMC state table	655
Table 512 – Primitives issued by FSPMCTL to CMCTL	660
Table 513 – Primitives issued by CMCTL to FSPMCTL	661
Table 514 – CMCTL state table	663
Table A-1 – Unicast FDB entries	684
Table A-2 – Multicast FDB entries	684
Table A-3 – Broadcast FDB entry	686

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158–1.

The application protocol provides the application service by making use of the services available from the data-link or other immediately lower layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer application entities (AEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- as a guide for implementors and designers;
- for use in the testing and procurement of equipment;
- as part of an agreement for the admittance of systems into the open systems environment;
- as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 6–10: Application layer protocol specification – Type 10 elements

1 Scope

1.1 General

The Fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs.”

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to Type 10 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible behavior provided by the Type 10 fieldbus application layer in terms of

- a) the abstract syntax defining the application layer protocol data units conveyed between communicating application entities,
- b) the transfer syntax defining the application layer protocol data units conveyed between communicating application entities,
- c) the application context state machine defining the application service behavior visible between communicating application entities; and
- d) the application relationship state machines defining the communication behavior visible between communicating application entities; and.

The purpose of this standard is to define the protocol provided to

- a) define the wire-representation of the service primitives defined in IEC 61158-5-10, and
- b) define the externally visible behavior associated with their transfer.

This standard specifies the protocol of the Type 10 fieldbus application layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

1.2 Specifications

The principal objective of this standard is to specify the syntax and behavior of the application layer protocol that conveys the application layer services defined in IEC 61158-5-10.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of protocols standardized in IEC 61158–6.

1.3 Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of application layer entities within industrial automation systems. Conformance is achieved through implementation of this application layer protocol specification.