



IEC 61158-4-12

Edition 1.0 2007-12

# INTERNATIONAL STANDARD

---

**Industrial communication networks – Fieldbus specifications –  
Part 4-12: Data-link layer protocol specification – Type 12 elements**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

PRICE CODE **XG**

ICS 35.100.20; 25.040.40

ISBN 2-8318-9439-5

## CONTENTS

FOREWORD.....	7
INTRODUCTION.....	9
1 Scope.....	10
1.1 General.....	10
1.2 Specifications.....	10
1.3 Procedures.....	10
1.4 Applicability.....	10
1.5 Conformance.....	10
2 Normative references .....	11
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Reference model terms and definitions.....	11
3.2 Service convention terms and definitions.....	12
3.3 Common terms and definitions .....	13
3.4 Additional Type 12 definitions.....	13
3.5 Common symbols and abbreviations .....	16
3.6 Additional Type 12 symbols and abbreviations .....	17
3.7 Conventions .....	19
4 Overview of the DL-protocol .....	24
4.1 Operating principle .....	24
4.2 Topology .....	24
4.3 Frame processing principles.....	24
4.4 Data-link layer overview .....	25
4.5 Error detection overview.....	26
4.6 Node reference model .....	26
4.7 Operation overview .....	27
5 Frame structure .....	28
5.1 Frame coding principles .....	28
5.2 Data types and encoding rules .....	28
5.3 DLPDU structure .....	31
5.4 Type 12 DLPDU structure.....	33
5.5 Network variable structure.....	48
5.6 Type 12 mailbox structure .....	48
6 Attributes.....	49
6.1 Management .....	49
6.2 Statistics .....	66
6.3 Watchdogs .....	69
6.4 Slave information interface.....	72
6.5 Media independent interface (MII).....	77
6.6 Fieldbus memory management unit (FMMU).....	80
6.7 Sync manager .....	83
6.8 Distributed clock.....	90
7 DL-user memory.....	94
7.1 Overview .....	94
7.2 Mailbox access type .....	95
7.3 Buffered access type.....	98
8 Type 12: FDL protocol state machines.....	100

8.1 Overview of slave DL state machines .....	100
8.2 State machine description .....	100
Annex A (informative) – Type 12: Additional specifications on DL-Protocol state machines .....	108
A.1 DHSM .....	108
A.2 SYSM .....	127
A.3 RMSM .....	140
Bibliography .....	144
Figure 1 – Type description example .....	20
Figure 2 – Common structure of specific fields .....	21
Figure 3 – Frame structure .....	25
Figure 4 – Mapping of data in a frame .....	26
Figure 5 – Slave node reference model .....	27
Figure 6 – Type 12 PDUs embedded in Ethernet frame .....	28
Figure 7 – Type 12 PDUs embedded in UDP/IP .....	28
Figure 8 – DL information type description .....	51
Figure 9 – Address type description .....	53
Figure 10 – DL control type description .....	55
Figure 11 – DL status type description .....	57
Figure 12 – Successful write sequence to DL-user control register .....	59
Figure 13 – Successful read sequence to the DL-user status register .....	60
Figure 14 – RX error counter type description .....	67
Figure 15 – Lost link counter type description .....	68
Figure 16 – Additional counter type description .....	69
Figure 17 – Sync configuration type description .....	70
Figure 18 – Watchdog divider type description .....	70
Figure 19 – Sync manager watchdog type description .....	71
Figure 20 – Sync manager watchdog status type description .....	71
Figure 21 – Watchdog counter type description .....	72
Figure 22 – Slave information interface access type description .....	72
Figure 23 – Slave information interface control/status type description .....	74
Figure 24 – Slave information interface address type description .....	76
Figure 25 – Slave information interface data type description .....	77
Figure 26 – MII control/status type description .....	78
Figure 27 – MII address type description .....	79
Figure 28 – MII data type description .....	80
Figure 29 – FMMU mapping example .....	80
Figure 30 – FMMU entity type description .....	81
Figure 31 – SyncM mailbox interaction .....	84
Figure 32 – SyncM buffer allocation .....	84
Figure 33 – SyncM buffer interaction .....	85
Figure 34 – Handling of write/read toggle with read mailbox .....	86
Figure 35 – Sync manager channel type description .....	88

Figure 36 – Distributed clock local time parameter type description .....	92
Figure 37 – Successful write sequence to mailbox .....	95
Figure 38 – Bad write sequence to mailbox .....	96
Figure 39 – Successful read sequence to mailbox .....	96
Figure 40 – Bad read sequence to mailbox .....	97
Figure 41 – Successful write sequence to buffer .....	98
Figure 42 – Successful read sequence to buffer .....	99
Figure 43 – Structuring of the protocol machines of an slave .....	100
Figure 44 – Slave information interface read operation .....	102
Figure 45 – Slave information interface write operation .....	103
Figure 46 – Slave information interface reload operation .....	104
Figure 47 – Distributed clock .....	106
Figure 48 – Delay measurement sequence .....	107
Table 1 – PDU element description example .....	20
Table 2 – Example attribute description .....	21
Table 3 – State machine description elements .....	22
Table 4 – Description of state machine elements .....	23
Table 5 – Conventions used in state machines .....	23
Table 6 – Transfer Syntax for bit sequences .....	29
Table 7 – Transfer syntax for data type Unsignedn .....	29
Table 8 – Transfer syntax for data type Integern .....	30
Table 9 – Type 12 frame inside an Ethernet frame .....	31
Table 10 – Type 12 frame inside an UDP PDU .....	32
Table 11 – Type 12 frame structure containing Type 12 PDUs .....	33
Table 12 – Type 12 frame structure containing network variables .....	33
Table 13 – Type 12 frame structure containing mailbox .....	33
Table 14 – Auto Increment Physical Read (APRD) .....	34
Table 15 – Configured Address Physical Read (FPRD) .....	35
Table 16 – Broadcast Read (BRD) .....	36
Table 17 – Logical Read (LRD) .....	37
Table 18 – Auto Increment Physical Write (APWR) .....	38
Table 19 – Configured Address Physical Write (FPWR) .....	39
Table 20 – Broadcast Write (BWR) .....	40
Table 21 – Logical Write (LWR) .....	41
Table 22 – Auto Increment Physical ReadWrite (APRW) .....	42
Table 23 – Configured Address Physical ReadWrite (FPRW) .....	43
Table 24 – Broadcast ReadWrite (BRW) .....	44
Table 25 – Logical ReadWrite (LRW) .....	45
Table 26 – Auto Increment Physical Read Multiple Write (ARMW) .....	46
Table 27 – Configured Address Physical Read Multiple Write (FRMW) .....	47
Table 28 – Network variable .....	48
Table 29 – Mailbox .....	48

Table 30 – Error Reply Service Data .....	49
Table 31 – DL information .....	52
Table 32 – Configured station address .....	54
Table 33 – DL control .....	55
Table 34 – DL status .....	58
Table 35 – DLS-user specific registers .....	61
Table 36 – DLS-user event .....	63
Table 37 – DLS-user event mask .....	64
Table 38 – External event .....	65
Table 39 – External event mask .....	66
Table 40 – RX error counter .....	67
Table 41 – Lost link counter .....	68
Table 42 – Watchdog divider .....	70
Table 43 – PDI watchdog .....	70
Table 44 – Sync manager channel watchdog .....	71
Table 45 – Sync manager watchdog Status .....	71
Table 46 – Watchdog counter .....	72
Table 47 – Slave information interface size .....	73
Table 48 – Slave information interface control/status .....	75
Table 49 – Actual slave information interface address .....	76
Table 50 – Actual slave information interface data .....	77
Table 51 – MII control/status .....	78
Table 52 – Actual MII address .....	79
Table 53 – Actual MII data .....	80
Table 54 – Fieldbus memory management unit (FMMU) entity .....	82
Table 55 – Fieldbus memory management unit (FMMU) .....	83
Table 56 – Sync manager channel .....	88
Table 57 – Sync manager Structure .....	90
Table 58 – Distributed clock local time parameter .....	93
Table 59 – Distributed clock DLS-user parameter .....	94
Table A.1 – Primitives issued by DHSM to PSM .....	108
Table A.2 – Primitives issued by PSM to DHSM .....	108
Table A.3 – Parameters used with primitives exchanged between DHSM and PSM .....	108
Table A.4 – Identifier for the octets of a Ethernet frame .....	109
Table A.5 – DHSM state table .....	111
Table A.6 – DHSM function table .....	127
Table A.7 – Primitives issued by SYSM to DHSM .....	127
Table A.8 – Primitives issued by DHSM to SYSM .....	128
Table A.9 – Primitives issued by DL-User to SYSM .....	128
Table A.10 – Primitives issued by SYSM to DL-User .....	128
Table A.11 – Parameters used with primitives exchanged between SYSM and DHSM .....	128
Table A.12 – SYSM state table .....	130
Table A.13 – SYSM function table .....	140

Table A.14 – Primitives issued by RMSM to SYSM .....	140
Table A.15 – Primitives issued by SYSM to RMSM .....	140
Table A.16 – Parameters used with primitives exchanged between RMSM and SYSM .....	140
Table A.17 – RMSM state table.....	142
Table A.18 – RMSM function table .....	143

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

---

**INDUSTRIAL COMMUNICATION NETWORKS –  
FIELDBUS SPECIFICATIONS –****Part 4-12: Data-link layer protocol specification – Type 12 elements**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in Type combinations as specified explicitly in the IEC 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

International Standard IEC 61158-4-12 has been prepared by subcommittee 65C: Industrial networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This first edition and its companion parts of the IEC 61158-4 subseries cancel and replace IEC 61158-4:2003. This edition of this part constitutes a technical addition, which also replaces IEC/PAS 62407, published in 2005.

This edition of IEC 61158-4 includes the following significant changes from the previous edition:

- a) deletion of the former Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data link layer, for lack of market relevance;
- b) addition of new types of fieldbuses;
- c) division of this part into multiple parts numbered -4-1, -4-2, ..., -4-19.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/474/FDIS	65C/485/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under <http://webstore.iec.ch> in the data related to the specific publication. At this date, the publication will be:

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

NOTE The revision of this standard will be synchronized with the other parts of the IEC 61158 series.

The list of all the parts of the IEC 61158 series, under the general title *Industrial communication networks – Fieldbus specifications*, can be found on the IEC web site.



## INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

## **INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –**

### **Part 4-12: Data-link layer protocol specification – Type 12 elements**

#### **1 Scope**

##### **1.1 General**

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides communication opportunities to all participating data-link entities

- a) in a synchronously-starting cyclic manner, and
- b) in a cyclic or acyclic asynchronous manner, as requested each cycle by each of those data-link entities.

Thus this protocol can be characterized as one which provides cyclic and acyclic access asynchronously but with a synchronous restart of each cycle.

##### **1.2 Specifications**

This standard specifies

- a) procedures for the transfer of data and control information from one data-link user entity to one or more user entity;
- b) the structure of the DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

##### **1.3 Procedures**

The procedures are defined in terms of

- a) the interactions between DL-entities (DLEs) through the exchange of DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and the MAC services of ISO/IEC 8802-3.

##### **1.4 Applicability**

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI reference model, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

##### **1.5 Conformance**

This standard also specifies conformance requirements for systems implementing these procedures. This part of this standard does not contain tests to demonstrate compliance with such requirements.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-2 (Ed.4.0), *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-12, *Industrial communication networks – Fieldbus specifications – Part 3-12: Data-link layer service definition – Type 12 elements*

IEC 61588, *Precision clock synchronization protocol for networked measurement and control system*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model – Basic Reference Model: Naming and addressing*

ISO/IEC 8802-1(E), ANSI/IEEE Std 802.1 *Local and metropolitan area networks – Virtual bridged local area networks.*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and Physical Layer specifications*

ISO/IEC 9899, *Programming Languages – C.*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

IEEE 802.1Q, *IEEE Standard for Local and metropolitan area networks – Virtual Bridged Local Area Networks*; available at <<http://www.ieee.org>>

IETF RFC 768, *User PDU Protocol*; available at <<http://www.ietf.org>>

IETF RFC 791, *Internet Protocol*; available at <<http://www.ietf.org>>