

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Fältbuss – Del 4-8: Specifikation av protokoll i datalänksskiktet – Delar i fältbuss, Typ 8

*Industrial communication networks –
Fieldbus specifications –
Part 4-8: Data-link layer protocol specification –
Type 8 elements*

Som svensk standard gäller europastandarden EN 61158-4-8:2008. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61158-4-8:2008.

Nationellt förord

Europastandarden EN 61158-4-8:2008

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61158-4-8, First edition, 2007 - Industrial communication networks - Fieldbus specifications - Part 4-8: Data-link layer protocol specification - Type 8 elements**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 61158-4, ersätter SS-EN 61158-4, utgåva 1, 2004.

Tidigare fastställd svensk standard SS-EN 61158-4, utgåva 1, 2004, gäller ej fr o m 2011-02-01.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Industrial communication networks -
Fieldbus specifications -
Part 4-8: Data-link layer protocol specification -
Type 8 elements
(IEC 61158-4-8:2007)**

Réseaux de communication industriels -
Spécifications des bus de terrain -
Partie 4-8: Spécification des protocoles
des couches de liaison de données -
Éléments de type 8
(CEI 61158-4-8:2007)

Industrielle Kommunikationsnetze -
Feldbusse -
Teil 4-8: Protokollspezifikation des
Data Link Layer (Sicherheitsschicht) -
Typ 8-Elemente
(IEC 61158-4-8:2007)

This European Standard was approved by CENELEC on 2008-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 65C/474/FDIS, future edition 1 of IEC 61158-4-8, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61158-4-8 on 2008-02-01.

This and the other parts of the EN 61158-4 series supersede EN 61158-4:2004.

With respect to EN 61158-4:2004 the following changes were made:

- deletion of Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data-link layer, for lack of market relevance;
- addition of new fieldbus types;
- partition into multiple parts numbered 4-1, 4-2, ..., 4-19.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-11-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-02-01

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in type combinations as specified explicitly in the EN 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

IEC and CENELEC draw attention to the fact that it is claimed that compliance with this standard may involve the use of patents as follows, where the [xx] notation indicates the holder of the patent right:

Type 8 and possibly other types:

DE 41 00 629 C1 [Px] Steuer- und Datenübertragungsanlage

IEC and CENELEC take no position concerning the evidence, validity and scope of these patent rights.

The holders of these patent rights have assured IEC that they are willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holders of these patent rights are registered with IEC. Information may be obtained from:

[Px]: Phoenix Contact GmbH & Co. KG
Referat Patente / Patent Department
Postfach 1341
D-32819 Blomberg
Germany

Attention is drawn to the possibility that some of the elements of this standard may be the subject of patent rights other than those identified above. IEC and CENELEC shall not be held responsible for identifying any or all such patent rights.

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 61158-4-8:2007 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61158-5-8	NOTE Harmonized as EN 61158-5-8:2008 (not modified).
IEC 61158-6-8	NOTE Harmonized as EN 61158-6-8:2008 (not modified).
IEC 61784-1	NOTE Harmonized as EN 61784-1:2008 (not modified).
IEC 61784-2	NOTE Harmonized as EN 61784-2:2008 (not modified).

Annex ZA

(normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 61158-2	2007	Industrial communication networks - Fieldbus specifications - Part 2: Physical layer specification and service definition	EN 61158-2	2008
IEC 61158-3-8	- ¹⁾	Industrial communication networks - Fieldbus specifications - Part 3-8: Data-link layer service definition - Type 8 elements	EN 61158-3-8	2008 ²⁾
ISO/IEC 7498-1	- ¹⁾	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	EN ISO/IEC 7498-1	1995 ²⁾
ISO/IEC 7498-3	- ¹⁾	Information technology - Open Systems Interconnection - Basic Reference Model: Naming and addressing	-	-
ISO/IEC 10731	- ¹⁾	Information technology - Open Systems Interconnection - Basic reference model - Conventions for the definition of OSI services	-	-

¹⁾ Undated reference.

²⁾ Valid edition at date of issue.

CONTENTS

INTRODUCTION.....	9
1 Scope.....	10
1.1 General.....	10
1.2 Specifications.....	10
1.3 Procedures.....	10
1.4 Applicability.....	10
1.5 Conformance.....	11
2 Normative references	11
3 Terms, definitions, symbols and abbreviations.....	11
3.1 Reference model terms and definitions.....	11
3.2 Service convention terms and definitions.....	12
3.3 Common terms and definitions	13
3.4 Additional Type 8 definitions.....	14
3.5 Symbols and abbreviations.....	15
4 DL-protocol	18
4.1 Overview	18
4.2 DL-service Interface (DLI)	18
4.3 Peripherals data link (PDL).....	22
4.4 Basic Link Layer (BLL)	58
4.5 Medium Access Control (MAC).....	74
4.6 Peripherals network management for layer 2 (PNM2).....	108
4.7 Parameters and monitoring times of the DLL	116
Annex A (informative) – Implementation possibilities of definite PNM2 functions.....	122
A.1 Acquiring the current configuration	122
A.2 Comparing the acquired and stored configurations prior to a DL-subnetwork error.....	126
Bibliography.....	132
Figure 1 – Relationships of DLSAPs, DLSAP-addresses and group DL-addresses.....	13
Figure 2 – Data Link Layer Entity.....	18
Figure 3 – Location of the DLI in the DLL.....	18
Figure 4 – State transition diagram of DLI.....	20
Figure 5 – Location of the PDL in the DLL.....	22
Figure 6 – PDL connection between slave and master	23
Figure 7 – Interface between PDL-user (DLI) and PDL in the layer model.....	24
Figure 8 – Overview of the PDL services	24
Figure 9 – PDL_Data_Ack service between master and only one slave.....	26
Figure 10 – Parallel processing of PDL_Data_Ack services	26
Figure 11 – PSM and GSM service for buffer access	26
Figure 12 – Buffer_Received service to indicate successful data transfer.....	27
Figure 13 – Data flow between PDL-user, PDL and BLL of a PDL_Data_Ack service	30
Figure 14 – Interface between PDL and PNM2 in the layer model	30
Figure 15 – Reset, Set Value and Get Value PDL services	32

Figure 16 – Event PDL service.....	32
Figure 17 – Transmit and receive FCBs on the master and slave sides.....	35
Figure 18 – Data transmission master → slave with SWA Message	36
Figure 19 – Time sequence of the data transmission master → slave with SWA Message	36
Figure 20 – Data transmission slave → master with SWA/RWA Message.....	37
Figure 21 – Time sequence of the data transmission slave → master with SWA/RWA Message	37
Figure 22 – Allocation of actions of the PDL protocol machines and data cycles	38
Figure 23 – Message transmission: master → slave.....	39
Figure 24 – Message transmission: slave → master.....	39
Figure 25 – Code octet of a PDL PDU.....	40
Figure 26 – Structure of a message with a size of one word.....	41
Figure 27 – Structure of a SPA Message	41
Figure 28 – Structure of a SVA Message	42
Figure 29 – Structure of a FCB_SET Message.....	42
Figure 30 – Structure of a RWA Message	42
Figure 31 – Structure of a SWA Message	43
Figure 32 – Structure of a confirmation for SPA or SVA Messages.....	43
Figure 33 – Structure of a FCB_SET as confirmation	43
Figure 34 – Structure of the data octet for FCB_SET as requests and confirmations.....	43
Figure 35 – Structure of a message with a size of more than one word	44
Figure 36 – PDL base protocol machine.....	45
Figure 37 – Locations of the PDL and the PDL protocol machines in the master and slaves	48
Figure 38 – PDL protocol machine	49
Figure 39 – TRANSMIT protocol machine	52
Figure 40 – RECEIVE protocol machine.....	55
Figure 41 – Location of the BLL in the DLL	58
Figure 42 – Interface between PDL and BLL in the layer model	59
Figure 43 – BLL_Data service.....	60
Figure 44 – Interface between PNM2 and BLL in the layer model.....	62
Figure 45 – Reset, Set Value and Get Value BLL services	64
Figure 46 – Event BLL service	64
Figure 47 – BLL operating protocol machine of the master.....	68
Figure 48 – BLL-BAC protocol machine	70
Figure 49 – BLL operating protocol machine of the slave	73
Figure 50 – Location of the MAC in the DLL.....	74
Figure 51 – Model details of layers 1 and 2.....	75
Figure 52 – DLPDU cycle of a data sequence without errors.....	76
Figure 53 – DLPDU cycle of a data sequence with errors.....	76
Figure 54 – Data sequence DLPDU transmitted by the master	77
Figure 55 – Data sequence DLPDU received by the master	77
Figure 56 – Check sequence DLPDU	77

Figure 57 – Loopback word (LBW)	77
Figure 58 – Checksum status generated by the master	80
Figure 59 – Checksum status received by the master	80
Figure 60 – MAC protocol machine of a master: transmission of a message	81
Figure 61 – MAC protocol machine of a master: receipt of a message	84
Figure 62 – MAC sublayer of a master: data sequence identification.....	88
Figure 63 – Data sequence DLPDU received by a slave.....	91
Figure 64 – Data sequence DLPDU transmitted by a slave	91
Figure 65 – Checksum status received by the slave.....	91
Figure 66 – Checksum status generated by the slave	92
Figure 67 – State transitions of the MAC sublayer of a slave: data sequence.....	93
Figure 68 – State transitions of the MAC sublayer of a slave: check sequence	94
Figure 69 – Interface between MAC-user and MAC in the layer model	99
Figure 70 – Interactions at the MAC-user interface (master)	100
Figure 71 – Interactions at the MAC-user interface (slave).....	101
Figure 72 – Interface between MAC and PNM2 in the layer model	104
Figure 73 – Reset, Set Value and Get Value MAC services.....	106
Figure 74 – Event MAC service.....	106
Figure 75 – Location of the PNM2 in the DLL.....	108
Figure 76 – Interface between PNM2-user and PNM2 in the layer model	109
Figure 77 – Reset, Set Value, Get Value and Get Active Configuration services	111
Figure 78 – Event PNM2 service	111
Figure 79 – Set Active Configuration, Get Current Configuration service.....	111
Figure 80 – The active_configuration parameter	115
Figure 81 – Device code structure	118
Figure 82 – Relations between data width, process data channel and parameter channel.....	120
Figure 83 – Structure of the control code	121
Figure A.1 – DL-subnetwork configuration in the form of a tree structure	122
Figure A.2 – State machine for the acquisition of the current configuration	124
Figure A.3 – State machine for comparing two configurations	128
Figure A.4 – State machine for comparing one line of two configuration matrices.....	130
Table 1 – Primitives issued by DLS-/DLMS-user to DLI	19
Table 2 – Primitives issued by DLI to DLS-/DLMS-user	19
Table 3 – DLI state table – sender transactions	20
Table 4 – DLI state table – receiver transactions	21
Table 5 – Function GetOffset	22
Table 6 – Function GetLength.....	22
Table 7 – Function GetRemAdd	22
Table 8 – Function GetDIsUserId	22
Table 9 – PDL_Data_Ack.....	27
Table 10 – PDL_Data_Ack L_status values.....	27

Table 11 – PSM	28
Table 12 – GSM.....	28
Table 13 – PDL_Reset.....	32
Table 14 – PDL_Set_Value.....	32
Table 15 – PDL variables.....	33
Table 16 – PDL_Get_Value.....	33
Table 17 – PDL_Event.....	34
Table 18 – Events.....	34
Table 19 – Encoding of the L_status	40
Table 20 – FCT code (PDL PDU-Types)	40
Table 21 – State transitions of the PDL base protocol machine.....	46
Table 22 – Counters of the PDL protocol machines.....	48
Table 23 – Meaning of the "connection" flag	49
Table 24 – State transitions of the PDL protocol machine	50
Table 25 – State transitions of the TRANSMIT protocol machine	53
Table 26 – State transitions of the RECEIVE protocol machine	55
Table 27 – BLL_Data	61
Table 28 – BLL_Data	64
Table 29 – BLL_Reset	65
Table 30 – BLL_Set_Value	65
Table 31 – BLL variables	66
Table 32 – BLL_Get_Value	66
Table 33 – BLL_Event.....	66
Table 34 – BLL_Event.....	67
Table 35 – State transitions of the BLL operating protocol machine of the master	69
Table 36 – State transitions of the BLL-BAC protocol machine.....	71
Table 37 – State transitions of the BLL operating protocol machine of the slave	73
Table 38 – FCS length and polynomial.....	78
Table 39 – MAC_Reset.....	106
Table 40 – MAC_Set_Value	106
Table 41 – MAC variables.....	107
Table 42 – MAC_Get_Value.....	107
Table 43 – MAC_Event	107
Table 44 – MAC_Event	108
Table 45 – PNM2_Reset.....	112
Table 46 – M_status values of the PNM2_Reset	112
Table 47 – PNM2_Set_Value	112
Table 48 – M_status values of the PNM2_Set_Value	113
Table 49 – PNM2_Get_Value.....	113
Table 50 – M_status values of the PNM2_Get_Value	113
Table 51 – PNM2_Event	114
Table 52 – MAC Events	114
Table 53 – PNM2_Get_Current_Configuration	114

Table 54 – PNM2_Get_Active_Configuration	115
Table 55 – PNM2_Set_Active_Configuration.....	116
Table 56 – Data direction.....	118
Table 57 – Number of the occupied octets in the parameter channel.....	119
Table 58 – Device class.....	119
Table 59 – Control data	119
Table 60 – Data width	120
Table 61 – Medium control.....	121
Table A.1 – DL-subnetwork configuration in the form of a matrix.....	123
Table A.2 – Acquire_Configuration.....	123
Table A.3 – State transitions of the state machine for the acquisition of the current configuration	125
Table A.4 – Check_Configuration.....	126
Table A.5 – Compare_Slave	127
Table A.6 – State transitions of the state machine for comparing two configurations	129
Table A.7 – State transitions of the state machine for comparing one line of two configuration matrixes	131

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

The data-link protocol provides the data-link service by making use of the services available from the physical layer. The primary aim of this standard is to provide a set of rules for communication expressed in terms of the procedures to be carried out by peer data-link entities (DLEs) at the time of communication. These rules for communication are intended to provide a sound basis for development in order to serve a variety of purposes:

- a) as a guide for implementors and designers;
- b) for use in the testing and procurement of equipment;
- c) as part of an agreement for the admittance of systems into the open systems environment;
- d) as a refinement to the understanding of time-critical communications within OSI.

This standard is concerned, in particular, with the communication and interworking of sensors, effectors and other automation devices. By using this standard together with other standards positioned within the OSI or fieldbus reference models, otherwise incompatible systems may work together in any combination.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 4-8: Data-link layer protocol specification – Type 8 elements

1 Scope

1.1 General

The data-link layer provides basic time-critical messaging communications between devices in an automation environment.

This protocol provides a highly-optimized means of interchanging fixed-length input/output data and variable-length segmented messages between a single master device and a set of slave devices interconnected in a loop (ring) topology. The exchange of input/output data is totally synchronous by configuration, and is unaffected by the messaging traffic.

Devices are addressed implicitly by their position on the loop. The determination of the number, identity and characteristics of each device can be configured, or can be detected automatically at start-up.

1.2 Specifications

This standard specifies

- a) procedures for the timely transfer of data and control information from one data-link user entity to a peer user entity, and among the data-link entities forming the distributed data-link service provider;
- b) the structure of the fieldbus DLPDUs used for the transfer of data and control information by the protocol of this standard, and their representation as physical interface data units.

1.3 Procedures

The procedures are defined in terms of

- a) the interactions between peer DL-entities (DLEs) through the exchange of fieldbus DLPDUs;
- b) the interactions between a DL-service (DLS) provider and a DLS-user in the same system through the exchange of DLS primitives;
- c) the interactions between a DLS-provider and a Ph-service provider in the same system through the exchange of Ph-service primitives.

1.4 Applicability

These procedures are applicable to instances of communication between systems which support time-critical communications services within the data-link layer of the OSI or fieldbus reference models, and which require the ability to interconnect in an open systems interconnection environment.

Profiles provide a simple multi-attribute means of summarizing an implementation's capabilities, and thus its applicability to various time-critical communications needs.

1.5 Conformance

This standard also specifies conformance requirements for systems implementing these procedures. This standard does not contain tests to demonstrate compliance with such requirements.

2 Normative references

The following referenced documents are indispensable for the application of this standard. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 61158-2 (Ed.4.0), *Industrial communication networks – Fieldbus specifications – Part 2: Physical layer specification and service definition*

IEC 61158-3-8, *Digital data communications for measurement and control – Fieldbus for use in industrial control systems – Part 3-8: Data link service definition – Type 8 elements*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model: The Basic Model*

ISO/IEC 7498-3, *Information technology – Open Systems Interconnection – Basic Reference Model: Naming and addressing*

ISO/IEC 10731, *Information technology – Open Systems Interconnection – Basic Reference Model – Conventions for the definition of OSI services*

[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]
[REDACTED]	[REDACTED]