

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Fältbuss – Del 5-10: Definition av tjänster i applikationsskiktet – Delar i fältbuss, Typ 10

*Industrial communication networks –
Fieldbus specifications –
Part 5-10: Application layer service definition –
Type 10 elements*

Som svensk standard gäller europastandarden EN 61158-5-10:2008. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61158-5-10:2008.

Nationellt förord

Europastandarden EN 61158-5-10:2008

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61158-5-10, First edition, 2007 - Industrial communication networks - Fieldbus specifications - Part 5-10: Application layer service definition - Type 10 elements**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 61158-5, ersätter SS-EN 61158-5, utgåva 1, 2004.

Tidigare fastställd svensk standard SS-EN 61158-5, utgåva 1, 2004, gäller ej fr o m 2011-02-01.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Industrial communication networks -
Fieldbus specifications -
Part 5-10: Application layer service definition -
Type 10 elements
(IEC 61158-5-10:2007)**

Réseaux de communication industriels -
Spécifications des bus de terrain -
Partie 5-10: Définition des services
des couches d'application -
Éléments de type 10
(CEI 61158-5-10:2007)

Industrielle Kommunikationsnetze -
Feldbusse -
Teil 5-10: Dienstfestlegungen
des Application Layer
(Anwendungsschicht) -
Typ 10-Elemente
(IEC 61158-5-10:2007)

This European Standard was approved by CENELEC on 2008-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

The text of document 65C/475/FDIS, future edition 1 of IEC 61158-5-10, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61158-5-10 on 2008-02-01.

This and the other parts of the EN 61158-5 series supersede EN 61158-5:2004.

With respect to EN 61158-5:2004 the following changes were made:

- deletion of Type 6 fieldbus and Type 1 fieldbus application layer, for lack of market relevance;
- addition of new fieldbus types;
- partition into multiple parts numbered 5-2, 5-3, ..., 5-20.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2008-11-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2011-02-01

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in type combinations as specified explicitly in the EN 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 61158-5-10:2007 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61784-1	NOTE Harmonized as EN 61784-1:2008 (not modified).
IEC 61784-2	NOTE Harmonized as EN 61784-2:2008 (not modified).
ISO/IEC 8877	NOTE Harmonized as EN 28877:1993 (not modified).
ISO 8601	NOTE Harmonized as EN 28601:1992 (not modified).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60559	- ¹⁾	Binary floating-point arithmetic for microprocessor systems	HD 592 S1	1991 ²⁾
IEC 61131-1	- ¹⁾	Programmable controllers - Part 1: General information	EN 61131-1	2003 ²⁾
IEC 61131-3	- ¹⁾	Programmable controllers - Part 3: Programming languages	EN 61131-3	2003 ²⁾
IEC 61158-6-3	- ¹⁾	Industrial communication networks - Fieldbus specifications - Part 6-3: Application layer protocol specification - Type 3 elements	EN 61158-6-3	2008 ²⁾
IEC 61158-6-10	- ¹⁾	Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements	EN 61158-6-10	2008 ²⁾
ISO/IEC 646	- ¹⁾	Information technology - ISO 7-bit coded character set for information interchange	-	-
ISO/IEC 7498-1	- ¹⁾	Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model	EN ISO/IEC 7498-1	1995 ²⁾
ISO/IEC 8802-1	- ¹⁾	Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 1: Overview of Local Area Network Standards	-	-
ISO/IEC 8802-3	- ¹⁾	Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-

¹⁾ Undated reference.

²⁾ Valid edition at date of issue.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
ISO/IEC 8822	- ¹⁾	Information technology - Open Systems Interconnection - Presentation service definition	-	-
ISO/IEC 8824-1	- ¹⁾	Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation	-	-
ISO/IEC 8859-1	- ¹⁾	Information technology - 8-bit single-byte coded graphic character sets - Part 1: Latin alphabet No.1	-	-
ISO/IEC 9545	- ¹⁾	Information technology - Open Systems Interconnection - Application Layer structure	-	-
ISO/IEC 10646-1	- ¹⁾	Information technology - Universal Multiple-Octet Coded Character Set (UCS) - Part 1: Architecture and Basic Multilingual Plane	-	-
ISO/IEC 10731	- ¹⁾	Information technology - Open Systems Interconnection - Basic reference model - Conventions for the definition of OSI services	-	-
IEEE 802	2001	IEEE standard for local and metropolitan area networks: overview and architecture	-	-
IEEE 802.1AB	2005	IEEE Standard for Local and metropolitan area networks Station and Media Access Control Connectivity Discovery	-	-
IEEE 802.1D	2004	IEEE standard for local and metropoitan area networks - Media access control (MAC) Bridges	-	-
IEEE 802.1Q	2005	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-
IEEE 802.3	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier Sense Multiple Access with Collision Detection	-	-
IEEE 802.15.1	2005	IEEE Standard for Information technology - Telecommunications and information exchange between systems - Local and metropolitan area networks - Specific requirement - Part 15.1: Wireless medium access control (MAC) and physical layer (PHY) specifications for wireless personal area networks (WPANs)	-	-
IETF RFC 768	- ¹⁾	User Datagram Protocol	-	-
IETF RFC 791	- ¹⁾	Internet Protocol	-	-
IETF RFC 792	- ¹⁾	Internet Control Message Protocol	-	-

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IETF RFC 826	- ¹⁾	Ethernet Address Resolution Protocol	-	-
IETF RFC 1034	- ¹⁾	Domain names - concepts and facilities	-	-
IETF RFC 1112	- ¹⁾	Host Extensions for IP Multicasting	-	-
IETF RFC 2131	- ¹⁾	Dynamic Host Configuration Protocol	-	-
IETF RFC 2674	- ¹⁾	Definitions of Managed Objects for Bridges with Traffic Classes, Multicast Filtering and Virtual LAN Extensions	-	-
IETF RFC 2737	- ¹⁾	Entity MIB (Version 2)	-	-
IETF RFC 2863	- ¹⁾	The Interfaces Group MIB	-	-
IETF RFC 3418	- ¹⁾	Management Information Base (MIB) for the Simple Network Management Protocol (SNMP)	-	-
IETF RFC 3490	- ¹⁾	Internationalizing Domain Names in Applications (IDNA)	-	-
IETF RFC 3621	- ¹⁾	Power Ethernet MIB	-	-
IETF RFC 3636	- ¹⁾	Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)	-	-
The Open Group C706	- ¹⁾	CAE Specification DCE11: Remote Procedure Call	-	-

CONTENTS

INTRODUCTION	18
1 Scope	19
1.1 Overview	19
1.2 Specifications	20
1.3 Conformance	20
2 Normative references	20
3 Terms, definitions, abbreviations, symbols and conventions	22
3.1 Referenced terms and definitions	22
3.2 Additional terms and definitions for distributed automation	23
3.3 Additional terms and definitions for decentralized periphery	25
3.4 Additional terms and definitions for media redundancy	33
3.5 Abbreviations and symbols	34
3.6 Additional abbreviations and symbols for distributed automation	35
3.7 Additional abbreviations and symbols for decentralized periphery	35
3.8 Additional abbreviations and symbols for media redundancy	36
3.9 Conventions	36
4 Concepts	39
5 Data type ASE	39
5.1 General	39
5.2 Formal definition of data type objects	42
5.3 FAL defined data types	43
5.4 Data type ASE service specification	86
6 Communication model for common services	86
6.1 Concepts	86
6.2 ASE data types	86
6.3 ASEs	87
7 Communication model for distributed automation	184
7.1 Concepts	184
7.2 ASE data types	191
7.3 ASEs	195
7.4 ARs	412
7.5 Summary of FAL classes	416
7.6 Summary of FAL services	417
8 Communication model for decentralized periphery	420
8.1 Concepts	420
8.2 ASE data types	436
8.3 ASEs	436
8.4 Behavior of an IO device	671
8.5 Behavior of an IO controller	737
8.6 Application characteristics	744

Annex A (informative) Device instances	746
Annex B (informative) Components of an Ethernet interface	748
Annex C (informative) Scheme of MAC address assignment	752
Annex D (informative) Collection of objects	753
Annex E (informative) Measurement of the fast startup time	754
Bibliography	755
Figure 1 – Data type class hierarchy example	40
Figure 2 – NetworkTime date relation	63
Figure 3 – UTF-8 coding of four different characters	67
Figure 4 – PTCP applications	100
Figure 5 – Clock drift measurement	110
Figure 6 – Multiple synchronization	110
Figure 7 –MRP stack	112
Figure 8 – Ring topology with one manager and clients	123
Figure 9 – MRM in an open ring	123
Figure 10 – More than one MRM in the ring	125
Figure 11 – Media redundancy diagnosis dependencies	126
Figure 12 – Locating the destination for redundant RT frames	165
Figure 13 – Example of periods at a local port	172
Figure 14 – FAL ASEs communication architecture	187
Figure 15 – Runtime object model	188
Figure 16 – Relationship between engineering and runtime	189
Figure 17 – Navigation in the runtime object model	190
Figure 18 – Operating state block diagram	229
Figure 19 – Device status model for the common diagnosis	230
Figure 20 – ACCO ASE structure	261
Figure 21 – Productive operation of data connections	262
Figure 22 – Quality code transfer – standard behavior	274
Figure 23 – Startup of a connection	275
Figure 24 – Quality code with communication fault	275
Figure 25 – Quality code when an connection is cleared	276
Figure 26 – Quality code when an connection is deactivated	276
Figure 27 – Quality code during the transfer of "incorrect" connection data	277
Figure 28 – Quality code for provider in "CBARReady" state	278
Figure 29 – Quality code when clearing an object from the provider	278
Figure 30 – Quality code when a connection is forced	279
Figure 31 – Quality code at QoS violation	279
Figure 32 – Push mode	286
Figure 33 – Pull mode overview	287

Figure 34 – Detailed sequence chart of the pull mode	288
Figure 35 – QoS and ORPC communication channel.....	289
Figure 36 – QoS Violation within Pull Mode.....	290
Figure 37 – Monitoring the providers heartbeat	291
Figure 38 – State machine RemoteAcco	293
Figure 39 – State machine RemoteAccoProvider.....	293
Figure 40 – State machine RemoteAccoProvider _{ORPC}	294
Figure 41 – State machine AR _{ORPC} – Provider	294
Figure 42 – State machine GetConnectionData – Provider.....	295
Figure 43 – State machine ProviderConnection.....	295
Figure 44 – State machine ProvConnActivation.....	296
Figure 45 – State machine WorkerORPC	296
Figure 46 – Communication stack of distributed automation devices	297
Figure 47 – Application relations between devices	298
Figure 48 – Communication relations	298
Figure 49 – RT communication channel	300
Figure 50 – Interaction between provider and consumer	302
Figure 51 – State machine AR _{SRT} – Consumer	304
Figure 52 – State machine AR _{SRT} – Provider.....	304
Figure 53 – State machine AccoDataCR – Consumer.....	305
Figure 54 – State machine AccoDataCR – Provider	306
Figure 55 – RT frame layout.....	307
Figure 56 – Establishing an AccoDataCR.....	308
Figure 57 – Flowchart of the copy cycle for local connections	309
Figure 58 – State machine connect attempt	313
Figure 59 – Productive operation of data connections (ORPC channel).....	320
Figure 60 – Productive operation of data connections (RT channel).....	321
Figure 61 – Productive operation of data connections (Local channel)	321
Figure 62 – Data flow for cyclic RT	322
Figure 63 – Failure of the provider in productive operation (ORPC push mode).....	324
Figure 64 – Failure of the provider in productive operation (ORPC pull mode)	325
Figure 65 – Scenario 1: Provider failure in productive operation (RT).....	326
Figure 66 – Scenario 2: Recovery from provider failure in productive operation (RT).....	327
Figure 67 – Failure of the consumer (push mode)	327
Figure 68 – Failure of the consumer (pull mode)	328
Figure 69 – Failure of the consumer.....	329
Figure 70 – Failure of the provider when setting up connections	331
Figure 71 – Information levels.....	332
Figure 72 – ACCO ASE status model for the common diagnosis	332
Figure 73 – ACCO ASE status model for the detailed diagnosis	333
Figure 74 – Structure of the transmitted connection data	375

Figure 75 – Example of communication between controlling devices and field devices	421
Figure 76 – Example of communication between an engineering station and several controlling and field devices	421
Figure 77 – Example of communication between field devices and a server station.....	422
Figure 78 – Example of communication between field devices	422
Figure 79 – Structural units of one arbitrary API of an IO device (general)	424
Figure 80 – Example 1 structural units for interfaces and ports within API 0	425
Figure 81 – Example 2 structural units for interfaces and ports within API 0	426
Figure 82 – Overview of application processes	428
Figure 83 – IO device with APs, slots and subslots	429
Figure 84 – Application Process with application objects (APOs)	432
Figure 85 – Access to a remote APO	433
Figure 86 – Access to a remote APO for provider/consumer association	434
Figure 87 – Example of one AR with two AREPs	435
Figure 88 – Relation of a record data object to one real object.....	437
Figure 89 – Relation of a record data object to two real objects	438
Figure 90 – Overview IO ASE service interactions	448
Figure 91 – Example of a resource model at the alarm source	525
Figure 92 – General isochronous application model (example).....	560
Figure 93 – ASE relations in an IO device operating in isochronous mode	566
Figure 94 – State machine relations in an IO device operating in isochronous mode	566
Figure 95 – SyncCtl state diagram	570
Figure 96 – Output state diagram.....	572
Figure 97 – Input state diagram	577
Figure 98 – Assignment of communication relationship to application relationship	650
Figure 99 – Implicit application relationship.....	653
Figure 100 – Example IO application relationship (one-to-one)	655
Figure 101 – Example IO application relationship one-to-many	656
Figure 102 – Overview ASE state machines for IO device	672
Figure 103 – State diagram application startup IO device.....	673
Figure 104 – State diagram startup manager IO device.....	681
Figure 105 – State diagram IRT port state IO device (standard).....	684
Figure 106 – State diagram IRT port state IO device (optimized).....	696
Figure 107 – State diagram neighborhood check.....	703
Figure 108 – State diagram PD parameter check IO device	712
Figure 109 – State diagram for a submodule.....	722
Figure 110 – State diagram IO controller during startup	738
Figure 111 – State diagram startup manager IO controller	741
Figure 112 – Example of network topology including slower wireless segments	745
Figure 113 – Example of media redundancy including wireless segments	745
Figure A.1 – Instance model	746

Figure B.1 – Scheme of an Ethernet interface	748
Figure B.2 – Scheme of an Ethernet interface with bridging ability	749
Figure B.3 – Scheme of an Ethernet interface with optical ports	750
Figure B.4 – Scheme of an Ethernet interface with bridging ability using radio communication	751
Figure B.5 – Scheme of an Ethernet interface with radio communication	751
Figure C.1 – Scheme of MAC address assignment	752
Figure D.1 – Example for an intersection of IO device, slot, and AR	753
Figure E-1 – Measurement of the fast startup time	754
Table 1 – PERSISTDEF	46
Table 2 – VARTYPE	47
Table 3 – ITEMQUALITYDEF	47
Table 4 – STATEDEF	51
Table 5 – GROUPEXCEPTIONDEF	51
Table 6 – ACCESSRIGHTSDEF	51
Table 7 – HRESULT	52
Table 8 – N2 value range	56
Table 9 – N2 octets	56
Table 10 – N4 value range	57
Table 11 – N4 octets	57
Table 12 – X2 value range	58
Table 13 – X2 octets	58
Table 14 – X4 value range	58
Table 15 – X4 octets	58
Table 16 – Unipolar2.16 value range	59
Table 17 – Unipolar2.16 octets	59
Table 18 – E2 value range	59
Table 19 – E2 octets	59
Table 20 – C4 value range	60
Table 21 – V2 octets	60
Table 22 – L2 octets	60
Table 23 – UUID for decentralized peripherals	61
Table 24 – UUID for distributed automation	62
Table 25 – NetworkTime values	63
Table 26 – NetworkTime octets	63
Table 27 – T2 values	64
Table 28 – T4 values	64
Table 29 – D2 values	65
Table 30 – R2 values	65
Table 31 – UNICODEString values	66

Table 32 – UTF-8 character encoding scheme	67
Table 33 – OctetString2+Unsigned8 octets	78
Table 34 – Float32+Unsigned8 octets	79
Table 35 – Unsigned8+Unsigned8 octets	79
Table 36 – Data Types for Value in a VARIANT	82
Table 37 – Unsigned16_S octets.....	83
Table 38 – Unsigned16_S meaning.....	83
Table 39 – Integer16_S octets	84
Table 40 – Integer16_S meaning	84
Table 41 – Unsigned8_S octets	84
Table 42 – Unsigned8_S meaning.....	84
Table 43 – OctetString_S octets	85
Table 44 – OctetString_S status bits	85
Table 45 – F message trailer with 4 octets	85
Table 46 – F message trailer with 5 octets	86
Table 47 – Get.....	92
Table 48 – Set	94
Table 49 – Identify	97
Table 50 – Hello.....	98
Table 51 – Clock stratum	102
Table 52 – Start bridge	104
Table 53 – Start slave	105
Table 54 – Start master	106
Table 55 – Stop bridge.....	107
Table 56 –Stop slave	107
Table 57 – Stop master.....	108
Table 58 – State change	109
Table 59 – Start MRM	117
Table 60 – Stop MRM	119
Table 61 – Change state.....	119
Table 62 – Start MRC	120
Table 63 – Stop MRC.....	121
Table 64 – Neighborhood changed.....	122
Table 65 – MRP network/connection parameters	127
Table 66 – MRM parameters	127
Table 67 – MRC parameters	127
Table 68 – Set prov data.....	128
Table 69 – Set prov status	129
Table 70 – PPM activate	130
Table 71 – Close.....	131
Table 72 – Start	131

Table 73 – Error	132
Table 74 – Get cons data	132
Table 75 – Get cons status	133
Table 76 – Set redRole	133
Table 77 – CPM activate	134
Table 78 – APMS activate	138
Table 79 – APMR activate	139
Table 80 – APMS A data	140
Table 81 – APMR A data	141
Table 82 – APMR ack	141
Table 83 – APMS error	142
Table 84 – APMS error ERRCLS/ERRCODE	142
Table 85 – APMR error	143
Table 86 – APMR error ERRCLS/ERRCODE	143
Table 87 – APMS_Close	143
Table 88 – APMR_Close	144
Table 89 – Connect	145
Table 90 – Release	146
Table 91 – Read	147
Table 92 – Write	148
Table 93 – Control	149
Table 94 – System capabilities	154
Table 95 – Auto negotiation support and status	155
Table 96 – MDI Power Support	156
Table 97 – Link aggregation status	156
Table 98 – Remote systems data change	159
Table 99 – Allowed values of ReductionRatio	162
Table 100 – Frame IDs for RT_CLASS_3	163
Table 101 – Sync Frame	163
Table 102 – FrameSendOffset	163
Table 103 – Tx Port Entry	164
Table 104 – Port state change	167
Table 105 – Set port state	167
Table 106 – Flush filtering data base	167
Table 107 – IFW IRT Schedule Add	168
Table 108 – IFW IRT Schedule Remove	168
Table 109 – IFW Schedule	169
Table 110 – MAU type change	173
Table 111 – Set MAU type	174
Table 112 – IP Multicast address	176
Table 113 – Set ARP cache	176

Table 114 – Enterprise number	179
Table 115 – Vendor OUI	179
Table 116 – IRT schedule sdd.....	180
Table 117 – IRT schedule remove.....	181
Table 118 – Schedule	181
Table 119 – N data	182
Table 120 – A data.....	183
Table 121 – C data	184
Table 122 – Connectable data types	192
Table 123 – Supported data types according to the Base Object Version	193
Table 124 – Usage of character sets.....	195
Table 125 – QueryInterface (Unknown interface)	197
Table 126 – AddRef (Unknown interface)	198
Table 127 – Release (Unknown interface).....	199
Table 128 – GetTypeInfoCount (Dispatch interface).....	200
Table 129 – GetTypeInfo (Dispatch interface)	201
Table 130 – GetIDsOfNames (Dispatch interface)	202
Table 131 – Invoke (Dispatch interface)	203
Table 132 – CRC table for the PDev stamp calculation (hexadecimal values)	208
Table 133 – get_Producer (Physical device interface).....	209
Table 134 – get_Product (Physical device interface).....	210
Table 135 – get_SerialNo (Physical device interface).....	211
Table 136 – get_ProductionDate (Physical device interface)	212
Table 137 – Revision (Physical device interface)	213
Table 138 – get_LogicalDevice (Physical device interface)	214
Table 139 – Type (Physical device interface)	215
Table 140 – PROFInetRevision (Physical device interface)	216
Table 141 – get_PDevStamp (Physical device interface).....	217
Table 142 – get_Count (Browse interface)	218
Table 143 – BrowseItems (Browse interface)	219
Table 144 – get_Count2 (Browse interface)	220
Table 145 – BrowseItems2 (Browse interface)	222
Table 146 – Save (Persist interface)	223
Table 147 – Save2 (Persist interface)	224
Table 148 – get_Name (Logical device interface).....	230
Table 149 – get_Producer (Logical device interface).....	231
Table 150 – get_Product (Logical device interface).....	232
Table 151 – get_SerialNo (Logical device interface).....	233
Table 152 – get_ProductionDate (Logical device interface).....	234
Table 153 – Revision (Logical device interface)	235
Table 154 – get_ACCO (Logical device interface)	236

Table 155 – get_RTAuto (Logical device interface)	237
Table 156 – PROFINetRevision (Logical device interface)	238
Table 157 – ComponentInfo (Logical device interface)	239
Table 158 – get_State (State interface).....	240
Table 159 – Activate (State interface)	242
Table 160 – Deactivate (State interface)	243
Table 161 – Reset (State interface).....	244
Table 162 – AdviseState (State interface)	245
Table 163 – UnadviseState (State interface)	246
Table 164 – get_Time (Time interface).....	247
Table 165 – put_Time (Time interface).....	248
Table 166 – get_Count (Browse interface)	249
Table 167 – BrowseItems (Browse interface)	250
Table 168 – get_Count2 (Browse interface)	251
Table 169 – BrowseItems2 (Browse interface)	253
Table 170 – GroupError (Group error interface)	254
Table 171 – AdviseGroupError (Group Error interface).....	256
Table 172 – UnadviseGroupError (Group Error interface).....	257
Table 173 – PingFactor values.....	259
Table 174 – QoS subtypes in the ORPC communication channel	268
Table 175 – QoS subtypes in the RT communication channel	269
Table 176 – QoS Types and Values	269
Table 177 – Epsilon value for connectable data types	271
Table 178 – Quality Codes	273
Table 179 – Quality code priority table	281
Table 180 – Maximum ORPC substitute value apply time.....	291
Table 181 – Maximum GetConnectionData hold time	292
Table 182 – Usage of RT Variants	299
Table 183 – Mapping QoS Value to RT cycle time.....	300
Table 184 – Maximum RT Substitute Value Apply Time	301
Table 185 – Time Intervals and Timeouts.....	323
Table 186 – Error codes for the ACCO ASE detailed diagnosis	334
Table 187 – AddConnections (ACCO management interface).....	336
Table 188 – RemoveConnections (ACCO management interface)	337
Table 189 – ClearConnections (ACCO management interface)	339
Table 190 – SetActivationState (ACCO management interface)	340
Table 191 – GetInfo (ACCO management interface)	341
Table 192 – GetIDs (ACCO management interface)	342
Table 193 – GetConnections (ACCO management interface)	343
Table 194 – ReviseQoS (ACCO management interface).....	345
Table 195 – get_PingFactor (ACCO management interface)	346

Table 196 – put_PingFactor (ACCO management interface)	347
Table 197 – get_CDBCcookie (ACCO management interface)	348
Table 198 – GetConsIDs (ACCO management interface)	349
Table 199 – GetConsConnections (ACCO management interface)	350
Table 200 – DiagConsConnections (ACCO management interface).....	351
Table 201 – GetProvIDs (ACCO management interface)	352
Table 202 – GetProvConnections (ACCO management interface)	354
Table 203 – GetDiagnosis (ACCO management interface)	355
Table 204 – Request.....	357
Table 205 – Connect (ACCO server interface)	364
Table 206 – Disconnect (ACCO server interface)	366
Table 207 – DisconnectMe (ACCO server interface)	367
Table 208 – SetActivation (ACCO server interface).....	368
Table 209 – Ping (ACCO server interface)	369
Table 210 – Connect2 (ACCO server interface)	371
Table 211 – GetConnectionData (ACCO server interface).....	373
Table 212 – OnDataChanged (ACCO callback interface).....	376
Table 213 – Version	376
Table 214 – Flags	377
Table 215 – Gnip (ACCO callback interface).....	378
Table 216 – ReadItems (ACCO sync interface)	379
Table 217 – WriteItems (ACCO sync interface)	381
Table 218 – WriteItemsQCD (ACCO sync interface).....	383
Table 219 – GroupError (Group Error interface)	384
Table 220 – AdviseGroupError (Group Error interface).....	385
Table 221 – UnadviseGroupError (Group Error interface).....	386
Table 222 – ConnectCR (ACCO server SRT interface).....	388
Table 223 – DisconnectCR (ACCO server SRT interface)	390
Table 224 – Connect (ACCO server SRT interface).....	391
Table 225 – Disconnect (ACCO server SRT interface)	392
Table 226 – DisconnectMe (ACCO server SRT interface).....	394
Table 227 – SetActivation (ACCO server SRT interface)	395
Table 228 –Hresult values for access to properties of Custom RT-Auto objects	400
Table 229 – Hresult values for access to properties of the System RT-Auto object.....	401
Table 230 – Common hresult values on access to properties of RT-Auto objects	401
Table 231 – Quality code for access to properties of Custom RT-Auto objects	401
Table 232 – Quality code for access to properties of the System RT-Auto object	402
Table 233 – get_Name (RT-Auto interface)	402
Table 234 – Revision (RT-Auto interface).....	403
Table 235 – ComponentInfo (RT-Auto interface)	404
Table 236 – get_Count (Browse interface)	405

Table 237 – BrowseItems (Browse interface)	406
Table 238 – get_Count2 (Browse interface)	408
Table 239 – BrowseItems2 (Browse interface)	409
Table 240 – get_StateCollection (System properties interface)	411
Table 241 – get_StampCollection (System Properties interface)	412
Table 242 – CoCreateInstance.....	414
Table 243 – CoDisconnectObject	415
Table 244 – Call.....	415
Table 245 – Distributed automation FAL class summary	416
Table 246 – Assignment of the services to client and server	417
Table 247 – Requirements and features.....	420
Table 248 – Persistence behavior for record data objects	440
Table 249 – Read	441
Table 250 – Read query.....	443
Table 251 – Write	445
Table 252 – Set input.....	455
Table 253 – Set input IOCS	456
Table 254 – Get input	457
Table 255 – Get input IOCS	458
Table 256 – New input	459
Table 257 – Set input APDU data status	460
Table 258 – New input APDU data status.....	461
Table 259 – Read input data	462
Table 260 – Set output.....	464
Table 261 – Set output IOCS	465
Table 262 – Get output	466
Table 263 – Get output IOCS.....	467
Table 264 – New output	468
Table 265 – Set output APDU data status	469
Table 266 – New output APDU data status	470
Table 267 – Read output data	471
Table 268 – Read output substitute data	474
Table 269 – Write output substitute data	476
Table 270 – Read logbook	480
Table 271 – Logbook event.....	481
Table 272 – Dependencies within channel properties.....	485
Table 273 – Ext channel error type	488
Table 274 – Ext channel add value for accumulative info	489
Table 275 – Dependencies within channel properties for manufacturer specific diagnosis.....	490
Table 276 – Read device diagnosis.....	492

Table 277 – Diagnosis item	494
Table 278 – Diagnosis event	500
Table 279 – State table diagnosis entry	503
Table 280 – Functions used in state tables	504
Table 281 – State table maintenance required entry	505
Table 282 – State table maintenance demanded entry	506
Table 283 – State table qualified entry	507
Table 284 – Alarm type	512
Table 285 – Channel diagnosis	513
Table 286 – Manufacturer specific diagnosis	513
Table 287 – Submodule diagnosis state	513
Table 288 – AR diagnosis state	514
Table 289 – User structure Identifier	515
Table 290 – Semantics of specifier	516
Table 291 – Alarm notification	521
Table 292 – Alarm ack	524
Table 293 – Module State	529
Table 294 – Usage with respect to CR type	531
Table 295 – Detail	532
Table 296 – ARInfo	533
Table 297 – Ident Info	533
Table 298 – Connect	534
Table 299 – Connect device access	541
Table 300 – Release	543
Table 301 – Abort	544
Table 302 – End of parameter	544
Table 303 – Application ready	545
Table 304 – Ready for companion	547
Table 305 – Read expected identification	548
Table 306 – Read real identification	551
Table 307 – Read identification difference	554
Table 308 – Write IsoM data	561
Table 309 – Read IsoM data	563
Table 310 – SYNCH event	565
Table 311 – Primitives issued by the AL to the SyncCtl state machine	567
Table 312 – Primitive issued by the SyncCtl state machine to the user	568
Table 313 – Primitives issued by the input state machine to the user	568
Table 314 – Primitive issued by the output state machine to the user	568
Table 315 – Primitives issued by the SyncCtl to the output state machine	568
Table 316 – Primitives issued by the output to the SyncCtl state machine	568
Table 317 – Primitives issued by the SyncCtl to the input state machine	569

Table 318 – Primitives issued by the output state machine to the AL	569
Table 319 – Primitives issued by the AL to the output state machine	569
Table 320 – Primitives issued by the input state machine to the AL.....	569
Table 321 – Primitives issued by the AL to the input state machine.....	569
Table 322 – SyncCtl state table	571
Table 323 – Output state table	573
Table 324 – Input state table.....	578
Table 325 – Subslot number for interface submodules	583
Table 326 – Subslot number for port submodules.....	583
Table 327 – Subslot Number for Interface Submodules	585
Table 328 – Subslot Number for Sync Interface Submodules	585
Table 329 – Sync Properties Role	586
Table 330 – Sync Class	587
Table 331 – Subslot Number for Fiber Optic Submodules	587
Table 332 – Fiber Optic Types	588
Table 333 – Fiber Optic Cable Types	588
Table 334 – Write expected port data.....	591
Table 335 – Write adjusted port data	594
Table 336 – Read real port data.....	596
Table 337 – Read expected port data	599
Table 338 – Read adjusted port data	601
Table 339 – Write IR data	604
Table 340 – Read IR data	608
Table 341 – Write sync data.....	612
Table 342 – Read real sync data.....	615
Table 343 – Read expected sync data	618
Table 344 – Read PDev data	621
Table 345 – Sync state info.....	626
Table 346 – Write adjusted fiber optic data	627
Table 347 – Read real fiber optic data	630
Table 348 – Write MRP interface data.....	632
Table 349 – Read MRP interface data.....	635
Table 350 – Write MRP port data	637
Table 351 – Read MRP port data	639
Table 352 – Write FSU data.....	641
Table 353 – Read FSU data.....	643
Table 354 – Set time.....	648
Table 355 – Device Access.....	659
Table 356 – Companion AR	659
Table 357 – Media Redundancy.....	663
Table 358 – Frame ID	664

Table 359 – Read AR data	669
Table 360 – State table application startup IO device.....	674
Table 361 – State table functions for startup IO device	680
Table 362 – State table startup manager IO device	682
Table 363 – State table functions for startup manager RT_CLASS_3 IO device	683
Table 364 – State table IRT port state IO device (standard)	685
Table 365 – State table functions for IRT port state IO device (standard).....	695
Table 366 – State table IRT port state IO device (optimized).....	697
Table 367 – State table neighborhood check.....	704
Table 368 – State table functions for neighborhood check	711
Table 369 – State table PD parameter check IO device.....	712
Table 370 – State table functions PD parameter check IO device.....	717
Table 371 – State table fiber optic maintenance required	718
Table 372 – State table fiber optic maintenance demanded.....	719
Table 373 – State table fiber optic diagnosis.....	720
Table 374 – State table for a submodule	722
Table 375 – State table for plug	732
Table 376 – State table for pull	733
Table 377 – State table of PTCP behavior	735
Table 378 – Functions used by PTCP behavior	736
Table 379 – State table IO controller during startup	739
Table 380 – State table startup manager IO controller	742
Table 381 – Functions for startup manager IO controller	744

INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the "three-layer" fieldbus reference model described in IEC/TR 61158-1.

The application service is provided by the application protocol making use of the services available from the data-link or other immediately lower layer. This standard defines the application service characteristics that fieldbus applications and/or system management may exploit.

Throughout the set of fieldbus standards, the term "service" refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the application layer service defined in this standard is a conceptual architectural service, independent of administrative and implementation divisions.

INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –

Part 5-10: Application layer service definition – Type 10 elements

1 Scope

1.1 Overview

The fieldbus Application Layer (FAL) provides user programs with a means to access the fieldbus communication environment. In this respect, the FAL can be viewed as a “window between corresponding application programs.”

This standard provides common elements for basic time-critical and non-time-critical messaging communications between application programs in an automation environment and material specific to type 10 fieldbus. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible service provided by the type 10 fieldbus Application Layer in terms of

- a) an abstract model for defining application resources (objects) capable of being manipulated by users via the use of the FAL service,
- b) the primitive actions and events of the service;
- c) the parameters associated with each primitive action and event, and the form which they take; and
- d) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the services provided to

- 1) the FAL user at the boundary between the user and the Application Layer of the Fieldbus Reference Model, and
- 2) Systems Management at the boundary between the Application Layer and Systems Management of the Fieldbus Reference Model.

This standard specifies the structure and services of the type 10 IEC fieldbus Application Layer, in conformance with the OSI Basic Reference Model (ISO/IEC 7498) and the OSI Application Layer Structure (ISO/IEC 9545).

FAL services and protocols are provided by FAL application-entities (AE) contained within the application processes. The FAL AE is composed of a set of object-oriented Application Service Elements (ASEs) and a Layer Management Entity (LME) that manages the AE. The ASEs provide communication services that operate on a set of related application process object (APO) classes. One of the FAL ASEs is a management ASE that provides a common set of services for the management of the instances of FAL classes.

Although these services specify, from the perspective of applications, how request and responses are issued and delivered, they do not include a specification of what the requesting and responding applications are to do with them. That is, the behavioral aspects of the applications are not specified; only a definition of what requests and responses they can send/receive is specified. This permits greater flexibility to the FAL users in standardizing such object behavior. In addition to these services, some supporting services are also defined in this standard to provide access to the FAL to control certain aspects of its operation.

1.2 Specifications

The principal objective of this standard is to specify the characteristics of conceptual application layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of application layer protocols for time-critical communications.

A secondary objective is to provide migration paths from previously-existing industrial communications protocols. It is this latter objective which gives rise to the diversity of services standardized as the various Types of IEC 61158, and the corresponding protocols standardized in subparts of IEC 61158-6.

This specification may be used as the basis for formal Application Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters, and
- b) the correlation of paired request and confirm, or indication and response, primitives.

1.3 Conformance

This standard does not specify individual implementations or products, nor do they constrain the implementations of application layer entities within industrial automation systems.

There is conformance of equipment to this application layer service definition standard mainly achieved through implementation of the modeled behavior of an application layer user (e.g. see user state machines) accompanied by implementation of conforming application layer protocols that fulfill the application layer services as defined in this standard.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60559, *Binary floating-point arithmetic for microprocessor systems*

IEC 61131-1, *Programmable controllers – Part 1: General information*

IEC 61131-3, *Programmable controllers – Part 3: Programming languages*

IEC 61158-6-3, *Industrial communication networks – Fieldbus specifications – Part 6-3: Application layer protocol specification – Type 3 elements*

IEC 61158-6-10, *Industrial communication networks – Fieldbus specifications – Part 6-10: Application layer protocol specification – Type 10 elements*

ISO/IEC 646, *Information technology – ISO 7-bit coded character set for information interchange*

ISO/IEC 7498-1, *Information technology – Open Systems Interconnection – Basic Reference Model – Part 1: The Basic Model*

ISO/IEC TR 8802-1, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 1: Overview of Local Area Network Standards*

ISO/IEC 8802-3, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3:*