

© Copyright SEK. Reproduction in any form without permission is prohibited.

## **Elektrisk utrustning för medicinskt bruk – Egenskaper hos digitala röntgenbildgivande anordningar – Del 1-3: Bestämning av effektivitet vid detektering av röntgenkvanta (DQE) – Detektorer för dynamisk bildgivning**

*Medical electrical equipment –  
Characteristics of digital X-ray imaging devices –  
Part 1-3: Determination of the detective quantum efficiency –  
Detectors used in dynamic imaging*

Som svensk standard gäller europastandarden EN 62220-1-3:2008. Den svenska standarden innehåller den officiella engelska språkversionen av EN 62220-1-3:2008.

### **Nationellt förord**

Europastandarden EN 62220-1-3:2008

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 62220-1-3, First edition, 2008 - Medical electrical equipment - Characteristics of digital X-ray imaging devices - Part 1-3: Determination of the detective quantum efficiency - Detectors used in dynamic imaging**

utarbetad inom International Electrotechnical Commission, IEC.

---

ICS 11.040.50

## *Standarder underlättar utvecklingen och höjer elsäkerheten*

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

## *SEK är Sveriges röst i standardiseringssarbetet inom elområdet*

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

## *Stora delar av arbetet sker internationellt*

Utdriften av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringssarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringssverksamhet och medlemsavgift till IEC och CENELEC.

## *Var med och påverka!*

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtidens standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

### **SEK Svensk Elstandard**

Box 1284  
164 29 Kista  
Tel 08-444 14 00  
[www.elstandard.se](http://www.elstandard.se)

English version

**Medical electrical equipment -  
Characteristics of digital X-ray imaging devices -  
Part 1-3: Determination of the detective quantum efficiency -  
Detectors used in dynamic imaging  
(IEC 62220-1-3:2008)**

Appareils électromédicaux -  
Caractéristiques des dispositifs d'imagerie  
numérique à rayonnement X -  
Partie 1-3: Détermination de  
l'efficacité quantique de détection -  
DéTECTeurs utilisés en imagerie dynamique  
(CEI 62220-1-3:2008)

Medizinische elektrische Geräte -  
Merkmale digitaler Röntgenbildgeräte -  
Teil 1-3: Bestimmung der  
detektiven Quanten-Ausbeute -  
Bildempfänger für  
dynamische Bildgebung  
(IEC 62220-1-3:2008)

This European Standard was approved by CENELEC on 2008-07-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: rue de Stassart 35, B - 1050 Brussels**

## Foreword

The text of document 62B/694/FDIS, future edition 1 of IEC 62220-1-3, prepared by SC 62B, Diagnostic imaging equipment, of IEC TC 62, Electrical equipment in medical practice, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62220-1-3 on 2008-07-01.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2009-04-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2011-07-01

In this standard, terms printed in SMALL CAPITALS are used as defined in IEC/TR 60788, in Clause 3 of this standard or in other IEC publications referenced in the Index of defined terms. Where a defined term is used as a qualifier in another defined or undefined term it is not printed in SMALL CAPITALS, unless the concept thus qualified is defined or recognized as a "derived term without definition".

NOTE Attention is drawn to the fact that, in cases where the concept addressed is not strongly confined to the definition given in one of the publications listed above, a corresponding term is printed in lower-case letters.

In this standard, certain terms that are not printed in SMALL CAPITALS have particular meanings, as follows:

- "shall" indicates a requirement that is mandatory for compliance;
- "should" indicates a strong recommendation that is not mandatory for compliance;
- "may" indicates a permitted manner of complying with a requirement or of avoiding the need to comply;
- "specific" is used to indicate definitive information stated in this standard or referenced in other standards, usually concerning particular operating conditions, test arrangements or values connected with compliance;
- "specified" is used to indicate definitive information stated by the manufacturer in accompanying documents or in other documentation relating to the equipment under consideration, usually concerning its intended purposes, or the parameters or conditions associated with its use or with testing to determine compliance.

This European Standard has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of EC Directive MDD (93/42/EEC). See Annex ZZ.

Annexes ZA and ZZ have been added by CENELEC.

---

### **Endorsement notice**

The text of the International Standard IEC 62220-1-3:2008 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 62220-1            NOTE Harmonized as EN 62220-1:2004 (not modified).

IEC 62220-1-2        NOTE Harmonized as EN 62220-1-2:2007 (not modified).

IEC 61262-5        NOTE Harmonized as EN 61262-5:1994 (not modified).

---

## Annex ZA

(normative)

### Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60336	<sup>1)</sup>	Medical electrical equipment - X-ray tube assemblies for medical diagnosis - Characteristics of focal spots	EN 60336	2005 <sup>2)</sup>
IEC/TR 60788	2004	Medical electrical equipment - Glossary of defined terms	-	-
IEC 61267	1994	Medical diagnostic X-ray equipment - Radiation conditions for use in the determination of characteristics	EN 61267 <sup>3)</sup>	1994
ISO 12232	1998	Photography - Electronic still-picture cameras - Determination of ISO speed	-	-

---

<sup>1)</sup> Undated reference.

<sup>2)</sup> Valid edition at date of issue.

<sup>3)</sup> IEC 61267:2005 is harmonised as EN 61267:2006 (not modified).

## CONTENTS

INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms and definitions .....	8
4 Requirements .....	10
4.1 Operating conditions .....	10
4.2 X-RAY EQUIPMENT .....	10
4.3 RADIATION QUALITY .....	10
4.4 TEST DEVICE.....	11
4.5 Geometry .....	12
4.6 IRRADIATION conditions .....	14
4.6.1 General conditions .....	14
4.6.2 AIR KERMA measurement .....	15
4.6.3 LAG EFFECTS.....	16
4.6.4 IRRADIATION to obtain the CONVERSION FUNCTION .....	16
4.6.5 IRRADIATION for determination of the NOISE POWER SPECTRUM and LAG EFFECTS .....	16
4.6.6 IRRADIATION with TEST DEVICE in the RADIATION BEAM.....	17
4.6.7 Overview of all necessary IRRADIATIONS .....	18
5 Corrections of RAW DATA.....	18
6 Determination of the DETECTIVE QUANTUM EFFICIENCY .....	19
6.1 Definition and formula of $DQE(u,v)$ .....	19
6.2 Parameters to be used for evaluation .....	19
6.3 Determination of different parameters from the images.....	20
6.3.1 Linearization of data .....	20
6.3.2 The LAG EFFECTS corrected NOISE POWER SPECTRUM (NPS) .....	20
6.3.3 Determination of the MODULATION TRANSFER FUNCTION (MTF).....	24
7 Format of conformance statement .....	24
8 Accuracy .....	25
Annex A (informative) Determination of LAG EFFECTS.....	26
Annex B (informative) Calculation of the input NOISE POWER SPECTRUM .....	29
Bibliography.....	30
Index of defined terms .....	32
 Figure 1 – TEST DEVICE .....	12
Figure 2 – Geometry for exposing the DIGITAL X-RAY IMAGING DEVICE in order to determine the CONVERSION FUNCTION, the NOISE POWER SPECTRUM and the MODULATION TRANSFER FUNCTION behind the TEST DEVICE.....	14
Figure 3 – Image acquisition sequence to determine the NOISE POWER SPECTRUM and LAG EFFECTS .....	17
Figure 4 – Geometric arrangement of the ROIs .....	21
Figure A.1 – Power spectral density of white noise $s$ and correlated signal $g$ (only positive frequencies are shown).....	27

Table 1 – RADIATION QUALITY (IEC 61267:1994) for the determination of DETECTIVE QUANTUM EFFICIENCY and corresponding parameters .....	11
Table 2 – Necessary IRRADIATIONS .....	18
Table 3 – Parameters mandatory for the application of this standard .....	20

## INTRODUCTION

DIGITAL X-RAY IMAGING DEVICES are increasingly used in medical diagnosis and will widely replace conventional (analogue) imaging devices such as screen-film systems or analogue X-RAY IMAGE INTENSIFIER television systems in the future. It is necessary, therefore, to define parameters that describe the specific imaging properties of these DIGITAL X-RAY IMAGING DEVICES and to standardize the measurement procedures employed.

There is growing consensus in the scientific world that the DETECTIVE QUANTUM EFFICIENCY (DQE) is the most suitable parameter for describing the imaging performance of an X-ray imaging device. The DQE describes the ability of the imaging device to preserve the signal-to-NOISE ratio from the radiation field to the resulting digital image data. Since in X-ray imaging, the NOISE in the radiation field is intimately coupled to the AIR KERMA level, DQE values can also be considered to describe the dose efficiency of a given DIGITAL X-RAY IMAGING DEVICE.

NOTE 1 In spite of the fact that the DQE is widely used to describe the performance of imaging devices, the connection between this physical parameter and the decision performance of a human observer is not yet completely understood [1], [3].<sup>1)</sup>

NOTE 2 IEC 61262-5 specifies a method to determine the DQE of X-RAY IMAGE INTENSIFIERS at nearly zero SPATIAL FREQUENCY. It focuses only on the electro-optical components of X-RAY IMAGE INTENSIFIERS, not on the imaging properties as this standard does. As a consequence, the output is measured as an optical quantity (luminance), and not as digital data. Moreover, IEC 61262-5 prescribes the use of a RADIATION SOURCE ASSEMBLY, whereas this standard prescribes the use of an X-RAY TUBE. The scope of IEC 61262-5 is limited to X-RAY IMAGE INTENSIFIERS and does not interfere with the scope of this standard.

The DQE is already widely used by manufacturers to describe the performance of their DIGITAL X-RAY IMAGING DEVICE. The specification of the DQE is also required by regulatory agencies (such as the Food and Drug Administration (FDA)) for admission procedures. However, there is presently no standard governing either the measurement conditions or the measurement procedure, with the consequence that values from different sources may not be comparable.

This standard has therefore been developed in order to specify the measurement procedure together with the format of the conformance statement for the DETECTIVE QUANTUM EFFICIENCY of DIGITAL X-RAY IMAGING DEVICES.

In the DQE calculations proposed in this standard, it is assumed that system response is measured for objects that attenuate all energies equally (task-independent) [5].

This standard will be beneficial for manufacturers, users, distributors and regulatory agencies. It is the third document out of a series of three related standards:

- Part 1, which is intended to be used in RADIOGRAPHY, excluding MAMMOGRAPHY and RADIOSCOPY.
- Part 1-2, which is intended to be used for MAMMOGRAPHY.
- the present Part 1-3, which is intended to be used for dynamic imaging detectors.

These standards can be regarded as the first part of the family of IEC 62220 standards describing the relevant parameters of DIGITAL X-RAY IMAGING DEVICES.

---

1) Figures in square brackets refer to the bibliography.

## MEDICAL ELECTRICAL EQUIPMENT – CHARACTERISTICS OF DIGITAL X-RAY IMAGING DEVICES –

### Part 1-3: Determination of the detective quantum efficiency – Detectors used in dynamic imaging

#### **1 Scope**

This part of IEC 62220 specifies the method for the determination of the DETECTIVE QUANTUM EFFICIENCY (DQE) of DIGITAL X-RAY IMAGING DEVICES as a function of AIR KERMA and of SPATIAL FREQUENCY for the working conditions in the range of the medical application as specified by the MANUFACTURER. The intended users of this part of IEC 62220 are manufacturers and well equipped test laboratories.

This Part 1-3 is restricted to DIGITAL X-RAY IMAGING DEVICES that are used for dynamic imaging such as, but not exclusively, direct and indirect flat panel-detector based systems.

It is not recommended to use this part of IEC 62220 for digital X-RAY IMAGE INTENSIFIER-based systems.

NOTE 1 This negative recommendation is based on the low frequency drop, vignetting and geometrical distortion present in these devices which may put severe limitations on the applicability of the measurement methods described in this standard.

This part of IEC 62220 is not applicable to:

- DIGITAL X-RAY IMAGING DEVICES intended to be used in mammography or in dental radiography;
- COMPUTED TOMOGRAPHY; and
- systems in which the X-ray field is scanned across the patient.

NOTE 2 The devices noted above are excluded because they contain many parameters (for instance, beam qualities, geometry, time dependence, etc.) which differ from those important for dynamic imaging. Some of these techniques are treated in separate standards (IEC 62220-1 and IEC 62220-1-2).

#### **2 Normative references**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60336, *Medical electrical equipment – X-ray tube assemblies for medical diagnosis – Characteristics of focal spots*

IEC TR 60788:2004, *Medical electrical equipment – Glossary of defined terms*

IEC 61267:1994,<sup>2)</sup> *Medical diagnostic X-ray equipment – Radiation conditions for use in the determination of characteristics*

ISO 12232:1998, *Photography – Electronic still-picture cameras – Determination of ISO speed*

---

2) Although a second edition (2005) of IEC 61267 exists, reference to the first edition (IEC 61267:1994) is expressly retained throughout this standard for reasons of harmonization within the IEC62220 family. (See 4.3, Note 1.)