

© Copyright SEK. Reproduction in any form without permission is prohibited.

## **Industriell processtyrning – Fältbuss – Del 3-17: Definition av tjänster i datalänkskiktet – Delar i fältbuss, Typ 17**

*Industrial communication networks –  
Fieldbus specifications –  
Part 3-17: Data-link layer service definition –  
Type 17 elements*

Som svensk standard gäller europastandarden EN 61158-3-17:2008. Den svenska standarden innehåller den officiella engelska språkversionen av EN 61158-3-17:2008.

### **Nationellt förord**

Europastandarden EN 61158-3-17:2008

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 61158-3-17, First edition, 2007 - Industrial communication networks - Fieldbus specifications - Part 3-17: Data-link layer service definition - Type 17 elements**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 61158-3, ersätter SS-EN 61158-3, utgåva 1, 2004.

Tidigare fastställd svensk standard SS-EN 61158-3, utgåva 1, 2004, gäller ej fr o m 2011-02-01.

### *Standarder underlättar utvecklingen och höjer elsäkerheten*

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

### *SEK är Sveriges röst i standardiseringsarbetet inom elområdet*

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

### *Stora delar av arbetet sker internationellt*

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

### *Var med och påverka!*

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

### **SEK Svensk Elstandard**

Box 1284  
164 29 Kista  
Tel 08-444 14 00  
[www.elstandard.se](http://www.elstandard.se)

English version

**Industrial communication networks -  
Fieldbus specifications -  
Part 3-17: Data-link layer service definition -  
Type 17 elements  
(IEC 61158-3-17:2007)**

Réseaux de communication industriels -  
Spécifications des bus de terrain -  
Partie 3-17: Définition des services  
des couches de liaison de données -  
Éléments de type 17  
(CEI 61158-3-17:2007)

Industrielle Kommunikationsnetze -  
Feldbusse -  
Teil 3-17: Dienstfestlegungen  
des Data Link Layer (Sicherheitsschicht) -  
Typ 17-Elemente  
(IEC 61158-3-17:2007)

This European Standard was approved by CENELEC on 2008-02-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: rue de Stassart 35, B - 1050 Brussels**

## Foreword

The text of document 65C/473/FDIS, future edition 1 of IEC 61158-3-17, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 61158-3-17 on 2008-02-01.

This and the other parts of the EN 61158-3 series supersede EN 61158-3:2004.

With respect to EN 61158-3:2004 the following changes were made:

- deletion of Type 6 fieldbus, and the placeholder for a Type 5 fieldbus data-link layer, for lack of market relevance;
- addition of new fieldbus types;
- partition into multiple parts numbered 3-1, 3-2, ..., 3-19.

The following dates were fixed:

- latest date by which the EN has to be implemented  
at national level by publication of an identical  
national standard or by endorsement (dop) 2008-11-01
- latest date by which the national standards conflicting  
with the EN have to be withdrawn (dow) 2011-02-01

NOTE Use of some of the associated protocol types is restricted by their intellectual-property-right holders. In all cases, the commitment to limited release of intellectual-property-rights made by the holders of those rights permits a particular data-link layer protocol type to be used with physical layer and application layer protocols in type combinations as specified explicitly in the EN 61784 series. Use of the various protocol types in other combinations may require permission from their respective intellectual-property-right holders.

Annex ZA has been added by CENELEC.

---

## Endorsement notice

The text of the International Standard IEC 61158-3-17:2007 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

|                |                                                       |
|----------------|-------------------------------------------------------|
| IEC 61158-4-17 | NOTE Harmonized as EN 61158-4-17:2008 (not modified). |
| IEC 61158-5-17 | NOTE Harmonized as EN 61158-5-17:2008 (not modified). |
| IEC 61158-6-17 | NOTE Harmonized as EN 61158-6-17:2008 (not modified). |
| IEC 61784-2    | NOTE Harmonized as EN 61784-2:2008 (not modified).    |

---

## Annex ZA (normative)

### Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

| <u>Publication</u> | <u>Year</u>     | <u>Title</u>                                                                                                                                                                                                                                                                     | <u>EN/HD</u>      | <u>Year</u>        |
|--------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|--------------------|
| ISO/IEC 7498-1     | - <sup>1)</sup> | Information technology - Open Systems Interconnection - Basic Reference Model: The Basic Model                                                                                                                                                                                   | EN ISO/IEC 7498-1 | 1995 <sup>2)</sup> |
| ISO/IEC 7498-3     | - <sup>1)</sup> | Information technology - Open Systems Interconnection - Basic Reference Model: Naming and addressing                                                                                                                                                                             | -                 | -                  |
| ISO/IEC 10731      | 1994            | Information technology - Open Systems Interconnection - Basic Reference Model - Conventions for the definition of OSI services                                                                                                                                                   | -                 | -                  |
| ISO/IEC 8802-3     | - <sup>1)</sup> | Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications | -                 | -                  |
| IETF RFC 826       | - <sup>1)</sup> | Ethernet Address Resolution Protocol                                                                                                                                                                                                                                             | -                 | -                  |

---

<sup>1)</sup> Undated reference.

<sup>2)</sup> Valid edition at date of issue.



## CONTENTS

|                                                                                                           |    |
|-----------------------------------------------------------------------------------------------------------|----|
| INTRODUCTION.....                                                                                         | 6  |
| 1 Scope.....                                                                                              | 7  |
| 2 Normative reference .....                                                                               | 8  |
| 3 Definitions .....                                                                                       | 8  |
| 3.1 Terms and definitions .....                                                                           | 8  |
| 3.2 Abbreviations and symbols .....                                                                       | 10 |
| 3.3 Conventions .....                                                                                     | 11 |
| 4 Overview of the data-link layer service .....                                                           | 11 |
| 4.1 General .....                                                                                         | 12 |
| 4.2 Overview of network structure .....                                                                   | 13 |
| 4.3 Overview of addressing .....                                                                          | 13 |
| 4.4 Types of data-link service .....                                                                      | 13 |
| 5 DLSAP management service .....                                                                          | 14 |
| 5.1 Overview .....                                                                                        | 14 |
| 5.2 Facilities of the DLSAP management service.....                                                       | 14 |
| 5.3 Model of the DLSAP management service .....                                                           | 14 |
| 5.4 Sequence of primitives at one DLSAP .....                                                             | 14 |
| 5.5 Create .....                                                                                          | 15 |
| 5.6 Delete .....                                                                                          | 16 |
| 5.7 Bind .....                                                                                            | 17 |
| 5.8 Unbind .....                                                                                          | 19 |
| 6 Connectionless-mode data-link service.....                                                              | 19 |
| 6.1 Overview .....                                                                                        | 19 |
| 6.2 Facilities of the connectionless-mode data-link service.....                                          | 20 |
| 6.3 Model of the data-link service .....                                                                  | 20 |
| 6.4 Quality of service .....                                                                              | 21 |
| 6.5 Sequence of primitives .....                                                                          | 23 |
| 6.6 Connectionless-mode function.....                                                                     | 24 |
| 6.7 Types of primitives and parameters .....                                                              | 24 |
| 7 DL-management Service .....                                                                             | 25 |
| 7.1 Scope and inheritance .....                                                                           | 25 |
| 7.2 Facilities of the DL-management service .....                                                         | 26 |
| 7.3 Model of the DL-management service.....                                                               | 26 |
| 7.4 Constraints on sequence of primitives .....                                                           | 26 |
| 7.5 Set .....                                                                                             | 26 |
| 7.6 Get.....                                                                                              | 27 |
| 7.7 Action.....                                                                                           | 28 |
| 7.8 Event .....                                                                                           | 29 |
| Bibliography.....                                                                                         | 30 |
| Figure 1 – Sequence of primitives for the DLSAP management DLS .....                                      | 15 |
| Figure 2 – Summary of DL-connectionless-mode service primitive time-sequence<br>diagrams .....            | 23 |
| Figure 3 – State transition diagram for sequences of connectionless-mode primitives<br>at one DLSAP ..... | 24 |

|                                                                                    |    |
|------------------------------------------------------------------------------------|----|
| Figure 4 – Sequence of primitives for the DLM action service .....                 | 26 |
| Table 1 – Summary of DLSAP management primitives and parameters .....              | 14 |
| Table 2 – DLSAP-management CREATE primitive and parameters .....                   | 15 |
| Table 3 – DLSAP-management DELETE primitive and parameters .....                   | 16 |
| Table 4 – DLSAP management BIND primitive and parameters.....                      | 17 |
| Table 5 – DLSAP management UNBIND primitive and parameter .....                    | 19 |
| Table 6 – Data delivery features of each type of service .....                     | 21 |
| Table 7 – Summary of DL-connectionless-mode primitives and parameters .....        | 23 |
| Table 8 – DL-connectionless-mode UNITDATA transfer primitives and parameters ..... | 24 |
| Table 9 – Summary of DL-management primitives and parameters .....                 | 26 |
| Table 10 – DLM-SET primitive and parameters .....                                  | 27 |
| Table 11 – DLM-GET primitive and parameters.....                                   | 27 |
| Table 12 – DLM-ACTION primitive and parameters.....                                | 28 |
| Table 13 – DLM-EVENT primitive and parameters .....                                | 29 |

## INTRODUCTION

This part of IEC 61158 is one of a series produced to facilitate the interconnection of automation system components. It is related to other standards in the set as defined by the “three-layer” fieldbus reference model described in IEC/TR 61158-1.

Throughout the set of fieldbus standards, the term “service” refers to the abstract capability provided by one layer of the OSI Basic Reference Model to the layer immediately above. Thus, the data-link layer service defined in this standard is a conceptual architectural service, independent of administrative and implementation divisions.

## **INDUSTRIAL COMMUNICATION NETWORKS – FIELDBUS SPECIFICATIONS –**

### **Part 3-17: Data-link layer service definition – Type 17 elements**

#### **1 Scope**

This part of IEC 61158 provides common elements for basic time-critical messaging communications between devices in an automation environment. The term “time-critical” is used to represent the presence of a time-window, within which one or more specified actions are required to be completed with some defined level of certainty. Failure to complete specified actions within the time window risks failure of the applications requesting the actions, with attendant risk to equipment, plant and possibly human life.

This standard defines in an abstract way the externally visible service provided by the Type 17 fieldbus data-link Layer in terms of

- a) the primitive actions and events of the service;
- b) the parameters associated with each primitive action and event, and the form which they take; and
- c) the interrelationship between these actions and events, and their valid sequences.

The purpose of this standard is to define the services provided to

- the Type 17 fieldbus application layer at the boundary between the application and data-link layers of the fieldbus reference model, and
- systems management at the boundary between the data-link layer and systems management of the fieldbus reference model;
- specifications

The principal objective of this standard is to specify the characteristics of conceptual data-link layer services suitable for time-critical communications, and thus supplement the OSI Basic Reference Model in guiding the development of data-link protocols for time-critical communications. A secondary objective is to provide migration paths from previously-existing industrial communications protocols.

This specification may be used as the basis for formal DL-Programming-Interfaces. Nevertheless, it is not a formal programming interface, and any such interface will need to address implementation issues not covered by this specification, including

- a) the sizes and octet ordering of various multi-octet service parameters, and
  - b) the correlation of paired request and confirm, or indication and response, primitives.
- Conformance

This standard does not specify individual implementations or products, nor does it constrain the implementations of data-link entities within industrial automation systems.

There is no conformance of equipment to this data-link layer service definition standard. Instead, conformance is achieved through implementation of the corresponding data-link protocol that fulfills the Type 17 data-link layer services defined in this standard.