



IEC 62246-2

Edition 1.0 2007-10

INTERNATIONAL STANDARD

**Reed contact units –
Part 2: Heavy-duty reed switches**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

PRICE CODE



ICS 29.120.70

ISBN 2-8318-9330-5

CONTENTS

FOREWORD.....	5
1 General	7
1.1 Scope.....	7
1.2 Normative references	7
1.3 Terms, definitions, abbreviations and symbols.....	7
1.4 Preferred values.....	8
1.4.1 Frequency of operation.....	8
1.4.2 Duty cycle	8
1.4.3 Open-circuit voltage across contacts	8
1.4.4 Current ratings	8
1.4.5 Load ratings	8
1.4.6 Number of operations	8
1.4.7 Climatic category.....	8
1.4.8 Preferred environmental severities	8
1.4.9 Rated operational voltage; U_e	8
1.4.10 Rated switching current; I_e	9
1.4.11 Rated insulation voltage	9
1.4.12 Rated impulse voltage	9
1.4.13 Utilization categories	9
1.4.14 Contact reliability.....	9
1.4.15 Limiting continuous current; I_{th}	9
1.5 Marking	10
1.6 Order of precedence	10
1.7 Precautions regarding mercury (for mercury wetted contact units).....	10
2 Quality assessment procedures	10
2.1 General.....	10
2.2 Self-certification	10
2.3 Two-party certification	10
2.4 Third-party certification.....	10
3 Test and measurement procedures.....	11
3.1 General.....	11
3.2 Alternative procedures	11
3.3 Standard conditions for testing	11
3.4 Visual inspection and check of dimensions.....	11
3.5 Functional tests	11
3.6 Remanence test	11
3.7 Contact circuit resistance	11
3.8 Dielectric test	11
3.9 Insulation resistance	11
3.10 Operate, release, transfer or bridging, and bounce times.....	11
3.11 Contact sticking.....	12
3.12 Robustness of terminals	12
3.13 Soldering (solderability and resistance to soldering heat)	12
3.14 Climatic sequence	12
3.15 Damp heat, steady state.....	12

3.16	Rapid change of temperature	12
3.17	Salt mist	12
3.18	Bump	12
3.19	Vibration	12
3.20	Shock	12
3.21	Acceleration test – Functional test only	12
3.22	Sealing	12
3.23	Electrical endurance	12
3.23.1	General	12
3.23.2	Types of electrical endurance test	13
3.23.3	Standard electrical endurance test	13
3.23.4	Application simulation endurance test	14
3.23.5	Requirements	14
3.23.6	Information to be stated in the detail specification	14
3.24	Mechanical endurance	15
3.25	Maximum cycling frequency	15
3.26	Mounting position test (for mercury wetted contact units)	15
3.27	Drain time test (for mercury wetted contact units)	15
3.28	Voltage surge test	15
3.29	Rated impulse voltage	15
3.29.1	Procedure	15
3.29.2	Requirements	16
3.29.3	Information to be stated in the detail specification	16
3.30	Rated making and breaking capacities	16
3.30.1	General test arrangements	16
3.30.2	Procedure	16
3.30.3	Requirements	16
3.30.4	Information to be stated in the detail specification	16
3.31	Rated conditional short-circuit current	19
3.31.1	General test arrangements	19
3.31.2	Procedure	19
3.31.3	Requirements	19
3.31.4	Information to be stated in the detail specification	20
3.32	Contact reliability test	20
3.32.1	General test arrangements	20
3.32.2	Procedure	20
3.32.3	Requirements	21
3.32.4	Information to be stated in the detail specification	21
3.33	Temperature rise	22
3.33.1	Procedure	22
3.33.2	Requirements	22
3.33.3	Information to be stated in the detail specification	22
3.34	Making current capacity test	23
3.34.1	General	23
3.34.2	Procedure	23
3.34.3	Requirements	23
3.34.4	Information to be stated in the detail specification	23
3.35	Breaking current capacity test	24
3.35.1	General	24

3.35.2 Procedure.....	24
3.35.3 Requirements	24
3.35.4 Information to be stated in the detail specification	24
Annex A (informative) Electrical endurance test circuit.....	26
Annex B (informative) Rated conditional short-circuit current test circuit	28
Annex C (informative) Electrical ratings based on utilization categories	29
Annex D (informative) Example of test arrangement for contact reliability test	31
Annex E (informative) Standard test coils for heavy-duty reed switches	32
Annex F (informative) Making current capacity test sequence	33
Annex G (informative) Breaking current capacity test sequence	34
Bibliography.....	35
Figure A.1 – Generalized endurance test circuit.....	26
Figure A.2 – Functional block diagram	27
Figure B.1 – Rated conditional short-circuit current test circuit.....	28
Figure D.1 – Contact reliability test circuit.....	31
Figure E.1 – Configuration of test coils	32
Figure F.1 – Making current capacity test sequence	33
Figure G.1 – Breaking current capacity test sequence	34
Table 1 – Utilization categories	9
Table 2 – Making and breaking capacity for electrical endurance tests	17
Table 3 – Verification of making and breaking capacity for AC-15 / DC-13 under normal conditions	18
Table 4 – Verification of making and breaking capacity for AC-15 / DC-13 under abnormal conditions.....	19
Table C.1 – Examples of contact rating designation based on utilization categories.....	29
Table E.1 – List of standard test coils	32

INTERNATIONAL ELECTROTECHNICAL COMMISSION

REED CONTACT UNITS –**Part 2: Heavy-duty reed switches**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62246-2 has been prepared by IEC technical committee 94: All-or-nothing electrical relays.

This part of IEC 62246 is to be read in conjunction with IEC 62246-1.

The text of this standard is based on the following documents:

CDV	Report on voting
94/243/CDV	94/257A/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of IEC 62246 series, published under the general title *Reed contact units*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

REED CONTACT UNITS –

Part 2: Heavy-duty reed switches

1 General

1.1 Scope

This part of IEC 62246 applies to the switching performance of heavy-duty reed switches for use in industrial applications based upon Part 1.

This part of IEC 62246 specifies reliability tests, rated making and breaking capacities, rated impulse voltages, rated conditional short-circuit currents, temperature rise and construction testing in addition to the requirements of Part 1.

Heavy-duty reed switches are glass sealed contact units and include high pressure sealed types. This part of IEC 62246 does not apply to mercury-wetted reed contact units.

NOTE 1 Heavy-duty reed switches are mainly used within electromagnetic switching devices, valves, solenoids, power relays, etc., as the electromagnetic load switching elements. The load conditions should be selected from the standard inductive loads and the load specifications specified in IEC 61810-1 and IEC 60947-5-1.

NOTE 2 For elementary relays using heavy-duty reed switches as contact elements, this standard should be used together with IEC 61810-1 and IEC 61811-1 as applicable.

NOTE 3 For electromechanical control circuit devices using heavy-duty reed switches as contact elements, this standard should be used together with IEC 60947-5-1 as applicable.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62246-1:2002, *Reed contact units – Part 1: Generic specification*

IECEE 01:2006, *IEC System of Conformity Assessment Schemes for Electrotechnical Equipment and Components (IECEE) – Basic rules*

IECEE 03:2006, *Rules of Procedure of the Scheme of the IECEE for Mutual Recognition of Conformity Assessment Certificates for Electrotechnical Equipment and Components (CB-FCS)*

IECQ 01:2003, *IEC Quality Assessment System for Electronic Components (IECQ) – Basic Rules*

IECQ QC 001002-1:1998, *IEC Quality Assessment System for Electronic Components (IECQ) – Rules of Procedure – Part 1: Administration*