

INTERNATIONAL STANDARD

IEC 62231

First edition
2006-02

Composite station post insulators for substations with a.c. voltages greater than 1 000 V up to 245 kV – Definitions, test methods and acceptance criteria

© IEC 2006 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembé, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CONTENTS

FOREWORD.....	4
INTRODUCTION.....	6
1 Scope and object.....	7
2 Normative references	7
3 Terms and definitions	8
4 Identification.....	11
5 Environmental conditions.....	11
6 Information on transport, storage and installation	12
7 Classification of tests	12
7.1 Design tests	12
7.2 Type tests	13
7.3 Sample tests	13
7.4 Routine tests	13
8 Design tests	14
8.1 General	14
8.2 Tests on interfaces and connections of end fittings.....	14
8.3 Assembled core load tests.....	15
8.4 Tests on shed and housing material	16
8.5 Tests on the core material	17
9 Type tests	17
9.1 Verification of dimensions	17
9.2 Electrical tests.....	17
9.3 Mechanical tests	19
10 Sample tests	20
10.1 General rules	20
10.2 Verification of dimensions (E1 + E2).....	21
10.3 Galvanizing test (E1 + E2).....	21
10.4 Verification of the specified mechanical loads (E1).....	21
10.5 Re-testing procedure.....	22
11 Routine tests	22
11.1 Identification of the station post insulator	22
11.2 Visual examination	22
11.3 Tensile load test.....	22
Annex A (informative) Notes on the mechanical loads and tests	24
Annex B (informative) Determination of the equivalent bending moment caused by combined cantilever and compression (tension) loads.....	26
Annex C (informative) Example of torsion load test arrangement	28
Annex D (normative) Tolerances of form and position	29
Annex E (informative) Notes on the compression and buckling test.....	32
Bibliography.....	33

Figure 1 – Thermal-mechanical pre-stressing test – Typical cycles 23

Figure B.1 – Combined loads applied to station post insulators..... 27

Figure D.1 – Parallelism, coaxiality and concentricity..... 29

Figure D.2 – Angular deviation of fixing holes: Example 1..... 30

Figure D.3 – Angular deviation of fixing holes: Example 2..... 30

Figure D.4 – Tolerances according to standard drawing practice..... 31

Table 1 – Tests to be carried out after design changes 12

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**COMPOSITE STATION POST INSULATORS FOR SUBSTATIONS
WITH AC VOLTAGES GREATER THAN 1000 V UP TO 245 kV –
DEFINITIONS, TEST METHODS AND ACCEPTANCE CRITERIA**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62231 has been prepared by subcommittee 36C: Insulators for substations, of IEC technical committee 36: Insulators.

The text of this standard is based on the following documents:

FDIS	Report on voting
36C/159/FDIS	36C/160/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This standard is to be read in conjunction with IEC 62217.

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

INTRODUCTION

Composite station post insulators consist of a cylindrical solid insulating core made of resin impregnated fibres, bearing the mechanical load, protected by an elastomer housing, the loads being transmitted to the core by metal fittings. Despite these common features, the materials used and the construction details employed by different manufacturers may be different.

Some tests have been grouped together as "design tests" to be performed only once for insulators of the same design. The design tests are performed in order to eliminate insulator designs, materials and manufacturing technologies not suitable for high-voltage applications. The influence of time on the electrical and mechanical properties of the complete composite station post insulator and its components (core material, housing material, interfaces, etc.) has been considered in specifying the design tests in order to ensure a satisfactory lifetime under normal service conditions.

The approach for mechanical testing under bending loads used in this Standard is based on IEC 61952. This approach uses the concept of a damage limit that is the maximum stress that can be developed in the insulator before damage begins to occur. Work is underway to validate the acoustic emission technique to determine the inception of damage.

In some cases, station post insulators can be subjected to a combination of loads. In order to give some guidance, Annex B explains how to calculate the equivalent bending moment in the insulators resulting from the combination of bending, tensile and compression loads.

Pollution tests, as specified in IEC 60507 and IEC 61245, are not included in this document, their applicability to composite station post insulators having not been proven. Such pollution tests performed on composite insulators do not correlate with experience obtained from service. Specific pollution tests for composite insulators are under consideration.

It has not been considered useful to specify a power arc test as a mandatory test. The test parameters are manifold and can have very different values depending on the configurations of the network and the supports and on the design of arc-protection devices. The heating effect of power arcs should be considered in the design of metal fittings. Critical damage to the metal fittings, resulting from the magnitude and duration of the short-circuit current can be avoided by properly designed arc-protection devices. This standard, however, does not exclude the possibility of a power arc test by agreement between the user and the manufacturer. IEC 61467 gives details of a.c. power arc testing of insulator sets.

Impulse (mechanical) loads in substation are typically caused by short-circuits. Post insulators are affected by forces due to the interaction of the currents circulating in conductors/busbars supported by insulators.

The impulse load or peak load may be evaluated using guidance found in the IEC 60865 series.

Work is in progress in CIGRE ESCC (Effects of Short-Circuit Currents) task force to review impulse loads caused by short-circuit currents in substations. The aim of this work is to introduce a new concept: the ESL factor (Equivalent Static Load factor) which is frequency dependent. The actual peak load may be replaced, in a first approximation, by the peak load times the ESL factor. This new value may be used as the MDCL in this document for the determination of the cantilever strength.

Radio interference and corona tests are not specified in this standard since the radio interference and corona performances are not characteristics of the insulator alone.

Composite hollow core station post insulators are currently not dealt with in this standard. IEC 61462 gives details of tests on hollow core composite insulators, many of which can be applied to such station post insulators.

COMPOSITE STATION POST INSULATORS FOR SUBSTATIONS WITH AC VOLTAGES GREATER THAN 1 000 V UP TO 245 kV – DEFINITIONS, TEST METHODS AND ACCEPTANCE CRITERIA

1 Scope and object

This International Standard applies to composite station post insulators consisting of a load bearing cylindrical insulating solid core made of resin impregnated fibres, a housing (outside the insulating solid core) made of elastomer material (e.g. silicone or ethylene-propylene) and end fittings attached to the insulating core. Composite station post insulators covered by this standard are subjected to cantilever, torsion, tension and compression loads. They are intended for substations with a.c. voltages greater than 1 000 V up to 245 kV.

The object of this standard is

- to define the terms used,
- to prescribe test methods,
- to prescribe acceptance or failure criteria.

This standard does not include requirements dealing with the choice of insulators for specific operating conditions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-471, *International Electrotechnical Vocabulary (IEV) – Chapter 471: Insulators*

IEC 60060-1, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60168:1994, *Tests on indoor and outdoor post insulators of ceramic material or glass for systems with nominal voltages greater than 1 000 V*

IEC 62217: —, *Polymeric insulators for indoor and outdoor use with a nominal voltage greater than 1000 V – General definitions, test methods and acceptance criteria*

ISO 1101, *Technical drawings – Geometrical tolerancing – Tolerancing of form, orientation, location and run-out – Generalities, definitions, symbols, indications on drawings*

ISO 3452, *Non-destructive testing – Penetrant inspection – General principles*