

© Copyright SEK. Reproduction in any form without permission is prohibited.

Kopplingsapparater för högst 1000 V – Del 7-3: Övrig hithörande materiel – Säkerhetsfordringar på plintar med säkring

*Low-voltage switchgear and controlgear –
Part 7-3: Ancillary equipment –
Safety requirements for fuse terminal blocks*

Som svensk standard gäller europastandarden EN 60947-7-3:2009. Den svenska standarden innehåller den officiella engelska språkversionen av EN 60947-7-3:2009.

Nationellt förord

Europastandarden EN 60947-7-3:2009

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 60947-7-3, Second edition, 2009 - Low-voltage switchgear and controlgear -
Part 7-3: Ancillary equipment - Safety requirements for
fuse terminal blocks**

utarbetad inom International Electrotechnical Commission, IEC.

Standarden ska användas tillsammans med SS-EN 60947-1 och SS-EN 60947-7-1.

Tidigare fastställd svensk standard SS-EN 60947-7-3, utgåva 1, 2003, gäller ej fr o m 2012-09-01.

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Low-voltage switchgear and controlgear -
Part 7-3: Ancillary equipment -
Safety requirements for fuse terminal blocks
(IEC 60947-7-3:2009)**

Appareillage à basse tension -
Partie 7-3: Matériels accessoires -
Exigences de sécurité pour les blocs
de jonction à fusible
(CEI 60947-7-3:2009)

Niederspannungsschaltgeräte -
Teil 7-3: Hilfseinrichtungen -
Sicherheitsanforderungen
für Sicherungs-Reihenklemmen
(IEC 60947-7-3:2009)

This European Standard was approved by CENELEC on 2009-09-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 17B/1657/FDIS, future edition 2 of IEC 60947-7-3, prepared by SC 17B, Low-voltage switchgear and controlgear, of IEC TC 17, Switchgear and controlgear, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 60947-7-3 on 2009-09-10.

This European Standard supersedes EN 60947-7-3:2002.

The main technical modifications of EN 60947-7-3:2009 since EN 60947-7-3:2002 are listed below:

- requirements regarding clearances and creepage distances replaced by reference to Annex H of EN 60947-1;
- requirements for the test of the mechanical strength of the clamping units improved in 8.3.3.1;
- requirements for tightening torques for the tests improved and referenced to Table 4 of EN 60947-1;
- requirements for the resistance and the dimensions of dummy fuse-links specified in 8.5.2.5.

This standard shall be read in conjunction with EN 60947-1 and EN 60947-7-1. The provisions of the general rules dealt with in EN 60947-1 and the requirements for terminal blocks of EN 60947-7-1 are applicable to this standard, where specifically called for. Clauses and subclauses, tables, figures and annexes thus applicable are identified by reference to EN 60947-1 or EN 60947-7-1, e.g. 1.2 of EN 60947-1, Table 4 of EN 60947-7-1 or Annex A of EN 60947-1.

The following dates were fixed:

- latest date by which the EN has to be implemented
at national level by publication of an identical
national standard or by endorsement (dop) 2010-06-01
- latest date by which the national standards conflicting
with the EN have to be withdrawn (dow) 2012-09-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 60947-7-3:2009 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 60127-6 + A1 + A2	NOTE Harmonized as EN 60127-6:1994 + A1:1996 + A2:2003 (not modified).
IEC 60715 + A1	NOTE Harmonized as EN 60715:2001 (not modified).
IEC 61180-1	NOTE Harmonized as EN 61180-1:1994 (not modified).
IEC 61180-2	NOTE Harmonized as EN 61180-2:1994 (not modified).

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60127-1	2006	Miniature fuses - Part 1: Definitions for miniature fuses and general requirements for miniature fuse-links	EN 60127-1	2006
IEC 60127-2	2003	Miniature fuses -	EN 60127-2	2003
A1	2003	Part 2: Cartridge fuse-links	A1	2003
IEC 60216-1	2001	Electrical insulating materials - Properties of thermal endurance - Part 1: Ageing procedures and evaluation of test results	EN 60216-1	2001
IEC 60695-11-5	2004	Fire hazard testing - Part 11-5: Test flames - Needle-flame test method - Apparatus, confirmatory test arrangement and guidance	EN 60695-11-5	2005
IEC 60947-1	2007	Low-voltage switchgear and controlgear - Part 1: General rules	EN 60947-1	2007
IEC 60947-7-1	¹⁾	Low-voltage switchgear and controlgear - Part 7-1: Ancillary equipment - Terminal blocks for copper conductors	EN 60947-7-1	2009
ISO 3	1973	Preferred numbers - Series of preferred numbers	-	-
ISO 4046-4	2002	Paper, board, pulps and related terms - Vocabulary - Part 4: Paper and board grades and converted products	-	-

¹⁾ Undated reference.

CONTENTS

INTRODUCTION.....	6
1 General	7
1.1 Scope.....	7
1.2 Normative references	7
2 Definitions	8
3 Classification.....	9
4 Characteristics	9
4.1 Fuse-links	9
4.2 Rated power dissipation value.....	9
4.2.1 Overload and short-circuit protection (P_V).....	9
4.2.2 Exclusive short-circuit protection (P_{VK}).....	9
4.3 Rated and limiting values	9
4.3.1 Rated voltages	9
4.3.2 Void.....	9
4.3.3 Standard cross-sections	9
4.3.4 Rated cross-section.....	9
4.3.5 Rated connecting capacity.....	9
4.3.6 Working voltage.....	10
5 Product information	10
5.1 Marking.....	10
5.2 Additional information.....	10
5.3 Marking on the packing unit.....	10
6 Normal service, mounting and transport conditions.....	11
6.1.1 Ambient temperature	11
7 Constructional and performance requirements.....	11
7.1 Constructional requirements.....	11
7.1.1 Clamping units	11
7.1.2 Mounting	11
7.1.3 Clearances and creepage distances	11
7.1.4 Terminal identification and marking	12
7.1.5 Void.....	12
7.1.6 Rated cross-section and rated connecting capacity	12
7.1.7 Void.....	12
7.1.8 Actuating conditions	12
7.2 Performance requirements	12
7.2.1 Mechanical requirements during actuation.....	12
7.2.2 Electrical requirements	12
7.2.3 Thermal requirements.....	13
7.3 Electromagnetic compatibility (EMC)	13
8 Tests.....	13
8.1 Kinds of test.....	13
8.2 General.....	13
8.3 Verification of mechanical characteristics	13
8.3.1 General	13
8.3.2 Attachment of the fuse terminal block on its support.....	14

8.3.3	Mechanical properties of clamping units of a fuse terminal block	14
8.3.4	Compatibility between fuse terminal blocks and the fuse-link	14
8.3.5	Mechanical strength of the connection between the terminal block base and the fuse-carrier	15
8.4	Verification of electrical characteristics	15
8.4.1	General	15
8.4.2	Void	16
8.4.3	Dielectric tests	16
8.4.4	Contact resistance	17
8.4.5	Temperature rise of clamping units	18
8.4.6	Void	18
8.4.7	Ageing test (for screwless-type fuse terminal blocks only)	18
8.5	Verification of thermal characteristics	19
8.5.1	General	19
8.5.2	Rated power dissipation	20
8.5.3	Durability	24
8.5.4	Needle flame test	24
8.6	Verification of EMC characteristics	26
Annex A (normative)	Gauges	27
Annex B (informative)	Power dissipation values P_V and P_{VK}	28
Annex C (normative)	Order of tests and number of specimens	36
	Bibliography	37
Figure 1	– Test arrangement for the verification of the contact resistance	17
Figure 2	– Test arrangement for separate arrangement	20
Figure 3	– Test arrangement for compound arrangement	21
Figure 4	– Test arrangement for compound arrangement of short-circuit protection	22
Figure 5	– Test arrangement for the needle flame test	25
Figure 6	– Point of test flame contact (view from the layer placed below the fuse terminal block)	25
Figure A.1	– Outline of the gauges	27
Figure B.1	– Derating curve in the case of exclusive short-circuit protection for a separate arrangement	30
Figure B.2	– Derating curve in the case of exclusive short-circuit protection for a compound arrangement	31
Figure B.3	– Derating curve in the case of overload and short-circuit protection for a separate arrangement	33
Figure B.4	– Derating curve in the case of overload and short-circuit protection for a compound arrangement	34
Table 1	– Test forces	14
Table 2	– Dummy fuse-links	23
Table A.1	– Dimensions and materials for gauges for fuse-links according to IEC 60127-2	27
Table B.1	– Results of derating curves in the case of exclusive short-circuit protection	32
Table B.2	– Results of derating curves in case of overload and short-circuit protection	35
Table C.1	– Order of tests and number of specimens	36

INTRODUCTION

The standard for fuse terminal blocks covers not only the terminal block requirements but also takes into account the specifications of the cartridge fuse-links according to IEC 60127-1 and IEC 60127-2. A connection between these two standards is made by adding (adapting) the fundamental specifications of cartridge fuse-links (rated current, rated voltage, maximum voltage drop and maximum sustained power dissipation for cartridge fuse-links with the dimension of 5 mm × 20 mm or 6,3 mm × 32 mm with their different response characteristics) to the IEC 60947-7-1 requirements for terminal blocks. By this means, it is possible to judge the quality of the product “fuse terminal blocks”.

An important fact when using such cartridge fuse-links with fuse terminal blocks is that fuses heat up much less under rated load than they would do under overload conditions. The rated load is the result of rated current and maximum voltage drop. But there is a considerably increased power dissipation under overload conditions, equalling the maximum sustained power dissipation loss according to IEC 60127-2.

In industrial applications, single fuse terminal blocks are used within an arrangement of terminal blocks or many of them forming an arrangement on their own. This means that the same current and fuse-link will result in different heat emissions. Furthermore, it should be taken into account that apart from the general full range fuse (for overload and short-circuit protection), some fuse terminal blocks are exclusively used for short-circuit protection according to IEC 60364-4-43, e.g. in control circuits, where no overloads occur (i.e. safety coils, indicator lights or similar equipment).

Consequently there are four different types of application that need to be described in the catalogue or indicated on the fuse terminal block. For more information, see Annex B.

LOW-VOLTAGE SWITCHGEAR AND CONTROLGEAR –

Part 7-3: Ancillary equipment – Safety requirements for fuse terminal blocks

1 General

1.1 Scope

This part of IEC 60947 applies to fuse terminal blocks with screw-type or screwless-type clamping units for the connection of rigid (solid or stranded) or flexible copper conductors for the reception of cartridge fuse-links in accordance with IEC 60127-2, intended primarily for industrial or similar use in circuits not exceeding 1 000 V a.c., up to 1 000 Hz or 1 500 V d.c., and having a maximum short-circuit breaking capacity of 1 500 A.

They are intended for installation in electrical equipment with enclosures which surround the fuse terminal blocks to such an extent that they are accessible only with the aid of a tool.

For certain applications, for example in control circuits, the fuse terminal blocks may be designed exclusively for short-circuit protection.

NOTE This standard may be used as a guide for fuse terminal blocks for the reception of special cartridge fuse-links which do not meet the requirements of IEC 60127-2.

The object of this standard is to specify safety requirements and test methods for the mechanical, electrical and thermal characteristics of fuse terminal blocks, to ensure the compatibility between terminal blocks and standardized fuse-links.

This standard may be used as a guide for

- fuse terminal blocks requiring the fixing of special devices to the conductors, for example quick connect terminations or wrapped connections, etc.;
- fuse terminal blocks providing direct contact to the conductors by means of edges or points penetrating the insulation, for example insulation displacement connections, etc.

Where applicable in this standard, the term “clamping unit” has been used instead of the term “terminal”. This is taken into account in case of reference to IEC 60947-1.

1.2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60127-1:2006, *Miniature fuses – Part 1: Definitions for miniature fuses and general requirements for miniature fuse-links*

IEC 60127-2:2003, *Miniature fuses – Part 2: Cartridge fuse-links*
Amendment 1 (2003)

IEC 60216-1:2001, *Electrical insulating materials – Properties of thermal endurance – Part 1: Ageing procedures and evaluation of test results*

IEC 60695-11-5:2004, *Fire hazard testing – Part 11-5: Test flames – Needle flame test method – Apparatus, confirmatory test arrangement and guidance*

IEC 60947-1:2007, *Low-voltage switchgear and controlgear – Part 1: General rules*

IEC 60947-7-1, *Low-voltage switchgear and controlgear – Part 7-1: Ancillary equipment – Terminal blocks for copper conductors*

ISO 3:1973, *Preferred numbers – Series of preferred numbers*

ISO 4046-4:2002, *Paper, board, pulp and related terms – Vocabulary– Part 4: Paper and board grades and covered products*

