

INTERNATIONAL STANDARD

IEC
61993-2

First edition
2001-12

Maritime navigation and radiocommunication equipment and systems – Automatic identification systems (AIS) –

Part 2: Class A shipborne equipment of the universal automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results

© IEC 2001 — Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission 3, rue de Varembé Geneva, Switzerland
Telefax: +41 22 919 0300 e-mail: inmail@iec.ch IEC web site <http://www.iec.ch>



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

PRICE CODE **XE**

For price, see current catalogue

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	6
1 Scope	7
2 Normative References	7
3 Abbreviations.....	9
4 General requirements	10
4.1 General	10
4.2 Modes of Operation	11
4.3 Manuals	11
4.4 Marking and identification.....	11
5 Environmental, power supply, special purpose and safety requirements	12
6 Performance requirements.....	12
6.1 Composition	12
6.2 Internal GNSS Receiver	13
6.3 User interface.....	13
6.4 Identification.....	14
6.5 Information	14
6.6 Security.....	15
6.7 Permissible initialisation period	15
6.8 Power supply.....	16
6.9 Technical characteristics	16
6.10 Alarms and indications, fall-back arrangements	16
6.11 Display, input and output.....	20
7 Technical requirements.....	21
7.1 General	21
7.2 Physical layer.....	22
7.3 Link layer	22
7.4 Network layer	24
7.5 Transport layer.....	25
7.6 Presentation interface	25
8 DSC compatibility	31
9 Long range applications.....	31
9.1 General	31
9.2 Interrogations and responses	31
10 Test conditions	32
10.1 General	32
10.2 Normal and extreme test conditions.....	33
10.3 Standard Test environment	33
10.4 Test Signals	33
10.5 Arrangements for test signals applied to the receiver input.....	33
10.6 Encoder for receiver measurements	34
10.7 Waiver for receivers	34
10.8 Impedance	34
10.9 Artificial antenna (dummy load)	34

10.10	Facilities for access	34
10.11	Modes of operation of the transmitter	34
10.12	Measurement uncertainties	35
11	Power supply, special purpose and safety tests	35
12	Environmental tests	35
13	E M C tests	36
14	Operational tests	36
14.1	Operating modes/Capability.....	36
14.2	Multiple slot messages	38
14.3	Information content	39
14.4	Reporting rates.....	39
14.5	Security.....	41
14.6	Initialisation period	41
14.7	Channel selection.....	41
14.8	Transceiver protection.....	41
14.9	Alarms and indicators, fall-back arrangements	42
14.10	Display and control.....	45
15	Physical Tests	46
15.1	TDMA Transmitter	46
15.2	DSC Transmissions	51
15.3	TDMA Receivers	52
15.4	DSC Receiver.....	62
15.5	Conducted Spurious Emissions conveyed to the antenna	65
16	Specific tests of Link Layer	66
16.1	TDMA Synchronisation	66
16.2	Time division (Frame format).....	67
16.3	Synchronisation jitter	67
16.4	Data encoding (bit stuffing)	68
16.5	Frame check sequence	68
16.6	Slot allocation (Channel access protocols)	68
16.7	Message Formats.....	70
17	Specific tests of Network Layer	71
17.1	Dual channel operation.....	71
17.2	regional area designation by VDL message.....	71
17.3	regional area designation by serial message	72
17.4	Power setting	72
17.5	Message priority handling.....	73
17.6	Slot reuse (link congestion)	73
17.7	Management of received regional operating settings	73
17.8	Continuation of autonomous mode reporting rate.....	76
18	Specific tests of Transport Layer.....	76
18.1	Addressed messages	76
18.2	Interrogation responses.....	77
18.3	Other non periodic messages	77

19	Specific Presentation Interface Tests	77
19.1	General	77
19.2	Check of the manufacturer's documentation	78
19.3	Electrical test	78
19.4	Test of input sensor interface performance	78
19.5	Test of sensor input	79
19.6	Test of high speed output	79
19.7	High speed output Interface performance	79
19.8	Test of high speed input	79
20	DSC functionality tests	80
20.1	General	80
20.2	Regional area designation	80
20.3	Scheduling	80
20.4	Polling	80
21	Long Range functionality tests	81
21.1	LR interrogation	81
21.2	LR "all ships" interrogation	81
21.3	Consecutive LR "all ships" interrogations	82
	Annex A (informative) Block diagram of AIS	83
	Annex B (informative) New IEC 61162-1 sentences due to AIS	84
	Annex C (informative) Long range application	113
	Annex D (normative) AIS Interface Overview	114
	Annex E (informative) Block diagram of AIS test system	115

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MARITIME NAVIGATION AND RADIOCOMMUNICATION
EQUIPMENT AND SYSTEMS –
AUTOMATIC IDENTIFICATION SYSTEMS (AIS)****Part 2: Class A shipborne equipment of the
universal automatic identification system (AIS) –
Operational and performance requirements,
methods of test and required test results**

FOREWORD

- 1) The IEC (International Electrotechnical Commission) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of the IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, the IEC publishes International Standards. Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. The IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of the IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested National Committees.
- 3) The documents produced have the form of recommendations for international use and are published in the form of standards, technical specifications, technical reports or guides and they are accepted by the National Committees in that sense.
- 4) In order to promote international unification, IEC National Committees undertake to apply IEC International Standards transparently to the maximum extent possible in their national and regional standards. Any divergence between the IEC Standard and the corresponding national or regional standard shall be clearly indicated in the latter.
- 5) The IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with one of its standards.
- 6) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. The IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61993-2 has been prepared by IEC technical committee 80: Maritime navigation and radiocommunication equipment and systems.

The text of this standard is based on the following documents:

FDIS	Report on voting
80/315/FDIS	80/328/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 3.

The committee has decided that the contents of this publication will remain unchanged until 2006-07. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition, or
- amended.

INTRODUCTION

Following the adoption by the International Maritime Organisation (IMO) of Resolution MSC.74(69) Annex 3, Performance Standard for a Universal Shipborne Automatic Identification System, TC 80 established Working Group 8A to develop IEC 61993-2. Technical requirements were provided in ITU-R M.1371 "Technical characteristics for a universal shipborne Automatic Identification System (AIS) using TDMA (Self-Organising Time Division Multiple Access) in the VHF maritime mobile band". Carriage requirements for SOLAS ships have been adopted by IMO for entry into force starting on July 1st 2002.

It was brought to the attention of WG8A that patents and patents pending pertaining to AIS have been made freely available. TC 80 WG8A considers the technical implementation specified by this International Standard to be in full accordance with the requirements of Recommendation ITU-R M.1371-1 and as such to be free from claims of intellectual property rights.

The provision of a high-speed network connection IEC 61162-3 is optional. It may become a requirement in a later revision of this standard, when the relevant standard (IEC 61162-3) has been adopted.

The IMO Resolution MSC.74(69) Annex 3, Performance Standard for an Universal Shipborne Automatic Identification System, requires that the AIS has a means of processing data from an electronic position fixing system that provides a resolution of one ten-thousandth of a minute of arc and uses the WGS 84 datum. Resolution A.815(19) requires an accuracy of position information better than 10 m in confined waters. This does not require but implies that if the ship is not equipped with a DGNSS, the GNSS sensor internal to the AIS should be a DGNSS and should be used as source of position information.

Moreover, Resolution MSC.74(69) Annex 3 does not include any requirement for backup arrangements of the position information. However, a GNSS sensor is included in the AIS equipment as the source of UTC. It is felt by IEC TC 80 that this GNSS sensor also can be used as a back-up arrangement for the position information obtained from the ships DGNSS. This would ensure the availability of the AIS system in case of failure of the ship's EPFS.

Therefore, IEC TC 80 strongly recommends that manufacturers of AIS equipment implement such an arrangement in accordance with table 4 of this International Standard.

Note that an IEC standard detailing class B AIS is being prepared as IEC 62287.

MARITIME NAVIGATION AND RADIOCOMMUNICATION EQUIPMENT AND SYSTEMS – AUTOMATIC IDENTIFICATION SYSTEMS (AIS)

Part 2: Class A shipborne equipment of the universal automatic identification system (AIS) – Operational and performance requirements, methods of test and required test results

1 Scope

This International Standard specifies the minimum operational and performance requirements, methods of testing and required test results conforming to performance standards adopted by the IMO in resolution MSC.74(69), Annex 3, Universal Shipborne Automatic Identification System. This standard incorporates the technical characteristics of Class A shipborne equipment included in Recommendation ITU-R M1371-1 and takes into account the ITU Radio Regulations where applicable. In addition it takes account of IMO resolution A.694(17) to which IEC 60945 is associated.

This International Standard also specifies the minimum requirements both for the means to input and display data and for the interfaces to other equipment suitable to be used as means of input and display data.

NOTE All text of this standard, that is identical to that in IMO resolution MSC.74(69), Annex 3 and IMO resolution A.694(17) or to that in ITU-R M.1371-1 is printed in *italics* and the resolution (abbreviated to – A3 or – A694 respectively) or the recommendation (abbreviated to – M.1371-1) and paragraph numbers are indicated in parentheses i.e. (A3/3.3) or (M.1371-1/3.3) respectively.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60945, *Maritime navigation and radiocommunication equipment and systems – General requirements – Methods of testing and required test results*

IEC 61108-1, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 1: Global positioning system (GPS) – Receiver equipment – Performance standards, methods of testing and required test results.*

IEC 61108-2, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 2: Global navigation satellite system (GLONASS) – Receiver equipment – Performance standards, methods of testing and required test results*

IEC 61108-4¹, *Maritime navigation and radiocommunication equipment and systems – Global navigation satellite systems (GNSS) – Part 4: Shipborne DGPS and DGLONASS maritime radio beacon receiver equipment*

IEC 61162-1, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 1: Single talker and multiple listeners*

¹ To be printed.

IEC 61162-2, *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 2: Single talker and multiple listeners, high-speed transmission*

IEC 61162-3²: *Maritime navigation and radiocommunication equipment and systems – Digital interfaces – Part 3: Multiple Talker and multiple listeners – High speed network bus*

IEC 61993-1, *Maritime navigation and radiocommunication equipment and systems – Part 1: Shipborne automatic transponder system installation using VHF digital selective calling (DSC) techniques – Operational and performance requirements, methods of testing and required test results*

ISO/IEC 3309, *Information technology – Telecommunications and information exchange between systems – High-level data link control (HDLC) procedures – Frame structure*

IMO Resolution A.694(17):1991, *General requirements for shipborne radio equipment forming part of the Global Maritime Distress and Safety System (GMDSS) and for electronic navigational aids*

IMO Resolution A.815(19):1995, *Worldwide radionavigation system*

IMO Resolution A.851(20):1997, *General principles for ship reporting systems and ship reporting requirements, including guidelines for reporting incidents involving dangerous goods, harmful substances and/or marine pollutants*

IMO Resolution MSC.43(64), as amended by MSC.111(73), *Guidelines and Criteria for Ship Reporting Systems*.

IMO Resolution MSC.74(69), *Annex 3, Recommendation on performance standards for AIS*

IMO Guidelines on the operational use of AIS (provisional)

ITU-R Recommendation M.489-2, *Technical characteristics of VHF radiotelephone equipment operating in the maritime mobile service in channels spaced by 25 kHz*

ITU-R Recommendation M.825-3, *Characteristics of a transponder system using digital selective calling techniques for use with vessel traffic services and ship-to-ship identification*

ITU-R Recommendation M.1084-4, *Interim solutions for improved efficiency in the use of the band 156-174 MHz by stations in the maritime mobile service*

NOTE ITU-R M.1371-1 references ITU-R M.1084-3, Annex 3. A Draft Revision of Recommendation ITU-R M.1084-3, consequentially leading to ITU-R M.1084-4, has been approved in parallel to the approval of ITU-R M.1371-1.

ITU-R Recommendation M.1371-1, *Technical characteristics for a universal shipborne automatic identification system using time division multiple access in the VHF maritime mobile band*

IALA Technical clarifications to recommendation ITU-R M.1371-1

² To be printed.