

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Nät med hög driftsäkerhet – Del 1: Grunder och beräkningsmetoder

*Industrial communication networks –
High availability automation networks –
Part 1: General concepts and calculation methods*

Som svensk standard gäller europastandarden EN 62439-1:2010. Den svenska standarden innehåller den officiella engelska språkversionen av EN 62439-1:2010.

Nationellt förord

Europastandarden EN 62439-1:2010

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 62439-1, First edition, 2010 - Industrial communication networks - High availability automation networks - Part 1: General concepts and calculation methods**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 62439, ersätter SS-EN 62439, utg 1, 2009.

Tidigare fastställd svensk standard SS-EN 62439, utgåva 1, 2009, gäller ej fr o m 2013-03-01.

ICS 25.040; 35.040

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringssarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utdriften av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringssarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringssverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtidens standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 62439-1

March 2010

ICS 25.040; 35.040

Supersedes EN 62439:2008 (partially)

English version

**Industrial communication networks -
High availability automation networks -
Part 1: General concepts and calculation methods
(IEC 62439-1:2010)**

Réseaux de communication industrielle –
Réseaux d'automatisme à haute
disponibilité –
Partie 1 : Concepts généraux et méthodes
de calcul
(CEI 62439-1:2010)

Industrielle Kommunikationsnetze -
Hochverfügbare Automatisierungsnetze -
Teil 1: Grundlagen
und Berechnungsmethoden
(IEC 62439-1:2010)

This European Standard was approved by CENELEC on 2010-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/583/FDIS, future edition 1 of IEC 662439-1, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62439-1 on 2010-03-01.

This EN 62439-1 together with EN 62439-2, EN 62439-3, EN 62439-4, EN 62439-5 and EN 62439-6 supersedes EN 62439:2008.

This EN 62439-1:2010 includes the following significant technical changes with respect to EN 62439:2008:

- adding a calculation method for RSTP (rapid spanning tree protocol, IEEE 802.1Q),
- adding two new redundancy protocols: HSR (High-availability Seamless Redundancy) and DRP (Distributed Redundancy Protocol),
- moving former Clauses 1 to 4 (introduction, definitions, general aspects) and the Annexes (taxonomy, availability calculation) to EN 62439-1, which serves now as a base for the other documents,
- moving Clause 5 (MRP) to EN 62439-2 with minor editorial changes,
- moving Clause 6 (PRP) was to EN 62439-3 with minor editorial changes,
- moving Clause 7 (CRP) was to EN 62439-4 with minor editorial changes, and
- moving Clause 8 (BRP) was to EN 62439-5 with minor editorial changes,
- adding a method to calculate the maximum recovery time of RSTP in a restricted configuration (ring) to EN 62439-1 as Clause 8,
- adding specifications of the HSR (High-availability Seamless Redundancy) protocol, which shares the principles of PRP to EN 62439-3 as Clause 5, and
- introducing the DRP protocol as EN 62439-6.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2010-12-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2013-03-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62439-1:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

| | |
|-----------------------|------------------------------------------------------|
| IEC 61158 series | NOTE Harmonized in EN 61158 series (not modified). |
| IEC/TR 61158-1 | NOTE Harmonized as CLC/TR 61158-1. |
| IEC/TR 61158-6 series | NOTE Harmonized in EN 61158-6 series (not modified). |
| IEC 61784-2:2007 | NOTE Harmonized as EN 61784-2:2008 (not modified). |
| IEC 62439-2 | NOTE Harmonized as EN 62439-2. |
| IEC 62439-3 | NOTE Harmonized as EN 62439-3. |
| IEC 62439-4 | NOTE Harmonized as EN 62439-4. |
| IEC 62439-5 | NOTE Harmonized as EN 62439-5. |
| IEC 62439-6 | NOTE Harmonized as EN 62439-6. |
| IEC 61918:2007 | NOTE Harmonized as EN 61918:2008 (modified). |

Annex ZA
(normative)

**Normative references to international publications
with their corresponding European publications**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

| <u>Publication</u> | <u>Year</u> | <u>Title</u> | <u>EN/HD</u> | <u>Year</u> |
|--------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|-------------|
| IEC 60050-191 | 1990 | International Electrotechnical Vocabulary (IEV) - Chapter 191: Dependability and quality of service | - | - |
| IEC 61158 | Series | Fieldbus standard for use in industrial control systems | EN 61158 | Series |
| IEC 61158-6-10 | - | Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements | EN 61158-6-10 | - |
| ISO/IEC 8802-3 | 2000 | Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications | - | - |
| IEEE 802.1D | 2004 | IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges | - | - |
| IEEE 802.1Q | - | IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks | - | - |
| IETF RFC 791 | - | Internet Protocol - DARPA Internet Program Protocol Specification | - | - |

CONTENTS

| | |
|--------------------------------------------------------------------------|----|
| INTRODUCTION..... | 7 |
| 1 Scope..... | 8 |
| 2 Normative references | 8 |
| 3 Terms, definitions, abbreviations, acronyms, and conventions | 9 |
| 3.1 Terms and definitions | 9 |
| 3.2 Abbreviations and acronyms..... | 16 |
| 3.3 Conventions | 17 |
| 3.3.1 General conventions..... | 17 |
| 3.3.2 Conventions for state machine definitions..... | 17 |
| 3.3.3 Conventions for PDU specification..... | 17 |
| 3.4 Reserved network addresses | 18 |
| 4 Conformance requirements (normative)..... | 18 |
| 4.1 Conformance to redundancy protocols..... | 18 |
| 4.2 Conformance tests | 19 |
| 4.2.1 Concept..... | 19 |
| 4.2.2 Methodology..... | 19 |
| 4.2.3 Test conditions and test cases..... | 20 |
| 4.2.4 Test procedure and measuring | 20 |
| 4.2.5 Test report..... | 20 |
| 5 Concepts for high availability automation networks (informative) | 21 |
| 5.1 Characteristics of application of automation networks..... | 21 |
| 5.1.1 Resilience in case of failure | 21 |
| 5.1.2 Classes of network redundancy | 22 |
| 5.1.3 Redundancy maintenance | 22 |
| 5.1.4 Comparison and indicators | 23 |
| 5.2 Generic network system | 24 |
| 5.2.1 Network elements..... | 24 |
| 5.2.2 Topologies..... | 26 |
| 5.2.3 Redundancy handling | 32 |
| 5.2.4 Network recovery time | 32 |
| 5.2.5 Diagnosis coverage | 32 |
| 5.2.6 Failures | 32 |
| 5.3 Safety | 34 |
| 5.4 Security..... | 34 |
| 6 Classification of networks (informative) | 34 |
| 6.1 Notation | 34 |
| 6.2 Classification of robustness..... | 35 |
| 7 Availability calculations for selected networks (informative) | 35 |
| 7.1 Definitions | 35 |
| 7.2 Reliability models | 36 |
| 7.2.1 Generic symmetrical reliability model..... | 36 |
| 7.2.2 Simplified symmetrical reliability model..... | 38 |
| 7.2.3 Asymmetric reliability model | 38 |
| 7.3 Availability of selected structures | 39 |
| 7.3.1 Single LAN without redundant leaves | 39 |

| | | |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------|----|
| 7.3.2 | Network without redundant leaves | 40 |
| 7.3.3 | Single LAN with redundant leaves | 41 |
| 7.3.4 | Network with redundant leaves | 41 |
| 7.3.5 | Considering second failures | 42 |
| 7.4 | Caveat | 44 |
| 8 | RSTP for High Availability Networks: configuration rules, calculation and measurement method for deterministic recovery time in a ring topology | 44 |
| 8.1 | General | 44 |
| 8.2 | Deployment and configuration rules for the ring topology | 44 |
| 8.3 | Calculations for fault recovery time in a ring | 45 |
| 8.3.1 | Dependencies and failure modes | 45 |
| 8.3.2 | Calculations for non-considered failure modes | 45 |
| 8.3.3 | Calculations for the considered failure modes | 45 |
| 8.4 | Timing measurement method | 46 |
| 8.4.1 | Measurement of T_{PA} | 46 |
| 8.4.2 | Measurement of T_L | 47 |
| 8.4.3 | Measurement of $(T_{TC} + T_F)$ | 48 |
| 8.4.4 | System test example | 50 |
| | Bibliography | 52 |
| | Figure 1 – Conformance test overview | 19 |
| | Figure 2 – General network elements (tree topology) | 24 |
| | Figure 3 – Link Redundancy Entity in a Doubly Attached Node (DAN) | 26 |
| | Figure 4 – Example of tree topology | 27 |
| | Figure 5 – Example of linear topology | 28 |
| | Figure 6 – Example of ring topology | 28 |
| | Figure 7 – Example of a partially meshed topology | 29 |
| | Figure 8 – Example of fully meshed topology | 30 |
| | Figure 9 – Single LAN structure without redundant leaf links | 30 |
| | Figure 10 – Single LAN structure with redundant leaf links | 31 |
| | Figure 11 – Redundant LAN structure without redundant leaf links | 31 |
| | Figure 12 – Redundant LAN structure with redundant leaf links | 31 |
| | Figure 13 – General symmetrical fault model | 37 |
| | Figure 14 – Simplified fault model | 38 |
| | Figure 15 – Asymmetric fault model | 39 |
| | Figure 16 – Network with no redundancy | 40 |
| | Figure 17 – Network with no single point of failure | 41 |
| | Figure 18 – Network with resiliency to second failure | 43 |
| | Figure 19 – Test rig for T_{PA} measurement | 47 |
| | Figure 20 – Test rig for T_L measurement | 48 |
| | Figure 21 – Test rig for $(T_{TC} + T_F)$ measurement | 49 |
| | Figure 22 – Test rig for system test | 50 |
| | Table 1 – Examples of application grace time | 21 |
| | Table 2 – Examples of redundancy protocols | 23 |

| | |
|----------------------------------------------------------|----|
| Table 3 – Code assignment for the <TYPE> field | 34 |
| Table 4 – Code assignment for the <PLCYleaf> field | 34 |
| Table 5 – Code assignment for the <TPLGY> field..... | 35 |
| Table 6 – Code assignment for the <ITYPE> field | 35 |

INTRODUCTION

The IEC 62439 series specifies relevant principles for high availability networks that meet the requirements for industrial automation networks.

In the fault-free state of the network, the protocols of the IEC 62439 series provide ISO/IEC 8802-3 (IEEE 802.3) compatible, reliable data communication, and preserve determinism of real-time data communication. In cases of fault, removal, and insertion of a component, they provide deterministic recovery times.

These protocols retain fully the typical Ethernet communication capabilities as used in the office world, so that the software involved remains applicable.

The market is in need of several network solutions, each with different performance characteristics and functional capabilities, matching diverse application requirements. These solutions support different redundancy topologies and mechanisms which are introduced in IEC 62439-1 and specified in the other Parts of the IEC 62439 series. IEC 62439-1 also distinguishes between the different solutions, giving guidance to the user.

The IEC 62439 series follows the general structure and terms of IEC 61158 series.

INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –

Part 1: General concepts and calculation methods

1 Scope

The IEC 62439 series is applicable to high-availability automation networks based on the ISO/IEC 8802-3 (IEEE 802.3) (Ethernet) technology.

This part of the IEC 62439 series specifies

- the common elements and definitions for other parts of the IEC 62439 series;
- the conformance test specification (normative);
- a classification scheme for network characteristics (informative);
- a methodology for estimating network availability (informative);
- the configuration rules, calculation and measurement method for a deterministic recovery time in RSTP.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-191:1990, *International Electrotechnical Vocabulary – Chapter 191: Dependability and quality of service*

IEC 61158 (all parts), *Industrial communication networks – Fieldbus specifications*

IEC 61158-6-10, *Industrial communication networks – Fieldbus specifications – Part 6-10: Application layer protocol specification – Type 10 elements*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

IEEE 802.1Q, *IEEE standards for local and metropolitan area network. Virtual bridged local area networks*

IEEE 802.1D:2004, *IEEE standard for local and metropolitan area networks Media Access Control (MAC) Bridges*

IETF RFC 791, *Internet Protocol*; available at <<http://www.ietf.org>>