

© Copyright SEK. Reproduction in any form without permission is prohibited.

Industriell processtyrning – Nät med hög driftsäkerhet – Del 2: Media Redundancy Protocol (MRP)

*Industrial communication networks –
High availability automation networks –
Part 2: Media Redundancy Protocol (MRP)*

Som svensk standard gäller europastandarden EN 62439-2:2010. Den svenska standarden innehåller den officiella engelska språkversionen av EN 62439-2:2010.

Nationellt förord

Europastandarden EN 62439-2:2010

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 62439-2, First edition, 2010 - Industrial communication networks - High availability automation networks - Part 2: Media Redundancy Protocol (MRP)**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 62439, ersätter SS-EN 62439, utg 1, 2009.

Tidigare fastställd svensk standard SS-EN 62439, utgåva 1, 2009, gäller ej fr o m 2013-03-01.

ICS 25.040; 35.040

Denna standard är fastställd av SEK Svensk Elstandard, som också kan lämna upplysningar om **sakinnehållet** i standarden.
Postadress: SEK, Box 1284, 164 29 KISTA
Telefon: 08 - 444 14 00. Telefax: 08 - 444 14 30
E-post: sek@elstandard.se. Internet: www.elstandard.se

Standarder underlättar utvecklingen och höjer elsäkerheten

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

SEK är Sveriges röst i standardiseringsarbetet inom elområdet

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

Stora delar av arbetet sker internationellt

Utformningen av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringsarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringsverksamhet och medlemsavgift till IEC och CENELEC.

Var med och påverka!

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtida standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

SEK Svensk Elstandard

Box 1284
164 29 Kista
Tel 08-444 14 00
www.elstandard.se

English version

**Industrial communication networks -
High availability automation networks -
Part 2: Media Redundancy Protocol (MRP)
(IEC 62439-2:2010)**

Réseaux de communication industrielle –
Réseaux d'automatisme à haute
disponibilité –
Partie 2 : Protocol de redondance
de média (MRP)
(CEI 62439-2:2010)

Industrielle Kommunikationsnetze -
Hochverfügbare Automatisierungsnetze -
Teil 2: Medienredundanz-Protokoll (MRP)
(IEC 62439-2:2010)

This European Standard was approved by CENELEC on 2010-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/583/FDIS, future edition 1 of IEC 62439-2, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62439-2 on 2010-03-01.

This EN 62439-2 together with EN 62439-1, EN 62439-3, EN 62439-4, EN 62439-5 and EN 62439-6 supersedes EN 62439:2008.

EN 62439-2:2010 includes the following significant technical changes with respect to EN 62439:2008:

- adding a calculation method for RSTP (rapid spanning tree protocol, IEEE 802.1Q),
- adding two new redundancy protocols: HSR (High-availability Seamless Redundancy) and DRP (Distributed Redundancy Protocol),
- moving former Clauses 1 to 4 (introduction, definitions, general aspects) and the Annexes (taxonomy, availability calculation) to EN 62439-1, which serves now as a base for the other documents,
- moving Clause 5 (MRP) to EN 62439-2 with minor editorial changes,
- moving Clause 6 (PRP) was to EN 62439-3 with minor editorial changes,
- moving Clause 7 (CRP) was to EN 62439-4 with minor editorial changes, and
- moving Clause 8 (BRP) was to EN 62439-5 with minor editorial changes,
- adding a method to calculate the maximum recovery time of RSTP in a restricted configuration (ring) to EN 62439-1 as Clause 8,
- adding specifications of the HSR (High-availability Seamless Redundancy) protocol, which shares the principles of PRP to EN 62439-3 as Clause 5, and
- introducing the DRP protocol as EN 62439-6.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- | | | |
|--|-------|------------|
| – latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement | (dop) | 2010-12-01 |
| – latest date by which the national standards conflicting with the EN have to be withdrawn | (dow) | 2013-03-01 |

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62439-2:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61158-2:2007	NOTE	Harmonized as EN 61158-2:2008 (not modified).
IEC 61158-5-10	NOTE	Harmonized as EN 61158-5-10.
IEC 61784-1:2007	NOTE	Harmonized as EN 61784-1:2008 (not modified).
IEC 61784-2:2007	NOTE	Harmonized as EN 61784-2:2008 (not modified).
IEC 62439-3	NOTE	Harmonized as EN 62439-3.
IEC 62439-4	NOTE	Harmonized as EN 62439-4.
IEC 62439-5	NOTE	Harmonized as EN 62439-5.
IEC 62439-6	NOTE	Harmonized as EN 62439-6.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-191	1990	International Electrotechnical Vocabulary (IEV) - Chapter 191: Dependability and quality of service	-	-
IEC 61158-6-10	-	Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements	EN 61158-6-10	-
IEC 62439-1	2010	Industrial communication networks - High availability automation networks - Part 1: General concepts and calculation methods	EN 62439-1	2010
ISO/IEC 8802-3	2000	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-
IEEE 802.1D	2004	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	-	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-

CONTENTS

INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions, abbreviations, acronyms, and conventions	8
3.1 Terms and definitions	8
3.2 Abbreviations and acronyms.....	8
3.3 Conventions	9
4 MRP Overview.....	9
5 MRP Media redundancy behavior	10
5.1 Ring ports	10
5.2 Media Redundancy Manager (MRM).....	11
5.3 Media Redundancy Client (MRC).....	12
5.4 Redundancy domain.....	12
5.5 Usage with diagnosis and alarms	12
5.6 Ring diagnosis.....	13
5.7 Multiple MRM in a single ring	13
5.8 BLOCKED not supported (option).....	13
6 MRP Class specification	14
6.1 General.....	14
6.2 Template	14
6.3 Attributes.....	14
7 MRP service specification.....	17
7.1 Start MRM.....	17
7.2 Stop MRM	18
7.3 State Change	19
7.4 Start MRC	20
7.5 Stop MRC.....	21
7.6 Read MRM	22
7.7 Read MRC	24
8 MRP protocol specification	25
8.1 PDU description	25
8.1.1 Basic data types	25
8.1.2 DLPDU abstract syntax reference.....	25
8.1.3 Coding of the DLPDU field SourceAddress	26
8.1.4 Coding of the DLPDU field DestinationAddress.....	26
8.1.5 Coding of the field TagControlInformation.....	27
8.1.6 Coding of the field LT	27
8.1.7 MRP APDU abstract syntax	27
8.1.8 Coding of the field MRP_TLVHeader	28
8.1.9 Coding of the field MRP_Version	29
8.1.10 Coding of the field MRP_SequenceID	29
8.1.11 Coding of the field MRP_SA	29
8.1.12 Coding of the field MRP_Prio.....	29
8.1.13 Coding of the field MRP_PortRole	29
8.1.14 Coding of the field MRP_RingState.....	29

8.1.15	Coding of the field MRP_Interval	30
8.1.16	Coding of the field MRP_Transition	30
8.1.17	Coding of the field MRP_TimeStamp	30
8.1.18	Coding of the field MRP_Blocked	30
8.1.19	Coding of the field MRP_ManufacturerOUI	31
8.1.20	Coding of the field MRP_ManufacturerData	31
8.1.21	Coding of the field MRP_DomainUUID	31
8.2	Protocol machines	31
8.2.1	MRM protocol machine	31
8.2.2	MRC protocol machine	41
8.2.3	MRM and MRC functions	48
8.2.4	FDB clear timer	51
8.2.5	Topology change timer	51
9	MRP installation, configuration and repair	51
9.1	Ring port parameters	51
9.2	Ring topology parameters	52
9.3	MRM parameters	52
9.4	MRC parameters and constraints	52
9.5	Calculation of MRP ring recovery time	53
9.5.1	Overview	53
9.5.2	Deduction of formula	53
9.5.3	Worst case calculation for recovery time of 10 ms	55
9.5.4	Worst case calculation for 50 devices	56
10	MRP Management Information Base (MIB)	56
10.1	General	56
10.2	MRP MIB with a monitoring view	56
10.3	MRP MIB with a management and monitoring view	64
	Bibliography	73
	Figure 1 – MRP stack	10
	Figure 2 – MRP ring topology with one manager and clients	11
	Figure 3 – MRP open ring with MRM	11
	Figure 4 – MRP ring with more than one MRM	13
	Figure 5 – MRP protocol machine for MRM	32
	Figure 6 – MRP protocol machine for MRC	42
	Table 1 – MRP Start MRM	17
	Table 2 – MRP Stop MRM	18
	Table 3 – MRP Change State	19
	Table 4 – MRP Start MRC	20
	Table 5 – MRP Stop MRC	21
	Table 6 – MRP Read MRM	22
	Table 7 – MRP Read MRC	24
	Table 8 – MRP DLPDU syntax for ISO/IEC 8802-3 (IEEE 802.3)	26
	Table 9 – MRP OUI	26
	Table 10 – MRP MulticastMACAddress	27

Table 11 – MRP TagControllInformation.Priority field.....	27
Table 12 – MRP LT field	27
Table 13 – MRP APDU syntax	28
Table 14 – MRP Substitutions.....	28
Table 15 – MRP_TLVHeader.Type.....	28
Table 16 – MRP_Version	29
Table 17 – MRP_Prio.....	29
Table 18 – MRP_PortRole	29
Table 19 – MRP_RingState.....	30
Table 20 – MRP_Interval	30
Table 21 – MRP_Transition.....	30
Table 22 – MRP_TimeStamp	30
Table 23 – MRP_Blocked.....	31
Table 24 – MRP_DomainUUID.....	31
Table 25 – MRP Local variables of MRM protocol machine	33
Table 26 – MRM State machine	34
Table 27 – MRP Local variables of MRC protocol machine	43
Table 28 – MRC state machine	43
Table 29 – MRP functions.....	49
Table 30 – MRP FDB clear timer.....	51
Table 31 – MRP topology change timer.....	51
Table 32 – MRP Network/Connection parameters	52
Table 33 – MRP MRM parameters	52
Table 34 – MRP MRC parameters.....	53

INTRODUCTION

The IEC 62439 series specifies relevant principles for high availability networks that meet the requirements for industrial automation networks.

In the fault-free state of the network, the protocols of the IEC 62439 series provide ISO/IEC 8802-3 (IEEE 802.3) compatible, reliable data communication, and preserve determinism of real-time data communication. In cases of fault, removal, and insertion of a component, they provide deterministic recovery times.

These protocols retain fully the typical Ethernet communication capabilities as used in the office world, so that the software involved remains applicable.

The market is in need of several network solutions, each with different performance characteristics and functional capabilities, matching diverse application requirements. These solutions support different redundancy topologies and mechanisms which are introduced in IEC 62439-1 and specified in the other Parts of the IEC 62439 series. IEC 62439-1 also distinguishes between the different solutions, giving guidance to the user.

The IEC 62439 series follows the general structure and terms of IEC 61158 series.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning ring protocol given in Clause 5.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

Siemens AG A&D
Gleiwitzerstr. 555
Nürnberg 90475
Germany

and

Hirschmann Automation and Control GmbH
Stuttgarter Strasse 45-51
Neckartenzlingen 72654
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (http://www.iec.ch/tctools/patent_decl.htm) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –

Part 2: Media Redundancy Protocol (MRP)

1 Scope

The IEC 62439 series is applicable to high-availability automation networks based on the ISO/IEC 8802-3 (IEEE 802.3) (Ethernet) technology.

This part of the IEC 62439 series specifies a recovery protocol based on a ring topology, designed to react deterministically on a single failure of an inter-switch link or switch in the network, under the control of a dedicated media redundancy manager node.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-191:1990, *International Electrotechnical Vocabulary – Chapter 191: Dependability and quality of service*

IEC 61158-6-10, *Industrial communication networks – Fieldbus specifications – Part 6-10: Application layer protocol specification – Type 10 elements*

IEC 62439-1:2010, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

IEEE 802.1Q, *IEEE standards for local and metropolitan area network. Virtual bridged local area networks*

IEEE 802.1D:2004, *IEEE standard for local Local and metropolitan area networks Media Access Control (MAC) Bridges*

█ [REDACTED]

█ [REDACTED]

[REDACTED]

█ [REDACTED]

[REDACTED]

█ [REDACTED]