

© Copyright SEK. Reproduction in any form without permission is prohibited.

## Industriell processtyrning – Nät med hög driftsäkerhet – Del 5: Beacon Redundancy Protocol (BRP)

*Industrial communication networks –  
High availability automation networks –  
Part 5: Beacon Redundancy Protocol (BRP)*

Som svensk standard gäller europastandarden EN 62439-5:2010. Den svenska standarden innehåller den officiella engelska språkversionen av EN 62439-5:2010.

### Nationellt förord

Europastandarden EN 62439-5:2010

består av:

- **europastandardens ikraftsättningsdokument**, utarbetat inom CENELEC
- **IEC 62439-5, First edition, 2010 - Industrial communication networks - High availability automation networks - Part 5: Beacon Redundancy Protocol (BRP)**

utarbetad inom International Electrotechnical Commission, IEC.

Denna standard, och de andra delarna i serien SS-EN 62439, ersätter SS-EN 62439, utg 1, 2009.

Tidigare fastställd svensk standard SS-EN 62439 utg 1, 2009, gäller ej fr o m 2013-03-01.

---

ICS 25.040; 35.040

## *Standarder underlättar utvecklingen och höjer elsäkerheten*

Det finns många fördelar med att ha gemensamma tekniska regler för bl a säkerhet, prestanda, dokumentation, utförande och skötsel av elprodukter, elanläggningar och metoder. Genom att utforma sådana standarder blir säkerhetskraven tydliga och utvecklingskostnaderna rimliga samtidigt som marknadens acceptans för produkten eller tjänsten ökar.

Många standarder inom elområdet beskriver tekniska lösningar och metoder som åstadkommer den elsäkerhet som föreskrivs av svenska myndigheter och av EU.

## *SEK är Sveriges röst i standardiseringssarbetet inom elområdet*

SEK Svensk Elstandard svarar för standardiseringen inom elområdet i Sverige och samordnar svensk medverkan i internationell och europeisk standardisering. SEK är en ideell organisation med frivilligt deltagande från svenska myndigheter, företag och organisationer som vill medverka till och påverka utformningen av tekniska regler inom elektrotekniken.

SEK samordnar svenska intressenters medverkan i SEKs tekniska kommittéer och stödjer svenska experters medverkan i internationella och europeiska projekt.

## *Stora delar av arbetet sker internationellt*

Utdriften av standarder sker i allt väsentligt i internationellt och europeiskt samarbete. SEK är svensk nationalkommitté av International Electrotechnical Commission (IEC) och Comité Européen de Normalisation Electrotechnique (CENELEC).

Standardiseringssarbetet inom SEK är organiserat i referensgrupper bestående av ett antal tekniska kommittéer som speglar hur arbetet inom IEC och CENELEC är organiserat.

Arbetet i de tekniska kommittéerna är öppet för alla svenska organisationer, företag, institutioner, myndigheter och statliga verk. Den årliga avgiften för deltagandet och intäkter från försäljning finansierar SEKs standardiseringssverksamhet och medlemsavgift till IEC och CENELEC.

## *Var med och påverka!*

Den som deltar i SEKs tekniska kommittéarbete har möjlighet att påverka framtidens standarder och får tidig tillgång till information och dokumentation om utvecklingen inom sitt teknikområde. Arbetet och kontakterna med kollegor, kunder och konkurrenter kan gynnsamt påverka enskilda företags affärsutveckling och bidrar till deltagarnas egen kompetensutveckling.

Du som vill dra nytta av dessa möjligheter är välkommen att kontakta SEKs kansli för mer information.

### **SEK Svensk Elstandard**

Box 1284  
164 29 Kista  
Tel 08-444 14 00  
[www.elstandard.se](http://www.elstandard.se)

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 62439-5**

March 2010

ICS 25.040; 35.040

Supersedes EN 62439:2008 (partially)

English version

**Industrial communication networks -  
High availability automation networks -  
Part 5: Beacon Redundancy Protocol (BRP)  
(IEC 62439-5:2010)**

Réseaux de communication industrielle -  
Réseaux d'automatisme à haute  
disponibilité -  
Partie 5 :Protocole de redondance à  
balise (BRP)  
(CEI 62439-5:2010)

Industrielle Kommunikationsnetze -  
Hochverfügbare Automatisierungsnetze -  
Teil 5: Funkbaken-Redundanz-Protokoll  
(BRP)  
(IEC 62439-5:2010)

This European Standard was approved by CENELEC on 2010-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Central Secretariat: Avenue Marnix 17, B - 1000 Brussels**

## Foreword

The text of document 65C/583/FDIS, future edition 1 of IEC 62439-5, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62439-5 on 2010-03-01.

This EN 62439-5 together with EN 62439-1, EN 62439-2, EN 62439-3, EN 62439-4 and EN 62439-6 supersedes EN 62439:2008.

EN 62439-5:2010 includes the following significant technical changes with respect to EN 62439:2008:

- adding a calculation method for RSTP (rapid spanning tree protocol, IEEE 802.1Q),
- adding two new redundancy protocols: HSR (High-availability Seamless Redundancy) and DRP (Distributed Redundancy Protocol),
- moving former Clauses 1 to 4 (introduction, definitions, general aspects) and the Annexes (taxonomy, availability calculation) to EN 62439-1, which serves now as a base for the other documents,
- moving Clause 5 (MRP) to EN 62439-2 with minor editorial changes,
- moving Clause 6 (PRP) was to EN 62439-3 with minor editorial changes,
- moving Clause 7 (CRP) was to EN 62439-4 with minor editorial changes, and
- moving Clause 8 (BRP) was to EN 62439-5 with minor editorial changes,
- adding a method to calculate the maximum recovery time of RSTP in a restricted configuration (ring) to EN 62439-1 as Clause 8,
- adding specifications of the HSR (High-availability Seamless Redundancy) protocol, which shares the principles of PRP to EN 62439-3 as Clause 5, and
- introducing the DRP protocol as EN 62439-6.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2010-12-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2013-03-01

Annex ZA has been added by CENELEC.

---

### **Endorsement notice**

The text of the International Standard IEC 62439-5:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

- |                  |  |
|------------------|--|
| IEC 61158 series | NOTE Harmonized in EN 61158 series (not modified). |
| IEC 62439-2      | NOTE Harmonized as EN 62439-2.                     |
| IEC 62439-3      | NOTE Harmonized as EN 62439-3.                     |
| IEC 62439-4      | NOTE Harmonized as EN 62439-4.                     |
| IEC 62439-6      | NOTE Harmonized as EN 62439-6.                     |

**Annex ZA**  
(normative)

**Normative references to international publications  
with their corresponding European publications**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-191	-	International Electrotechnical Vocabulary (IEV) - Chapter 191: Dependability and quality of service	-	-
IEC 62439-1	2010	Industrial communication networks - High availability automation networks - Part 1: General concepts and calculation methods	EN 62439-1	2010
ISO/IEC/TR 8802-1	-	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 1: Overview of Local Area Network Standards	-	-
ISO/IEC 8802-3	2000	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-
IEEE 802.1D	-	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	-	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-

## CONTENTS

INTRODUCTION.....	6
1 Scope.....	7
2 Normative references .....	7
3 Terms, definitions, abbreviations, acronyms, and conventions .....	7
3.1 Terms and definitions .....	7
3.2 Abbreviations and acronyms.....	8
3.3 Conventions .....	8
4 BRP overview.....	8
5 BRP principle of operation.....	8
5.1 General .....	8
5.2 Network topology.....	8
5.3 Network components .....	10
5.4 Rapid reconfiguration of network traffic .....	11
6 BRP stack and fault detection features .....	11
7 BRP protocol specification.....	13
7.1 MAC addresses .....	13
7.2 EtherType .....	13
7.3 Fault detection mechanisms .....	13
7.4 End node state diagram .....	13
7.5 Beacon end node state diagram .....	21
8 BRP message structure.....	27
8.1 General .....	27
8.2 ISO/IEC 8802-3 (IEEE 802.3) tagged frame header.....	28
8.3 Beacon message.....	28
8.4 Learning_Update message .....	28
8.5 Failure_Notify message .....	29
8.6 Path_Check_Request message .....	29
8.7 Path_Check_Response message .....	29
9 BRP fault recovery time.....	29
10 BRP service definition .....	30
10.1 Supported services.....	30
10.2 Common service parameters .....	31
10.3 Set_Node_Parameters service .....	31
10.4 Get_Node_Parameters service .....	33
10.5 Add_Node_Receive_Parameters service .....	35
10.6 Remove_Node_Receive_Parameters service .....	37
10.7 Get_Node_Status service .....	38
11 BRP Management Information Base (MIB).....	39
Bibliography.....	41
Figure 1 – BRP star network example .....	9
Figure 2 – BRP linear network example .....	9
Figure 3 – BRP ring network example .....	10
Figure 4 – BRP stack architecture.....	11

Figure 5 – BRP state diagram of end node.....	14
Figure 6 – BRP state diagram for beacon end node .....	21
Table 1 – BRP end node flags .....	16
Table 2 – BRP end node state transition table .....	17
Table 3 – BRP beacon end node flags .....	23
Table 4 – BRP beacon end node state transition table .....	24
Table 5 – BRP common header with ISO/IEC 8802-3 (IEEE 802.3) tagged frame format.....	28
Table 6 – BRP beacon message format .....	28
Table 7 – BRP Learning_Update message format.....	28
Table 8 – BRP Failure_Notify message format.....	29
Table 9 – BRP Path_Check_Request message format.....	29
Table 10 – BRP Path_Check_Response message format .....	29
Table 11 – BRP Set_Node_Parameters service parameters.....	32
Table 12 – BRP Get_Node_Parameters service parameters .....	34
Table 13 – BRP Add_Node_Receive_Parameters service parameters .....	36
Table 14 – BRP Remove_Node_Receive_Parameters service parameters.....	37
Table 15 – BRP Get_Node_Status service parameters .....	38

## INTRODUCTION

The IEC 62439 series specifies relevant principles for high availability networks that meet the requirements for industrial automation networks.

In the fault-free state of the network, the protocols of the IEC 62439 series provide ISO/IEC 8802-3 (IEEE 802.3) compatible, reliable data communication, and preserve determinism of real-time data communication. In cases of fault, removal, and insertion of a component, they provide deterministic recovery times.

These protocols retain fully the typical Ethernet communication capabilities as used in the office world, so that the software involved remains applicable.

The market is in need of several network solutions, each with different performance characteristics and functional capabilities, matching diverse application requirements. These solutions support different redundancy topologies and mechanisms which are introduced in IEC 62439-1 and specified in the other Parts of the IEC 62439 series. IEC 62439-1 also distinguishes between the different solutions, giving guidance to the user.

The IEC 62439 series follows the general structure and terms of IEC 61158 series.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning fault-tolerant Ethernet provided through the use of special interfaces providing duplicate ports that may be alternatively enabled with the same network address. Switching between the ports corrects for single faults in a two-way redundant system. This is given in Clauses 5 and 6.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

Rockwell Automation Technologies  
1 Allen-Bradley Drive  
Mayfield Heights  
Ohio  
USA

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO ([www.iso.org/patents](http://www.iso.org/patents)) and IEC ([http://www.iec.ch/tctools/patent\\_decl.htm](http://www.iec.ch/tctools/patent_decl.htm)) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

## INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –

### Part 5: Beacon Redundancy Protocol (BRP)

## 1 Scope

The IEC 62439 series is applicable to high-availability automation networks based on the ISO/IEC 8802-3 (IEEE 802.3) (Ethernet) technology.

This part of the IEC 62439 series specifies a redundancy protocol that is based on the duplication of the network, the redundancy protocol being executed within the end nodes, as opposed to a redundancy protocol built in the switches. Fast error detection is provided by two beacon nodes, the switchover decision is taken in every node individually. The cross-network connection capability enables single attached end nodes to be connected on either of the two networks.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-191, *International Electrotechnical Vocabulary – Chapter 191: Dependability and quality of service*

IEC 62439-1:2010, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*

ISO/IEC/TR 8802-1, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 1: Overview of Local Area Network Standards* (IEEE 802.1)

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

IEEE 802.1D, *IEEE standard for local and metropolitan area networks Media Access Control (MAC) Bridges*

IEEE 802.1Q, *IEEE standards for local and metropolitan area network. Virtual bridged local area networks*

